

L^AT_EX Class for *Association for Computing Machinery**

Boris Veytsman[†]

2017/08/29, v1.46

Abstract

This package provides a class for typesetting publications of Association for Computing Machinery.

Contents

1	Introduction	3
2	User's guide	3
2.1	Installation	3
2.2	Invocation and options	5
2.3	Topmatter commands	7
2.4	Algorithms	19
2.5	Figures and tables	19
2.6	Theorems	21
2.7	Online-only and offline-only material	21
2.8	Note about anonymous mode	22
2.9	Acknowledgments	22
2.10	Bibliography	23
2.11	Colors	25
2.12	Other notable packages and typographic remarks	26
2.13	A note for wizards: <code>acmart-preload-hook.tex</code>	26
3	Implementation	28
3.1	Identification	28
3.2	Preload	28
3.3	Options	28
3.4	Setting switches	31

*©2016–2017, Association for Computing Machinery

[†]borisv@lk.net, boris@varphi.com

3.5	Loading base class and package	32
3.6	Paper size and paragraphing	39
3.7	Fonts	42
3.8	Floats	43
3.9	Lists	45
3.10	Top matter data	47
3.11	Concepts system	59
3.12	Copyright system	60
3.13	Typesetting top matter	65
3.14	Headers and Footers	79
3.15	Sectioning	84
3.16	TOC Lists	86
3.17	Theorems	86
3.18	Acknowledgments	89
3.19	Conditional typesetting	89
3.20	Additional bibliography commands	90
3.21	End of Class	90

1 Introduction

Association for Computing Machinery is the world's largest educational and scientific computing society, which delivers resources that advance computing as a science and a profession¹. It was one of the early adopters of T_EX for its typesetting.

It provided several different classes for a number of journal and conference proceedings. Unfortunately during the years since these classes were written, the code was patched many times, and the support of the different versions of the classes became difficult.

This package provides the uniform interface for all ACM publications. It is intended to replace all different classes and packages and provide an up to date L^AT_EX package.

The package uses only free T_EX packages and fonts included in T_EXLive, MikT_EX and other popular T_EX distributions. It is intended to be published in these distributions itself, which minimizes users' efforts in the installation and support of the package.

I am grateful to Michael D. Adams, Leif Andersen, Dirk Beyer, Benjamin Byholm, Michael Ekstrand, Matthew Fluet, Paolo G. Giarrusso, Ben Greenman, LianTze Lim, Ben Liblit, Kai Mindermann, Frank Mittelbach, Ross Moore, John Owens, Joel Nider, Tobias Pape, Mathias Rav, Matteo Riondato, Craig Rodkin, Bernard Rous, David Shamma, Stephen Spencer, John Wickerson, and many others for their invaluable help.

The development version of the package is available at <https://github.com/borisveytsman/acmart>.

2 User's guide

The class uses many commands and customization options, so it might appear intimidating for a casual user. Do not panic! Many of these commands and options can be safely left with their default values, or the values recommended by your conference or journal editors. If you have problems or questions, do not hesitate to ask me directly or the community at <https://github.com/borisveytsman/acmart>, <https://tex.stackexchange.com> or the closest T_EX Users Group. The world-wide T_EX Users Group is at <https://tug.org/>; please consider joining us if you use T_EX regularly.

2.1 Installation

Most probably, you already have this package installed in your favorite T_EX distribution; if not, you may want to upgrade. You may need to upgrade it anyway since the package uses a number of relatively recent packages, especially the ones related to the fonts.

The latest released version of the package can be found on CTAN: <https://www.ctan.org/pkg/acmart>. The development version can be found on GitHub: <https://github.com/borisveytsman/acmart>. At this address you can file a bug report—or even contribute your own enhancement making a pull request.

Most users should not attempt to install this package themselves, and rather rely on their T_EX distributions to provide it. If you decide to install the package yourself, follow the standard rules:

¹<http://www.acm.org/>

1. Run `latex` on `acmart.ins`. This will produce the file `acmart.cls`
2. Put the file `acmart.cls` and the bibliography files `*.bst` to the places where \LaTeX can find them (see [1] or the documentation for your \TeX system).
3. Update the database of file names. Again, see [1] or the documentation for your \TeX system for the system-specific details.
4. The file `acmart.pdf` provides the documentation for the package (this is the file you are probably reading now).

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

The class uses a number of other packages. They are included in all major \TeX distributions (\TeX Live, Mac \TeX , Mik \TeX) of 2015 and later, so you probably have them installed. Just in case here is the list of these packages:

- *amscs*, <http://www.ctan.org/pkg/amscs>
- *amsfonts*, <http://www.ctan.org/pkg/amsfonts>
- *amsmath*, <http://www.ctan.org/pkg/amsmath>
- *binhex*, <http://www.ctan.org/pkg/binhex>
- *caption*, <http://www.ctan.org/pkg/caption>
- *comment*, <http://www.ctan.org/pkg/comment>
- *cm-super*, <http://www.ctan.org/pkg/cm-super>
- *cmap*, <http://www.ctan.org/pkg/cmap>
- *draftwatermark*, <http://www.ctan.org/pkg/draftwatermark>
- *environ*, <http://www.ctan.org/pkg/environ>
- *etoolbox*, <http://www.ctan.org/pkg/etoolbox>
- *fancyhdr*, <http://www.ctan.org/pkg/fancyhdr>
- *float*, <http://www.ctan.org/pkg/float>
- *fontaxes*, <http://www.ctan.org/pkg/fontaxes>
- *geometry*, <http://www.ctan.org/pkg/geometry>
- *graphics*, <http://www.ctan.org/pkg/graphics>
- *hyperref*, <http://www.ctan.org/pkg/hyperref>
- *ifluatex*, <http://www.ctan.org/pkg/ifluatex>
- *ifxetex*, <http://www.ctan.org/pkg/ifxetex>

- *inconsolata*, <http://www.ctan.org/pkg/inconsolata>
- *libertine*, <http://www.ctan.org/pkg/libertine>
- *manyfoot*, <http://www.ctan.org/pkg/manyfoot>
- *microtype*, <http://www.ctan.org/pkg/microtype>
- *mmap*, <http://www.ctan.org/pkg/mmap>
- *ms*, <http://www.ctan.org/pkg/ms>
- *mweights*, <http://www.ctan.org/pkg/mweights>
- *natbib*, <http://www.ctan.org/pkg/natbib>
- *nccfoots*, <http://www.ctan.org/pkg/nccfoots>
- *newtx*, <http://www.ctan.org/pkg/newtx>
- *oberdiek*, <http://www.ctan.org/pkg/oberdiek>
- *pdftex-def*, <http://www.ctan.org/pkg/pdftex-def>
- *refcount*, <http://www.ctan.org/pkg/refcount>
- *setspace*, <http://www.ctan.org/pkg/setspace>
- *textcase*, <http://www.ctan.org/pkg/textcase>
- *totpages*, <http://www.ctan.org/pkg/totpages>
- *trimspaces*, <http://www.ctan.org/pkg/trimspaces>
- *upquote*, <http://www.ctan.org/pkg/upquote>
- *url*, <http://www.ctan.org/pkg/url>
- *xcolor*, <http://www.ctan.org/pkg/xcolor>
- *xkeyval*, <http://www.ctan.org/pkg/xkeyval>
- *xstring*, <http://www.ctan.org/pkg/xstring>

2.2 Invocation and options

To use the class put in the preamble of your document

```
\documentclass[options]{acmart}
```

There are several options corresponding to the type of the document and its general appearance. They are described below. Generally speaking, the options have key=value forms, for example

```
\documentclass[format=acmsmall, screen=true, review=false]{acmart}
```

Table 1: The possible values for the format option

Value	Meaning
manuscript	A manuscript. This is the default
acmsmall	Small single column format, used for CIE, CSUR, JACM, JDIQ, JEA, JERIC, JETC, PACMHCI, PACMPL, TAAS, TACCESS, TACO, TALG, TALLIP (formerly TALIP), TCPS, TEAC, TECS, TIIS, TISSEC, TIST, TKDD, TMIS, TOCE, TOCHI, TOCL, TOCS, TOCT, TODAES, TODS, TOIS, TOIT, TOMACS, TOMM (formerly TOMCCAP), TOMPECS, TOMS, TOPC, TOPLAS, TOPS, TOS, TOSEM, TOSN, TRET, TSAS, TSC, TSLP, TWEB, including special issues.
acmlarge	Large single column format, used for IMWUT, JOCCH, POMACS, TAP, including special issues.
acmtog	Large double column format, used for TOG, including special issues.
sigconf	Proceedings format for most of ACM conferences (with the exceptions listed below) and all ICPS volumes.
siggraph	As of March 2017, this format is no longer used. Please use sigconf for SIGGRAPH conferences.
sigplan	Proceedings format for SIGPLAN conferences.
sigchi	Proceedings format for SIGCHI conferences.
sigchi-a	Format for SIGCHI extended abstract.

The option format describes the format of the output. There are several possible values for this option, for example,

```
\documentclass[format=acmtog]{acmart}
```

Actually the words format= can be omitted, e.g.,

```
\documentclass[acmtog, review=false]{acmart}
```

The possible formats are listed in Table 1. Note that formats starting with acm are intended for journals and transactions, while formats starting with sig are intended for proceedings published as books.

Note that sometimes conference proceedings are published as a special issue (or issues) of an ACM journal. In this case you should use the journal format for a conference paper. Please contact your conference committee if in doubt.

There are several Boolean options which can take true or false values. They are listed in Table 2. The words =true can be omitted when setting the Boolean option, so instead of screen=true one can write just screen, for example,

```
\documentclass[acmsmall, screen, review]{acmart}
```

The option review is useful when combined with the manuscript format option: it provides a version suitable for reviewers and copyeditors.

Table 2: Boolean options

Option	Default	Meaning
review	false	A review version: lines are numbered, hyperlinks are colored
screen	see text	A screen version: hyperlinks are colored
natbib	true	Whether to use natbib package (see Section 2.10)
anonymous	false	Whether to make author(s) anonymous
authorversion	false	Whether to generate a special version for authors' personal use or posting (see Section 2.3)
timestamp	false	Whether to put a time stamp in the footer of each page
authordraft	false	Whether author's draft mode is enabled
acmthm	true	Whether to define theorem-like environments, see Section 2.6

The default for the option `screen` depends on the publication. At present it is `false` for all publications *but* PACM, since PACM is now electronic-only. Thus PACM titles (see Table 3) set this option to `true`. This option may in the future involve additional features suitable for on-screen versions of the articles.

The option `natbib` is used when the corresponding BibTeX style is based on `natbib`. In most cases you do not need to set it. See Section 2.10.

The option `anonymous` is used for anonymous review process: all author information becomes obscured.

The option `timestamp` is used to include a time stamp in the footer of each page. When preparing a document, this can help avoid confusing different revisions. The footer also include the page range of the document. This helps detect missing pages in hard copies.

The option `authordraft` is intended for the authors' drafts, not intended for distribution. It typesets copyright block to give the authors the idea of its size and overall size of the paper, but overprints it with the phrase "Unpublished working draft. Not for distribution", which also is used as a watermark. This option sets `timestamp` and `review` to `true`, but these decisions can be overridden by setting these options to `false` *after* `authordraft`.

2.3 Topmatter commands

A number of commands set up *top matter* information, or, in the computer science jargon, *metadata* for the article. They establish the publication name, article title, authors, doi and other data. Some of these commands, like `\title` or `\author`, should be put by the authors. Others, like `\acmVolume` or `\acmDOI`—by the editors. Below we describe these commands and mention who should issue them. These macros should be used *before* the `\maketitle` command. Note that in the previous versions of ACM classes some of these commands should be used before `\maketitle`, and some after it. Now they all must be used before `\maketitle`.

	<p>The class internally loads <code>amsart</code> class, so many top matter commands are inherited from <code>amsart</code> [2].</p>
<code>\acmJournal</code>	<p>The macro <code>\acmJournal{<shortName>}</code> sets the name of the journal or transaction for journals and transactions. The argument is the short name of the publication <i>in uppercase</i>, for example,</p> <pre>\acmJournal{TOMS}</pre>
	<p>The currently recognized journals are listed in Table 3. Note that conference proceedings published in <i>book</i> form do not set this macro.</p> <p>It is expected that this command is inserted by the author of the manuscript when she decides to which journal to submit the manuscript.</p>
<code>\acmConference</code>	<p>The macro <code>\acmConference[<short name>]{<name>}{<date>}{<venue>}</code> is used for conference proceedings published in the book form. The arguments are the following:</p> <p>short name: the abbreviated name of the conference (optional).</p> <p>name: the name of the conference.</p> <p>date: the date(s) of the conference.</p> <p>venue: the place of the conference.</p> <p>Examples:</p> <pre>\acmConference[TD'15]{Technical Data Conference}{November 12--16}{Dallas, TX, USA} \acmConference[SA'15 Art Papers]{November 02--06, 2015}{Kobe, Japan}</pre>
<code>\acmBooktitle</code>	<p>By default we assume that the conference proceedings are published in the book named <i>Proceedings of CONFERENCE</i>, where <i>CONFERENCE</i> is the name of the conference inferred from the command <code>\acmConference</code> above. However, sometimes the book title is different. The command <code>\acmBooktitle</code> may be used to set this title, for example,</p> <pre>\acmBooktitle{Companion to the first International Conference on the Art, Science and Engineering of Programming (Programming '17)}</pre>
<code>\editor</code>	<p>In most cases conference proceedings are edited. You can use the command <code>\editor[<editor>]</code> to set the editor of the volume. This command can be repeated, for example,</p> <pre>\editor{Jennifer B. Sartor} \editor{Theo D'Hondt} \editor{Wolfgang De Meuter}</pre>
<code>\title</code>	<p>The command <code>\title</code>, as in <code>amsart</code> class, has two arguments: one optional, and one mandatory:</p>

Table 3: ACM publications and arguments of the \acmJournal command

Abbreviation	Publication
CIE	ACM Computers in Entertainment
CSUR	ACM Computing Surveys
IMWUT	PACM on Interactive, Mobile, Wearable and Ubiquitous Technologies
JACM	Journal of the ACM
JDIQ	ACM Journal of Data and Information Quality
JEA	ACM Journal of Experimental Algorithmics
JERIC	ACM Journal of Educational Resources in Computing
JETC	ACM Journal on Emerging Technologies in Computing Systems
JOCH	ACM Journal on Computing and Cultural Heritage
PACMHCI	PACM on Human-Computer Interaction
PACMPL	PACM on Programming Languages
POMACS	PACM on Measurement and Analysis of Computing Systems
TAAS	ACM Transactions on Autonomous and Adaptive Systems
TACCESS	ACM Transactions on Accessible Computing
TACO	ACM Transactions on Architecture and Code Optimization
TALG	ACM Transactions on Algorithms
TALLIP	ACM Transactions on Asian and Low-Resource Language Information Processing
TAP	ACM Transactions on Applied Perception
TCPS	ACM Transactions on Cyber-Physical Systems
TEAC	ACM Transactions on Economics and Computation
TECS	ACM Transactions on Embedded Computing Systems
TIIS	ACM Transactions on Interactive Intelligent Systems
TISSEC	ACM Transactions on Information and System Security
TIST	ACM Transactions on Intelligent Systems and Technology
TKDD	ACM Transactions on Knowledge Discovery from Data
TMIS	ACM Transactions on Management Information Systems
TOCE	ACM Transactions on Computing Education
TOCHI	ACM Transactions on Computer-Human Interaction
TOCL	ACM Transactions on Computational Logic
TOCS	ACM Transactions on Computer Systems
TOCT	ACM Transactions on Computation Theory
TODAES	ACM Transactions on Design Automation of Electronic Systems
TODS	ACM Transactions on Database Systems
TOG	ACM Transactions on Graphics
TOIS	ACM Transactions on Information Systems
TOIT	ACM Transactions on Internet Technology
TOMACS	ACM Transactions on Modeling and Computer Simulation
TOMM	ACM Transactions on Multimedia Computing, Communications and Applications
TOMPECS	ACM Transactions on Modeling and Performance Evaluation of Computing Systems
TOMS	ACM Transactions on Mathematical Software
TOPC	ACM Transactions on Parallel Computing
TOPLAS	ACM Transactions on Programming Languages and Systems
TOPS	ACM Transactions on Privacy and Security
TOS	ACM Transactions on Storage
TOSEM	ACM Transactions on Software Engineering and Methodology
TOSN	ACM Transactions on Sensor Networks
TRETS	ACM Transactions on Reconfigurable Technology and Systems
TSAS	ACM Transactions on Spatial Algorithms and Systems
TSC	ACM Transactions on Social Computing
TSLP	ACM Transactions on Speech and Language Processing
TWEB	ACM Transactions on the Web

`\title[ShortTitle]{FullTitle}`

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

It is expected that this command is inserted by the author of the manuscript.

`\subtitle` Besides title, ACM classes allow subtitle, set with the `\subtitle{subtitle}` macro.

The commands for specification of authors are highly structured. The reason is, they serve double duty: the authors' information is typeset in the manuscript, *and* is used by the metadata extraction tools for indexing and cataloguing. Therefore it is very important to follow the guidelines exactly.

`\author` The basic commands are `\author`, `\orcid` (for the researchers registered with OR-

`\orcid` CID, <http://www.orcid.org/>), `\affiliation` and `\email`. In the simplest case you

`\affiliation` enter them in this order:

`\email`

```
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
```

Do *not* use \LaTeX `\and` macro! Each author deserves his or her own `\author` command.

Note that some formats do not typeset e-mails of ORCID identifiers. Do not worry: metadata tools will get them.

Sometimes an author has several affiliations. In this case the `\affiliation` command should be repeated:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

Similarly you can repeat `\email` command.

You may have several authors with the same affiliation, different affiliations, or overlapping affiliations (author A_1 is affiliated with institutions I_1 and I_2 , while author A_2 is affiliated with I_2 only, and author A_3 is affiliated with I_1 and I_3 , ...). The recommended solution is to put the `\affiliation` commands after each author, possibly repeating them:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
```

```

\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}

```

In some cases when several authors share the same affiliation you may try to save the space using the format

```

\author{...}
\email{...}
\author{...}
\email{...}
\affiliation{...}

```

However, this format is not generally recommended.

`\additionalaffiliation`

In some cases too many affiliations take too much space. The command `\additionalaffiliation{<affiliation>}` creates a footnote after author’s name with the words “Also with *{<affiliation>}*”. You should use this command only as the last resort. An example of usage is:

```

\author{G. Tobin}
\author{Ben Trovato}
\additionalaffiliation{%
  \institution{The Th{\o}rv{\a}ld Group}
  \streetaddress{1 Th{\o}rv{\a}ld Circle}
  \city{Hekla}
  \country{Iceland}}
\affiliation{%
  \institution{Institute for Clarity in Documentation}
  \streetaddress{P.O. Box 1212}
  \city{Dublin}
  \state{Ohio}
  \postcode{43017-6221}
}

```

Here Trovato and Tobin share their affiliation with the Institute for Clarity in Documentation, but only Ben Trovato is affiliated with The Thørvæld Group.

<pre> \position \institution \department \streetaddress \city \state \postcode \country </pre>	<p>The <code>\affiliation</code> and <code>\additionalaffiliation</code> commands are further structured to interact with the metadata extraction tools. Inside these commands you should use <code>\position</code>, <code>\institution</code>, <code>\department</code>, <code>\city</code>, <code>\streetaddress</code>, <code>\state</code>, <code>\postcode</code> and <code>\country</code> macros to indicate the corresponding parts of the affiliation. Note that in some cases (for example, journals) these parts are not printed in the resulting copy, but they <i>are</i> necessary since they are used by the XML metadata extraction programs. Do <i>not</i> put commas or <code>\\</code> between the elements of <code>\affiliation</code>: they will be provided automatically.</p>
--	--

An example of the author block:

```

\author{A. U. Thor}
\orcid{1234-4564-1234-4565}
\affiliation{%
  \institution{University of New South Wales}
  \department{School of Biomedical Engineering}
  \streetaddress{Samuels Building (F25), Kensington Campus}
  \city{Sidney}
  \state{NSW}
  \postcode{2052}
  \country{Australia}}
\email{author@nsw.au.edu}
\author{A. N. Other}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}
\author{C. O. Respondent}
\orcid{1234-4565-4564-1234}
\affiliation{%
  \institution{University of Pennsylvania}
  \city{Philadelphia}
  \state{PA}
  \country{USA}}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}

```

Note that old ACM conference formats did not allow for more than six authors and required some efforts from the authors to achieve alignment. The new format is much better in this.

Sometimes an author works in several departments within the same insitution. There could be two situations: the departments are independent, or one department is within another. In the first case just repeat the command `\department` several times. To handle the second case the command has an optional numerical parameter. The departments with higher numbers are higher in the organizational chart. Compare

```

\affiliation{%
\department[0]{Department of Lunar Studies} % 0 is the default
\department[1]{John Doe Institute} % higher than 0
\institution{University of San Serriffe}
\country{San Serriffe}}

```

and

```

\affiliation{%

```

```

\department{Department of Lunar Studies} % Not within JD Inst!
\department{John Doe Institute}
\institution{University of San Serriffe}
\country{San Serriffe}}

```

The command `\affiliation` formats the output according to American conventions. This might be wrong for some cases. Consider, for example, a German address. In Germany postcode is put before city and is not separated by a comma. We can handle this order using

```

\affiliation{%
  \institution{Fluginstitut}
  \streetaddress{Sonnenallee 17}
  \postcode{123456}
  \city{Helm}
  \country{Germany}
}

```

However, the comma after postcode is unfortunate: the address will be typeset (in some formats) as

```

Fluginstitut
Sonnenallee 17
123456, Helm, Germany

```

To overcome this problem, the command `\affiliation` has an optional parameter `obeypunctuation`, which can be `false` (the default) or `true`. If this parameter is `true`, `\affiliation` obeys the author's command. Thus

```

\affiliation[obeypunctuation=true]{%
  \institution{Fluginstitut}\\
  \streetaddress{Sonnenallee 17}\\
  \postcode{123456}
  \city{Helm},
  \country{Germany}
}

```

will be typeset as

```

Fluginstitut
Sonnenallee 17
123456 Helm, Germany

```

Note that you should *not* use this option for journals.

It is expected that these commands are inserted by the author of the manuscript.

`\thanks` Like `amsart` (and unlike standard \TeX), we allow `\thanks` only *outside* of commands

`\title` and `\author`. This command is obsolete, and should *not* be used in most cases. Do not list your acknowledgements and grant sponsors here: put this information in the `acks` environment (see Section 2.9).

`\authorsaddresses` In some formats the addresses are printed as a footnote on the first page. By default \TeX typesets them itself using the information you give it. However, you can override its choice using the command `\authorsaddresses{<contact addresses>}`, for example,

```
\authorsaddresses{%
  Authors' addresses: G.~Zhou, Computer Science Department, College of
  William and Mary, 104 Jameson Rd, Williamsburg, PA 23185, US;
  V.~B\eranger, Inria Paris-Rocquencourt, Rocquencourt, France;
  A.~Patel, Rajiv Gandhi University, Rono-Hills, Doimukh, Arunachal
  Pradesh, India; H.~Chan, Tsinghua University, 30 Shuangqing Rd,
  Haidian Qu, Beijing Shi, China; T.~Yan, Eaton Innovation Center,
  Prague, Czech Republic; T.~He, C.~Huang, J.~A.~Stankovic University
  of Virginia, School of Engineering Charlottesville, VA 22903, USA;
  T. F. Abdelzaher, (Current address) NASA Ames Research Center,
  Moffett Field, California 94035.}
```

You can *suppress* printing authors' addresses by setting them to an empty string: `\authorsaddresses{}`.

`\titlenote` While the command `\thanks` generates a note without footnote mark, sometimes
`\subtitlenote` the authors might need notes more tightly connected to the title, subtitle or author. The
`\authornote` commands `\titlenote`, `\subtitlenote` and `\authornote` that follow the corresponding
 commands (`\title`, `\subtitle` and `\author`) generate such notes, for example

```
\title{This is a title}
\titlenote{This is a titlenote}
\author{A. U. Thor}
\authornote{This is an authornote}
```

Please never use `\footnotes` inside `\author` or `\title` commands, since this confuses metadata extraction software (actually these commands now produce errors).

`\authornotemark` Sometimes one may need to have the same footnote connected to several authors. The command `\authornotemark[<number>]` adds just the footnote mark, for example

```
\author{A. U. Thor}
\authornote{Both authors contributed equally to the paper}
...
\author{A. N. Other}
\authornotemark[1]
```

The correct numbering of these marks is the responsibility of the user.

`\acmVolume` The macros `\acmVolume`, `\acmNumber`, `\acmArticle`, `\acmYear` and `\acmMonth` are
`\acmNumber` inserted by the editor and set the journal volume, issue, article number, year and month
`\acmArticle` correspondingly. The arguments of all these commands, including `\acmMonth` is numerical,
`\acmYear` including `\acmMonth`, for example,
`\acmMonth`

```

\acmVolume{9}
\acmNumber{4}
\acmArticle{39}
\acmYear{2010}
\acmMonth{3}

```

Note that `\acmArticle` is used not only for journals, but also for some conference proceedings.

`\acmArticleSeq` The articles in the same issue of a journal have a *sequential number*. It is used to vertically position the black blob in some formats. By default it is the same as article number, but the command `\acmArticleSeq{<n>}` can be used to change it:

```

\acmArticle{39}     % The sequence number will be 39 by default
\acmArticleSeq{5}   % We redefine it to 5

```

Setting this number to zero suppresses the blob.

`\acmSubmissionID` If you paper got a Submission ID from the Conference Management System, put it here:

```

\acmSubmissionID{123-A56-BU3}

```

`\acmPrice` The macro `\acmPrice{<price>}` sets the price for the article

```

\acmPrice{25.00}

```

Note that you do not need to put the dollar sign here, just the amount. By default the price is \$15.00, unless the copyright is set to `usgov` or `rightsretained`, when it is suppressed. Note that to override the defaults you need to set the price *after* the `\setcopyright` command to override the default. Also, the command `\acmPrice{}` suppresses the printing of the price.

`\acmISBN` Book-like volumes have ISBN numbers attached to them. The macro `\acmISBN{<ISBN>}` sets it. Normally it is set by the typesetter, for example,

```

\acmISBN{978-1-4503-3916-2}

```

Setting it to empty string, as `\acmISBN{}`, suppresses printing of ISBN.

`\acmDOI` The macro `\acmDOI{<DOI>}` sets the DOI number of the article, for example,

```

\acmDOI{10.1145/9999997.9999999}

```

It is normally set by the typesetter. Setting it to empty string, `\acmDOI{}` suppresses DOI.

`\acmBadgeR` Some conference articles get special distinction, for example, the artifact evaluation
`\acmBadgeL` for PPOPP 2016 (see <http://ctuning.org/ae/ppopp2016.html>). These articles display special badges supplied by the conference organizers. The class provides commands to

add these badges: `\acmBadgeR[\url]{\graphics}` and `\acmBadgeL[\url]{\graphics}`. The first command puts the badge to the right of the title, and the second one—to the left. The exception is the `sigchi-a` mode for SIGCHI Extended abstract, which puts the badges on the left margin. The argument have the following meaning: [*\url*], if provided, sets the link to the badge authority in the screen version, while {*\graphics*} sets the graphics file with the badge image. The file must be a cropped square, which is scaled to a standard size in the output. For example, if the badge image is `ae-logo.pdf`, the command is

```
\acmBadgeR[http://ctuning.org/ae/ppopp2016.html]{ae-logo}
```

`\startPage` The macro `\startPage{\page}` sets the first page of the article in the journal or book. It is used by the typesetter.

`\terms` The command `\keywords{\keyword, keyword,...}` sets keywords for the article.

`\keywords` They must be separated by commas, for example,

```
\keywords{wireless sensor networks, media access control,
multi-channel, radio interference, time synchronization}
```

`CCSXML` ACM publications are classified according to the ACM Computing Classification
`\ccsdesc` Scheme (CCS). CCS codes are used both in the typeset version of the publications *and* in the metadata in the various databases. Therefore you need to provide both \TeX commands and XML metadata with the paper.

The tool at <http://dl.acm.org/ccs.cfm> can be used to generate CCS codes. After you select the topics, click on “Generate CCS codes” to get the result like the following:

```
\begin{CCSXML}
<ccs2012>
  <concept>
    <concept_id>10010520.10010553.10010562</concept_id>
    <concept_desc>Computer systems organization~Embedded systems</concept_desc>
    <concept_significance>500</concept_significance>
  </concept>
  <concept>
    <concept_id>10010520.10010575.10010755</concept_id>
    <concept_desc>Computer systems organization~Redundancy</concept_desc>
    <concept_significance>300</concept_significance>
  </concept>
  <concept>
    <concept_id>10010520.10010553.10010554</concept_id>
    <concept_desc>Computer systems organization~Robotics</concept_desc>
    <concept_significance>100</concept_significance>
  </concept>
  <concept>
    <concept_id>10003033.10003083.10003095</concept_id>
    <concept_desc>Networks~Network reliability</concept_desc>
    <concept_significance>100</concept_significance>
  </concept>
</ccs2012>
\end{CCSXML}
```


Table 4: Parameters for \setcopyright command

Parameter	Meaning
none	The copyright and permission information is not typeset (this is the option for some ACM conferences).
acmcopyright	The authors transfer the copyright to ACM (the “traditional” choice).
acmlicensed	The authors retain the copyright but license the publication rights to ACM.
rightsretained	The authors retain the copyright and publication rights to themselves or somebody else.
usgov	All the authors are employees of the US Government.
usgovmixed	Some authors are employees of the US Government.
cagov	All the authors are employees of the Canadian Government.
cagovmixed	Some authors are employees of the Canadian Government.
licensedusgovmixed	Some authors are employees of the US Government, and the publication rights are licensed to ACM.
licensedcagov	All the authors are employees of the Canadian Government, and the publication rights are licensed to ACM.
licensedcagovmixed	Some authors are employees of the Canadian Government, and the publication rights are licensed to ACM.
othergov	Authors are employees of a Government other than US or Canada.
licensedothergov	Authors are employees of a Government other than US or Canada, and the publication rights are licensed to ACM.

</ccs2012>

\end{CCSXML}

\ccsdesc[500]{Computer systems organization~Embedded systems}

\ccsdesc[300]{Computer systems organization~Redundancy}

\ccsdesc{Computer systems organization~Robotics}

\ccsdesc[100]{Networks~Network reliability}

You need to just copy this code and paste it in your paper anywhere before \maketitle.

\setcopyright

There are several possibilities for the copyright of the papers published by ACM: the authors may transfer the rights to ACM, license them to ACM, some or all authors might be employees of the US or Canada Government, etc. Accordingly the command \setcopyright{...} is introduced. Its argument is the copyright status of the paper, for example, \setcopyright{acmcopyright}. The possible values for this command are listed in Table 4.

The ACM submission software should generate the right command for you to paste into your file.

`\copyrightyear` Each copyright statement must have the year of copyright. By default it is the same as `\acmYear`, but you can override this decision using the macro `\copyrightyear`, e.g.,

```
\acmYear{2016}
\copyrightyear{2015}
```

There is a special case for a personal copy that the authors may be allowed to generate for their use or a posting on a personal site (check the instructions for the specific journal or conference for the details). The document option `authorversion=true` produces the special form of the copyright statement for this case. Note that you still need the `\setcopyright` command and (optionally) `\copyrightyear` command to tell \TeX about the copyright owner and year. Also, you should be aware that due to the different sizes of the permission blocks for the printed version and authors' version the page breaks might be different between them.

`abstract` The environment `abstract` must *precede* `\maketitle` command. Again, this is different from the standard \LaTeX .

`teaserfigure` A special kind of figure is used for many two-column conference proceedings. This figure is placed just after the authors, but before the main text. The environment `teaserfigure` is used for these figures. This environment must be used *before* `\maketitle`, for example,

```
\begin{teaserfigure}
  \includegraphics[width=\textwidth]{sampleteaser}
  \caption{This is a teaser}
  \label{fig:teaser}
\end{teaserfigure}
```

`\settopmatter` Some information in the top matter is printed for certain journals or proceedings and suppressed for others. You may override these defaults using the command `\settopmatter{<settings>}`. The settings and their meanings are listed in Table 5. For example,

```
\settopmatter{printacmref=false, printccs=true, printfolios=true}
```

The parameter `authorsperrow` requires some explanation. In conference proceedings authors' information is typeset in boxes, several boxes per row (see `sample-sigconf.pdf`, `sample-sigplan.pdf` etc.). The number of the boxes per row is determined automatically. If you want to override this decision, you may do it using this parameter, for example,

```
\settopmatter{authorsperrow=4}
```

However, in most cases you should *not* do this and use the default settings. Setting `authorsperrow` to 0 will revert to default settings.

`\received` The command `\received[<stage>]{<date>}` sets the history of the publication. The

Table 5: Settings for `\settopmatter` command

Parameter	Values	Meaning
<code>printccs</code>	true/false	Whether to print CCS categories
<code>printacmref</code>	true/false	Whether to print ACM bibliographic entry
<code>printfolios</code>	true/false	Whether to print page numbers (folios)
<code>authorsperrow</code>	numeric	Number of authors per row for title page in conference proceedings formats

[`<stage>`] argument is optional; the default is Received for the first date and revised for the subsequent ones. For example

```
\received{February 2007}
\received[revised]{March 2009}
\received[accepted]{June 2009}
```

`\maketitle` The macro `\maketitle` must be the last command in the top matter group: i.e., it must follow the commands defined in this section.

`\shortauthors` *After* the command `\maketitle` the macro `\shortauthors` stores the names of the authors for the running head. You may redefine it if the list of author's name is too long, e.g.,

```
\maketitle
\renewcommand{\shortauthors}{Zhou et al.}
```

2.4 Algorithms

There are now several good packages for typesetting algorithms [3, 4, 5], and the authors are now free to choose their favorite one.

2.5 Figures and tables

New ACM styles use the standard L^AT_EX interface for figures and tables. There are some important items to be aware of, however.

1. The captions for figures must be entered *after* the figure bodies, and for the tables *before* the table bodies.
2. ACM uses the standard types for figures and tables and adds several new ones. In total there are the following types:

figure, table: a standard figure or table, taking full text width in one-column formats and one column in two-column formats.

figure*, table* in two-column formats, a special figure or table taking full text width.

teaserfigure: a special figure before `\maketitle`.

sidebar, marginfigure, margintable: in the sigchi-a format, special sidebars, tables and figures on the margin.

3. Accordingly, when scaling the images, one should use the following sizes:

- (a) For figure in one-column mode, figure* in two-column mode or teaserfigure—`\textwidth` (in the one-column you can also use `\columnwidth`, which coincides with `\textwidth` in this case).
- (b) For figure in two-column mode—`\columnwidth`.
- (c) For marginfigure—`\marginparwidth`.
- (d) For figure* in SIGCHI Extended abstracts—`\fulltextwidth`.

It is strongly recommended to use the package `booktabs` [6] and follow its main principles of typography with respect to tables:

- 1. Never, ever use vertical rules.
- 2. Never use double rules.

It is also a good idea not to overuse horizontal rules.

For table *footnotes* you have several options described in TeX FAQ [1]. The simplest one is to use `\minipage` environment:

```
\begin{table}
\caption{Simulation Configuration}
\label{tab:conf}
\begin{minipage}{\columnwidth}
\begin{center}
\begin{tabular}{ll}
\toprule
TERRAIN\footnote{This is a table footnote. This is a
table footnote. This is a table footnote.} &
(200\,m$\times$200\,m) Square\\
Node Number & 289\\
Node Placement & Uniform\\
Application & Many-to-Many/Gossip CBR Streams\\
Payload Size & 32 bytes\\
Routing Layer & GF\\
MAC Layer & CSMA/MMSN\\
Radio Layer & RADIO-ACCNOISE\\
Radio Bandwidth & 250Kbps\\
Radio Range & 20m--45m\\
\bottomrule
\end{tabular}
\end{center}
\bigskip
\footnotesize\emph{Source:} This is a table
sourcernote. This is a table sourcernote. This is a table
```

```
sourcenote.
```

```
\emph{Note:} This is a table footnote.  
\end{minipage}  
\end{table}
```

sidebar
marginfigure
margintable

SIGCHI extended abstract extensively uses margin space. The package provides three environments for this with option captions:

sidebar: textual information on the margin

marginfigure: a figure on the margin

margintable: a table on the margin

Tables and figures (including margin tables and margin figures) are by default centered. However, in some cases (for example, when you use several subimages per figure) you may need to override this decision. A good way to do so is to put the contents into a `\minipage` of the width `\columnwidth`.

2.6 Theorems

ACM classes define two theorem styles and several pre-defined theorem environments:

acmplain: this is the style used for theorem, conjecture, proposition, lemma, and corollary, and

acmdefinition: this is the style used for example and definition.

These environments are defined by default. In the unusual circumstance that a user does not wish to have these environments defined, the option `acmthm=false` in the preamble will suppress them.

2.7 Online-only and offline-only material

printonly
screenonly

Some supplementary material in ACM publication is put online, but not in the printed version. The text inside the environment `screenonly` will be typeset only when the option `screen` (see Section 2.2) is set to true. Conversely, the text inside the environment `printonly` is typeset only when this option is set to false. For example

```
\section{Supplementary materials}  
  
\begin{printonly}  
  This section is included in the online version of the paper.  
\end{printonly}  
  
\begin{screenonly}  
  (The actual section).  
\end{screenonly}
```

We use *comment* package for typesetting this code, so `\begin` and `\end` should start at the first positions of the lines of their own (no initial spaces etc.).

2.8 Note about anonymous mode

`anonsuppress` When the option `anonymous` is selected, \TeX suppresses author information (including number of authors) for a blind review. However, sometimes the information identifying the authors may be present in the body of the paper

```
\begin{anonsuppress}
  This is the continuation of the previous work by the author
  \cite{prev1, prev2}.
\end{anonsuppress}
```

As for `printonly` and `screenonly` environments, `\begin{anonsuppress}` and `\end{anonsuppress}` should start the line of their own (no leading or trailing spaces).

2.9 Acknowledgments

The traditional “Acknowledgments” section is conventionally used to thank persons and granting agencies for their help and support. However, there are several important considerations about this section.

First, in the anonymous mode this section must be omitted: it gives too much information to the reviewers. Second, the data about the grants is extracted and stored separately by the postprocessing software. ACM classes provide facilities for both these tasks.

`acks` The environment `acks` starts an unnumbered section “Acknowledgments” unless the anonymous mode is chosen. Put all thanks inside this environment.

As for `printonly` and `screenonly` environments, `\begin{acks}` and `\end{acks}` should start the line of their own (no leading or trailing spaces).

`\grantsponsor` All the financial support *must* be listed using the commands `\grantsponsor` and
`\grantnum` `\grantnum`. These commands tell the postprocessing software about the granting organization and the grant. The format of the command is the following:

```
\grantsponsor{\<sponsorID>}{\<name>}{\<url>}
\grantnum[\<url>]{\<sponsorID>}{\<number>}.
```

Here `{\<sponsorID>}` is the unique ID used to match grants to sponsors, `{\<name>}` is the name of the sponsor, `{\<url>}` is its URL, and `{\<number>}` is the grant number. The `{\<sponsorID>}` of the `\grantnum` command must correspond to `\sponsorID` of a `\grantsponsor` command. Some awards have their own web pages, which you can include using the optional argument of `\grantnum` command.

At present `{\<sponsorID>}` is chosen by the authors and can be an arbitrary key, in the same way the label of `\cite` is arbitrarily chosen. There might be a change to this policy if ACM decides to create a global database of sponsoring organizations.

Example:

```

\begin{acks}
  The authors would like to thank Dr. Yuhua Li for providing the
  matlab code of the \textit{BEPS} method.

  The authors would also like to thank the anonymous referees for
  their valuable comments and helpful suggestions. The work is
  supported by the \grantsponsor{GS501100001809}{National Natural
  Science Foundation of
  China}{https://doi.org/10.13039/501100001809} under Grant
  No.:~\grantnum{GS501100001809}{61273304}
  and~\grantnum[http://www.nnsf.cn/youngscientsts]{GS501100001809}{Young
  Scientists' Support Program}.
\end{acks}

```

2.10 Bibliography

ACM uses the *natbib* package for formatting references and the style `ACM-Reference-Format.bst` for Bib_{TeX} processing. You may disable loading of *natbib* by using the option `natbib=false` in `\documentclass`. However, it is not recommended, as well as the use of Bib_{TeX} styles other than `ACM-Reference-Format.bst`, and may delay the processing of the manuscript.

`\citestyle` If you use *natbib*, you can select one of two predefined citation styles: the author-year format `acmauthoryear` or the numeric format `acmnumeric` using the command `\citestyle`, for example,

```
\citestyle{acmauthoryear}
```

Note that numeric citations are the default mode for most formats.

`\setcitestyle` You may further customize *natbib* using `\setcitestyle` command, for example,

```
\setcitestyle{numbers,sort&compress}
```

If you use *natbib*, then commands like `\citep` and `\citeauthor` are automatically supported. The command `\shortcite` is the same as `\cite` in numerical mode, and cites the year in the author-date mode.

There are several customized Bib_{TeX} entries and fields in ACM style `ACM-Reference-Format.bst` you may want to be aware of.

The style supports fields `doi` and `url`, for example,

```
doi = "10.1145/1188913.1188915",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.pdf",
```

The style supports arXiv recommended fields `eprint` and (optionally) `primaryclass`, for example,

```
eprint = "960935712",
primaryclass = "cs",
```

See the examples at <http://arxiv.org/hypertex/bibstyles/>.

There are special entries online and game for Web pages and games, for example,

```
@online{Thornburg01,
  author =      "Harry Thornburg",
  year =       "2001",
  title =      "Introduction to Bayesian Statistics",
  url =        "http://ccrma.stanford.edu/~jos/bayes/bayes.html",
  month =      mar,
  lastaccessed = "March 2, 2005",
}
```

For these entries you can use the lastaccessed field to add the access date to the URL.

There are two ways to enter video and audio sources in the bibliography corresponding to two different possibilities. For standalone sources available on WWW you can use an online entry, setting there howpublished field, for example,

```
@online{Obama08,
  author =      "Barack Obama",
  year =       "2008",
  title =      "A more perfect union",
  howpublished = "Video",
  day =        "5",
  url =        "http://video.google.com/videoplay?docid=6528042696351994555",
  month =      mar,
  lastaccessed = "March 21, 2008",
}
```

For the sources available as attachments to conference proceedings and similar documents, you can use the usual inproceedings entry, again setting the howpublished field:

```
@inproceedings{Novak03,
  author =      "Dave Novak",
  title =      "Solder man",
  booktitle =   "ACM SIGGRAPH 2003 Video Review on Animation theater Program",
  year =       "2003",
  publisher =   "ACM Press",
  address =     "New York, NY",
  pages =      "4",
  month =      "March 21, 2008",
  doi =        "10.9999/woot07-S422",
  howpublished = "Video",
}
```

Sometimes you need to cite a complete issue of a journal. The entry periodical is intended for this:


```
@periodical{JCohen96,
  key =      "Cohen",
  editor =   "Jacques Cohen",
  title =    "Special issue: Digital Libraries",
  journal =  "Communications of the {ACM}",
  volume =   "39",
  number =   "11",
  month =    nov,
  year =     "1996",
}
```

If you do not know the year of publication, the style will add “[n. d.]” (for “no date”) entry.

If you do not know the author (this is often the case for online entries), use key field to add a key for sorting and citations, for example,

```
@online{TUGInstmem,
  key =      {TUG},
  year =     2017,
  title =    "Institutional members of the {\TeX} Users Group",
  url =      "http://wwtug.org/instmem.html",
  lastaccessed = "May 27, 2017",
}
```

2.11 Colors

While printed ACM publications are usually black and white, screen mode allows the use of colors. The ACM classes pre-define several colors according to [7]: ACMBLue, ACMYellow, ACMOrange, ACMRed, ACMLightBlue, ACMGreen, ACMPurple, ACMDarkBlue. You can use them in the color assignments.

ACM provides the following recommendation on color use.

The most accessible approach would be to ensure that your article is still readable when printed in greyscale. The most notable reasons for this are:

1. The most common type of inherited Color Vision Deficiency (CVD) is red-green (in which similar-brightness colors that only differ in their amounts of red or green are often confused), and it affects up to 8% of males and 0.5% of females of Northern European descent.
2. The most common type of acquired Color Vision Deficiency (CVD) is blue-yellow (including mild cases for many older adults).
3. Most printing is in Black & White.
4. Situational impairments (e.g., bright sunlight shining on a mobile screen) tend to reduce the entire color gamut, reducing color discriminability.

Note: It is *not* safe to encode information using only variations in color (i.e., only differences in hue and/or saturation), as there is bound to be someone affected!

To ensure that you are using the most accessible colors, ACM recommends that you choose sets of colors to help ensure suitable variations in Black & White using either of the following tools:

1. ColourBrewer: <http://colorbrewer2.org/>
2. ACE: The Accessible Colour Evaluator: <http://daprlab.com/ace/> for designing WCAG 2.0 compliant palettes.

2.12 Other notable packages and typographic remarks

Several other packages are recommended for specialized tasks.

The package *subcaption* [8] is recommended for complex figures with several subplots or subfigures that require separate subcaptioning. The packages *nomencl* [9] and *glossaries* [10] can be used for the automatic creation of the lists of symbols and concepts used.

By default `acmart` prevents all widows and orphans (i.e. lonely lines at the beginning and the end of the page) and hyphenation at the end of the page. This is done by rather strict settings

```
\widowpenalty=10000
\clubpenalty=10000
\brokenpenalty=10000
```

However, this may lead to frustrating results when the authors must obey a page limit. Setting these penalties to smaller values may help if you absolutely need to.

Another problem might be the too strict line breaking rules. Again, a strategically placed `\sloppy` command or putting the problematic paragraph inside `sloppypar` environment might help—but beware the results might be, well, sloppy.

Note that the uppercasing in section titles is done using *textcase* package [11], so command `\NoCaseChange` inside title may help to prevent extraneous uppercasing.

2.13 A note for wizards: `acmart-preload-hook.tex`

Sometimes you need to change the behavior of `acmart`. The usual way to do this is to redefine commands in the preamble. However, these definitions are executed *after* `acmart` is loaded, and certain decisions are made. This presents a number of problems.

For example, one may want to use `titletoc` package with `acmart`. This package should be loaded before `hyperref`. However, since `acmart` loads `hyperref` itself, the line `\usepackage{titletoc}` in the preamble will lead to grief (see <http://tex.stackexchange.com/questions/357265/using-titletoc-with-acm-acmart-style>).

Another example is passing options to package. Suppose you want to use `dvipsnames` option of `xcolor` package. Normally you cannot do this because `acmart` loads this package itself without options.

The file `acmart-preload-hook.tex` may be used to solve these problems. If this file exists, it will be processed before any other package. You can use this file to load packages or pass options to them. For example, if you put in this file

```
\let\LoadClassOrig\LoadClass
\renewcommand\LoadClass[2][\LoadClassOrig[#1]{#2}%
\usepackage{titletoc}}
```

then `titletoc` will be loaded before `hyperref`. If you put in this file

```
\PassOptionsToPackage{dvipsnames}{xcolor}
```

you will pass `dvipsnames` to `xcolor`.

Important note. This hook makes it too easy to create a manuscript which is not acceptable by ACM. Even easier it is to create a file which cannot be compiled. So please do not use it *unless you know what you are doing*. And if you use it, *do not ask for support*. If you decided to use this hook, you are on your own.

3 Implementation

3.1 Identification

We start with the declaration who we are. Most .dtx files put driver code in a separate driver file .drv. We roll this code into the main file, and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{acmart.dtx}
4 </gobble>
5 <class>\ProvidesClass{acmart}
6 [2017/08/29 v1.46 Typesetting articles for Association of
7 Computing Machinery]
```

And the driver code:

```
8 <*gobble>
9 \documentclass{ltxdoc}
10 \usepackage{array,booktabs,amsmath,graphicx,fancyvrb,tabularx}
11 \usepackage[tt=false, type1=true]{libertine}
12 \usepackage[varqu]{zi4}
13 \usepackage[libertine]{newtxmath}
14 \usepackage[tableposition=top]{caption}
15 \usepackage{hypdoc}
16 \PageIndex
17 \CodelineIndex
18 \RecordChanges
19 \EnableCrossrefs
20 \begin{document}
21   \DocInput{acmart.dtx}
22 \end{document}
23 </gobble>
24 <*class>
25 \def\@classname{acmart}
```

3.2 Preload

We preload acmart-preload-hook:

```
26 \InputIfFileExists{acmart-preload-hook.tex}{%
27   \ClassWarning{\@classname}{%
28     I am loading acmart-preload-hook.tex. You are fully responsible
29     for any problems from now on.}}{}
```

3.3 Options

We need xkeyval since some of our options may have values:

```
30 \RequirePackage{xkeyval}
```

We use xstring to check whether user input is integer

```
31 \RequirePackage{xstring}
```

format The possible formats

```

32 \define@choicekey*+{acmart.cls}{format}[\ACM@format\ACM@format@nr]{%
33 manuscript, acmsmall, acmlarge, acmtog, sigconf, siggraph,
34 sigplan, sigchi, sigchi-a}[manuscript]{}{%
35 \ClassError{\@classname}{The option format must be manuscript,
36 acmsmall, acmlarge, acmtog, sigconf, siggraph,
37 sigplan, sigchi or sigchi-a}}
38 \def\@DeclareACMFormat#1{\DeclareOptionX{#1}{\setkeys{acmart.cls}{format=#1}}}
39 \@DeclareACMFormat{manuscript}
40 \@DeclareACMFormat{acmsmall}
41 \@DeclareACMFormat{acmlarge}
42 \@DeclareACMFormat{acmtog}
43 \@DeclareACMFormat{sigconf}
44 \@DeclareACMFormat{siggraph}
45 \@DeclareACMFormat{sigplan}
46 \@DeclareACMFormat{sigchi}
47 \@DeclareACMFormat{sigchi-a}
48 \ExecuteOptionsX{format}

```

\if@ACM@screen Whether we use screen mode

```

49 \define@boolkey+{acmart.cls}[@ACM@]{screen}[true]{%
50 \if@ACM@screen
51 \PackageInfo{\@classname}{Using screen mode}%
52 \else
53 \PackageInfo{\@classname}{Not using screen mode}%
54 \fi}{\PackageError{\@classname}{Option screen can be either true or
55 false}}
56 \ExecuteOptionsX{screen=false}

```

\if@ACM@acmthm Whether we define theorem-like environments.

```

57 \define@boolkey+{acmart.cls}[@ACM@]{acmthm}[true]{%
58 \if@ACM@acmthm
59 \PackageInfo{\@classname}{Requiring acmthm}%
60 \else
61 \PackageInfo{\@classname}{Suppressing acmthm}%
62 \fi}{\PackageError{\@classname}{Option acmthm can be either true or
63 false}}
64 \ExecuteOptionsX{acmthm=true}

```

\if@ACM@review Whether we use review mode

```

65 \define@boolkey+{acmart.cls}[@ACM@]{review}[true]{%
66 \if@ACM@review
67 \PackageInfo{\@classname}{Using review mode}%
68 \else
69 \PackageInfo{\@classname}{Not using review mode}%
70 \fi}{\PackageError{\@classname}{Option review can be either true or
71 false}}
72 \ExecuteOptionsX{review=false}

```

```

\if@ACM@authorversion Whether we use author's version
73 \define@boolkey+{acmart.cls}[@ACM@]{authorversion}[true]{%
74   \if@ACM@authorversion
75     \PackageInfo{\@classname}{Using authorversion mode}%
76   \else
77     \PackageInfo{\@classname}{Not using authorversion mode}%
78   \fi}{\PackageError{\@classname}{Option authorversion can be either true or
79     false}}
80 \ExecuteOptionsX{authorversion=false}

```

\if@ACM@natbib@override

```

\if@ACM@natbib Whether we use natbib mode
81 \define@boolkey+{acmart.cls}[@ACM@]{natbib}[true]{%
82   \if@ACM@natbib
83     \PackageInfo{\@classname}{Explicitly selecting natbib mode}%
84   \else
85     \PackageInfo{\@classname}{Explicitly deselecting natbib mode}%
86   \fi}{\PackageError{\@classname}{Option natbib can be either true or
87     false}}
88 \ExecuteOptionsX{natbib=true}

```

```

\if@ACM@anonymous Whether we use anonymous mode
89 \define@boolkey+{acmart.cls}[@ACM@]{anonymous}[true]{%
90   \if@ACM@anonymous
91     \PackageInfo{\@classname}{Using anonymous mode}%
92   \else
93     \PackageInfo{\@classname}{Not using anonymous mode}%
94   \fi}{\PackageError{\@classname}{Option anonymous can be either true or
95     false}}
96 \ExecuteOptionsX{anonymous=false}

```

```

\if@ACM@timestamp Whether we use timestamp mode
97 \define@boolkey+{acmart.cls}[@ACM@]{timestamp}[true]{%
98   \if@ACM@timestamp
99     \PackageInfo{\@classname}{Using timestamp mode}%
100   \else
101     \PackageInfo{\@classname}{Not using timestamp mode}%
102   \fi}{\PackageError{\@classname}{Option timestamp can be either true or
103     false}}
104 \ExecuteOptionsX{timestamp=false}

```

```

\if@ACM@authordraft Whether we use authordraft mode
105 \define@boolkey+{acmart.cls}[@ACM@]{authordraft}[true]{%
106   \if@ACM@authordraft
107     \PackageInfo{\@classname}{Using authordraft mode}%
108     \@ACM@timestamptrue
109     \@ACM@reviewtrue
110   \else

```

```

111 \PackageInfo{\@classname}{Not using authordraft mode}%
112 \fi}{\PackageError{\@classname}{Option authordraft can be either true or
113     false}}
114 \ExecuteOptionsX{authordraft=false}

```

\ACM@fontsize The font size to pass to the base class

```

115 \def\ACM@fontsize{}
116 \DeclareOptionX{9pt}{\edef\ACM@fontsize{\CurrentOption}}
117 \DeclareOptionX{10pt}{\edef\ACM@fontsize{\CurrentOption}}
118 \DeclareOptionX{11pt}{\edef\ACM@fontsize{\CurrentOption}}
119 \DeclareOptionX{12pt}{\edef\ACM@fontsize{\CurrentOption}}

120 \DeclareOptionX{draft}{\PassOptionsToClass{\CurrentOption}{amsart}}
121 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
122 \ProcessOptionsX
123 \ClassInfo{\@classname}{Using format \ACM@format, number \ACM@format@nr}

```

3.4 Setting switches

\if@ACM@manuscript Whether we use manuscript mode

```

124 \newif\if@ACM@manuscript

```

\if@ACM@journal There are two kinds of publications: journals and books

```

125 \newif\if@ACM@journal

```

\if@ACM@sigchiamode The formatting of SIGCHI abstracts is quite unusual. We have a special switch for them.

```

126 \newif\if@ACM@sigchiamode

```

Setting up switches

```

127 \ifnum\ACM@format@nr=5\relax % siggraph
128 \ClassWarning{\@classname}{The format 'siggraph' is now obsolete.
129     I am switching to sigconf.}
130 \setkeys{acmart.cls}{format=sigconf}
131 \fi
132 \ifnum\ACM@format@nr=0\relax
133 \@ACM@manuscripttrue
134 \else
135 \@ACM@manuscriptfalse
136 \fi
137 \@ACM@sigchiamodefalse
138 \ifcase\ACM@format@nr
139 \relax % manuscript
140 \@ACM@journaltrue
141 \or % acmsmall
142 \@ACM@journaltrue
143 \or % acmlarge
144 \@ACM@journaltrue
145 \or % acmtog

```

```

146 \ACM@journaltrue
147 \or % sigconf
148 \ACM@journalfalse
149 \or % siggraph
150 \ACM@journalfalse
151 \or % sigplan
152 \ACM@journalfalse
153 \or % sigchi
154 \ACM@journalfalse
155 \or % sigchi-a
156 \ACM@journalfalse
157 \ACM@sigchiamodetrue
158 \fi

```

3.5 Loading base class and package

At this point we either have \ACM@fontsize, or use defaults

```

159 \ifx\ACM@fontsize\@empty
160 \ifcase\ACM@format@nr
161 \relax % manuscript
162 \def\ACM@fontsize{9pt}%
163 \or % acmsmall
164 \def\ACM@fontsize{10pt}%
165 \or % acmlarge
166 \def\ACM@fontsize{10pt}%
167 \or % acmtog
168 \def\ACM@fontsize{9pt}%
169 \or % sigconf
170 \def\ACM@fontsize{9pt}%
171 \or % siggraph
172 \def\ACM@fontsize{9pt}%
173 \or % sigplan
174 \def\ACM@fontsize{10pt}%
175 \or % sigchi
176 \def\ACM@fontsize{10pt}%
177 \or % sigchi-a
178 \def\ACM@fontsize{10pt}%
179 \fi
180 \fi
181 \ClassInfo{\@classname}{Using fontsize \ACM@fontsize}
182 \LoadClass[\ACM@fontsize, reqno]{amsart}
183 \RequirePackage{microtype}

```

We need etoolbox for delayed code

```
184 \RequirePackage{etoolbox}
```

We need totpages package to calculate the number of pages and refcount to use the number

```

185 \RequirePackage{refcount}
186 \RequirePackage{totpages}

```


The `amsmath \collect@body` is defined using `\def`. We load `environ` to access the `\long` version of the command

```
187 \RequirePackage{environ}
```

We use `setspace` for doublespacing

```
188 \if@ACM@manuscript
```

```
189 \RequirePackage{setspace}
```

```
190 \onehalfspacing
```

```
191 \fi
```

We need `textcase` for better upcasing

```
192 \RequirePackage{textcase}
```

Citations. We patch `\setcitestyle` to allow, e.g., `\setcitestyle{sort}` and `\setcitestyle{nosort}`. We patch `\citestyle` to warn about undefined citation styles.

```
193 \if@ACM@natbib
```

```
194 \RequirePackage{natbib}
```

```
195 \renewcommand{\bibsection}{%
```

```
196 \section*{\refname}%
```

```
197 \phantomsection\addcontentsline{toc}{section}{\refname}%
```

```
198 }
```

```
199 \renewcommand{\bibfont}{\bibliofont}
```

```
200 \renewcommand{\setcitestyle}[1]{
```

```
201 \@for\@tempa:=#1\do
```

```
202 {\def\@tempb{round}\ifx\@tempa\@tempb
```

```
203 \renewcommand\NAT@open{(\}\renewcommand\NAT@close{)}\fi
```

```
204 \def\@tempb{square}\ifx\@tempa\@tempb
```

```
205 \renewcommand\NAT@open{[}\renewcommand\NAT@close{]}\fi
```

```
206 \def\@tempb{angle}\ifx\@tempa\@tempb
```

```
207 \renewcommand\NAT@open{$<$}\renewcommand\NAT@close{$>$}\fi
```

```
208 \def\@tempb{curly}\ifx\@tempa\@tempb
```

```
209 \renewcommand\NAT@open{\{}\renewcommand\NAT@close{\}}\fi
```

```
210 \def\@tempb{semicolon}\ifx\@tempa\@tempb
```

```
211 \renewcommand\NAT@sep{;}\fi
```

```
212 \def\@tempb{colon}\ifx\@tempa\@tempb
```

```
213 \renewcommand\NAT@sep{;}\fi
```

```
214 \def\@tempb{comma}\ifx\@tempa\@tempb
```

```
215 \renewcommand\NAT@sep{,}\fi
```

```
216 \def\@tempb{authoryear}\ifx\@tempa\@tempb
```

```
217 \NAT@numbersfalse\fi
```

```
218 \def\@tempb{numbers}\ifx\@tempa\@tempb
```

```
219 \NAT@numberstrue\NAT@superfalse\fi
```

```
220 \def\@tempb{super}\ifx\@tempa\@tempb
```

```
221 \NAT@numberstrue\NAT@supertrue\fi
```

```
222 \def\@tempb{nobibstyle}\ifx\@tempa\@tempb
```

```
223 \let\bibstyle=\@gobble\fi
```

```
224 \def\@tempb{bibstyle}\ifx\@tempa\@tempb
```

```
225 \let\bibstyle=\@citestyle\fi
```

```
226 \def\@tempb{sort}\ifx\@tempa\@tempb
```

```

227 \def\NAT@sort{\@ne}\fi
228 \def\@tempb{nosort}\ifx\@tempa\@tempb
229 \def\NAT@sort{\@z}\fi
230 \def\@tempb{compress}\ifx\@tempa\@tempb
231 \def\NAT@cmprs{\@ne}\fi
232 \def\@tempb{nocompress}\ifx\@tempa\@tempb
233 \def\NAT@cmprs{\@z}\fi
234 \def\@tempb{sort&compress}\ifx\@tempa\@tempb
235 \def\NAT@sort{\@ne}\def\NAT@cmprs{\@ne}\fi
236 \def\@tempb{mcite}\ifx\@tempa\@tempb
237 \let\NAT@merge\@ne\fi
238 \def\@tempb{merge}\ifx\@tempa\@tempb
239 \ifnum{\NAT@merge<\tw}{\let\NAT@merge\tw}\fi
240 \def\@tempb{elide}\ifx\@tempa\@tempb
241 \ifnum{\NAT@merge<\thr}{\let\NAT@merge\thr}\fi
242 \def\@tempb{longnamesfirst}\ifx\@tempa\@tempb
243 \NAT@longnamestrue\fi
244 \def\@tempb{nonamebreak}\ifx\@tempa\@tempb
245 \def\NAT@nmfmt#1{\mbox{\NAT@up#1}}\fi
246 \expandafter\NAT@find@eq\@tempa=\relax\@nil
247 \if\@tempc\relax\else
248 \expandafter\NAT@rem@eq\@tempc
249 \def\@tempb{open}\ifx\@tempa\@tempb
250 \xdef\NAT@open{\@tempc}\fi
251 \def\@tempb{close}\ifx\@tempa\@tempb
252 \xdef\NAT@close{\@tempc}\fi
253 \def\@tempb{aysep}\ifx\@tempa\@tempb
254 \xdef\NAT@aysep{\@tempc}\fi
255 \def\@tempb{yysep}\ifx\@tempa\@tempb
256 \xdef\NAT@yrsep{\@tempc}\fi
257 \def\@tempb{notesep}\ifx\@tempa\@tempb
258 \xdef\NAT@cmt{\@tempc}\fi
259 \def\@tempb{citesep}\ifx\@tempa\@tempb
260 \xdef\NAT@sep{\@tempc}\fi
261 \fi
262 }%
263 \NAT@@setcites
264 }
265 \renewcommand\citestyle[1]{%
266 \ifcsname bibstyle@#1\endcsname%
267 \csname bibstyle@#1\endcsname\let\bibstyle\@gobble%
268 \else%
269 \@latex@error{Undefined ‘#1’ citestyle}%
270 \fi
271 }%
272 \fi

```

\bibstyle@acmauthoryear The default author-year format:

```

273 \newcommand{\bibstyle@acmauthoryear}{%
274 \setcitestyle{%

```

```

275    authoryear,%
276    open={},close={},citesep={;},%
277    aysep={},yysep={,},%
278    notesep={, }}

```

`\bibstyle@acmnumeric` The default numeric format:

```

279 \newcommand{\bibstyle@acmnumeric}{%
280   \setcitestyle{%
281     numbers,sort&compress,%
282     open={},close={},citesep={,},%
283     notesep={, }}

```

The default is numeric:

```

284 \if@ACM@natbib
285 \citestyle{acmnumeric}
286 \fi

```

`\@startsection` Before we call `hyperref`, we redefine `\startsection` commands to their \LaTeX defaults, since `amsart` ones are too AMS-specific. We need to do this early since we want `hyperref` to have a chance to redefine them again:

```

287 \def\@startsection#1#2#3#4#5#6{%
288   \if@noskipsec \leavevmode \fi
289   \par
290   \@tempskipa #4\relax
291   \@afterindenttrue
292   \ifdim \@tempskipa <\z@
293     \@tempskipa -\@tempskipa \@afterindentfalse
294   \fi
295   \if@nobreak
296     \everypar{}%
297   \else
298     \addpenalty\@secpenalty\addvspace\@tempskipa
299   \fi
300   \@ifstar
301     {\@ssect{#3}{#4}{#5}{#6}}%
302     {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}
303 \def\@sect#1#2#3#4#5#6[#7]#8{%
304   \edef\@toclevel{\ifnum#2=\@m 0\else\number#2\fi}%
305   \ifnum #2>\c@secnumdepth
306     \let\@svsec\@empty
307   \else
308     \refstepcounter{#1}%
309     \protected@edef\@svsec{\@secntformat{#1}\relax}%
310   \fi
311   \@tempskipa #5\relax
312   \ifdim \@tempskipa>\z@
313     \begingroup
314       #6{%
315         \@hangfrom{\hskip #3\relax\@svsec}%

```

```

316         \interlinepenalty \@M #8\@par}%
317     \endgroup
318     \csname #1mark\endcsname{#7}%
319     \ifnum #2>\c@secnumdepth \else
320         \@tochangmeasure{\csname the#1\endcsname}%
321     \fi
322     \addcontentsline{toc}{#1}{%
323         \ifnum #2>\c@secnumdepth \else
324             \protect\numberline{\csname the#1\endcsname}%
325         \fi
326         #7}%
327 \else
328     \def\@svsechd{%
329         #6{\hspace #3\relax
330             \@svsec #8}%
331         \csname #1mark\endcsname{#7}%
332         \ifnum #2>\c@secnumdepth \else
333             \@tochangmeasure{\csname the#1\endcsname\space}%
334         \fi
335         \addcontentsline{toc}{#1}{%
336             \ifnum #2>\c@secnumdepth \else
337                 \protect\numberline{\csname the#1\endcsname}%
338             \fi
339             #7}}%
340 \fi
341 \xsect{#5}}
342 \def\xsect#1{%
343     \@tempskipa #1\relax
344     \ifdim \@tempskipa>\z@
345         \par \nobreak
346         \vskip \@tempskipa
347         \afterheading
348     \else
349         \@nobreakfalse
350         \global\@noskipsectrue
351         \everypar{%
352             \if@noskipsec
353                 \global\@noskipsecfalse
354                 {\setbox\z@\lastbox}%
355                 \clubpenalty\@M
356                 \begingroup \@svsechd \endgroup
357                 \unskip
358                 \@tempskipa #1\relax
359                 \hspace -\@tempskipa
360             \else
361                 \clubpenalty \@clubpenalty
362             \everypar{}%
363         \fi}%
364 \fi
365 \ignorespaces}

```

```

366 \def\@secntformat#1{\csname the#1\endcsname\quad}
367 \def\@sect#1#2#3#4#5{%
368   \@tempskipa #3\relax
369   \ifdim \@tempskipa>\z@
370     \begingroup
371       #4{%
372         \@hangfrom{\hskip #1}%
373         \interlinepenalty \@M #5\@par}%
374     \endgroup
375   \else
376     \def\@svsechd{#4\hskip #1\relax #5}%
377   \fi
378   \@xsect{#3}}

```

\@startsection Amsart redefines \@startsection. Here we redefine it again to make TOC working

```

379 \def\@starttoc#1#2{\begingroup\makeatletter
380   \setTrue{#1}%
381   \par\removelastskip\vskip\z@skip
382   \@startsection{section}\@M\z@{\linespacing\@plus\linespacing}%
383     {.5\linespacing}{\centering\contentsnamefont}{#2}%
384   \@input{\jobname.#1}%
385   \if@filesw
386     \xp\newwrite\csname tf@#1\endcsname
387     \immediate\xp\openout\csname tf@#1\endcsname \jobname.#1\relax
388   \fi
389   \global\@nobeakfalse \endgroup
390   \addvspace{32\p@\@plus14\p@}%
391 }

```

\l@section Section spacing is more generous than for amsart

```

392 \def\l@section{\@tocline{1}{0pt}{1pc}{2pc}{}}

```

\l@subsection Amsart has too large spacing

```

393 \def\l@subsection{\@tocline{2}{0pt}{1pc}{3pc}{}}

```

\l@subsubsection Amsart has too large spacing

```

394 \def\l@subsubsection{\@tocline{2}{0pt}{1pc}{5pc}{}}

```

And hyperref

```

395 \let\@footnotemark@nolink\@footnotemark
396 \let\@footnotetext@nolink\@footnotetext
397 \RequirePackage[bookmarksnumbered,unicode]{hyperref}
398 \pdfstringdefDisableCommands{%
399   \def\unskip{}%
400   \def\textbullet{-}%
401   \def\textrightarrow{->}%
402   \def\footnotemark{}%
403 }
404 \urlstyle{rm}

```

```

405 \ifcase\ACM@format@nr
406 \relax % manuscript
407 \or % acmsmall
408 \or % acmlarge
409 \or % acmtog
410 \or % sigconf
411 \or % siggraph
412 \or % sigplan
413 \urlstyle{sf}
414 \or % sigchi
415 \or % sigchi-a
416 \urlstyle{sf}
417 \fi
418 \AtEndPreamble{%
419   \if@ACM@screen
420     \hypersetup{colorlinks,
421       linkcolor=ACMRed,
422       citecolor=ACMPurple,
423       urlcolor=ACMDarkBlue,
424       filecolor=ACMDarkBlue}
425   \else
426     \hypersetup{hidelinks}
427   \fi}
  Bibliography mangling.
428 \if@ACM@natbib
429   \let\cite\Ncite
430   \let\cite\citep
431   \let\citeANP\citeauthor
432   \let\citeNN\citeyearpar
433   \let\citeyearNP\citeyear
434   \let\citeyear\citeyearpar
435   \let\citeNP\citealt
436   \DeclareRobustCommand\citeA
437     {\begingroup\NAT@swafalse
438       \let\NAT@ctype\@ne\NAT@partrue\NAT@fullfalse\NAT@open\NAT@citetc}%
439   \providecommand\newblock{}%
440 \else
441   \AtBeginDocument{%
442     \let\shortcite\cite%
443     \providecommand\citename[1]{#1}}
444 \fi
445 \newcommand\shortcite[2][{}]{%
446   \ifNAT@numbers\cite[#1]{#2}\else\citeyear[#1]{#2}\fi}

```

`\bibliographystyle` Amsart redefines `\bibliographystyle` since it prefers AMS bibliography. We turn it back to \LaTeX definition:

```

447 \def\bibliographystyle#1{%
448   \ifx\@begindocumenthook\@undefined\else
449     \expandafter\AtBeginDocument

```

```

450 \fi
451 {\if@filesw
452 \immediate\write\@auxout{\string\bibstyle{#1}}%
453 \fi}}

```

Graphics and color

```

454 \RequirePackage{graphicx, xcolor}

We define ACM colors according to [7]:

455 \definecolor[named]{ACMBlue}{cmyk}{1,0.1,0,0.1}
456 \definecolor[named]{ACMYellow}{cmyk}{0,0.16,1,0}
457 \definecolor[named]{ACMOrange}{cmyk}{0,0.42,1,0.01}
458 \definecolor[named]{ACMRed}{cmyk}{0,0.90,0.86,0}
459 \definecolor[named]{ACMLightBlue}{cmyk}{0.49,0.01,0,0}
460 \definecolor[named]{ACMGreen}{cmyk}{0.20,0,1,0.19}
461 \definecolor[named]{ACMPurple}{cmyk}{0.55,1,0,0.15}
462 \definecolor[named]{ACMDarkBlue}{cmyk}{1,0.58,0,0.21}

```

Author draft mode

```

463 \if@ACM@authordraft
464 \RequirePackage{draftwatermark}
465 \SetWatermarkFontSize{0.5in}
466 \SetWatermarkColor[gray]{.9}
467 \SetWatermarkText{\parbox{12em}{\centering
468 Unpublished working draft\
469 Not for distribution}}
470 \fi

```

3.6 Paper size and paragraphing

We use geometry for dimensions. Note the presently margins do not depend on the font size option - maybe we will need to change this. See <https://github.com/borisveytsman/acmart/issues/5#issuecomment-272881329>.

```

471 \RequirePackage{geometry}
472 \ifcase\ACM@format@nr
473 \relax % manuscript
474 \geometry{letterpaper,head=13pt,
475 marginparwidth=6pc,heightrounded}%
476 \or % acmsmall
477 \geometry{twoside=true,
478 includeheadfoot, head=13pt, foot=2pc,
479 paperwidth=6.75in, paperheight=10in,
480 top=58pt, bottom=44pt, inner=46pt, outer=46pt,
481 marginparwidth=2pc,heightrounded
482 }%
483 \or % acmlarge
484 \geometry{twoside=true, head=13pt, foot=2pc,
485 paperwidth=8.5in, paperheight=11in,
486 includeheadfoot,
487 top=78pt, bottom=114pt, inner=81pt, outer=81pt,

```

```

488     marginparwidth=4pc,heightrounded
489   }%
490 \or % acmtog
491   \geometry{twoside=true, head=13pt, foot=2pc,
492     paperwidth=8.5in, paperheight=11in,
493     includeheadfoot, columnsep=24pt,
494     top=52pt, bottom=75pt, inner=52pt, outer=52pt,
495     marginparwidth=2pc,heightrounded
496   }%
497 \or % sigconf
498   \geometry{twoside=true, head=13pt,
499     paperwidth=8.5in, paperheight=11in,
500     includeheadfoot, columnsep=2pc,
501     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
502     marginparwidth=2pc,heightrounded
503   }%
504 \or % siggraph
505   \geometry{twoside=true, head=13pt,
506     paperwidth=8.5in, paperheight=11in,
507     includeheadfoot, columnsep=2pc,
508     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
509     marginparwidth=2pc,heightrounded
510   }%
511 \or % sigplan
512   \geometry{twoside=true, head=13pt,
513     paperwidth=8.5in, paperheight=11in,
514     includeheadfoot=false, columnsep=2pc,
515     top=1in, bottom=1in, inner=0.75in, outer=0.75in,
516     marginparwidth=2pc,heightrounded
517   }%
518 \or % sigchi
519   \geometry{twoside=true, head=13pt,
520     paperwidth=8.5in, paperheight=11in,
521     includeheadfoot, columnsep=2pc,
522     top=66pt, bottom=73pt, inner=54pt, outer=54pt,
523     marginparwidth=2pc,heightrounded
524   }%
525 \or % sigchi-a
526   \geometry{twoside=false, head=13pt,
527     paperwidth=11in, paperheight=8.5in,
528     includeheadfoot, marginparsep=72pt,
529     marginparwidth=170pt, columnsep=20pt,
530     top=72pt, bottom=72pt, left=314pt, right=72pt
531   }%
532   \@mparswitchfalse
533   \reversemarginpar
534 \fi

```

\parindent Paragraphing

\parskip 535 \setlength\parindent{10\p@}


```

536 \setlength\parskip{\z@}
537 \ifcase\ACM@format@nr
538 \relax % manuscript
539 \or % acmsmall
540 \or % acmlarge
541 \or % acmtog
542 \setlength\parindent{9\p@}%
543 \or % sigconf
544 \or % siggraph
545 \or % sigplan
546 \or % sigchi
547 \or % sigchi-a
548 \fi

```

`\normalparindent` amsart defines the `\normalparindent` length and initializes it to 12pt (the value of `\parindent` in amsart). It is later used to set the `\listparindent` length in the quotation environment and the `\parindent` length in the `\@footnotetext` command. We set `\normalparindent` to the value of `\parindent` as selected by acmart for consistent paragraph indents.

```

549 \setlength\normalparindent{\parindent}

```

Footnotes require some consideration. We have several layers of footnotes: front-matter footnotes, “regular” footnotes and the special insert for bibstrip. In the old ACM classes bibstrip was a `\@float`. The problem with floats is that they tend to, well, float—and we want the guarantee they stay.

We use *manyfoot* for layered footnotes instead.

`\copyrightpermissionfootnoterule` This is the footnote rule that separates bibstrip from the rest of the paper. It is a full width rule.

```

550 \def\copyrightpermissionfootnoterule{\kern-3\p@
551 \hrule \@width \columnwidth \kern 2.6\p@}

552 \RequirePackage{manyfoot}
553 \SelectFootnoteRule[2]{copyrightpermission}
554 \DeclareNewFootnote{authorsaddresses}
555 \SelectFootnoteRule[2]{copyrightpermission}
556 \DeclareNewFootnote{copyrightpermission}

```

`\footnoterule` Tschichold’s rules:

```

557 \def\footnoterule{\kern-3\p@
558 \hrule \@width 4pc \kern 2.6\p@}

```

`\endminipage` We do not use footnote rules in minipages

```

559 \def\endminipage{%
560 \par
561 \unskip
562 \ifvoid\@mpfootins\else
563 \vskip\skip\@mpfootins
564 \normalcolor

```

```

565     \unvbox\@mpfootins
566     \fi
567     \@minipagefalse    %% added 24 May 89
568     \color@endgroup
569     \egroup
570     \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}}

\@makefnmark We do not use indentation for footnotes
571 \def\@makefnmark{\noindent\@makefnmark}

\@footnotetext In sigchi-a mode our footnotes are on the margins!
572 \if@ACM@sigchiamode
573 \long\def\@footnotetext#1{\marginpar{%
574     \reset@font\small
575     \interlinepenalty\interfootnotelinepenalty
576     \protected@edef\@currentlabel{%
577         \csname p@footnote\endcsname\@thefnmark
578     }%
579     \color@begingroup
580     \@makefnmark{%
581         \rule{z@{footnotesep}\ignorespaces#1\@finalstrut\strutbox}%
582     \color@endgroup}}%
583 \fi

\@mpfootnotetext We want the footnotes in minipages centered:
584 \long\def\@mpfootnotetext#1{%
585     \global\setbox\@mpfootins\vbox{%
586         \unvbox\@mpfootins
587         \reset@font\footnotesize
588         \hsize\columnwidth
589         \@parboxrestore
590         \protected@edef\@currentlabel
591             {\csname p@mpfootnote\endcsname\@thefnmark}%
592         \color@begingroup\centering
593         \@makefnmark{%
594             \rule{z@{footnotesep}\ignorespaces#1\@finalstrut\strutbox}%
595         \color@endgroup}}

\@makefnmark AMS classes use a buggy definition of \makefnmark. We revert to the standard one.
596 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}

\@textbottom Added some stretch according to David Carlisle's advice at http://tex.stackexchange.com/a/62318/5522
597 \def\@textbottom{\vskip \z@ \@plus 1pt}
598 \let\@texttop\relax

```

3.7 Fonts

Somehow PDF_TEX and XeTeX require different incantations to make PDF compliant with the current Acrobat bugs. Xpdf is much better.

The code below is by Ross Moore.

```
599 \RequirePackage{iftex}
600 \ifPDFTeX
601 \input{glyphtounicode}
602 \pdfglyphtounicode{f_f}{FB00}
603 \pdfglyphtounicode{f_f_i}{FB03}
604 \pdfglyphtounicode{f_f_l}{FB04}
605 \pdfglyphtounicode{f_i}{FB01}
606 \pdfglyphtounicode{t_t}{00740074}
607 \pdfglyphtounicode{f_t}{00660074}
608 \pdfglyphtounicode{T_h}{00540068}
609 \pdfgentounicode=1
610 \fi
611 \RequirePackage{cmap}
```

\if@ACM@newfonts Whether we load the new fonts

```
612 \newif\if@ACM@newfonts
613 \@ACM@newfontstrue
614 \IfFileExists{libertine.sty}{\ClassWarning{\@classname}{You do not
615   have libertine package installed. Please upgrade your
616   TeX}\@ACM@newfontsfalse}
617 \IfFileExists{zi4.sty}{\ClassWarning{\@classname}{You do not
618   have zi4 package installed. Please upgrade your TeX}\@ACM@newfontsfalse}
619 \IfFileExists{newtxmath.sty}{\ClassWarning{\@classname}{You do not
620   have newtxmath package installed. Please upgrade your
621   TeX}\@ACM@newfontsfalse}
```

We use Libertine throughout.

```
622 \if@ACM@newfonts
623 \RequirePackage[tt=false, type1=true]{libertine}
624 \RequirePackage[varqu]{zi4}
625 \RequirePackage[libertine]{newtxmath}
626 \RequirePackage[T1]{fontenc}
627 \fi
```

\liningnums Libertine defines \liningnums, which makes fontspec unhappy. While we do not use fontspec, some users do...

```
628 \let\liningnums\@undefined
629 \AtEndPreamble{%
630   \DeclareTextFontCommand{\liningnums}{\libertineLF}}
```

The SIGCHI extended abstracts are sans serif:

```
631 \if@ACM@sigchiamode
632   \renewcommand{\familydefault}{\sfdefault}
633 \fi
```

3.8 Floats

We use caption package

```

634 \RequirePackage{caption, float}
635 \captionsetup[table]{position=top}
636 \if@ACM@journal
637   \captionsetup{labelfont={sf, small},
638     textfont={sf, small}, margin=\z@}
639   \captionsetup[figure]{name={Fig.}}
640 \else
641   \captionsetup{labelfont={bf},
642     textfont={bf}, labelsep=colon, margin=\z@}
643   \ifcase\ACM@format@nr
644   \relax % manuscript
645   \or % acmsmall
646   \or % acmlarge
647   \or % acmtog
648   \or % sigconf
649   \or % siggraph
650     \captionsetup{textfont={it}}
651   \or % sigplan
652     \captionsetup{labelfont={bf},
653       textfont={normalfont}, labelsep=period, margin=\z@}
654   \or % sigchi
655     \captionsetup[figure]{labelfont={bf, small},
656       textfont={bf, small}}
657   \or % sigchi-a
658     \captionsetup[figure]{labelfont={bf, small},
659       textfont={bf, small}}
660   \fi
661 \fi

```

sidebar The sidebar environment:

```

662 \newfloat{sidebar}{}{sbar}
663 \floatname{sidebar}{Sidebar}
664 \renewenvironment{sidebar}{}{\Collect@Body\@sidebar}{}

```

\@sidebar The processing of the saved text

```

665 \long\def\@sidebar#1{\bgroup\captionsetup{type=sidebar}%
666   \marginpar{\small#1}\egroup}

```

marginfigure The marginfigure environment:

```

667 \newenvironment{marginfigure}{}{\Collect@Body\@marginfigure}{}

```

\@marginfigure The processing of the saved text

```

668 \long\def\@marginfigure#1{\bgroup\captionsetup{type=figure}%
669   \marginpar{\centering\small#1}\egroup}

```

marginatable The marginatable environment:

```

670 \newenvironment{marginatable}{}{\Collect@Body\@marginatable}{}

```

`\@margintable` The processing of the saved text

```
671 \long\def\@margintable#1{\bgroup\captionsetup{type=table}%  
672   \marginpar{\centering\small#1}\egroup}
```

SIGCHI extended abstract provides an interesting possibility to push into the margin. Here we use `figure*` and `table*` for this.

`\fulltextwidth` We define the width of the boxes as

```
673 \newdimen\fulltextwidth  
674 \fulltextwidth=\dimexpr(\textwidth+\marginparwidth+\marginparsep)
```

`\@dblfloat` We redefine the double float command. First, we make the size bigger. Second, our default position is going to be `tp` (to give marginalia a chance)

```
675 \if@ACM@sigchiamode  
676 \def\@dblfloat{\bgroup\columnwidth=\fulltextwidth  
677   \let\endfloatbox\endwidefloatbox  
678   \def\@fpsaddddefault{\def\@fps{tp}}%  
679   \@float}  
680 \fi
```

`\enddblfloat` And the end. Just adding a `\bgroup`.

```
681 \if@ACM@sigchiamode  
682 \def\enddblfloat{%  
683   \end@float\egroup}  
684 \fi
```

`\@endwidefloatbox` This is the end of a wide box - we basically move everything to the left

```
685 \def\@endwidefloatbox{%  
686   \par\vskip\z@skip  
687   \@minipagefalse  
688   \outer@nobreak  
689   \egroup  
690   \color@endbox  
691   \global\setbox\@currbox=\vbox{\moveleft  
692     \dimexpr(\fulltextwidth-\textwidth)\box\@currbox}%  
693   \wd\@currbox=\textwidth  
694 }
```

3.9 Lists

```
695 \ifcase\ACM@format@nr  
696 \relax % manuscript  
697 \or % acmsmall  
698 \or % acmlarge  
699 \or % acmtog  
700 \or % sigconf  
701 \or % siggraph  
702 \or % sigplan  
703 \def\labelenumi{\theenumi.}
```

```

704 \def\labelenumii{\theenumii.}
705 \def\labelenumiii{\theenumiii.}
706 \def\labelenumiv{\theenumiv.}
707 \or % sigchi
708 \or % sigchi-a
709 \fi

```

AMS uses generous margins for the lists. Note that `amsart` defines `\leftmargin` values for list levels at begin document, so we must redefine them in the same manner. Also, note that `amsart` redefines `enumerate` and `itemize` environments with a `\makelabel` command that uses `\llap`, so the `\labelwidth` value is (effectively) irrelevant; nonetheless, we follow `amsart` and set `\labelwidth` to `\leftmargin` minus `\labelsep`.

```

710 \newdimen\@ACM@labelwidth
711 \AtBeginDocument{%
712   \setlength\labelsep{4pt}
713   \setlength{\@ACM@labelwidth}{6.5pt}
714
715   %% First-level list: when beginning after the first line of an
716   %% indented paragraph or ending before an indented paragraph, labels
717   %% should not hang to the left of the preceding/following text.
718   \setlength\leftmarginii{\z@}
719   \addtolength\leftmarginii{\parindent}
720   \addtolength\leftmarginii{2\labelsep}
721   \addtolength\leftmarginii{\@ACM@labelwidth}
722
723   %% Second-level and higher lists.
724   \setlength\leftmarginiii{\z@}
725   \addtolength\leftmarginiii{0.5\labelsep}
726   \addtolength\leftmarginiii{\@ACM@labelwidth}
727   \setlength\leftmarginiiii{\leftmarginii}
728   \setlength\leftmarginiv{\leftmarginiii}
729   \setlength\leftmarginv{\leftmarginiv}
730   \setlength\leftmarginvi{\leftmarginv}
731   \@listi}
732 \newskip\listisep
733 \listisep\smallskipamount
734 \def\@listI{\leftmargin\leftmarginii
735   \labelwidth\leftmarginii \advance\labelwidth-\labelsep
736   \listparindent\z@
737   \topsep\listisep}
738 \let\@listi\@listI
739 \def\@listii{\leftmargin\leftmarginii
740   \labelwidth\leftmarginiii \advance\labelwidth-\labelsep
741   \topsep\z@skip}
742 \def\@listiii{\leftmargin\leftmarginiii
743   \labelwidth\leftmarginiiii \advance\labelwidth-\labelsep}
744 \def\@listiv{\leftmargin\leftmarginiv
745   \labelwidth\leftmarginiv \advance\labelwidth-\labelsep}
746 \def\@listv{\leftmargin\leftmarginv
747   \labelwidth\leftmarginv \advance\labelwidth-\labelsep}

```

```

748 \def\@listvi{\leftmargin\leftmarginvi
749   \labelwidth\leftmarginvi \advance\labelwidth-\labelsep}
\descriptionlabel We do not use default colon as \amsart does:
750 \renewcommand{\descriptionlabel}[1]{\upshape\bfseries #1}

\description Make description environment indentation consistent with that of itemize and
enumerate environments.
751 \renewenvironment{description}{\list{}{\%
752   \labelwidth\@ACM\labelwidth
753   \let\makelabel\descriptionlabel}%
754 }{
755   \endlist
756 }
757 \let\enddescription=\endlist % for efficiency

```

3.10 Top matter data

We use keyval interface to define journal title and relevant information

```

758 \define@choicekey*+{ACM}{acmJournal}[\@journalCode\@journalCode@nr]{%
759   CIE,%
760   CSUR,%
761   IMWUT,%
762   JACM,%
763   JDIQ,%
764   JEA,%
765   JERIC,%
766   JETC,%
767   JOCCH,%
768   PACMHCI,%
769   PACMPL,%
770   POMACS,%
771   TAAS,%
772   TACCESS,%
773   TACO,%
774   TALG,%
775   TALLIP,%
776   TAP,%
777   TCPS,%
778   TEAC,%
779   TECS,%
780   TIIS,%
781   TISSEC,%
782   TIST,%
783   TKDD,%
784   TMIS,%
785   TOCE,%
786   TOCHI,%
787   TOCL,%

```

```

788 TOCS,%
789 TOCT,%
790 TODAES,%
791 TODS,%
792 TOG,%
793 TOIS,%
794 TOIT,%
795 TOMACS,%
796 TOMM,%
797 TOMPECS,%
798 TOMS,%
799 TOPC,%
800 TOPS,%
801 TOPLAS,%
802 TOS,%
803 TOSEM,%
804 TOSN,%
805 TRETS,%
806 TSAS,%
807 TSC,%
808 TSLP,%
809 TWEB%
810 }{%
811 \ifcase\@journalCode@nr
812 \relax % CIE
813 \def\@journalName{ACM Computers in Entertainment}%
814 \def\@journalNameShort{ACM Comput. Entertain.}%
815 \def\@permissionCodeOne{1544-3574}%
816 \or % CSUR
817 \def\@journalName{ACM Computing Surveys}%
818 \def\@journalNameShort{ACM Comput. Surv.}%
819 \def\@permissionCodeOne{0360-0300}%
820 \or % IMWUT
821 \def\@journalName{Proceedings of the ACM on Interactive, Mobile,
822     Wearable and Ubiquitous Technologies}%
823 \def\@journalNameShort{Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.}%
824 \def\@permissionCodeOne{2474-9567}%
825 \@ACM@screentru
826 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
827 \or % JACM
828 \def\@journalName{Journal of the ACM}%
829 \def\@journalNameShort{J. ACM}%
830 \def\@permissionCodeOne{0004-5411}%
831 \or % JDIQ
832 \def\@journalName{ACM Journal of Data and Information Quality}%
833 \def\@journalNameShort{ACM J. Data Inform. Quality}%
834 \def\@permissionCodeOne{1936-1955}%
835 \or % JEA
836 \def\@journalName{ACM Journal of Experimental Algorithmics}%
837 \def\@journalNameShort{ACM J. Exp. Algor.}%

```



```

838 \def\@permissionCodeOne{1084-6654}%
839 \or % JERIC
840 \def\@journalName{ACM Journal of Educational Resources in Computing}%
841 \def\@journalNameShort{ACM J. Edu. Resources in Comput.}%
842 \def\@permissionCodeOne{1073-0516}%
843 \or % JETC
844 \def\@journalName{ACM Journal on Emerging Technologies in Computing Systems}%
845 \def\@journalNameShort{ACM J. Emerg. Technol. Comput. Syst.}%
846 \def\@permissionCodeOne{1550-4832}%
847 \or % JOCCH
848 \def\@journalName{ACM Journal on Computing and Cultural Heritage}%
849 \def\@journalName{ACM J. Comput. Cult. Herit.}%
850 \or % PACMHCI
851 \def\@journalName{Proceedings of the ACM on Human-Computer Interaction}%
852 \def\@journalName{Proc. ACM Hum.-Comput. Interact.}%
853 \def\@permissionCodeOne{2573-0142}%
854 \@ACM@screentru
855 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
856 \or % PACMPL
857 \def\@journalName{Proceedings of the ACM on Programming Languages}%
858 \def\@journalName{Proc. ACM Program. Lang.}%
859 \def\@permissionCodeOne{2475-1421}%
860 \@ACM@screentru
861 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
862 \or % POMACS
863 \def\@journalName{Proceedings of the ACM on Measurement and Analysis of Computing Systems}%
864 \def\@journalName{Proc. ACM Meas. Anal. Comput. Syst.}%
865 \def\@permissionCodeOne{2476-1249}%
866 \@ACM@screentru
867 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
868 \or % TAAS
869 \def\@journalName{ACM Transactions on Autonomous and Adaptive Systems}%
870 \def\@journalNameShort{ACM Trans. Autonom. Adapt. Syst.}%
871 \def\@permissionCodeOne{1556-4665}%
872 \or % TACCESS
873 \def\@journalName{ACM Transactions on Accessible Computing}%
874 \def\@journalNameShort{ACM Trans. Access. Comput.}%
875 \def\@permissionCodeOne{1936-7228}%
876 \or % TACO
877 \def\@journalName{ACM Transactions on Architecture and Code Optimization}%
878 \or % TALG
879 \def\@journalName{ACM Transactions on Algorithms}%
880 \def\@journalNameShort{ACM Trans. Algor.}%
881 \def\@permissionCodeOne{1549-6325}%
882 \or % TALLIP
883 \def\@journalName{ACM Transactions on Asian and Low-Resource Language Information Processing}%
884 \def\@journalNameShort{ACM Trans. Asian Low-Resour. Lang. Inf. Process.}%
885 \def\@permissionCodeOne{2375-4699}%
886 \or % TAP
887 \def\@journalName{ACM Transactions on Applied Perception}%

```

```

888 \or % TCPS
889 \def\@journalName{ACM Transactions on Cyber-Physical Systems}%
890 \or % TEAC
891 \def\@journalName{ACM Transactions on Economics and Computation}%
892 \or % TECS
893 \def\@journalName{ACM Transactions on Embedded Computing Systems}%
894 \def\@journalNameShort{ACM Trans. Embedd. Comput. Syst.}%
895 \def\@permissionCodeOne{1539-9087}%
896 \or % TIIS
897 \def\@journalName{ACM Transactions on Interactive Intelligent Systems}%
898 \def\@journalNameShort{ACM Trans. Interact. Intell. Syst.}%
899 \def\@permissionCodeOne{2160-6455}%
900 \or % TISSEC
901 \def\@journalName{ACM Transactions on Information and System Security}%
902 \def\@journalNameShort{ACM Trans. Info. Syst. Sec.}%
903 \def\@permissionCodeOne{1094-9224}%
904 \or % TIST
905 \def\@journalName{ACM Transactions on Intelligent Systems and Technology}%
906 \def\@journalNameShort{ACM Trans. Intell. Syst. Technol.}%
907 \def\@permissionCodeOne{2157-6904}%
908 \or % TKDD
909 \def\@journalName{ACM Transactions on Knowledge Discovery from Data}%
910 \def\@journalNameShort{ACM Trans. Knowl. Discov. Data.}%
911 \def\@permissionCodeOne{1556-4681}%
912 \or % TMIS
913 \def\@journalName{ACM Transactions on Management Information Systems}%
914 \def\@journalNameShort{ACM Trans. Manag. Inform. Syst.}%
915 \def\@permissionCodeOne{2158-656X}%
916 \or % TOCE
917 \def\@journalName{ACM Transactions on Computing Education}%
918 \def\@journalNameShort{ACM Trans. Comput. Educ.}%
919 \def\@permissionCodeOne{1946-6226}%
920 \or % TOCHI
921 \def\@journalName{ACM Transactions on Computer-Human Interaction}%
922 \def\@journalNameShort{ACM Trans. Comput.-Hum. Interact.}%
923 \def\@permissionCodeOne{1073-0516}%
924 \or % TOCL
925 \def\@journalName{ACM Transactions on Computational Logic}%
926 \def\@journalNameShort{ACM Trans. Comput. Logic}%
927 \def\@permissionCodeOne{1529-3785}%
928 \or % TOCS
929 \def\@journalName{ACM Transactions on Computer Systems}%
930 \def\@journalNameShort{ACM Trans. Comput. Syst.}%
931 \def\@permissionCodeOne{0734-2071}%
932 \or % TOCT
933 \def\@journalName{ACM Transactions on Computation Theory}%
934 \def\@journalNameShort{ACM Trans. Comput. Theory}%
935 \def\@permissionCodeOne{1942-3454}%
936 \or % TODAES
937 \def\@journalName{ACM Transactions on Design Automation of Electronic Systems}%

```

```

938 \def\@journalNameShort{ACM Trans. Des. Autom. Electron. Syst.}%
939 \def\@permissionCodeOne{1084-4309}%
940 \or % TODS
941 \def\@journalName{ACM Transactions on Database Systems}%
942 \def\@journalNameShort{ACM Trans. Datab. Syst.}%
943 \def\@permissionCodeOne{0362-5915}%
944 \or % TOG
945 \def\@journalName{ACM Transactions on Graphics}%
946 \def\@journalNameShort{ACM Trans. Graph.}%
947 \def\@permissionCodeOne{0730-0301}%
948 \or % TOIS
949 \def\@journalName{ACM Transactions on Information Systems}%
950 \def\@journalName{ACM Transactions on Information Systems}%
951 \def\@permissionCodeOne{1046-8188}%
952 \or % TOIT
953 \def\@journalName{ACM Transactions on Internet Technology}%
954 \def\@journalNameShort{ACM Trans. Internet Technol.}%
955 \def\@permissionCodeOne{1533-5399}%
956 \or % TOMACS
957 \def\@journalName{ACM Transactions on Modeling and Computer Simulation}%
958 \def\@journalName{ACM Transactions on Modeling and Computer Simulation}%
959 \def\@journalNameShort{ACM Trans. Model. Comput. Simul.}%
960 \or % TOMM
961 \def\@journalName{ACM Transactions on Multimedia Computing, Communications and Applications}%
962 \def\@journalNameShort{ACM Trans. Multimedia Comput. Commun. Appl.}%
963 \def\@permissionCodeOne{1551-6857}%
964 \def\@permissionCodeTwo{0100}%
965 \or % TOMPECS
966 \def\@journalName{ACM Transactions on Modeling and Performance Evaluation of Computing Systems}%
967 \def\@journalNameShort{ACM Trans. Model. Perform. Eval. Comput. Syst.}%
968 \def\@permissionCodeOne{2376-3639}%
969 \or % TOMS
970 \def\@journalName{ACM Transactions on Mathematical Software}%
971 \def\@journalNameShort{ACM Trans. Math. Softw.}%
972 \def\@permissionCodeOne{0098-3500}%
973 \or % TOPC
974 \def\@journalName{ACM Transactions on Parallel Computing}%
975 \def\@journalNameShort{ACM Trans. Parallel Comput.}%
976 \def\@permissionCodeOne{1539-9087}%
977 \or % TOPS
978 \def\@journalName{ACM Transactions on Privacy and Security}%
979 \def\@journalNameShort{ACM Trans. Priv. Sec.}%
980 \def\@permissionCodeOne{2471-2566}%
981 \or % TOPLAS
982 \def\@journalName{ACM Transactions on Programming Languages and Systems}%
983 \def\@journalNameShort{ACM Trans. Program. Lang. Syst.}%
984 \def\@permissionCodeOne{0164-0925}%
985 \or % TOS
986 \def\@journalName{ACM Transactions on Storage}%
987 \def\@journalNameShort{ACM Trans. Storage}%

```

```

988 \def\@permissionCodeOne{1553-3077}%
989 \or % TOSEM
990 \def\@journalName{ACM Transactions on Software Engineering and Methodology}%
991 \def\@journalNameShort{ACM Trans. Softw. Eng. Methodol.}%
992 \def\@permissionCodeOne{1049-331X}%
993 \or % TOSN
994 \def\@journalName{ACM Transactions on Sensor Networks}%
995 \def\@journalNameShort{ACM Trans. Sensor Netw.}%
996 \def\@permissionCodeOne{1550-4859}%
997 \or % TRET
998 \def\@journalName{ACM Transactions on Reconfigurable Technology and Systems}%
999 \def\@journalNameShort{ACM Trans. Reconfig. Technol. Syst.}%
1000 \def\@permissionCodeOne{1936-7406}%
1001 \or % TSAS
1002 \def\@journalName{ACM Transactions on Spatial Algorithms and Systems}%
1003 \def\@journalNameShort{ACM Trans. Spatial Algorithms Syst.}%
1004 \def\@permissionCodeOne{2374-0353}%
1005 \or % TSC
1006 \def\@journalName{ACM Transactions on Social Computing}%
1007 \def\@journalNameShort{ACM Trans. Soc. Comput.}%
1008 \def\@permissionCodeOne{2469-7818}%
1009 \or % TSLP
1010 \def\@journalName{ACM Transactions on Speech and Language Processing}%
1011 \def\@journalNameShort{ACM Trans. Speech Lang. Process.}%
1012 \def\@permissionCodeOne{1550-4875}%
1013 \or % TWEB
1014 \def\@journalName{ACM Transactions on the Web}%
1015 \def\@journalNameShort{ACM Trans. Web}%
1016 \def\@permissionCodeOne{1559-1131}%
1017 \fi
1018 \ClassInfo{\@classname}{Using journal code \@journalCode}%
1019 }{%
1020 \ClassError{\@classname}{Incorrect journal #1}%
1021 }%

```

\acmJournal And the syntactic sugar around it

```

1022 \def\acmJournal#1{\setkeys{ACM}{acmJournal=#1}}

```

The defaults:

```

1023 \def\@journalCode@nr{0}
1024 \def\@journalName{}%
1025 \def\@journalNameShort{\@journalName}%
1026 \def\@permissionCodeOne{XXXX-XXXX}%
1027 \def\@permissionCodeTwo{}%

```

\acmConference This is the conference command

```

1028 \newcommand\acmConference[4][{}]{%
1029 \gdef\acmConference@shortname{#1}%
1030 \gdef\acmConference@name{#2}%

```

```

1031 \gdef\acmConference@date{#3}%
1032 \gdef\acmConference@venue{#4}%
1033 \ifx\acmConference@shortname\empty
1034 \gdef\acmConference@shortname{#2}%
1035 \fi}
1036 \acmConference[Conference'17]{ACM Conference}{July 2017}{Washington,
1037 DC, USA}

\acmBooktitle The book title of the conference:
\@acmBooktitle 1038 \def\acmBooktitle#1{\gdef\@acmBooktitle{#1}}
1039 \acmBooktitle{Proceedings of \acmConference@name
1040 \ifx\acmConference@name\acmConference@shortname\else
1041 \ (\acmConference@shortname)\fi}

\@editorsAbbrev How to abbreviate editors
1042 \def\@editorsAbbrev{(Ed.)}

\@acmEditors The list of editors

\editor Add new editor to the list
1043 \def\editor#1{\ifx\@acmEditors\empty
1044 \gdef\@acmEditors{#1}%
1045 \else
1046 \gdef\@editorsAbbrev{(Eds.)}%
1047 \g@addto@macro\@acmEditors{\and#1}%
1048 \fi}

\subtitle The subtitle macro
1049 \def\subtitle#1{\def\@subtitle{#1}}
1050 \subtitle{}

\num@authorgroups The total number of “groups”. Each group is several authors with the same affiliations(s)
1051 \newcount\num@authorgroups
1052 \num@authorgroups=0\relax

\num@author The total number of authors.
1053 \newcount\num@author
1054 \num@author=0\relax

\if@insideauthorgroup Whether we are continuing an author group @insideauthorgroup insideauthorgroup-
false

\author Adding an author to the list of authors and addresses
1055 \renewcommand\author[2][{}]{%
1056 \global\advance\num@author by 1\relax
1057 \if@insideauthorgroup\else
1058 \global\advance\num@authorgroups by 1\relax
1059 \global\@insideauthorgrouptrue
1060 \fi

```

```

1061 \ifx\addresses\@empty
1062   \if@ACM@anonymous
1063     \gdef\addresses{\@author{Anonymous Author(s)}}%
1064     \gdef\authors{Anonymous Author(s)}%
1065   \else
1066     \gdef\addresses{\@author{#2}}%
1067     \gdef\authors{#2}%
1068   \fi
1069 \else
1070   \if@ACM@anonymous\else
1071     \g@addto@macro\addresses{\and\@author{#2}}%
1072     \g@addto@macro\authors{\and#2}%
1073   \fi
1074 \fi
1075 \if@ACM@anonymous
1076   \ifx\shortauthors\@empty
1077     \gdef\shortauthors{Anon.}%
1078   \fi
1079 \else
1080   \def\@tempa{#1}%
1081   \ifx\@tempa\@empty
1082     \ifx\shortauthors\@empty
1083       \gdef\shortauthors{#2}%
1084     \else
1085       \g@addto@macro\shortauthors{\and#2}%
1086     \fi
1087   \else
1088     \ifx\shortauthors\@empty
1089       \gdef\shortauthors{#1}%
1090     \else
1091       \g@addto@macro\shortauthors{\and#1}%
1092     \fi
1093   \fi
1094 \fi}

```

`\affiliation` The macro `\affiliation` mimics `\address` from `amsart`. Note that it has an optional argument, which we use differently from `amsart`.

```

1095 \newcommand{\affiliation}[2][\%
1096   \global\@insideauthorgroupfalse
1097   \if@ACM@anonymous\else
1098     \g@addto@macro\addresses{\affiliation{#1}{#2}}%
1099   \fi}

```

`@ACM@affiliation@obeypunctuation` Whether to use author's punctuation (by default false = add American punctuation)

```

1100 \define@boolkey+{@ACM@affiliation@}{@ACM@affiliation@}{obeypunctuation}%
1101 [true][\ClassError{\@classname}{obeypunctuation must be true or false}]

```

`\additionalaffiliation` Additional affiliations go to footnotes

```

1102 \def\additionalaffiliation#1{\authornote{\@additionalaffiliation{#1}}}

```

`\@additionalaffiliation` Process additionalaffiliation inside \authornote

```

1103 \def\@additionalaffiliation#1{\bgroup
1104   \def\position##1{\ignorespaces}%
1105   \def\institution##1{##1\ignorespaces}%
1106   \def\department{\@ifnextchar[{\@department}{\@department[]}}%
1107   \def\@department[##1]##2{\unskip, ##2\ignorespaces}%
1108   \let\streetaddress\position
1109   \let\city\position
1110   \let\state\position
1111   \let\postcode\position
1112   \let\country\position
1113   Also with #1\unskip.\egroup}

```

`\email` The macro \email mimics \email from amsart. Agian it has an optional argument we do not currently need, but keep for the possible future use.

```

1114 \renewcommand{\email}[2][{}]{%
1115   \if@ACM@anonymous\else
1116     \g@addto@macro\addresses{\email{#1}{#2}}%
1117   \fi}

```

`\orcid` Right now we do not typeset orcid

`\authorsaddresses` Setting up authors' addresses

`\@titlenotes` The titlenotes

```

1118 \def\@titlenotes{}

```

`\titlenote` Adding note to the title

```

1119 \def\titlenote#1{%
1120   \g@addto@macro\@title{\footnotemark}%
1121   \if@ACM@anonymous
1122     \g@addto@macro\@titlenotes{%
1123       \stepcounter{footnote}\footnotetext{Title note}}%
1124   \else
1125     \g@addto@macro\@titlenotes{\stepcounter{footnote}\footnotetext{#1}}%
1126   \fi}

```

`\@subtitlenotes` The subtitlenotes

```

1127 \def\@subtitlenotes{}

```

`\subtitlenote` Adding note to the subtitle

```

1128 \def\subtitlenote#1{%
1129   \g@addto@macro\@subtitle{\footnotemark}%
1130   \if@ACM@anonymous
1131     \g@addto@macro\@subtitlenotes{%
1132       \stepcounter{footnote}\footnotetext{Subtitle note}}%
1133   \else
1134     \g@addto@macro\@subtitlenotes{%
1135       \stepcounter{footnote}\footnotetext{#1}}%
1136   \fi}

```

`\@authornotes` The authornotes
1137 `\def\@authornotes{}`

`\authornote` Adding note to the author
1138 `\def\authornote#1{%`
1139 `\if@ACM@anonymous\else`
1140 `\g@addto@macro\addresses{\@authornotemark}%`
1141 `\g@addto@macro\@authornotes{%`
1142 `\stepcounter{footnote}\footnotetext{#1}}%`
1143 `\fi}`

`\authornotemark` Adding footnotemark to authors
1144 `\newcommand\authornotemark[1][\relax]{%`
1145 `\ifx#1\relax\relax\relax`
1146 `\g@addto@macro\addresses{\@authornotemark}%`
1147 `\else`
1148 `\g@addto@macro\addresses{\@authornotemark{#1}}%`
1149 `\fi}`

`\acmVolume` The current volume
1150 `\def\acmVolume#1{\def\@acmVolume{#1}}`
1151 `\acmVolume{1}`

`\acmNumber` The current number
1152 `\def\acmNumber#1{\def\@acmNumber{#1}}`
1153 `\acmNumber{1}`

`\acmArticle` The current article
1154 `\def\acmArticle#1{\def\@acmArticle{#1}}`
1155 `\acmArticle{}`

`\acmArticleSeq` The sequence number
1156 `\def\acmArticleSeq#1{\def\@acmArticleSeq{#1}}`
1157 `\acmArticleSeq{\@acmArticle}`

`\acmYear` The current year
1158 `\def\acmYear#1{\def\@acmYear{#1}}`
1159 `\acmYear{\the\year}`

`\acmMonth` The current month
1160 `\def\acmMonth#1{\def\@acmMonth{#1}}`
1161 `\acmMonth{\the\month}`

`\@acmPubDate` The publication date
1162 `\def\@acmPubDate{\ifcase\@acmMonth\or`
1163 `January\or February\or March\or April\or May\or June\or`
1164 `July\or August\or September\or October\or November\or`
1165 `December\fi~\@acmYear}`

<code>\acmPrice</code>	<p>The price</p> <pre>1166 \def\acmPrice#1{\def\@acmPrice{#1}} 1167 \acmPrice{15.00}</pre>
<code>\acmSubmissionID</code>	<p>The submission id</p> <pre>1168 \def\acmSubmissionID#1{\def\@acmSubmissionID{#1}} 1169 \acmSubmissionID{}</pre>
<code>\acmISBN</code>	<p>The book isbn</p> <pre>1170 \def\acmISBN#1{\def\@acmISBN{#1}} 1171 \acmISBN{978-x-xxxx-xxxx-x/YY/MM}</pre>
<code>\acmDOI</code>	<p>The paper doi</p> <pre>1172 \def\acmDOI#1{\def\@acmDOI{#1}} 1173 \acmDOI{10.1145/nnnnnnn.nnnnnnn}</pre>
<code>\if@ACM@badge</code>	<p>Whether to print badge. Note that either left or right badge triggers it:</p> <pre>1174 \newif\if@ACM@badge 1175 \@ACM@badgefalse</pre>
<code>\@ACM@badge@width</code>	<p>The width of the badge</p> <pre>1176 \newlength\@ACM@badge@width 1177 \setlength\@ACM@badge@width{5pc}</pre>
<code>\@ACM@title@width</code>	<p>The width of the badge</p> <pre>1178 \newlength\@ACM@title@width</pre>
<code>\@ACM@badge@skip</code>	<p>The space between the badge and the title</p> <pre>1179 \newlength\@ACM@badge@skip 1180 \setlength\@ACM@badge@skip{1pc}</pre>
<code>\acmBadgeR</code>	<p>Setting the right badge</p> <pre>1181 \newcommand\acmBadgeR[2][\@ACM@badgetrue 1182 \def\@acmBadgeR@url{#1}% 1183 \def\@acmBadgeR@image{#2}} 1184 \def\@acmBadgeR@url{} 1185 \def\@acmBadgeR@image{}</pre>
<code>\acmBadgeL</code>	<p>Setting the left badge</p> <pre>1186 \newcommand\acmBadgeL[2][\@ACM@badgetrue 1187 \def\@acmBadgeL@url{#1}% 1188 \def\@acmBadgeL@image{#2}} 1189 \def\@acmBadgeL@url{} 1190 \def\@acmBadgeL@image{}</pre>
<code>\startPage</code>	<p>The start page of the paper</p> <pre>1191 \def\startPage#1{\def\@startPage{#1}} 1192 \startPage{}</pre>

`\terms` Terms are obsolete, we use CCS now.
1193 `\def\terms#1{\ClassWarning{\@classname}{The command \string\terms{} is`
1194 `obsolete. I am going to ignore it}}`

`\keywords` Keywords are mostly obsolete, we use CCS now. Still it makes sense to keep them for compatibility.
1195 `\def\keywords#1{\def\@keywords{#1}}`
1196 `\keywords{}`

`abstract` Amsart puts abstract in the box. Since we do not know whether we will use two column mode, we prefer to save the text
1197 `\renewenvironment{abstract}{\Collect@Body\@saveabstract}{}`

`\@saveabstract` And saving the abstract
1198 `\long\def\@saveabstract#1{\long\gdef\@abstract{#1}}`
1199 `\@saveabstract{}`

`\@empty` The long version of `\@empty` (to compare with `\@abstract`)
1200 `\long\def\@empty{}`

`\if@ACM@printccs` Whether to print CCS
1201 `\define@boolkey+{@ACM@topmatter@}[@ACM@]{printccs}[true]{%`
1202 `\if@ACM@printccs`
1203 `\ClassInfo{\@classname}{Printing CCS}%`
1204 `\else`
1205 `\ClassInfo{\@classname}{Suppressing CCS}%`
1206 `\fi}{\ClassError{\@classname}{printccs must be true or false}}`

`\if@ACM@printacmref` Whether to print ACM bib
1207 `\define@boolkey+{@ACM@topmatter@}[@ACM@]{printacmref}[true]{%`
1208 `\if@ACM@printacmref`
1209 `\ClassInfo{\@classname}{Printing bibformat}%`
1210 `\else`
1211 `\ClassInfo{\@classname}{Suppressing bibformat}%`
1212 `\fi}{\ClassError{\@classname}{printacmref must be true or false}}`

`\if@ACM@printfolios` Whether to print folios
1213 `\define@boolkey+{@ACM@topmatter@}[@ACM@]{printfolios}[true]{%`
1214 `\if@ACM@printfolios`
1215 `\ClassInfo{\@classname}{Printing folios}%`
1216 `\else`
1217 `\ClassInfo{\@classname}{Suppressing folios}%`
1218 `\fi}{\ClassError{\@classname}{printfolios must be true or false}}`

`\@ACM@authorssperrow` The number of authors per row. 0 means use default algorithm.
1219 `\define@cmdkey{@ACM@topmatter@}[@ACM@]{authorssperrow}[0]{%`
1220 `\IfInteger{#1}{\ClassInfo{\@classname}{Setting authorssperrow to`
1221 `#1}}{\ClassWarning{\@classname}{Parameter authorssperrow must be`
1222 `numerical. Ignoring the input #1}\gdef\@ACM@authorssperrow{0}}`

`\settopmatter` The usual syntactic sugar

```
1223 \def\settopmatter#1{\setkeys{@ACM@topmatter@}{#1}}
```

Now the settings

```
1224 \settopmatter{printccs=true, printacmref=true}
1225 \if@ACM@manuscript
1226   \settopmatter{printfolios=true}
1227 \else
1228   \if@ACM@journal
1229     \settopmatter{printfolios=true}
1230   \else
1231     \settopmatter{printfolios=false}
1232   \fi
1233 \fi
1234 \settopmatter{authorsperrow=0}
```

`\@received` The container for the paper history

```
1235 \def\@received{}
```

`\received` The `\received` command

```
1236 \newcommand\received[2][\def\@tempa{#1}%
1237   \ifx\@tempa\@empty
1238     \ifx\@received\@empty
1239       \gdef\@received{Received #2}%
1240     \else
1241       \g@addto@macro{\@received}{; revised #2}%
1242     \fi
1243   \else
1244     \ifx\@received\@empty
1245       \gdef\@received{#1 #2}%
1246     \else
1247       \g@addto@macro{\@received}{; #1 #2}%
1248     \fi
1249   \fi}
1250 \AtEndDocument{%
1251   \ifx\@received\@empty\else
1252     \par\bigskip\noindent\small\normalfont\@received\par
1253   \fi}
```

3.11 Concepts system

We exclude CCSXML stuff generated by the ACM system:

```
1254 \RequirePackage{comment}
1255 \excludecomment{CCSXML}
```

`\@concepts` This is the storage macro for concepts

```
1256 \let\@concepts\@empty
```

\ccsdesc The first argument is the significance, the second is the concept(s)

```
1257 \newcommand\ccsdesc[2][100]{%
1258   \ccsdesc@parse#1~#2~\ccsdesc@parse@end}
```

\ccsdesc@parse The parser of the expression Significance~General~Specific (we need textcomp for \textrightarrow). Note that Specific can be empty!

```
1259 \RequirePackage{textcomp}
1260 \def\ccsdesc@parse#1~#2~#3~{%
1261   \expandafter\ifx\csname CCS@General@#2\endcsname\relax
1262     \expandafter\gdef\csname CCS@General@#2\endcsname{\textbullet\
1263       \textbf{#2}}}%
1264   \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{; }%
1265   \expandafter\gdef\csname CCS@Specific@#2\endcsname{}%
1266   \g@addto@macro{\@concepts}{\csname CCS@General@#2\endcsname
1267     \csname CCS@Punctuation@#2\endcsname
1268     \csname CCS@Specific@#2\endcsname}%
1269   \fi
1270   \ifx#3\relax\relax\else
1271     \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{
1272       \textrightarrow\ }%
1273     \expandafter\g@addto@macro\expandafter{\csname CCS@Specific@#2\endcsname}{%
1274       \ifnum#1>499\textbf{#3}; \else
1275       \ifnum#1>299\textit{#3}; \else
1276       #3; \fi\fi}%
1277     \fi
1278   \ccsdesc@parse@finish}
```

\ccdesc@parse@finish Gobble everything to \ccsdesc@parse@end

```
1279 \def\ccsdesc@parse@finish#1\ccsdesc@parse@end{}
```

3.12 Copyright system

This is from acmcopyright.sty

\if@printcopyright A flag whether to print copyright symbol

```
1280 \newif\if@printcopyright
1281 \@printcopyrighttrue
```

\if@printpermission Whether to print permission block

```
1282 \newif\if@printpermission
1283 \@printpermissiontrue
```

\if@acmowned Whether ACM owns the rights to the paper

```
1284 \newif\if@acmowned
1285 \@acmownedtrue
```

Keys:

```
1286 \define@choicekey*{ACM@}{acmcopyrightmode}[%
```

```

1287 \acm@copyrightinput\acm@copyrightmode]{none,%
1288   acmcopyright,acmlicensed,rightsretained,%
1289   usgov,usgovmixed,cagov,cagovmixed,%
1290   licensedusgovmixed,%
1291   licensedcagov,licensedcagovmixed,othergov,licensedothergov}{%
1292 \@printpermissiontrue
1293 \@printcopyrighttrue
1294 \@acmownedtrue
1295 \ifnum\acm@copyrightmode=0\relax % none
1296   \@printpermissionfalse
1297   \@printcopyrightfalse
1298   \@acmownedfalse
1299 \fi
1300 \ifnum\acm@copyrightmode=2\relax % acmlicensed
1301   \@acmownedfalse
1302 \fi
1303 \ifnum\acm@copyrightmode=3\relax % rightsretained
1304   \@acmownedfalse
1305   \acmPrice{}%
1306 \fi
1307 \ifnum\acm@copyrightmode=4\relax % usgov
1308   \@printpermissiontrue
1309   \@printcopyrightfalse
1310   \@acmownedfalse
1311   \acmPrice{}%
1312 \fi
1313 \ifnum\acm@copyrightmode=6\relax % cagov
1314   \@acmownedfalse
1315 \fi
1316 \ifnum\acm@copyrightmode=8\relax % licensedusgovmixed
1317   \@acmownedfalse
1318 \fi
1319 \ifnum\acm@copyrightmode=9\relax % licensedcagov
1320   \@acmownedfalse
1321 \fi
1322 \ifnum\acm@copyrightmode=10\relax % licensedcagovmixed
1323   \@acmownedfalse
1324 \fi
1325 \ifnum\acm@copyrightmode=11\relax % othergov
1326   \@acmownedtrue
1327 \fi
1328 \ifnum\acm@copyrightmode=12\relax % licensedothergov
1329   \@acmownedfalse
1330 \fi}

```

\setcopyright This is the syntactic sugar around setting keys.

```

1331 \def\setcopyright#1{\setkeys{ACM@}{acmcopyrightmode=#1}}
1332 \setcopyright{acmcopyright}

```

\@copyrightowner Here is the owner of the copyright

```

1333 \def\@copyrightowner{%
1334   \ifcase\acm@copyrightmode\relax % none
1335   \or % acmcopyright
1336   Association for Computing Machinery.
1337   \or % acmlicensed
1338   Copyright held by the owner/author(s). Publication rights licensed to
1339   Association for Computing Machinery.
1340   \or % rightsretained
1341   Copyright held by the owner/author(s).
1342   \or % usgov
1343   \or % usgovmixed
1344   Association for Computing Machinery.
1345   \or % cagov
1346   Crown in Right of Canada.
1347   \or %cagovmixed
1348   Association for Computing Machinery.
1349   \or %licensedusgovmixed
1350   Copyright held by the owner/author(s). Publication rights licensed to
1351   Association for Computing Machinery.
1352   \or % licensedcagov
1353   Crown in Right of Canada. Publication rights licensed to
1354   Association for Computing Machinery.
1355   \or %licensedcagovmixed
1356   Copyright held by the owner/author(s). Publication rights licensed to
1357   Association for Computing Machinery.
1358   \or % othergov
1359   Association for Computing Machinery.
1360   \or % licensedothergov
1361   Copyright held by the owner/author(s). Publication rights licensed to
1362   Association for Computing Machinery.
1363   \fi}

```

\@formatdoi Print a clickable doi

```

1364 \def\@formatdoi#1{\url{https://doi.org/#1}}

```

\@copyrightpermission The canned permission block.

```

1365 \def\@copyrightpermission{%
1366   \ifcase\acm@copyrightmode\relax % none
1367   \or % acmcopyright
1368   Permission to make digital or hard copies of all or part of this
1369   work for personal or classroom use is granted without fee provided
1370   that copies are not made or distributed for profit or commercial
1371   advantage and that copies bear this notice and the full citation on
1372   the first page. Copyrights for components of this work owned by
1373   others than ACM must be honored. Abstracting with credit is
1374   permitted. To copy otherwise, or republish, to post on servers or to
1375   redistribute to lists, requires prior specific permission
1376   and\hspace*{.5pt}/or a fee. Request permissions from
1377   permissions@acm.org.
1378   \or % acmlicensed

```

1379 Permission to make digital or hard copies of all or part of this
 1380 work for personal or classroom use is granted without fee provided
 1381 that copies are not made or distributed for profit or commercial
 1382 advantage and that copies bear this notice and the full citation on
 1383 the first page. Copyrights for components of this work owned by
 1384 others than the author(s) must be honored. Abstracting with credit
 1385 is permitted. To copy otherwise, or republish, to post on servers
 1386 or to redistribute to lists, requires prior specific permission
 1387 and\hspace*{.5pt}/or a fee. Request permissions from
 1388 permissions@acm.org.
 1389 \or % rightsretained
 1390 Permission to make digital or hard copies of part or all of this work
 1391 for personal or classroom use is granted without fee provided that
 1392 copies are not made or distributed for profit or commercial advantage
 1393 and that copies bear this notice and the full citation on the first
 1394 page. Copyrights for third-party components of this work must be
 1395 honored. For all other uses, contact the
 1396 owner\hspace*{.5pt}/author(s).
 1397 \or % usgov
 1398 This paper is authored by an employee(s) of the United States
 1399 Government and is in the public domain. Non-exclusive copying or
 1400 redistribution is allowed, provided that the article citation is
 1401 given and the authors and agency are clearly identified as its
 1402 source.
 1403 \or % usgovmixed
 1404 ACM acknowledges that this contribution was authored or co-authored
 1405 by an employee, contractor, or affiliate of the United States government. As such,
 1406 the United States government retains a nonexclusive, royalty-free right to
 1407 publish or reproduce this article, or to allow others to do so, for
 1408 government purposes only.
 1409 \or % cagov
 1410 This article was authored by employees of the Government of Canada.
 1411 As such, the Canadian government retains all interest in the
 1412 copyright to this work and grants to ACM a nonexclusive,
 1413 royalty-free right to publish or reproduce this article, or to allow
 1414 others to do so, provided that clear attribution is given both to
 1415 the authors and the Canadian government agency employing them.
 1416 Permission to make digital or hard copies for personal or classroom
 1417 use is granted. Copies must bear this notice and the full citation
 1418 on the first page. Copyrights for components of this work owned by
 1419 others than the Canadian Government must be honored. To copy
 1420 otherwise, distribute, republish, or post, requires prior specific
 1421 permission and\hspace*{.5pt}/or a fee. Request permissions from
 1422 permissions@acm.org.
 1423 \or % cagovmixed
 1424 ACM acknowledges that this contribution was co-authored by an
 1425 affiliate of the national government of Canada. As such, the Crown
 1426 in Right of Canada retains an equal interest in the copyright.
 1427 Reprints must include clear attribution to ACM and the author's
 1428 government agency affiliation. Permission to make digital or hard

1429 copies for personal or classroom use is granted. Copies must bear
 1430 this notice and the full citation on the first page. Copyrights for
 1431 components of this work owned by others than ACM must be honored.
 1432 To copy otherwise, distribute, republish, or post, requires prior
 1433 specific permission and\hspace*{.5pt}/or a fee. Request permissions
 1434 from permissions@acm.org.
 1435 \or % licensedusgovmixed
 1436 Publication rights licensed to ACM\@. ACM acknowledges that this
 1437 contribution was authored or co-authored by an employee, contractor
 1438 or affiliate of the United States government. As such, the
 1439 Government retains a nonexclusive, royalty-free right to publish or
 1440 reproduce this article, or to allow others to do so, for Government
 1441 purposes only.
 1442 \or % licensedcagov
 1443 This article was authored by employees of the Government of Canada.
 1444 As such, the Canadian government retains all interest in the
 1445 copyright to this work and grants to ACM a nonexclusive,
 1446 royalty-free right to publish or reproduce this article, or to allow
 1447 others to do so, provided that clear attribution is given both to
 1448 the authors and the Canadian government agency employing them.
 1449 Permission to make digital or hard copies for personal or classroom
 1450 use is granted. Copies must bear this notice and the full citation
 1451 on the first page. Copyrights for components of this work owned by
 1452 others than the Canadian Government must be honored. To copy
 1453 otherwise, distribute, republish, or post, requires prior specific
 1454 permission and\hspace*{.5pt}/or a fee. Request permissions from
 1455 permissions@acm.org.
 1456 \or % licensedcagovmixed
 1457 Publication rights licensed to ACM\@. ACM acknowledges that this
 1458 contribution was authored or co-authored by an employee, contractor
 1459 or affiliate of the national government of Canada. As such, the
 1460 Government retains a nonexclusive, royalty-free right to publish or
 1461 reproduce this article, or to allow others to do so, for Government
 1462 purposes only.
 1463 \or % othergov
 1464 ACM acknowledges that this contribution was authored or co-authored
 1465 by an employee, contractor or affiliate of a national government. As
 1466 such, the Government retains a nonexclusive, royalty-free right to
 1467 publish or reproduce this article, or to allow others to do so, for
 1468 Government purposes only.
 1469 \or % licensedothergov
 1470 Publication rights licensed to ACM\@. ACM acknowledges that this
 1471 contribution was authored or co-authored by an employee, contractor
 1472 or affiliate of a national government. As such, the Government
 1473 retains a nonexclusive, royalty-free right to publish or reproduce
 1474 this article, or to allow others to do so, for Government purposes
 1475 only.
 1476 \fi}

`\copyrightyear` By default, the copyright year is the same as `\acmYear`, but one can override this:

```
1477 \def\copyrightyear#1{\def\@copyrightyear{#1}}
1478 \copyrightyear{\@acmYear}
```

`\@teaserfigures` The teaser figures container

```
1479 \def\@teaserfigures{}
```

`teaserfigure` The teaser figure

```
1480 \newenvironment{teaserfigure}{\Collect@Body\@saveteaser}{}
```

`\@saveteaser` Saving the teaser

```
1481 \long\def\@saveteaser#1{\g@addto@macro\@teaserfigures{\@teaser{#1}}}
```

`\thanks` We redefine `amsart \thanks`, so the anonymous key works

```
1482 \renewcommand{\thanks}[1]{%
1483   \ifnotempty{#1}{%
1484     \if@ACM@anonymous
1485       \g@addto@macro\thankses{\thanks{A note}}%
1486     \else
1487       \g@addto@macro\thankses{\thanks{#1}}%
1488     \fi}}
```

3.13 Typesetting top matter

`\mktitle@bx` Some of our formats use two column design, some use one column one. In all cases we use wide title. Thus we typeset the top matter in a special box to be use in the construction `\@twocolumn[\box]`.

```
1489 \newbox\mktitle@bx
```

`\maketitle` The (in)famous `\maketitle`. Note that in `sigchi-a` mode authors are *not* in the title box.

Another note: there is a subtle difference between author notes, title notes and `thankses`. The latter refer to the paper itself, and therefore belong to the copyright/permission block. By the way, this was the default behavior of the old ACM classes.

```
1490 \def\maketitle{%
1491   \if@ACM@anonymous
1492     % Anonymize omission of \author-s
1493     \ifnum\@authorgroups=0\author{}\fi
1494   \fi
1495   \begingroup
1496   \let\@footnotemark\@footnotemark@nolink
1497   \let\@footnotetext\@footnotetext@nolink
1498   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1499   \global\@topnum\z@ % this prevents floats from falling
1500                     % at the top of page 1
1501   \global\@botnum\z@ % we do not want them to be on bottom either
1502   \hsize=\textwidth
1503   \def\@makefnmark{\hbox{\@textsuperscript{\@thefnmark}}}%
1504   \mktitle\if@ACM@sigchiamode\else\@mkauthors\fi\@mkteasers
```

```

1505 \@printtopmatter
1506 \if@ACM@sigchiamode\mkauthors\fi
1507 \setcounter{footnote}{0}%
1508 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}%
1509 \@titlenotes
1510 \@subtitlenotes
1511 \@authornotes
1512 \let\@makefnmark\relax \let\@thefnmark\relax
1513 \let\@makefntext\noindent
1514 \ifx\@empty\thankses\else
1515   \footnotetextauthorsaddresses{%
1516     \def\par{\let\par\@par}\parindent\z@\@setthanks}%
1517 \fi
1518 \ifx\@empty\@authorsaddresses\else
1519   \if@ACM@anonymous\else
1520     \if@ACM@journal
1521       \footnotetextauthorsaddresses{%
1522         \def\par{\let\par\@par}\parindent\z@\@setauthorsaddresses}%
1523     \fi
1524   \fi
1525 \fi
1526 \footnotetextcopyrightpermission{%
1527   \if@ACM@authordraft
1528     \raisebox{-2ex}{\z@\z@{\makebox[0pt][l]{\large\bfseries
1529       Unpublished
1530       working draft. Not for distribution}}}%
1531     \color[gray]{0.9}%
1532   \fi
1533   \parindent\z@\parskip0.1\baselineskip
1534   \if@ACM@authorversion\else
1535     \if@printpermission\@copyrightpermission\par\fi
1536   \fi
1537   \if@ACM@manuscript\else
1538     \if@ACM@journal\else % Print the conference information
1539       {\itshape \acmConference@shortname, \acmConference@date, \acmConference@venue}\par
1540     \fi
1541   \fi
1542   \if@printcopyright
1543     \copyright\ \@copyrightyear\ \@copyrightowner\
1544   \else
1545     \@copyrightyear.\
1546   \fi
1547   \if@ACM@manuscript
1548     Manuscript submitted to ACM\
1549   \else
1550     \if@ACM@authorversion
1551       This is the author's version of the work. It is posted here for
1552       your personal use. Not for redistribution. The definitive Version
1553       of Record was published in
1554     \if@ACM@journal

```

```

1555         \emph{\@journalName}%
1556     \else
1557         \emph{\@acmBooktitle}%
1558     \fi
1559     \ifx\@acmDOI\@empty
1560     .
1561     \else
1562         , \@formatdoi{\@acmDOI}.
1563     \fi\
1564 \else
1565     \if@ACM@journal
1566         \@permissionCodeOne/\@acmYear/\@acmMonth-ART\@acmArticle
1567         \ifx\@acmPrice\@empty\else\ $\@acmPrice\fi\
1568         \@formatdoi{\@acmDOI}%
1569     \else % Conference
1570         \ifx\@acmISBN\@empty\else ACM~ISBN~\@acmISBN
1571         \ifx\@acmPrice\@empty.\else\dots$\@acmPrice\fi\fi
1572         \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi%
1573     \fi
1574 \fi
1575 \fi}
1576 \endgroup
1577 \setcounter{footnote}{0}%
1578 \@mkabstract
1579 \if@ACM@printccs
1580     \ifx\@concepts\@empty\else\bgroup
1581     {\@specialsection{CCS Concepts}%
1582     \@concepts\par}\egroup
1583 \fi
1584 \fi
1585 \ifx\@keywords\@empty\else\bgroup
1586     {\if@ACM@journal
1587     \@specialsection{Additional Key Words and Phrases}%
1588     \else
1589     \@specialsection{Keywords}%
1590     \fi
1591     \@keywords}\par\egroup
1592 \fi
1593 \andify\authors
1594 \andify\shortauthors
1595 \global\let\authors=\authors
1596 \global\let\shortauthors=\shortauthors
1597 \if@ACM@printacmref
1598     \@mkbibcitation
1599 \fi
1600 \hypersetup{pdfauthor={\authors},
1601     pdftitle={\@title},
1602     pdfsubject={\@concepts},
1603     pdfkeywords={\@keywords}}%
1604 \@printendtopmatter

```

```

1605 \@afterindentfalse
1606 \@afterheading
1607 }

```

`\@specialsection` This macro starts section for proceedings and uses small for journals

```

1608 \def\@specialsection#1{%
1609   \ifcase\ACM@format@nr
1610     \relax % manuscript
1611     \par\medskip\small\noindent#1: %
1612   \or % acmsmall
1613     \par\medskip\small\noindent#1: %
1614   \or % acmlarge
1615     \par\medskip\small\noindent#1: %
1616   \or % acmtog
1617     \par\medskip\small\noindent#1: %
1618   \or % sigconf
1619     \section*{#1}%
1620   \or % siggraph
1621     \section*{#1}%
1622   \or % sigplan
1623     \paragraph*{#1}%
1624   \or % sigchi
1625     \section*{#1}%
1626   \or % sigchi-a
1627     \section*{#1}%
1628   \fi}

```

`\@printtopmatter` The printing of top matter starts the new page, and uses the given title box. Note that for sigchi-a we print badges here rather than in `\mktitle` since we want them on the margins.

```

1629 \def\@printtopmatter{%
1630   \ifx\@startPage\@empty
1631     \gdef\@startPage{1}%
1632   \else
1633     \setcounter{page}{\@startPage}%
1634   \fi
1635   \thispagestyle{firstpagestyle}%
1636   \noindent
1637   \ifcase\ACM@format@nr
1638     \relax % manuscript
1639     \box\mktitle@bx\par
1640   \or % acmsmall
1641     \box\mktitle@bx\par
1642   \or % acmlarge
1643     \box\mktitle@bx\par
1644   \or % acmtog
1645     \twocolumn[\box\mktitle@bx]%
1646   \or % sigconf
1647     \twocolumn[\box\mktitle@bx]%

```

```

1648 \or % siggraph
1649   \twocolumn[\box\mktitle@bx]%
1650 \or % sigplan
1651   \twocolumn[\box\mktitle@bx]%
1652 \or % sigchi
1653   \twocolumn[\box\mktitle@bx]%
1654 \or % sigchi-a
1655   \par\box\mktitle@bx\par\bigskip
1656   \if@ACM@badge
1657     \marginpar{\noindent
1658       \ifx\@acmBadgeL@image\@empty\else
1659         \href{\@acmBadgeL@url}{%
1660           \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}%
1661         \hskip\@ACM@badge@skip
1662       \fi
1663       \ifx\@acmBadgeR@image\@empty\else
1664         \href{\@acmBadgeR@url}{%
1665           \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}%
1666       \fi}%
1667   \fi
1668 \fi
1669 }

\@mktitle The title of the article
1670 \def\@mktitle{%
1671   \ifcase\ACM@format@nr
1672   \relax % manuscript
1673     \@mktitle@i
1674   \or % acmsmall
1675     \@mktitle@i
1676   \or % acmlarge
1677     \@mktitle@i
1678   \or % acmtog
1679     \@mktitle@i
1680   \or % sigconf
1681     \@mktitle@iii
1682   \or % siggraph
1683     \@mktitle@iii
1684   \or % sigplan
1685     \@mktitle@iii
1686   \or % sigchi
1687     \@mktitle@iii
1688   \or % sigchi-a
1689     \@mktitle@iv
1690   \fi
1691 }

\@titlefont The font to typeset title
1692 \def\@titlefont{%
1693   \ifcase\ACM@format@nr

```

```

1694 \relax % manuscript
1695 \LARGE\sffamily\bfseries
1696 \or % acmsmall
1697 \LARGE\sffamily\bfseries
1698 \or % acmlarge
1699 \LARGE\sffamily\bfseries
1700 \or % acmtog
1701 \Huge\sffamily
1702 \or % sigconf
1703 \Huge\sffamily\bfseries
1704 \or % siggraph
1705 \Huge\sffamily\bfseries
1706 \or % sigplan
1707 \Huge\bfseries
1708 \or % sigchi
1709 \Huge\sffamily\bfseries
1710 \or % sigchi-a
1711 \Huge\bfseries
1712 \fi}

\@subtitlefont The font to typeset title
1713 \def\@subtitlefont{\normalsize
1714 \ifcase\ACM@format@nr
1715 \relax % manuscript
1716 \mdseries
1717 \or % acmsmall
1718 \mdseries
1719 \or % acmlarge
1720 \mdseries
1721 \or % acmtog
1722 \LARGE
1723 \or % sigconf
1724 \LARGE\mdseries
1725 \or % siggraph
1726 \LARGE\mdseries
1727 \or % sigplan
1728 \LARGE\mdseries
1729 \or % sigchi
1730 \LARGE\mdseries
1731 \or % sigchi-a
1732 \mdseries
1733 \fi}

\@mktitle@i The version of \mktitle for most journals
1734 \def\@mktitle@i{\hsize=\textwidth
1735 \ACM@title@width=\hsize
1736 \ifx\@acmBadgeL@image\@empty\else
1737 \advance\ACM@title@width by -\ACM@badge@width
1738 \advance\ACM@title@width by -\ACM@badge@skip
1739 \fi

```

```

1740 \ifx\@acmBadgeR@image\@empty\else
1741   \advance\@ACM@title@width by -\@ACM@badge@width
1742   \advance\@ACM@title@width by -\@ACM@badge@skip
1743 \fi
1744 \setbox\mktitle@bx=\vbox{\noindent\@titlefont
1745   \ifx\@acmBadgeL@image\@empty\else
1746     \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeL@url}{%
1747       \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}%
1748     \hskip\@ACM@badge@skip
1749   \fi
1750   \parbox[t]{\@ACM@title@width}{\raggedright
1751     \@titlefont\noindent
1752     \@title
1753   \ifx\@subtitle\@empty\else
1754     \par\noindent{\@subtitlefont\@subtitle}
1755   \fi}%
1756   \ifx\@acmBadgeR@image\@empty\else
1757     \hskip\@ACM@badge@skip
1758     \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
1759       \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}%
1760   \fi
1761   \par\bigskip}}%

```

\mktitle@ii The version of \mktitle for TOG. Since v1.06 is subsumed by the \mktitle@i macro

\mktitle@iii The version of \mktitle for sigproc. Note that since the title is centered, we leave the space for the left badge even if only the right badge is defined.

```

1762 \def\mktitle@iii{\hsize=\textwidth
1763   \setbox\mktitle@bx=\vbox{\@titlefont\centering
1764     \@ACM@title@width=\hsize
1765     \if@ACM@badge
1766       \advance\@ACM@title@width by -2\@ACM@badge@width
1767       \advance\@ACM@title@width by -2\@ACM@badge@skip
1768       \parbox[b]{\@ACM@badge@width}{\strut
1769         \ifx\@acmBadgeL@image\@empty\else
1770           \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeL@url}{%
1771             \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}%
1772         \fi}%
1773       \hskip\@ACM@badge@skip
1774     \fi
1775     \parbox[t]{\@ACM@title@width}{\centering\@titlefont
1776       \@title
1777       \ifx\@subtitle\@empty\else
1778         \par\noindent{\@subtitlefont\@subtitle}
1779       \fi
1780     }%
1781     \if@ACM@badge
1782       \hskip\@ACM@badge@skip
1783       \parbox[b]{\@ACM@badge@width}{\strut
1784         \ifx\@acmBadgeR@image\@empty\else

```

```

1785         \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
1786         \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}%
1787     \fi}%
1788 \fi
1789 \par\bigskip}}%

```

\@mktitle@iv The version of \@mktitle for sigchi-a

```

1790 \def\@mktitle@iv{\hsize=\textwidth
1791     \setbox\mktitle@bx=\vbox{\raggedright\leftskip5pc\@titlefont
1792     \noindent\leavevmode\leaders\hrule height 2pt\hfill\kern0pt\par
1793     \noindent\@title
1794     \ifx\@subtitle\@empty\else
1795     \par\noindent\@subtitlefont\@subtitle
1796     \fi
1797     \par\bigskip}}%

```

\@ACM@addtoaddress The macro adds an item to address using the following rules:

1. If we start a paragraph, add the item
2. Otherwise, add a comma and the item
3. However, the comma is deleted, if it is on the end of the line. We use the magic cleaders trick for this.

```

1798 \newbox\@ACM@commabox
1799 \def\@ACM@addtoaddress#1{%
1800     \ifvmode\else
1801     \if@ACM@affiliation@obeypunctuation\else
1802     \setbox\@ACM@commabox=\hbox{, }%
1803     \unskip\cleaders\copy\@ACM@commabox\hskip\wd\@ACM@commabox
1804     \fi\fi
1805     #1}

```

\institution heoretically we can define the macros for \@affiliation inside the \@mkauthors-style commands. However, this would lead to a strange error if an author uses them outside
\position commands. Of course we can make them produce an error message, but...
\department \@affiliation. Of course we can make them produce an error message, but...
\streetaddress

```

1806 \def\streetaddress#1{\unskip\ignorespaces}
1807 \def\postcode#1{\unskip\ignorespaces}
1808 \if@ACM@journal
1809     \def\position#1{\unskip\ignorespaces}
1810     \def\institution#1{\unskip~#1\ignorespaces}
1811     \def\city#1{\unskip\ignorespaces}
1812     \def\state#1{\unskip\ignorespaces}
1813     \newcommand\department[2][0]{\unskip\ignorespaces}
1814     \def\country#1{\if@ACM@affiliation@obeypunctuation\else, \fi#1\ignorespaces}
1815 \else
1816     \def\position#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1817     \def\institution#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1818     \newcommand\department[2][0]{\if@ACM@affiliation@obeypunctuation

```



```

1819     #2\else#2\par\fi}%
1820 % \def\streetaddress#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1821 \let\city\@ACM@addtoaddress
1822 \let\state\@ACM@addtoaddress
1823 % \def\postcode#1{\if@ACM@affiliation@obeypunctuation#1\else\unskip\space#1\fi}%
1824 \let\country\@ACM@addtoaddress
1825 \fi

```

\@mkauthors Typesetting authors

```

1826 \def\@mkauthors{\begingroup
1827   \hsize=\textwidth
1828   \ifcase\ACM@format@nr
1829   \relax % manuscript
1830     \@mkauthors@i
1831   \or % acmsmall
1832     \@mkauthors@i
1833   \or % acmlarge
1834     \@mkauthors@i
1835   \or % acmtog
1836     \@mkauthors@i
1837   \or % sigconf
1838     \@mkauthors@iii
1839   \or % siggraph
1840     \@mkauthors@iii
1841   \or % sigplan
1842     \@mkauthors@iii
1843   \or % sigchi
1844     \@mkauthors@iii
1845   \or % sigchi-a
1846     \@mkauthors@iv
1847   \fi
1848   \endgroup
1849 }

```

\@authorfont Somehow different conferences use different fonts for author names. Why?

```

1850 \def\@authorfont{\Large\sffamily}

```

\@affiliationfont Font for affiliations

```

1851 \def\@affiliationfont{\normalsize\normalfont}

```

Adjusting fonts for different formats

```

1852 \ifcase\ACM@format@nr
1853 \relax % manuscript
1854 \or % acmsmall
1855   \def\@authorfont{\large\sffamily}
1856   \def\@affiliationfont{\small\normalfont}
1857 \or % acmlarge
1858 \or % acmtog
1859   \def\@authorfont{\LARGE\sffamily}

```

```

1860 \def\@affiliationfont{\large}
1861 \or % sigconf
1862 \def\@authorfont{\LARGE}
1863 \def\@affiliationfont{\large}
1864 \or % siggraph
1865 \def\@authorfont{\normalsize\normalfont}
1866 \def\@affiliationfont{\normalsize\normalfont}
1867 \or % sigplan
1868 \def\@authorfont{\Large\normalfont}
1869 \def\@affiliationfont{\normalsize\normalfont}
1870 \or % sigchi
1871 \def\@authorfont{\bfseries}
1872 \def\@affiliationfont{\mdseries}
1873 \or % sigchi-a
1874 \def\@authorfont{\bfseries}
1875 \def\@affiliationfont{\mdseries}
1876 \fi

```

\typeset@author@line At this point we have \@currentauthors and \@currentaffiliations. We typeset them in the journal style

```

1877 \def\@typeset@author@line{%
1878 \andify\@currentauthors\par\noindent
1879 \@currentauthors\def\@currentauthors{}%
1880 \ifx\@currentaffiliations\@empty\else
1881 \andify\@currentaffiliations
1882 \unskip, {\@currentaffiliations}\par
1883 \fi
1884 \def\@currentaffiliations{}}

```

\mkauthors@i This is version used in most journal formats. Note that \and between authors with the same affiliation becomes _and_:

```

1885 \def\@mkauthors@i{%
1886 \def\@currentauthors{}%
1887 \def\@currentaffiliations{}%
1888 \global\let\and\@typeset@author@line
1889 \def\@author##1{%
1890 \ifx\@currentauthors\@empty
1891 \gdef\@currentauthors{\@authorfont\MakeTextUppercase{##1}}%
1892 \else
1893 \g@addto@macro{\@currentauthors}{\and\MakeTextUppercase{##1}}%
1894 \fi
1895 \gdef\and{}}%
1896 \def\email##1##2{%
1897 \def\affiliation##1##2{%
1898 \def\@tempa{##2}\ifx\@tempa\@empty\else
1899 \ifx\@currentaffiliations\@empty
1900 \gdef\@currentaffiliations{%
1901 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1902 \setkeys{@ACM@affiliation@}{##1}}%

```

```

1903         \@affiliationfont##2}%
1904     \else
1905         \g@addto@macro{\@currentaffiliations}{\and
1906             \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1907             \setkeys{@ACM@affiliation@}{##1}##2}%
1908     \fi
1909 \fi
1910 \global\let\and\@typeset@author@line}%
1911 \global\setbox\mktitle@bx=\vbox{\noindent\box\mktitle@bx\par\medskip
1912     \noindent\addresses\@typeset@author@line
1913     \par\medskip}%
1914 }

```

\@mkauthors@ii \@mkauthors@ii was version used in acmtog. No longer necessary

\author@bx The box to put individual author to
1915 \newbox\author@bx

\author@bx@wd The width of the author box
1916 \newdimen\author@bx@wd

\author@bx@sep The separation between the author boxes
1917 \newskip\author@bx@sep
1918 \author@bx@sep=1pc\relax

\@typeset@author@bx Typesetting the box with authors. Note that in SIGCHI-A the box is not centered.

```

1919 \def\@typeset@author@bx{\bgroup\hsize=\author@bx@wd\def\and{\par}%
1920     \global\setbox\author@bx=\vtop{\if@ACM@sigchiamode\else\centering\fi
1921         \@authorfont\@currentauthors\par\@affiliationfont
1922         \@currentaffiliation}\egroup
1923     \box\author@bx\hspace{\author@bx@sep}%
1924     \gdef\@currentauthors{}}%
1925     \gdef\@currentaffiliation{}}

```

\@mkauthors@iii The sigconf version. Here we use centered design with each author in a separate box.
1926 \def\@mkauthors@iii{%

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width $(\text{textwidth} - \text{author@bx@sep})/N - \text{author@bx@sep}$, where N is the number of boxes per row.

```

1927 \author@bx@wd=\textwidth\relax
1928 \advance\author@bx@wd by -\author@bx@sep\relax
1929 \ifnum\@ACM@authorsperrrow>0\relax
1930     \divide\author@bx@wd by \@ACM@authorsperrrow\relax
1931 \else
1932     \ifcase\@num@authorgroups
1933         \relax % 0?
1934         \or % 1=one author per row

```

```

1935 \or % 2=two authors per row
1936 \divide\author@bx@wd by \num@authorgroups\relax
1937 \or % 3=three authors per row
1938 \divide\author@bx@wd by \num@authorgroups\relax
1939 \or % 4=two authors per row (!)
1940 \divide\author@bx@wd by 2\relax
1941 \else % three authors per row
1942 \divide\author@bx@wd by 3\relax
1943 \fi
1944 \fi
1945 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

1946 \gdef\@currentauthors{}%
1947 \gdef\@currentaffiliation{}%
1948 \def\@author##1{\ifx\@currentauthors\@empty
1949 \gdef\@currentauthors{\par##1}%
1950 \else
1951 \g@addto@macro\@currentauthors{\par##1}%
1952 \fi
1953 \gdef\and{}}%
1954 \def\email##1##2{\ifx\@currentaffiliation\@empty
1955 \gdef\@currentaffiliation{\nolinkurl{##2}}%
1956 \else
1957 \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
1958 \fi}%
1959 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
1960 \gdef\@currentaffiliation{%
1961 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1962 \setkeys{@ACM@affiliation@}{##1}##2}%
1963 \else
1964 \g@addto@macro\@currentaffiliation{\par
1965 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1966 \setkeys{@ACM@affiliation@}{##1}##2}%
1967 \fi
1968 \global\let\and\@typeset@author@bx
1969 }%

```

Actual typesetting is done by \and macro:

```

1970 \hspace=\textwidth
1971 \global\setbox\mktitle@bx=\vbox{\noindent
1972 \box\mktitle@bx\par\medskip\leavevmode
1973 \lineskip=1pc\relax\centering\hspace*{-1em}%
1974 \addresses\let\and\@typeset@author@bx\and\par\bigskip}}

```

\@mkauthors@iv The sigchia version. Now we put authors in the main text, and no more than 2 authors per line, unless overridden.

```

1975 \def\@mkauthors@iv{%

```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must

be of width $(\text{textwidth} - \text{author@bx@sep})/N - \text{author@bx@sep}$, where N is the number of boxes per row.

```

1976 \author@bx@wd=\columnwidth\relax
1977 \advance\author@bx@wd by -\author@bx@sep\relax
1978 \ifnum\@ACM@authorsperrow>0\relax
1979 \divide\author@bx@wd by \@ACM@authorsperrow\relax
1980 \else
1981 \ifcase\num@authorgroups
1982 \relax % 0?
1983 \or % 1=one author per row
1984 \else % 2=two authors per row
1985 \divide\author@bx@wd by 2\relax
1986 \fi
1987 \fi
1988 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

1989 \gdef\@currentauthors{}%
1990 \gdef\@currentaffiliation{}%
1991 \def\@author##1{\ifx\@currentauthors\@empty
1992 \gdef\@currentauthors{\par##1}%
1993 \else
1994 \g@addto@macro\@currentauthors{\par##1}%
1995 \fi
1996 \gdef\and{}}%
1997 \def\email##1##2{\ifx\@currentaffiliation\@empty
1998 \gdef\@currentaffiliation{\nolinkurl{##2}}%
1999 \else
2000 \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
2001 \fi}%
2002 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
2003 \gdef\@currentaffiliation{%
2004 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2005 \setkeys{@ACM@affiliation@}{##1}##2}%
2006 \else
2007 \g@addto@macro\@currentaffiliation{\par
2008 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2009 \setkeys{@ACM@affiliation@}{##1}##2}%
2010 \fi
2011 \global\let\and\@typeset@author@bx}%
2012 %

```

Actual typesetting is done by \and macro

```

2013 \bgroup\hsize=\columnwidth
2014 \par\raggedright\leftskip=\z@
2015 \lineskip=1pc\noindent
2016 \addresses\let\and\@typeset@author@bx\and\par\bigskip\egroup}

```

\@mkauthorsaddresses Typesetting authors' addresses in the footnote style

\@setaddresses This is an amsart macro, which we do not need.

```

2017 \def\@setaddresses{}

\@authornotemark Adding footnotemark to authors. This version adds “normal” footnotemark.
2018 \def\@authornotemark{\g@addto@macro\@currentauthors{\footnotemark\relax}}

\@@authornotemark Adding footnotemark to authors with the given number
2019 \def\@@authornotemark#1{\g@addto@macro\@currentauthors{\footnotemark[#1]}}

\@mkteasers Typesetting teasers
2020 \def\@mkteasers{%
2021   \ifx\@teaserfigures\@empty\else
2022     \def\@teaser##1{\par\bigskip\bgroup
2023       \captionsetup{type=figure}##1\egroup\par}
2024     \global\setbox\mktitle@bx=\vbox{\noindent\box\mktitle@bx\par
2025       \noindent\@teaserfigures\par\medskip}%
2026     \fi}

\@mkabstract Typesetting abstract
2027 \def\@mkabstract{\bgroup
2028   \ifx\@abstract\@empty\else
2029     {\phantomsection\addcontentsline{toc}{section}{Abstract}%
2030     \if@ACM@journal
2031       \small\noindent
2032     \else
2033       \section*{Abstract}%
2034     \fi
2035     \ignorespaces\@abstract\par}%
2036   \fi\egroup}

\@mkbibcitation Print bibcitation format
2037 \def\@mkbibcitation{\bgroup
2038   \def\@pages@word{\ifnum\getrefnumber{TotPages}=1\relax page\else pages\fi}%
2039   \def\footnotemark{}%
2040   \def\unskip{} \ignorespaces}%
2041   \def\footnote{\ClassError{\@classname}{Please do not use footnotes
2042     inside \string\title{} or \string\author{} command! Use
2043     \string\titlenote{} or \string\authornote{} instead!}}%
2044   \def\@article@string{\ifx\@acmArticle\@empty{\ }else,
2045     Article~\@acmArticle\ }fi}%
2046   \par\medskip\small\noindent{\bfseries ACM Reference Format:}\par\nobreak
2047   \noindent\authors. \@acmYear. \@title
2048   \ifx\@subtitle\@empty. \else: \@subtitle. \fi
2049   \if@ACM@journal
2050     \textit{\@journalNameShort}
2051     \@acmVolume, \@acmNumber \@article@string (\@acmPubDate),
2052     \ref{TotPages}~\@pages@word.
2053   \else
2054     In \textit{\@acmBooktitle}%
2055     \ifx\@acmEditors\@empty\textit{.}\else

```

```

2056      \andify\@acmEditors\textit{, }\@acmEditors~\@editorsAbbrev.%
2057      \fi\
2058      ACM, New York, NY, USA%
2059      \@article@string\unskip, \ref{TotPages}~\@pages@word.
2060      \fi
2061      \@formatdoi{\@acmDOI}
2062 \par\egroup}

\@printendtopmatter End the top matter
2063 \def\@printendtopmatter{\par\bigskip}

\@setthanks We redefine \setthanks using \long
2064 \def\@setthanks{\long\def\thanks##1{\par##1\@addpunct.}\thankses}

\@setauthorsaddresses
2065 \def\@setauthorsaddresses{\@authorsaddresses\unskip\@addpunct.}

```

3.14 Headers and Footers

We use fancyhdr for our headers and footers:

```

2066 \RequirePackage{fancyhdr}

\ACM@linecount@bx This is the box displayed in the review mode
2067 \if@ACM@review
2068   \newsavebox{\ACM@linecount@bx}
2069   \newlength\ACM@linecount@bxht
2070   \newcount\ACM@linecount
2071   \ACM@linecount\@ne\relax
2072   \def\ACM@mk@linecount{%
2073     \savebox{\ACM@linecount@bx}[4em][t]{\parbox[t]{4em}{%
2074       \setlength{\ACM@linecount@bxht}{0pt}%
2075       \loop{\color{red}\scriptsize\the\ACM@linecount}\@ne
2076       \global\advance\ACM@linecount by \@ne
2077       \addtolength{\ACM@linecount@bxht}{\baselineskip}%
2078       \ifdim\ACM@linecount@bxht<\textheight\repeat
2079       {\color{red}\scriptsize\the\ACM@linecount}\hfill
2080       \global\advance\ACM@linecount by \@ne}}}%
2081   \fi

\ACM@linecountL How to display the box on the left
2082 \def\ACM@linecountL{%
2083   \if@ACM@review
2084     \ACM@mk@linecount
2085     \begin{picture}(0,0)%
2086       \put(-26,-22){\usebox{\ACM@linecount@bx}}%
2087     \end{picture}%
2088   \fi}

```

\ACM@linecountR How to display the box on the right

```
2089 \def\ACM@linecountR{%
2090   \if@ACM@review
2091   \ACM@mk@linecount
2092   \begin{picture}(0,0)%
2093     \put(20,-22){\usebox{\ACM@linecount@bx}}%
2094   \end{picture}%
2095   \fi}
```

\ACM@timestamp The timestamp system

```
2096 \if@ACM@timestamp
2097   % Subtracting 30 from \time gives us the effect of rounding-down despite
2098   % \numexpr rounding to nearest
2099   \newcounter{ACM@time@hours}
2100   \setcounter{ACM@time@hours}{\numexpr (\time - 30) / 60 \relax}
2101   \newcounter{ACM@time@minutes}
2102   \setcounter{ACM@time@minutes}{\numexpr \time - \theACM@time@hours * 60 \relax}
2103   \newcommand\ACM@timestamp{%
2104     \footnotesize%
2105     \the\year-\two@digits{\the\month}-\two@digits{\the\day}{ }%
2106     \two@digits{\theACM@time@hours}:\two@digits{\theACM@time@minutes}{ }%
2107     page~\thepage\ (pp. \@startPage-\pageref*{TotPages})%
2108     \ifx\@acmSubmissionID\@empty\relax\else
2109     ~Submission~ID: \@acmSubmissionID
2110   \fi
2111 }
2112 \fi
```

\@shortauthors Even if the author redefined \shortauthors, we do not print them in the anonymous mode in the headers:

```
2113 \def\@shortauthors{\if@ACM@anonymous Anon.\else\shortauthors\fi}
```

\@headfootfont The font to typeset header and footer text.

```
2114 \def\@headfootfont{%
2115   \ifcase\ACM@format@nr
2116   \relax % manuscript
2117   \sffamily
2118   \or % acmsmall
2119   \sffamily
2120   \or % acmlarge
2121   \sffamily
2122   \or % acmtog
2123   \sffamily
2124   \or % sigconf
2125   \sffamily
2126   \or % siggraph
2127   \sffamily
2128   \or % sigplan
2129   \sffamily
```



```

2130 \or % sigchi
2131 \sffamily
2132 \or % sigchi-a
2133 \sffamily
2134 \fi}

```

standardpagestyle The pagestyle for all pages but the first one

```

2135 \fancypagestyle{standardpagestyle}{%
2136 \fancyhf{}%
2137 \renewcommand{\headrulewidth}{\z@}%
2138 \renewcommand{\footrulewidth}{\z@}%
2139 \ifcase\ACM@format@nr
2140 \relax % manuscript
2141 \fancyhead[LE]{\ACM@linecountL\if@ACM@printfolios\thepage\fi}%
2142 \fancyhead[RO]{\if@ACM@printfolios\thepage\fi}%
2143 \fancyhead[RE]{\@shortauthors}%
2144 \fancyhead[LO]{\ACM@linecountL\shorttitle}%
2145 \fancyfoot[RO,LE]{\footnotesize Manuscript submitted to ACM}%
2146 \or % acmsmall
2147 \fancyhead[LE]{\ACM@linecountL\@headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2148 \fancyhead[RO]{\@headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2149 \fancyhead[RE]{\@headfootfont\@shortauthors}%
2150 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2151 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2152 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2153 \or % acmlarge
2154 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2155 \@acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2156 \fancyhead[LO]{\ACM@linecountL}%
2157 \fancyhead[RO]{\@headfootfont
2158 \shorttitle\quad\textbullet\quad\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2159 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2160 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2161 \or % acmtog
2162 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2163 \@acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2164 \fancyhead[LO]{\ACM@linecountL}%
2165 \fancyhead[RE]{\ACM@linecountR}%
2166 \fancyhead[RO]{\@headfootfont
2167 \shorttitle\quad\textbullet\quad\@acmArticle\if@ACM@printfolios:\thepage\fi\ACM@linecountR}%
2168 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2169 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2170 \else % Proceedings
2171 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2172 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2173 \fancyhead[RE]{\@headfootfont\@shortauthors\ACM@linecountR}%
2174 \fancyhead[LE]{\ACM@linecountL\@headfootfont\acmConference@shortname,
2175 \acmConference@date, \acmConference@venue}%
2176 \fancyhead[RO]{\@headfootfont\acmConference@shortname,
2177 \acmConference@date, \acmConference@venue\ACM@linecountR}%

```

```

2178 \fi
2179 \if@ACM@sigchiamode
2180 \fancyheadoffset[L]{\dimexpr(\marginparsep+\marginparwidth)}%
2181 \fi
2182 \if@ACM@timestamp
2183 \fancyfoot[LO,RE]{\ACM@timestamp}
2184 \fi
2185 }
2186 \pagestyle{standardpagestyle}

\@folio@wd Folio blob width, height, offsets and max number
\@folio@ht
\@folio@voffset
\@folio@max
2187 \newdimen\@folio@wd
2188 \@folio@wd=\z@
2189 \newdimen\@folio@ht
2190 \@folio@ht=\z@
2191 \newdimen\@folio@voffset
2192 \@folio@voffset=\z@
2193 \def\@folio@max{1}
2194 \ifcase\ACM@format@nr
2195 \relax % manuscript
2196 \or % acmsmall
2197 \@folio@wd=45.75pt\relax
2198 \@folio@ht=1.25in\relax
2199 \@folio@voffset=.2in\relax
2200 \def\@folio@max{8}
2201 \or % acmlarge
2202 \@folio@wd=43.25pt\relax
2203 \@folio@ht=79pt\relax
2204 \@folio@voffset=.55in\relax
2205 \def\@folio@max{10}
2206 \fi

\@folioblob The macro to typeset the folio blob.
2207 \def\@folioblob{\@tempcnta=0\@acmArticleSeq\relax
2208 \ifnum\@tempcnta=0\relax\else
First, we calculate \@acmArticleSeq modulo \@folio@max
2209 \loop
2210 \ifnum\@tempcnta>\@folio@max\relax
2211 \advance\@tempcnta by - \@folio@max
2212 \repeat
2213 \advance\@tempcnta by -1\relax
2214 \@tempdima=\@folio@ht\relax
2215 \multiply\@tempdima by \the\@tempcnta\relax
2216 \advance\@tempdima by -\@folio@voffset\relax
2217 \begin{picture}(0,0)
2218 \makebox[\z@]{\raisebox{-\@tempdima}{%
2219 \rlap{%
2220 \raisebox{-0.45\@folio@ht}{\z@}\z@}{%
2221 \rule{\@folio@wd}{\@folio@ht}}}%

```

```

2222         \parbox{\@folio@wd}{%
2223             \centering
2224             \textcolor{white}{\LARGE\sffamily\bfseries\@acmArticle}}}}
2225     \end{picture}\fi}
2226

```

firstpagestyle The pagestyle for the first page only.

```

2227 \fancypagestyle{firstpagestyle}{%
2228     \fancyhf{}%
2229     \renewcommand{\headrulewidth}{\z@}%
2230     \renewcommand{\footrulewidth}{\z@}%
2231     \ifcase\ACM@format@nr
2232     \relax % manuscript
2233         \fancyhead[L]{\ACM@linecountL}%
2234         \fancyfoot[RO,LE]{\if@ACM@printfolios\small\thepage\fi}%
2235         \fancyfoot[RE,LO]{\footnotesize Manuscript submitted to ACM}%
2236     \or % acmsmall
2237         \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2238             \@acmNumber, Article \@acmArticle. Publication date:
2239             \@acmPubDate.}%
2240         \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2241         \fancyhead[LO]{\ACM@linecountL}%
2242         \fancyhead[RO]{\@folioblob}%
2243         \fancyheadoffset[RO,LE]{0.6\@folio@wd}%
2244     \or % acmlarge
2245         \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2246             \@acmNumber, Article \@acmArticle. Publication date:
2247             \@acmPubDate.}%
2248         \fancyhead[RO]{\@folioblob}%
2249         \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2250         \fancyhead[LO]{\ACM@linecountL}%
2251         \fancyheadoffset[RO,LE]{1.4\@folio@wd}%
2252     \or % acmtog
2253         \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2254             \@acmNumber, Article \@acmArticle. Publication date:
2255             \@acmPubDate.}%
2256         \fancyhead[L]{\ACM@linecountL}%
2257         \fancyhead[R]{\ACM@linecountR}%
2258     \else % Conference proceedings
2259         \fancyhead[L]{\ACM@linecountL}%
2260         \fancyhead[R]{\ACM@linecountR}%
2261         \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2262     \fi
2263     \if@ACM@timestamp
2264         \ifnum\ACM@format@nr=0\relax % Manuscript
2265             \fancyfoot[LO,RE]{\ACM@timestamp\quad
2266                 \footnotesize Manuscript submitted to ACM}
2267         \else
2268             \fancyfoot[LO,RE]{\ACM@timestamp}
2269         \fi

```

```
2270 \fi
2271 }
```

`\ACM@restore@pagestyle` The following code by Ross Moore protects against changes by `totpages` package:

```
2272 \let\ACM@ps@plain\ps@plain
2273 \let\ACM@ps@myheadings\ps@myheadings
2274 \let\ACM@ps@headings\ps@headings
2275 \def\ACM@restore@pagestyle{%
2276   \let\ps@plain\ACM@ps@plain
2277   \let\ps@myheadings\ACM@ps@myheadings
2278   \let\ps@headings\ACM@ps@headings}
2279 \AtBeginDocument{\ACM@restore@pagestyle}
```

3.15 Sectioning

Sectioning is different for different levels

```
2280 \renewcommand\section{\@startsection{section}{1}{\z@}%
2281   {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2282   {.25\baselineskip}%
2283   {\@secfont}}
2284 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
2285   {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2286   {.25\baselineskip}%
2287   {\@subsecfont}}
2288 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{10pt}%
2289   {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2290   {-3.5\p@}%
2291   {\@subsubsecfont\@adddotafter}}
2292 \renewcommand\paragraph{\@startsection{paragraph}{4}{\parindent}%
2293   {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2294   {-3.5\p@}%
2295   {\@parfont\@adddotafter}}
2296 \renewcommand\part{\@startsection{part}{9}{\z@}%
2297   {-10\p@ \@plus -4\p@ \@minus -2\p@}%
2298   {4\p@}%
2299   {\@parfont}}
```

`\section@raggedright` Special version of `\raggedright` compatible with `\MakeUppercase`

```
2300 \def\section@raggedright{\@rightskip\@flushglue
2301   \rightskip\@rightskip
2302   \leftskip\z@skip
2303   \parindent\z@}
```

`\@secfont` Fonts for sections etc. are different for different formats.

```
\@subsecfont 2304 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
\@subsubsecfont 2305 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
\@parfont 2306 \def\@subsubsecfont{\sffamily\itshape}
2307 \def\@parfont{\itshape}
2308 \setcounter{secnumdepth}{3}
```

```

2309 \ifcase\ACM@format@nr
2310 \relax % manuscript
2311 \or % acmsmall
2312 \or % acmlarge
2313 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2314 \def\@subsecfont{\sffamily\large\section@raggedright}
2315 \or % acmtog
2316 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2317 \def\@subsecfont{\sffamily\large\section@raggedright}
2318 \or % sigconf
2319 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
2320 \def\@subsecfont{\bfseries\Large\section@raggedright}
2321 \or % siggraph
2322 \def\@secfont{\sffamily\bfseries\Large\section@raggedright\MakeTextUppercase}
2323 \def\@subsecfont{\sffamily\bfseries\Large\section@raggedright}
2324 \or % sigplan
2325 \def\@secfont{\bfseries\Large\section@raggedright}
2326 \def\@subsecfont{\bfseries\section@raggedright}
2327 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
2328   {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2329   {.25\baselineskip}%
2330   {\@subsubsecfont}}
2331 \def\@subsubsecfont{\bfseries\section@raggedright}
2332 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
2333   {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2334   {-3.5\p@}%
2335   {\@parfont\@addspaceafter}}
2336 \def\@parfont{\bfseries\itshape}
2337 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\z@}%
2338   {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2339   {-3.5\p@}%
2340   {\@subparfont\@addspaceafter}}
2341 \def\@subparfont{\itshape}
2342 \or % sigchi
2343 \setcounter{secnumdepth}{1}
2344 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2345 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2346 \or % sigchi-a
2347 \setcounter{secnumdepth}{0}
2348 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2349 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2350 \fi

```

\@adddotafter Add punctuation after the command

```
2351 \def\@adddotafter#1{#1\@addpunct{.}}
```

\@addspaceafter Add space after the command

```
2352 \def\@addspaceafter#1{#1\@addpunct{\enspace}}
```

3.16 TOC Lists

`\dotsep` Related to the `\tableofcontents` are all the horizontal fillers. Base \TeX defines `\dottedtocline`, which we should not disable. Yet, this command expects `\dotsep` to be defined, but leaves this to the class implementation. Since `amsart` does not provide this, we copy the standard variant from `article` here.

```
2353 \providecommand*\dotsep{4.5}
```

3.17 Theorems

`\acmplainbodyfont` The font to typeset the `acmplain` theorem style body.

```
2354 \def\acmplainbodyfont{\itshape}
```

`\acmplainindent` The amount to indent the `acmplain` theorem style.

```
2355 \def\acmplainindent{\parindent}
```

`\acmplainheadfont` The font to typeset the `acmplain` theorem style head.

```
2356 \def\acmplainheadfont{\scshape}
```

`\acmplainnotefont` The font to typeset the `acmplain` theorem style note.

```
2357 \def\acmplainnotefont{\@empty}
```

Customization of `acmplain` theorem style:

```
2358 \ifcase\ACM@format@nr
2359 \relax % manuscript
2360 \or % acmsmall
2361 \or % acmlarge
2362 \or % acmtog
2363 \or % sigconf
2364 \or % siggraph
2365 \or % sigplan
2366 \def\acmplainbodyfont{\itshape}
2367 \def\acmplainindent{\z@}
2368 \def\acmplainheadfont{\bfseries}
2369 \def\acmplainnotefont{\normalfont}
2370 \or % sigchi
2371 \or % sigchi-a
2372 \fi
```

`acmplain` The `acmplain` theorem style

```
2373 \newtheoremstyle{acmplain}%
2374 { .5\baselineskip\@plus.2\baselineskip
2375   \@minus.2\baselineskip}% space above
2376 { .5\baselineskip\@plus.2\baselineskip
2377   \@minus.2\baselineskip}% space below
2378 {\acmplainbodyfont}% body font
2379 {\acmplainindent}% indent amount
2380 {\acmplainheadfont}% head font
```

```

2381 {.}% punctuation after head
2382 {.5em}% spacing after head
2383 {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmplainnotefont{#3}}}}% head spec

\@acmdefinitionbodyfont The font to typeset the acmdefinition theorem style body.
2384 \def\@acmdefinitionbodyfont{\normalfont}

\@acmdefinitionindent The amount to indent the acmdefinition theorem style.
2385 \def\@acmdefinitionindent{\parindent}

\@acmdefinitionheadfont The font to typeset the acmdefinition theorem style head.
2386 \def\@acmdefinitionheadfont{\itshape}

\@acmdefinitionnotefont The font to typeset the acmdefinition theorem style note.
2387 \def\@acmdefinitionnotefont{\@empty}

Customization of acmdefinition theorem style:
2388 \ifcase\ACM@format@nr
2389 \relax % manuscript
2390 \or % acmsmall
2391 \or % acmlarge
2392 \or % acmtog
2393 \or % sigconf
2394 \or % siggraph
2395 \or % sigplan
2396 \def\@acmdefinitionbodyfont{\normalfont}
2397 \def\@acmdefinitionindent{\z@}
2398 \def\@acmdefinitionheadfont{\bfseries}
2399 \def\@acmdefinitionnotefont{\normalfont}
2400 \or % sigchi
2401 \or % sigchi-a
2402 \fi

acmdefinition The acmdefinition theorem style
2403 \newtheoremstyle{acmdefinition}%
2404 { .5\baselineskip \@plus.2\baselineskip
2405 \@minus.2\baselineskip}% space above
2406 { .5\baselineskip \@plus.2\baselineskip
2407 \@minus.2\baselineskip}% space below
2408 {\@acmdefinitionbodyfont}% body font
2409 {\@acmdefinitionindent}% indent amount
2410 {\@acmdefinitionheadfont}% head font
2411 {.}% punctuation after head
2412 {.5em}% spacing after head
2413 {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmdefinitionnotefont{#3}}}}% head spec

Make acmplain the default theorem style.
2414 \theoremstyle{acmplain}

```

Delay defining the theorem environments until after other packages have been loaded. In particular, the `cleveref` package must be loaded before the theorem environments are defined in order to show the correct environment name (see <https://github.com/borisveytsman/acmart/issues/10>). The `acmthm` option is used to suppress the definition of any theorem environments. Also, to avoid obscure errors arising from these environment definitions conflicting with environments defined by the user or by user-loaded packages, we only define environments that have not yet been defined.

```

2415 \AtEndPreamble{%
2416   \if@ACM@acmthm
2417   \theoremstyle{acmplain}
2418   \@ifundefined{theorem}{%
2419     \newtheorem{theorem}{Theorem}[section]
2420   }{}
2421   \@ifundefined{conjecture}{%
2422     \newtheorem{conjecture}[theorem]{Conjecture}
2423   }{}
2424   \@ifundefined{proposition}{%
2425     \newtheorem{proposition}[theorem]{Proposition}
2426   }{}
2427   \newtheorem{lemma}[theorem]{Lemma}
2428   \@ifundefined{lemma}{}{}
2429   \@ifundefined{corollary}{%
2430     \newtheorem{corollary}[theorem]{Corollary}
2431   }{}
2432   \theoremstyle{acmdefinition}
2433   \@ifundefined{example}{%
2434     \newtheorem{example}[theorem]{Example}
2435   }{}
2436   \@ifundefined{definition}{%
2437     \newtheorem{definition}[theorem]{Definition}
2438   }{}
2439   \fi
2440   \theoremstyle{acmplain}
2441 }

```

`\@proofnamefont` The font to typeset the proof name.

```

2442 \def\@proofnamefont{\scshape}

```

`\@proofindent` Whether or not to indent proofs.

```

2443 \def\@proofindent{\indent}

```

Customization of proof environment.

```

2444 \ifcase\ACM@format@nr
2445 \relax % manuscript
2446 \or % acmsmall
2447 \or % acmlarge
2448 \or % acmtog
2449 \or % sigconf
2450 \or % siggraph

```



```

2451 \or % sigplan
2452 \def\@proofnamefont{\itshape}
2453 \def\@proofindent{\noindent}
2454 \or % sigchi
2455 \or % sigchi-a
2456 \fi

proof We want some customization of proof environment.

2457 \renewenvironment{proof}[1][\proofname]{\par
2458 \pushQED{\qed}%
2459 \normalfont \topsep6\p@\@plus6\p@\relax
2460 \trivlist
2461 \item[\@proofindent\hskip\labelsep
2462 {\@proofnamefont #1\@addpunct{.}}]\ignorespaces
2463 }{%
2464 \popQED\endtrivlist\@endpfalse
2465 }

```

3.18 Acknowledgments

```

\acks This is a comment-like structure

2466 \specialcomment{acks}{%
2467 \begingroup
2468 \section*{Acknowledgments}
2469 \phantomsection\addcontentsline{toc}{section}{Acknowledgments}
2470 }{%
2471 \endgroup
2472 }

```

\grantsponsor We just typeset the name of the sponsor

```

2473 \def\grantsponsor#1#2#3{#2}

```

\grantnum

```

2474 \newcommand\grantnum[3][\]{#3%
2475 \def\@tempa{#1}\ifx\@tempa\@empty\else\space(\url{#1})\fi}

```

3.19 Conditional typesetting

We use the comment package for conditional typesetting:

```

2476 \AtEndPreamble{%
2477 \if@ACM@screen
2478 \includecomment{screenonly}
2479 \excludecomment{printonly}
2480 \else
2481 \excludecomment{screenonly}
2482 \includecomment{printonly}
2483 \fi
2484 \if@ACM@anonymous

```

```

2485 \excludecomment{anonsuppress}
2486 \excludecomment{acks}
2487 \else
2488 \includecomment{anonsuppress}
2489 \fi}

```

3.20 Additional bibliography commands

`\showeprint` The command `\showeprint` has two arguments: the (optional) prefix and the eprint number. Right now the only prefix we understand is the (lowercase) word ‘arxiv’ (see <http://arxiv.org/hypertex/bibstyles/>).

```

2490 \newcommand\showeprint[2][arxiv]{%
2491   \def\@tempa{#1}%
2492   \ifx\@tempa\@empty\def\@tempa{arxiv}\fi
2493   \def\@tempb{arxiv}%
2494   \ifx\@tempa\@tempb
2495     arXiv:\href{http://arxiv.org/abs/#2}{#2}\else arXiv:#2%
2496   \fi}

```

3.21 End of Class

```

2497 \normalsize\normalfont\frenchspacing
2498 </class>

```

References

- [1] UK T_EX Users Group. UK list of T_EX frequently asked questions. <http://www.tex.ac.uk>, 2016.
- [2] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://www.ctan.org/pkg/amslatex>.
- [3] Cristophe Fiorio. *algorithm2e.sty—package for algorithms*, October 2015. <http://www.ctan.org/pkg/algorithm2e>.
- [4] Rogério Brito. *The algorithms bundle*, August 2009. <http://www.ctan.org/pkg/algorithms>.
- [5] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*, June 2015. <http://www.ctan.org/pkg/listings>.
- [6] Simon Fear. *Publication quality tables in L^AT_EX*, April 2005. <http://www.ctan.org/pkg/booktabs>.
- [7] Association for Computing Machinery. *ACM Visual Identity Standards*, 2007. <http://identitystandards.acm.org>.
- [8] Axel Sommerfeldt. *The subcaption package*, April 2013. <http://www.ctan.org/pkg/subcaption>.
- [9] Boris Veytsman, Bern Schandl, Lee Netherton, and C. V. Radhakrishnan. *A package to create a nomenclature*, September 2005. <http://www.ctan.org/pkg/nomencl>.
- [10] Nicola L. C. Talbot. *User Manual for glossaries.sty v4.25*, June 2016. <http://www.ctan.org/pkg/subcaption>.
- [11] David Carlisle. *The textcase package*, October 2004. <http://www.ctan.org/pkg/textcase>.

Change History

v1.00		v1.05	
General: First released version	28	General: Added processing doi numbers for acmsiggraph and doi numbers for sigproc.bib	28
v1.01		Patched \setcitestyle command; closes https://github.com/borisveytsman/acmart/issues/19	28
General: Changed hyperref colors in screen mode (closes https://github.com/borisveytsman/acmart/issues/1)	28		
Defined ACM colors	28	v1.06	
Explicitly put draft option (closes https://github.com/borisveytsman/acmart/issues/4)	31	\@ACM@badge@skip: Added macro	57
Set headheight to 1pc for all formats (closes https://github.com/borisveytsman/acmart/issues/5)	28	\@ACM@badge@width: Added macro	57
v1.02		\@ACM@title@width: Added macro	57
General: Added TOPS and TSC (closes https://github.com/borisveytsman/acmart/issues/12)	28	\@mktitle@i: Added processing badges	70
Documentation changes (closes https://github.com/borisveytsman/acmart/issues/13)	28	Made generic	70
v1.03		\@mktitle@ii: Now this macro is obsolete	71
\@formatdoi: Added macro	62	\@mktitle@iii: Added processing badges	71
\if@ACM@authorversion: Added macro	30	Made more generic	71
\maketitle: Added special case of authorversion	65	\@mktitle@iv: Made more generic	72
General: Added anon suppress environment	28	\@printtopmatter: Added processing badges	68
Added authorversion option (closes https://github.com/borisveytsman/acmart/issues/9)	28	\@subtitlefont: Added macro	70
v1.04		\@titlefont: Added macro	69
\acmArticleSeq: Name change by Matthew Fluet	56	\acmBadgeL: Added macro	57
\acmDOI: Name change by Matthew Fluet	57	\acmBadgeR: Added macro	57
\acmISBN: Name change by Matthew Fluet	57	\if@ACM@badge: Added macro	57
General: Updated bibliography for siggraph	28	v1.07	
		\maketitle: Corrected a bug with abstract footnotes	65
		Corrected a bug with permission and footnotes order	65
		v1.08	
		General: SIGPLAN reformatting by Matthew Fluet	28
		Typos corrected (Tobias Pape)	28
		v1.09	
		General: Revert SIGPLAN caption rules	28
		v1.10	
		\maketitle: Corrected a bug with doi in manuscript and author version, https://github.com/borisveytsman/acmart/issues/36	65

General: Changes of	v1.14
‘licensedothergov’ wording	60
standardpagestyle: Reversed folios	
location	81
v1.11	
General: Customization of ACM	
theorem styles and proof	
environment by Matthew Fluet . . .	28
v1.12	
\@marginfigure: Now centering by	
default	44
\@marginfigure: Now centering by	
default	45
\@parfont: Moved to	
\section@raggedright	84
\copyrightpermissionfootnoterule:	
Added macro	41
\descriptionlabel: Redefined	47
\footnoterule: Made shorter	41
\if@ACM@natbib@override: Added	
macro	30
\if@ACM@newfonts: Added macro . . .	43
\maketitle: Moved thanks to	
copyrightpermission box	65
\section@raggedright: Introduced	
macro	84
General: Added graceful behavior	
when libertine fonts are absent . .	42
Documentation updates	28
v1.13	
\@mpfootnotetext: Made minipage	
footnotes centered	42
\bibliographystyle: Redefined	
macro	38
\bibstyle@acmauthoryear: Added	
macro	34
\bibstyle@acmnumeric: Added	
macro	35
\if@ACM@printfolios: Added macro .	58
General: Font adjustments for	
acmsmall	73
Increased font size for ACM Large	
Print bibliographic information by	
default for the proceedings	59
standardpagestyle: Added headers	
for sigs	81
Expanded headers for sigchi-a . . .	81
Suppressed folios if sig	81
\bibstyle@acmauthoryear: Moved	
def of \bibstyle@acmauthoryear	
before use	34
\bibstyle@acmnumeric: Moved def of	
\bibstyle@numeric before use . . .	35
General: \citestyle updates	
(Matthew Fluet)	28
Patched \citestyle	33
v1.15	
\@ACM@addtoaddress: Added macro .	72
\@mkauthors@iii: New authors	
system	75
\@shortauthors: Introduced macro . .	80
\@typeset@author@bx: Moved to	
separate macro	75
\acks: Added macro	89
\affiliation: Added code for author	
groups	54
\author: Added code for author	
groups	53
\city: Added macro	72
\country: Added macro	72
\department: Added macro	72
\grantnum: Added macro	89
\grantsponsor: Added macro	89
\if@insideauthorgroup: Introduced	
macro	53
\institution: Added macro	72
\num@authorgroups: Renamed	53
\orcid: Introduced macro	55
\position: Added macro	72
\postcode: Added macro	72
\state: Added macro	72
\streetaddress: Added macro	72
standardpagestyle: Better handling	
of anonymous mode	81
v1.16	
\@headfootfont: Added macro	80
General: Formatting header/footer	
(Matthew Fluet)	28
standardpagestyle: Customize	
header/footer text font	81
v1.17	
\@makefnmark: Redefined	42
\@mkauthors: TOG now uses the same	
authors block as other journals . .	73
\@mkauthors@ii: Deleted	75
\@mkbibcitation: Added \nobreak	
Changed format for sigs	78

\acmArticle: The default is now numerical	56	v1.25	General: Updated PACMPL	47
\acmMonth: The default must be numerical. Closes #50.	56	v1.26	General: Corrected \shortcite bug	28
\acmNumber: The default is now numerical	56		Documentation typos fixed (thanks to Stephen Spencer)	28
\acmVolume: The default is now numerical	56	v1.27	\if@ACM@printccs: Typo corrected	58
\acmYear: The default is now numerical	56	v1.28	\ccsdesc@parse: Change from \to to \textrightarrow (Matteo Riondato)	60
\description: Decreased indent	47		General: Corrected option natbib behavior	35
\granthum: Added url	89		Got rid of warnings in pdf keywords	37
\grantsponsor: Renamed	89			
\if@ACM@printacmref: Renamed from \if@ACM@printbib	58	v1.29	\@mkabstract: Removed spurious indentation (John Wickerson)	78
General: Slightly decreased margins for sigs	39		\ccsdesc@parse: Add spacing after bullet and around rightarrow; semicolon separators no longer in bold/italic (John Wickerson)	60
standardpagestyle: Added paper title to sigs	81		General: Increased head to 13pt	39
v1.18			standardpagestyle: Corrected printfolios (Matthew Fluet)	81
\@mkauthors@i: Now we andify affiliations	74			
\@typeset@author@line: Added macro	74	v1.30	\department: Added optional parameter	72
General: Natbib is now the default for all formats	28		General: Added \frenchspacing	90
v1.19			Bibtex style now recognizes https:// in doi	28
\@mkabstract: Include 'Abstract' in PDF bookmarks (Matthew Fluet)	78		Switched to T1: looks like libertine has problems with \l in OT1	43
\acks: Include 'Acknowledgements' in PDF bookmarks (Matthew Fluet)	89		Updated IMWUT and PACMPL	47
General: Include 'Abstract', 'Acknowledgements', and 'References' in PDF bookmarks (Matthew Fluet)	28	v1.31	\@additionalaffiliation: Added macro	55
Include 'References' in PDF bookmarks (Matthew Fluet)	33		\@mkbibcitation: Disabled linebreak	78
v1.20			\@startsection: Added \tochangmeasure	35
\@mkabstract: Deleted spurious space	78		Redefined macro	37
General: Bug fixes for bst	28		\@textbottom: Redefined	42
v1.21			\acmMonth: The default now is the current month (Matteo Riondato)	56
\showeprint: Added macro	90		\acmYear: The default now is the current year (Matteo Riondato)	56
v1.22			\additionalaffiliation: Added macro	54
General: More bibliography changes for Aptara	28		\l@section: Redefined macro	37
v1.23			\l@subsection: Redefined macro	37
General: Add PACMPL journal option	28			
v1.24				
General: Add IMWUT journal option	47			

General: Documentation changes . . .	28	BibTeX comma before articleno bug corrected	28
v1.32		BibTeX crossref bug corrected . . .	28
\@formatdoi: New doi format	62	BibTeX numpages bug corrected . .	28
General: Added POMACS journal option	28	Documentation updates	28
Format siggraph is now obsolete . .	28	Moved \citenam definition for non-natbib bibliography, so a package may redefine it	38
v1.33		Switched to Type 1 fonts for libertine even if OTF-capable engine is used (Kai Mindermann) .	43
\@ACM@addtoaddress: Added obexpunctuation code	72	firstpagestyle: Added right linecount for two column formats	83
\@mkauthors@i: Added obexpunctuation code	74	Added timestamp (Michael D. Adams)	83
\@mkauthors@iii: Added obexpunctuation code	75	standardpagestyle: Added right linecount for two column formats	81
\@mkauthors@iv: Added obexpunctuation code	76	Added timestamp (Michael D. Adams)	81
\@subtitlefont: Added \normalsize	70	v1.34	
\ACM@linecountL: Renamed macro .	79	\@mkbibcitation: Deleted DOI from doi numbers	78
\ACM@linecountR: Added macro . .	80	\ACM@linecount@bx: Rulers now are continuous	79
\ACM@timestamp: Added current page number	80	\ACM@linecountL: Rulers now are continuous	79
Added macro (Michael D. Adams) .	80	\ACM@linecountR: Rulers now are continuous	80
Added submission id	80	\maketitle: Added date to the bibstrip in conf proceedings	65
\acmSubmissionID: Added macro . .	57	Deleted 'DOI' from doi numbers .	65
\city: Added obexpunctuation code	72	Rearranged bibstrip	65
\country: Added obexpunctuation code	72	The \terms command is now obsolete	65
\department: Added obexpunctuation code	72	\terms: The \terms command now just produces a warning	58
\if@ACM@affiliation@obexpunctuation: Added macro	54	v1.35	
\if@ACM@authordraft: Added macro	30	\@bibstyle@acmauthoryear: Square brackets for author-year style . . .	34
\if@ACM@natbib@override: Deleted macro	30	General: BibTeX bug fixed: et al. . . .	28
\if@ACM@timestamp: Added macro (Michael D. Adams)	30	If the copyright is set to usgov or rigtsretained, the price is suppressed	60
\institution: Added obexpunctuation code	72	v1.36	
\maketitle: Fixed the bug with figures on top and bottom of the title page, thanks to David Epstein	65	\@ACM@authorsperrow: Added macro	58
\position: Added obexpunctuation code	72	\@mkauthors@iii: Added authorsperrow override	75
\postcode: Added obexpunctuation code	72	\@mkauthors@iv: Added authorsperrow override	76
\state: Added obexpunctuation code	72		
\streetaddress: Added obexpunctuation code	72		
General: Added acmart-preload-hook	28		
Added cmap and glyphtounicode .	42		

\if@ACM@authordraft: Corrected typo, thanks to bargteil	30	General: Added 'textcase' package . .	33
General: Added PACMHCI journal options	47	Added heightrounded to geometry	39
Added the possibility to adjust number of author boxes per row in conference formats	28	Added new copyright version: licensedcagov	28
v1.37		Added package cleveref	28
\description: Reduce list indentation (Matthew Fluet)	47	Added Ross Moore code for glyphtounicode	42
\descriptionlabel: Reduce list indentation (Matthew Fluet)	47	Bibliography changes	28
\normalparindent: Set \normalparindent (Matthew Fluet)	41	v1.41	
General: Reduce list indentation (Matthew Fluet)	46	General: Added new badges	28
Set \normalparindent; Reduce list indentation (Matthew Fluet)	28	v1.42	
v1.38		General: Deleted ACM badges	28
General: Increase default font size for SIGPLAN	28, 32	v1.43	
v1.39		\@startsection: Added \makeatletter	37
\@authornotemark: Added macro . .	78	\country: Added comma before country for journals	72
\authornotemark: Added macro . . .	56	v1.44	
v1.40		\@acmBooktitle: Added macro	53
\@copyrightowner: Added new copyright version: licensedcagov .	61	\@acmEditors: Added macro	53
\@copyrightpermission: Added new copyright version: licensedcagov .	62	\@editorsAbbrev: Added macro . . .	53
\@mkauthors@i: Switched to MakeTextUppercase	74	\@folioblob: Suppress the blob if acmArticleSeq is empty	82
\@parfont: Switched to MakeTextUppercase	84	\@mkbibcitation: If the paper has just one page, use 'page' instead of 'pages'	78
\ACM@linecount@bx: Work around a bug in xcolor: looks like cmyk colors in boxes do not work	79	\ACM@restore@pagestyle: Added macro	84
\ccdesc@parse@finish: Added macro	60	\acmArticle: The default is now empty	56
\city: We now do not print this even in SIG	72	\acmArticleSeq: Now acmArticle might be empty	56
\country: Fixed bugs with extra spaces	72	\acmBooktitle: Added macro	53
\l@subsection: Redefined macro . .	37	\editor: Added macro	53
\postcode: We now do not print this even in SIG	72	\if@ACM@acmthm: Added macro	29
\state: We now do not print this even in SIG	72	\maketitle: Empty DOI or ISBN are not printed (by Michael Ekstrand)	65
\streetaddress: We now do not print this even in SIG	72	General: Added package refcount . . .	28
		Deleted package cleveref	28
		Put theorem defs in a separate style	28
		v1.45	
		\@folioblob: Switched \bfseries\sffamily to \sffamily\bfseries	82
		\@parfont: Switched \bfseries\sffamily to \sffamily\bfseries	84
		\@titlefont: Switched \bfseries\sffamily to \sffamily\bfseries	69

v1.46		
\mkauthorsaddresses: Introduced		\country: T 72
macro 77		\if@ACM@acmthm: Modified
\@mkbibcitation: Added subtitle . . 78		description 29
\@printendtopmatter: Made it		\liningnums: Workaround for
\par\bigskip uniformly 79		compatibility with fontspec 43
\@printtopmatter: Deleted rule . . . 68		\maketitle: Added authors' addresses
\@setauthorsaddresses: Introduced		Thankses go before authors'
macro 79		addresses 65
\ACM@linecount@bx: Rearranged the		\num@author: Introduced macro . . . 53
code to get rid of spurious		General: Added etoolbox 28
underfull messages (Benjamin		Bst file bug fixes: label width is
Byholm) 79		calculated correctly 28
\author: Started counting authors . . 53		Delayed hypersetup since journal
\authorsaddresses: Introduced		options may change screen mode . 37
macro 55		PACM now set screen to true 47
		Restore theorem defs to class file . 28

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		
\\$	1567, 1571	\@ACM@title@width 1178,
\@	1436, 1457, 1470	1735, 1737, 1738,
\@authornotemark	1148, 2019	1741, 1742, 1750,
\@par	316, 373	1764, 1766, 1767, 1775
\@ACM@addtoaddress	1798, 1821, 1822, 1824	\@DeclareACMFormat 38, 39, 40, 41,
\@ACM@authorsperrrow	1219,	42, 43, 44, 45, 46, 47
\@ACM@badge@skip	1929, 1930, 1978, 1979	\@M 316, 355, 373, 382
\@ACM@badge@width	1176, 1660,	\@abstract 1198, 2028, 2035
\@ACM@badge@false	1665, 1737, 1741,	\@acmArticle 1154, 1157,
\@ACM@badge@true 1181, 1186	1747, 1759, 1766,	1566, 2044, 2045,
\@ACM@commabox	1768, 1771, 1783, 1786	2147, 2148, 2152,
\@ACM@journalfalse	1175	2155, 2158, 2160,
\@ACM@journaltrue	148, 150, 152, 154, 156	2163, 2167, 2169,
\@ACM@labelwidth	710, 713, 721, 726, 752	2224, 2238, 2246, 2254
\@ACM@manuscriptfalse 135		\@acmArticleSeq 1156, 2207
\@ACM@manuscripttrue 133		\@acmBadgeL@image 1188, 1190,
\@ACM@newfontfalse	616, 618, 621	1658, 1660, 1736,
\@ACM@newfonttrue	613	1745, 1747, 1769, 1771
\@ACM@reviewtrue	109	\@acmBadgeL@url . 1187,
\@ACM@screentru	825, 854, 860, 866	1189, 1659, 1746, 1770
\@ACM@sigchiamodfalse	137	\@acmBadgeR@image 1183, 1185,
\@ACM@sigchiamodtrue 157		1663, 1665, 1740,
\@ACM@timestamptrue 108		1756, 1759, 1784, 1786
		\@acmBadgeR@url . 1182,
		1184, 1664, 1758, 1785
		\@acmBooktitle 1038, 1557, 2054
		\@acmDOI . . 1172, 1559,
		1562, 1568, 1572, 2061
		\@acmEditors 1043, 1043,
		1044, 1047, 2055, 2056
		\@acmISBN 1170, 1570
		\@acmMonth 1160, 1162, 1566
		\@acmNumber 1152,
		2051, 2152, 2160,
		2169, 2238, 2246, 2254
		\@acmPrice 1166, 1567, 1571
		\@acmPubDate . . . 1162,
		2051, 2152, 2160,
		\@acmSubmissionID 1168, 2108, 2109
		\@acmVolume 1150,
		2051, 2151, 2159,
		2168, 2237, 2245, 2253
		\@acmYear 1158,
		1165, 1478, 1566, 2047
		\@acmdefinitionbodyfont 2384, 2396, 2408
		\@acmdefinitionheadfont 2386, 2398, 2410
		\@acmdefinitionindent 2385, 2397, 2409
		\@acmdefinitionnotefont 2387, 2399, 2413
		\@acmownedfalse 1298, 1301,
		1304, 1310, 1314,
		1317, 1320, 1323, 1329
		\@acmownedtrue 1285, 1294, 1326
		\@acmplainbodyfont 2354, 2366, 2378
		\@acmplainheadfont 2356, 2368, 2380
		\@acmplainindent 2355, 2367, 2379
		\@acmplainnotefont 2357, 2369, 2383
		\@adddotafter 2291, 2295, 2351
		\@additionalaffiliation 1102, 1103
		\@addpunct 2064,
		2065, 2351, 2352, 2462
		\@addspaceafter 2335, 2340, 2352
		\@affiliationfont 1851, 1856, 1860,
		1863, 1866, 1869,
		1872, 1875, 1903, 1921
		\@afterheading 347, 1606

\@afterindentfalse .	1990, 1997, 1998,	\@folio@wd	2187,
..... 293, 1605	2000, 2002, 2003, 2007	2221, 2222, 2243, 2251	
\@afterindenttrue ..	291	\@folioblob	2207,
\@article@string . . .	2044, 2051, 2059	2240, 2242, 2248, 2249	
\@author	1063, 1066,	\@footnotemark	395, 1496
1071, 1889, 1948, 1991		\@footnotemark@nolink	
\@authorfont 395, 1496	
1850, 1855, 1859,	1878, 1879,	\@footnotetext	396, 572, 1497
1862, 1865, 1868,	1886, 1890, 1891,	\@footnotetext@nolink	
1871, 1874, 1891, 1921	1893, 1921, 1924, 396, 1497	
\@authornotemark . . .	1946, 1948, 1949,	\@for	201
1140, 1146, 2018	1951, 1989, 1991,	\@formatdoi	1364,
\@authornotes	1992, 1994, 2018, 2019	1562, 1568, 1572, 2061	
1137, 1141, 1511	\@currentlabel	\@fps	678
\@authorsaddresses . .	576, 590	\@fpsadddefault	678
1518, 2065	\@dblarg	\@gobble	223, 267
\@auxout	302	\@hangfrom	315, 372
\@begindocumenthook . .	\@dblfloat	\@headfootfont	
448	675	2114, 2147, 2148,	
\@botnum	\@department	2149, 2150, 2154,	
1501	\@dotsep	2157, 2162, 2166,	
\@citestyle	2353	2172, 2173, 2174, 2176	
\@classname	\@editorsAbbrev	\@ifnextchar	1106
25,	1042, 1046, 2056	\@ifnotempty	1483
27, 35, 51, 53, 54,	\@empty	\@ifnum	239, 241
59, 61, 62, 67, 69,	159, 306,	\@ifstar	300
70, 75, 77, 78, 83,	1033, 1043, 1061,	\@ifundefined	
85, 86, 91, 93, 94,	1076, 1081, 1082,	2418, 2421, 2424,	
99, 101, 102, 107,	1088, 1237, 1238,	2428, 2429, 2433, 2436	
111, 112, 123, 128,	1244, 1251, 1256,	\@iiiparbox	570
181, 614, 617, 619,	1514, 1518, 1559,	\@input	384
826, 855, 861, 867,	1567, 1570, 1571,	\@insideauthorgroupfalse	
1018, 1020, 1101,	1572, 1580, 1585, 1096	
1193, 1203, 1205,	1630, 1658, 1663,	\@insideauthorgroupttrue	
1206, 1209, 1211,	1736, 1740, 1745, 1059	
1212, 1215, 1217,	1753, 1756, 1769,	\@journalCode	758,
1218, 1220, 1221, 2041	1777, 1784, 1794,	826, 855, 861, 867, 1018	
\@clubpenalty	1880, 1890, 1898,	\@journalCode@nr	
361	1899, 1948, 1954, 758, 811, 1023	
\@concepts	1959, 1991, 1997,	\@journalName	
1256,	2002, 2021, 2044,	813,	
1266, 1580, 1582, 1602	2048, 2055, 2108,	817, 821, 828, 832,	
\@copyrightowner . . .	2357, 2387, 2475, 2492	836, 840, 844, 848,	
..... 1333, 1543	\@endfloatbox	849, 851, 852, 857,	
\@copyrightpermission	677	858, 863, 864, 869,	
..... 1365, 1535	\@endpefalse	873, 877, 879, 883,	
\@copyrightyear	2464	887, 889, 891, 893,	
1477, 1543, 1545	\@endwidefloatbox 677, 685	897, 901, 905, 909,	
\@currbox	\@finalstrut	913, 917, 921, 925,	
691, 692, 693	581, 594	929, 933, 937, 941,	
\@currentaffiliation	\@float		
1922, 1925, 1947,	679		
1954, 1955, 1957,	\@flushglue		
1959, 1960, 1964,	2300		
	\@fnsymbol		
	1498		
	\@folio@ht		
	2187, 2214, 2220, 2221		
	\@folio@max 2187, 2210, 2211		
	\@folio@voffset 2187, 2216		

945, 949, 950, 953, 957, 958, 961, 966, 970, 974, 978, 982, 986, 990, 994, 998, 1002, 1006, 1010, 1014, 1024, 1025, 1555, 2151, 2159, 2168, 2237, 2245, 2253	\@mkauthors@iii . 1838, 1840, 1842, 1844, 1926 \@mkauthors@iv 1846, 1975 \@mkauthorsaddresses 2017 \@mkbibcitation 1598, 2037 \@mkteasers . . . 1504, 2020 \@mktitle 1504, 1670 \@mktitle@i 1673, 1675, 1677, 1679, 1734 \@mktitle@ii 1762 \@mktitle@iii . . 1681, 1683, 1685, 1687, 1762 \@mktitle@iv . . 1689, 1790 \@mpargs 570 \@mparswitchfalse . . 532 \@mpfootins 562, 563, 565, 585, 586 \@mpfootnotetext . . 584 \@ne . 227, 231, 235, 237, 438, 2071, 2076, 2080 \@nil 246 \@nobreakfalse . 349, 389 \@noskipsecfalse . . 353 \@noskipsectrue . . . 350 \@pages@word 2038, 2052, 2059 \@par 1516, 1522 \@parboxrestore . . . 589 \@parfont . 2295, 2299, 2304 \@permissionCodeOne 815, 819, 824, 830, 834, 838, 842, 846, 853, 859, 865, 871, 875, 881, 885, 895, 899, 903, 907, 911, 915, 919, 923, 927, 931, 935, 939, 943, 947, 951, 955, 963, 968, 972, 976, 980, 984, 988, 992, 996, 1000, 1004, 1008, 1012, 1016, 1026, 1566 \@permissionCodeTwo 964, 1027 \@plus . . 382, 390, 597, 2281, 2285, 2289, 2293, 2297, 2328, 2333, 2338, 2374, 2376, 2404, 2406, 2459	\@printcopyrightfalse 1297, 1309 \@printcopyrighttrue 1281, 1293 \@printendtopmatter 1604, 2063 \@printpermissionfalse 1296 \@printpermissiontrue . . . 1283, 1292, 1308 \@printtopmatter 1505, 1629 \@proofindent 2443, 2453, 2461 \@proofnamefont 2442, 2452, 2462 \@received . 1235, 1238, 1239, 1241, 1244, 1245, 1247, 1251, 1252 \@rightskip . . . 2300, 2301 \@saveabstract 1197, 1198 \@save teaser . . 1480, 1481 \@secCNTformat . 309, 366 \@secfont 2283, 2304 \@secpenalty 298 \@sect 302, 303 \@setaddresses . . . 2017 \@setauthorsaddresses 1522, 2065 \@setthanks . . . 1516, 2064 \@shortauthors 2113, 2143, 2149, 2155, 2163, 2173 \@sidebar 664, 665 \@specialsection 1581, 1587, 1589, 1608 \@essect 301, 367 \@startPage . . . 1191, 1630, 1631, 1633, 2107 \@startsection 287, 379, 2280, 2284, 2288, 2292, 2296, 2327, 2332, 2337 \@starttoc 379 \@subparfont . . 2340, 2341 \@subsecfont . . 2287, 2304 \@subsubsecfont 2291, 2304 \@subtitle . 1049, 1129, 1753, 1754, 1777, 1778, 1794, 1795, 2048
\@journalNameShort 814, 818, 823, 829, 833, 837, 841, 845, 870, 874, 880, 884, 894, 898, 902, 906, 910, 914, 918, 922, 926, 930, 934, 938, 942, 946, 954, 959, 962, 967, 971, 975, 979, 983, 987, 991, 995, 999, 1003, 1007, 1011, 1015, 1025, 2050		
\@keywords 1195, 1585, 1591, 1603		
\@latex@error 269		
\@empty 1200, 2028		
\@listI 734, 738		
\@listi 731, 738		
\@listii 739		
\@listiii 742		
\@listiv 744		
\@listv 746		
\@listvi 748		
\@m 304		
\@makefnmark . . . 571, 596, 1503, 1508, 1512		
\@makefntext 571, 580, 593, 1513		
\@marginfigure . 667, 668		
\@margintable . . 670, 671		
\@minipagefalse . 567, 687		
\@minus . . . 2281, 2285, 2289, 2293, 2297, 2328, 2333, 2338, 2375, 2377, 2405, 2407		
\@mkabstract . . 1578, 2027		
\@mkauthors 1504, 1506, 1826		
\@mkauthors@i . . 1830, 1832, 1834, 1836, 1885		
\@mkauthors@ii . . . 1915		

\@subtitelfont	\@titlenotes	2194, 2231, 2264, 2309, 2358, 2388, 2444
1713, 1754, 1778, 1795	1118, 1122, 1125, 1509	
\@subtitlenotes	\@tochangmeasure 320, 333	\ACM@linecount
1127, 1131, 1134, 1510	\@toclevel 304 2070, 2071,
\@svsec . . . 306, 309, 315, 330	\@tocline . . . 392, 393, 394	2075, 2076, 2079, 2080
\@svsechd . . . 328, 356, 376	\@topnum 1499	\ACM@linecount@bx . .
\@teaser 1481, 2022	\@typeset@author@bx	. . . 2067, 2086, 2093
\@teaserfigures 1919,	\ACM@linecount@bxht
1479, 1481, 2021, 2025	1968, 1974, 2011, 2016	2069, 2074, 2077, 2078
\@tempa 201,	\@typeset@author@line	\ACM@linecountL
202, 204, 206, 208,	1877, 1888, 1910, 1912 2082, 2141,
210, 212, 214, 216,	\@undefined 448, 628	2144, 2147, 2150,
218, 220, 222, 224,	\@width 551, 558	2154, 2156, 2162,
226, 228, 230, 232,	\@exp 386, 387	2164, 2172, 2174,
234, 236, 238, 240,	\@xsect 341, 342, 378	2233, 2240, 2241,
242, 244, 246, 249,	\@z 233	2249, 2250, 2256, 2259
251, 253, 255, 257,	\\ 468, 1543, 1548, 1563,	\ACM@linecountR
259, 1080, 1081,	1567, 1571, 2040, 2075	2089, 2165, 2167,
1236, 1237, 1898,	\{ 209	2173, 2177, 2257, 2260
2475, 2491, 2492, 2494	\} 209	\ACM@mk@linecount . .
\@tempb 202, 204,		. . . 2072, 2084, 2091
206, 208, 210, 212,	_ . . . 1041, 1262, 1272,	\ACM@ps@headings . . .
214, 216, 218, 220,	1543, 1545, 1567, 2274, 2278
222, 224, 226, 228,	2044, 2045, 2057, 2107	\ACM@ps@myheadings .
230, 232, 234, 236,	 2273, 2277
238, 240, 242, 244,		\ACM@ps@plain . 2272, 2276
249, 251, 253, 255,		\ACM@restore@pagestyle
257, 259, 2493, 2494	 2272
\@tempboxa 570	A	\ACM@timestamp
\@tempc . . 247, 248, 250,	\abstract 1197	2096, 2183, 2265, 2268
252, 254, 256, 258, 260	abstract (environment) 18	\acmArticle 14, 1154
\@tempcnta . 2207, 2208,	\acks 2466	\acmArticleSeq . . 15, 1156
2210, 2211, 2213, 2215	acks (environment) 22	\acmBadgeL 15, 1186
\@tempdima	\acm@copyrightinput 1287	\acmBadgeR 15, 1181
2214, 2215, 2216, 2218	\acm@copyrightmode .	\acmBooktitle . . . 8, 1038
\@tempskipa	1287, 1295, 1300,	\acmConference . . . 8, 1028
290, 292, 293, 298,	1303, 1307, 1313,	\acmConference@date
311, 312, 343, 344,	1316, 1319, 1322,	. . . 1031, 1539, 2175, 2177
346, 358, 359, 368, 369	1325, 1328, 1334, 1366	\acmConference@name
\@textbottom 597	\ACM@fontsize 1030, 1039, 1040
\@textsuperscript . .	115, 159, 162, 164,	\acmConference@shortname
. . . . 596, 1503, 1508	166, 168, 170, 172, 1029,
\@texttop 598	174, 176, 178, 181, 182	1033, 1034, 1040,
\@thefnmark . . 577, 591,	\ACM@format 32, 123	1041, 1539, 2174, 2176
596, 1503, 1508, 1512	\ACM@format@nr	\acmConference@venue
\@title . . . 1120, 1601,	. . . 32, 123, 127,	. . . 1032, 1539, 2175, 2177
1752, 1776, 1793, 2047	132, 138, 160, 405,	\acmdefinition 2403
\@titlefont 1692, 1744,	472, 537, 643, 695,	\acmDOI 15, 1172
1751, 1763, 1775, 1791	1609, 1637, 1671,	\acmISBN 15, 1170
	1693, 1714, 1828,	\acmJournal 8, 1022
	1852, 2115, 2139,	

1203, 1205, 1209, 1211, 1215, 1217, 1220	228, 229, 230, 231, 232, 233, 234, 235, 236, 238, 240, 242, 244, 245, 249, 251, 253, 255, 257, 259, 287, 303, 328, 342, 366, 367, 376, 379, 392, 393, 394, 399, 400, 401, 402, 447, 550, 557, 559, 571, 573, 584, 596, 597, 665, 668, 671, 676, 678, 682, 685, 703, 704, 705, 706, 734, 739, 742, 744, 746, 748, 813, 814, 815, 817, 818, 819, 821, 823, 824, 828, 829, 830, 832, 833, 834, 836, 837, 838, 840, 841, 842, 844, 845, 846, 848, 849, 851, 852, 853, 857, 858, 859, 863, 864, 865, 869, 870, 871, 873, 874, 875, 877, 879, 880, 881, 883, 884, 885, 887, 889, 891, 893, 894, 895, 897, 898, 899, 901, 902, 903, 905, 906, 907, 909, 910, 911, 913, 914, 915, 917, 918, 919, 921, 922, 923, 925, 926, 927, 929, 930, 931, 933, 934, 935, 937, 938, 939, 941, 942, 943, 945, 946, 947, 949, 950, 951, 953, 954, 955, 957, 958, 959, 961, 962, 963, 964, 966, 967, 968, 970, 971, 972, 974, 975, 976, 978, 979, 980, 982, 983, 984, 986, 987, 988, 990, 991, 992, 994, 995, 996, 998, 999, 1000, 1002, 1003, 1004, 1006,	1007, 1008, 1010, 1011, 1012, 1014, 1015, 1016, 1022, 1023, 1024, 1025, 1026, 1027, 1038, 1042, 1043, 1049, 1080, 1102, 1103, 1104, 1105, 1106, 1107, 1118, 1119, 1127, 1128, 1137, 1138, 1150, 1152, 1154, 1156, 1158, 1160, 1162, 1166, 1168, 1170, 1172, 1182, 1183, 1184, 1185, 1187, 1188, 1189, 1190, 1191, 1193, 1195, 1198, 1200, 1223, 1235, 1236, 1260, 1279, 1331, 1333, 1364, 1365, 1477, 1479, 1481, 1490, 1503, 1508, 1516, 1522, 1608, 1629, 1670, 1692, 1713, 1734, 1762, 1790, 1799, 1806, 1807, 1809, 1810, 1811, 1812, 1814, 1816, 1817, 1820, 1823, 1826, 1850, 1851, 1855, 1856, 1859, 1860, 1862, 1863, 1865, 1866, 1868, 1869, 1871, 1872, 1874, 1875, 1877, 1879, 1884, 1885, 1886, 1887, 1889, 1896, 1897, 1898, 1919, 1926, 1948, 1954, 1959, 1975, 1991, 1997, 2002, 2017, 2018, 2019, 2020, 2022, 2027, 2037, 2038, 2039, 2040, 2041, 2044, 2063, 2064, 2065, 2072, 2082, 2089, 2113, 2114, 2193, 2200,
\ClassWarning 27, 128, 614, 617, 619, 1193, 1221		
\cleaders 1803		
\clubpenalty . . . 355, 361		
\CodelineIndex 17		
\Collect@Body . . 664, 667, 670, 1197, 1480		
\color . . . 1531, 2075, 2079		
\color@begingroup 579, 592		
\color@endbox 690		
\color@endgroup 568, 582, 595		
\columnwidth . . . 551, 588, 676, 1976, 2013		
\contentsnamefont . . 383		
\copy 1803		
\copyright 1543		
\copyrightpermissionfootnoterule 550		
\copyrightyear . . 18, 1477		
\country . . . 11, 1112, 1806		
\csname . 267, 318, 320, 324, 331, 333, 337, 366, 386, 387, 577, 591, 1261, 1262, 1264, 1265, 1266, 1267, 1268, 1271, 1273		
\CurrentOption . 116, 117, 118, 119, 120, 121		
D		
\day 2105		
\DeclareNewFootnote 554, 556		
\DeclareOptionX 38, 116, 117, 118, 119, 120, 121		
\DeclareRobustCommand 436		
\DeclareTextFontCommand 630		
\def 25, 38, 115, 162, 164, 166, 168, 170, 172, 174, 176, 178, 202, 204, 206, 208, 210, 212, 214, 216, 218, 220, 222, 224, 226, 227,		

2205, 2207, 2275,	327, 332, 336, 348,	1267, 1268, 1271, 1273
2300, 2304, 2305,	360, 375, 425, 440,	\enddescription 757
2306, 2307, 2313,	446, 448, 562, 640,	\endgroup 317, 356, 374,
2314, 2316, 2317,	1040, 1045, 1057,	389, 1576, 1848, 2471
2319, 2320, 2322,	1065, 1069, 1070,	\endlist 755, 757
2323, 2325, 2326,	1079, 1084, 1087,	\endminipage 559
2331, 2336, 2341,	1090, 1097, 1115,	\endtrivlist 2464
2344, 2345, 2348,	1124, 1133, 1139,	\enspace 2352
2349, 2351, 2352,	1147, 1204, 1210,	environments:
2354, 2355, 2356,	1216, 1227, 1230,	abstract 18
2357, 2366, 2367,	1240, 1243, 1246,	acks 22
2368, 2369, 2384,	1251, 1270, 1274,	anonsuppress 22
2385, 2386, 2387,	1275, 1486, 1504,	CCSXML 16
2396, 2397, 2398,	1514, 1518, 1519,	marginfigure 21
2399, 2442, 2443,	1534, 1537, 1538,	marginable 21
2452, 2453, 2473,	1544, 1549, 1556,	printonly 21
2475, 2491, 2492, 2493	1561, 1564, 1567,	screenonly 21
\define@boolkey	1569, 1570, 1571,	sidebar 21
..... 49, 57, 65,	1572, 1580, 1585,	teaserfigure 18
73, 81, 89, 97, 105,	1588, 1632, 1658,	\everypar ... 296, 351, 362
1100, 1201, 1207, 1213	1663, 1736, 1740,	\excludecomment . 1255,
\define@choicekey ..	1745, 1753, 1756,	2479, 2481, 2485, 2486
..... 32, 758, 1286	1769, 1777, 1784,	\ExecuteOptionsX ...
\define@cmdkey 1219	1794, 1800, 1801, 48, 56, 64,
\definecolor	1814, 1815, 1816,	72, 80, 88, 96, 104, 114
... 455, 456, 457,	1817, 1819, 1820,	\expandafter
458, 459, 460, 461, 462	1823, 1880, 1892,	... 246, 248, 449,
\department . 11, 1106, 1806	1898, 1904, 1920,	570, 1261, 1262,
\description 751	1931, 1941, 1950,	1264, 1265, 1271, 1273
\descriptionlabel 750, 753	1956, 1963, 1980,	
\dimexpr .. 674, 692, 2180	1984, 1993, 1999,	F
\divide 1930, 1936, 1938,	2006, 2021, 2028,	\familydefault 632
1940, 1942, 1979, 1985	2032, 2038, 2044,	\fancyfoot 2145,
\do 201	2048, 2053, 2055,	2151, 2159, 2168,
\DocInput 21	2108, 2113, 2170,	2171, 2183, 2234,
\documentclass 9	2208, 2258, 2267,	2235, 2237, 2245,
\dots 1571	2475, 2480, 2487, 2495	2253, 2261, 2265, 2268
	\email 10,	\fancyhead . 2141, 2142,
E	1114, 1896, 1954, 1997	2143, 2144, 2147,
\edef 116, 117, 118, 119, 304	\emph 1555, 1557	2148, 2149, 2150,
\editor 8, 1043	\EnableCrossrefs 19	2154, 2156, 2157,
\egroup 569,	\end ... 22, 2087, 2094, 2225	2162, 2164, 2165,
666, 669, 672,	\end@dblfloat 681	2166, 2172, 2173,
683, 689, 1113,	\end@float 683	2174, 2176, 2233,
1582, 1591, 1922,	\endcsname	2240, 2241, 2242,
2016, 2023, 2036, 2062	266, 267, 318, 320,	2248, 2249, 2250,
\else ... 52, 60, 68, 76,	324, 331, 333, 337,	2256, 2257, 2259, 2260
84, 92, 100, 110,	366, 386, 387, 577,	\fancyheadoffset ...
134, 247, 268, 297,	591, 1261, 1262,	... 2180, 2243, 2251
304, 307, 319, 323,	1264, 1265, 1266,	\fancyhf 2136, 2228

<code>\fancypagestyle</code>	2135, 2227	1779, 1787, 1788,	1047, 1071, 1072,
<code>\fi</code> . . .	54, 62, 70, 78, 86,	1796, 1804, 1814,	1085, 1091, 1098,
	94, 102, 112, 131,	1816, 1817, 1819,	1116, 1120, 1122,
	136, 158, 179, 180,	1820, 1823, 1825,	1125, 1129, 1131,
	191, 203, 205, 207,	1847, 1876, 1883,	1134, 1140, 1141,
	209, 211, 213, 215,	1894, 1908, 1909,	1146, 1148, 1241,
	217, 219, 221, 223,	1920, 1943, 1944,	1247, 1266, 1273,
	225, 227, 229, 231,	1952, 1958, 1967,	1481, 1485, 1487,
	233, 235, 237, 239,	1986, 1987, 1995,	1893, 1905, 1951,
	241, 243, 245, 250,	2001, 2010, 2026,	1957, 1964, 1994,
	252, 254, 256, 258,	2034, 2036, 2038,	2000, 2007, 2018, 2019
	260, 261, 270, 272,	2045, 2048, 2057,	<code>\gdef</code> 1029,
	286, 288, 294, 299,	2060, 2081, 2088,	1030, 1031, 1032,
	304, 310, 321, 325,	2095, 2110, 2112,	1034, 1038, 1044,
	334, 338, 340, 363,	2113, 2134, 2141,	1046, 1063, 1064,
	364, 377, 388, 417,	2142, 2147, 2148,	1066, 1067, 1077,
	427, 444, 446, 450,	2155, 2158, 2163,	1083, 1089, 1198,
	453, 470, 534, 548,	2167, 2171, 2178,	1222, 1239, 1245,
	566, 583, 610, 627,	2181, 2184, 2206,	1262, 1264, 1265,
	633, 660, 661, 680,	2225, 2234, 2261,	1271, 1631, 1891,
	684, 709, 1017,	2262, 2269, 2270,	1895, 1900, 1924,
	1035, 1041, 1048,	2350, 2372, 2402,	1925, 1946, 1947,
	1060, 1068, 1073,	2439, 2456, 2475,	1949, 1953, 1955,
	1074, 1078, 1086,	2483, 2489, 2492, 2496	1960, 1989, 1990,
	1092, 1093, 1094,	<code>\firstpagestyle</code> 2227	1992, 1996, 1998, 2003
	1099, 1117, 1126,	<code>\floatname</code> 663	<code>\geometry</code>
	1136, 1143, 1149,	<code>\footnote</code> 2041	474, 477, 484, 491,
	1165, 1206, 1212,	<code>\footnotemark</code> 402, 1120,	498, 505, 512, 519, 526
	1218, 1232, 1233,	1129, 2018, 2019, 2039	<code>\getrefnumber</code> 2038
	1242, 1248, 1249,	<code>\footnoterule</code> 557	<code>\global</code>
	1253, 1269, 1276,	<code>\footnotesep</code> . . . 581, 594	350, 353, 389, 585,
	1277, 1299, 1302,	<code>\footnotesize</code>	691, 1056, 1058,
	1306, 1312, 1315,	. 587, 2104, 2145,	1059, 1096, 1499,
	1318, 1321, 1324,	2151, 2159, 2168,	1501, 1595, 1596,
	1327, 1330, 1363,	2171, 2235, 2237,	1888, 1910, 1911,
	1476, 1488, 1493,	2245, 2253, 2261, 2266	1920, 1968, 1971,
	1494, 1504, 1506,	<code>\footnotetext</code> . . 1123,	2011, 2024, 2076, 2080
	1517, 1523, 1524,	1125, 1132, 1135, 1142	<code>\grantnum</code> 22, 2474
	1525, 1532, 1535,	<code>\footnotetextauthorsaddresses</code>	<code>\grantsponsor</code> . . 22, 2473
	1536, 1540, 1541, 1515, 1521	
	1546, 1558, 1563,	<code>\footnotetextcopyrightpermission</code>	H
	1567, 1571, 1572, 1526	<code>\hbox</code> . 596, 1503, 1508, 1802
	1573, 1574, 1575,	<code>\footrulewidth</code> 2138, 2230	<code>\headrulewidth</code> 2137, 2229
	1583, 1584, 1590,	<code>\format</code> 32	<code>\hfill</code> 1792, 2079
	1592, 1599, 1628,	<code>\frenchspacing</code> 2497	<code>\href</code> . 1659, 1664, 1746,
	1634, 1662, 1666,	<code>\fulltextwidth</code>	1758, 1770, 1785, 2495
	1667, 1668, 1690, 673, 676, 692	<code>\hrule</code> 551, 558, 1792
	1712, 1733, 1739,		<code>\hsize</code> 588,
	1743, 1749, 1755,	G	
	1760, 1772, 1774,	<code>\g@addto@macro</code>	1502, 1734, 1735,

	1762, 1764, 1790, 1827, 1919, 1970, 2013	2155, 2158, 2163, 2167, 2171, 2234, 2261	228, 230, 232, 234, 236, 238, 240, 242, 244, 249, 251, 253, 255, 257, 259, 448, 1033, 1040, 1043, 1061, 1076, 1081, 1082, 1088, 1145, 1237, 1238, 1244, 1251, 1261, 1270, 1514, 1518, 1559, 1567, 1570, 1571, 1572, 1580, 1585, 1630, 1658, 1663, 1736, 1740, 1745, 1753, 1756, 1769, 1777, 1784, 1794, 1880, 1890, 1898, 1899, 1948, 1954, 1959, 1991, 1997, 2002, 2021, 2028, 2044, 2048, 2055, 2108, 2475, 2492, 2494
\hskip 315, 329, 359, 372, 376, 1661, 1748, 1757, 1773, 1782, 1803, 2461	\if@ACM@review 65, 2067, 2083, 2090 \if@ACM@screen 49, 419, 2477 \if@ACM@sigchiamode 126, 572, 631, 675, 681, 1504, 1506, 1920, 2179	
\hspace 1376, 1387, 1396, 1421, 1433, 1454, 1923, 1973	\if@ACM@timestamp .. . 97, 2096, 2182, 2263 \if@acmowned 1284 \if@filesw 385, 451 \if@insideauthorgroup 1055, 1057 \if@nobreak 295	
\Huge 1701, 1703, 1705, 1707, 1709, 1711		
\hypersetup	420, 426, 1600		
I			
\if 247		
\if@ACM@acmthm	. 57, 2416		
\if@ACM@affiliation@obeypunct 1100, 1801, 1814, 1816, 1817, 1818, 1820, 1823	\if@booksec .. 288, 352 \if@printcopyright 1280, 1542 \if@printpermission 1282, 1535 \ifcase 138, 160, 405, 472, 537, 643, 695, 811, 1162, 1334, 1366, 1609, 1637, 1671, 1693, 1714, 1828, 1852, 1932, 1981, 2115, 2139, 2194, 2231, 2309, 2358, 2388, 2444	
\if@ACM@anonymous	89, 1062, 1070, 1075, 1097, 1115, 1121, 1130, 1139, 1484, 1491, 1519, 2113, 2484		
\if@ACM@authordraft 105, 463, 1527		
\if@ACM@authorversion 73, 1534, 1550		
\if@ACM@badge 1174, 1656, 1765, 1781	\ifcsname 266 \ifdim 292, 312, 344, 369, 2078 \IfFileExists 614, 617, 619 \IfInteger 1220 \ifNAT@numbers 446 \ifnum 127, 132, 304, 305, 319, 323, 332, 336, 1274, 1275, 1295, 1300, 1303, 1307, 1313, 1316, 1319, 1322, 1325, 1328, 1493, 1929, 1978, 2038, 2208, 2210, 2264	
\if@ACM@journal	. 125, 636, 1228, 1520, 1538, 1554, 1565, 1586, 1808, 2030, 2049		
\if@ACM@manuscript 124, 188, 1225, 1537, 1547		
\if@ACM@natbib 81, 193, 284, 428		
\if@ACM@natbib@override 81		
\if@ACM@newfonts	612, 622		
\if@ACM@printacmref 1207, 1597	\ifPDFTeX 600 \ifvmode 1800 \ifvoid 562 \ifx 159, 202, 204, 206, 208, 210, 212, 214, 216, 218, 220, 222, 224, 226,	
\if@ACM@printccs 1201, 1579		
\if@ACM@printfolios 1213, 2141, 2142, 2147, 2148,		
J			
\jobname 384, 387		
			\ignorespaces .. 365, 581, 594, 1104, 1105, 1107, 1806, 1807, 1809, 1810, 1811, 1812, 1813, 1814, 2035, 2040, 2462 \immediate 387, 452 \includecomment 2478, 2482, 2488 \includegraphics 1660, 1665, 1747, 1759, 1771, 1786 \indent 2443 \input 601 \InputIfFileExists .. 26 \institution 11, 1105, 1806 \interfootnotelinepenalty 575 \interlinepenalty 316, 373, 575 \item 2461 \itshape .. 1539, 2306, 2307, 2336, 2341, 2354, 2366, 2386, 2452

K		
\kern	550, 551, 557, 558, 1792	
\keywords	16, 1195	
L		
\l@section	392	
\l@subsection	392, 393	
\l@subsubsection	394	
\labelenumi	703	
\labelenumii	704	
\labelenumiii	705	
\labelenumiv	706	
\labelsep	712,	
	720, 725, 735, 740,	
	743, 745, 747, 749, 2461	
\labelwidth	735, 740,	
	743, 745, 747, 749, 752	
\LARGE	1695,	
	1697, 1699, 1722,	
	1724, 1726, 1728,	
	1730, 1859, 1862, 2224	
\Large	1850, 1868, 2319,	
	2320, 2322, 2323, 2325	
\large	1528,	
	1855, 1860, 1863,	
	2313, 2314, 2316, 2317	
\lastbox	354	
\leaders	1792	
\leavevmode	288, 1792, 1972	
\leftmargin	734,	
	739, 742, 744, 746, 748	
\leftmargini	718,	
	719, 720, 721, 734, 735	
\leftmarginii	724,	
	725, 726, 727, 739, 740	
\leftmarginiii	727, 728, 742, 743	
	728, 729, 744, 745	
\leftmarginiv	729, 730, 746, 747	
\leftmarginvi	730, 748, 749	
\leftskip	1791, 2014, 2302	
\let	223, 225,	
	237, 239, 241, 267,	
	306, 395, 396, 429,	
	430, 431, 432, 433,	
	434, 435, 438, 442,	
	598, 628, 677, 738,	
	753, 757, 1108,	
	1109, 1110, 1111,	
	1112, 1256, 1496,	
	1497, 1512, 1513,	
	1516, 1522, 1595,	
	1596, 1821, 1822,	
	1824, 1888, 1910,	
	1968, 1974, 2011,	
	2016, 2272, 2273,	
	2274, 2276, 2277, 2278	
\libertineLF	630	
\lineskip	1973, 2015	
\linespacing	382, 383	
\liningnums	628	
\list	751	
\listisep	732, 733, 737	
\listparindent	736	
\LoadClass	182	
\long	573,	
	584, 665, 668, 671,	
	1198, 1200, 1481, 2064	
\loop	2075, 2209	
M		
\makeatletter	379	
\makebox	1528, 2218	
\makelabel	753	
\MakeTextUppercase	1891, 1893,	
	2304, 2313, 2316,	
	2319, 2322, 2344, 2348	
\maketitle	19, 1490	
\marginfigure	667	
marginfigure (environ-		
ment)	21	
\marginpar	573,	
	666, 669, 672, 1657	
\marginparsep	674, 2180	
\marginparwidth	674, 2180	
\margintable	670	
margintable (environ-		
ment)	21	
\mbox	245	
\mdseries	1716, 1718, 1720,	
	1724, 1726, 1728,	
	1730, 1732, 1872, 1875	
\medskip	1611, 1613,	
	1615, 1617, 1911,	
	1913, 1972, 2025, 2046	
\mktitle@bx	1489,	
	1639, 1641, 1643,	
	1645, 1647, 1649,	
	1651, 1653, 1655,	
	1744, 1763, 1791,	
	1911, 1971, 1972, 2024	
\month	1161, 2105	
\moveleft	691	
\multiply	2215	
N		
\NAT@setcites	263	
\NAT@aysep	254	
\NAT@citetp	438	
\NAT@close	203, 205, 207, 209, 252	
\NAT@cmprs	231, 233, 235	
\NAT@cmt	258	
\NAT@ctype	438	
\NAT@find@eq	246	
\NAT@fullfalse	438	
\NAT@longnametrue	243	
\NAT@merge	237, 239, 241	
\NAT@nmfmt	245	
\NAT@numbersfalse	217	
\NAT@numberstrue	219, 221	
\NAT@open	203,	
	205, 207, 209, 250, 438	
\NAT@partrue	438	
\NAT@rem@eq	248	
\NAT@sep	211, 213, 215, 260	
\NAT@sort	227, 229, 235	
\NAT@superfalse	219	
\NAT@supertrue	221	
\NAT@swafalse	437	
\NAT@up	245	
\NAT@yrsep	256	
\NeedsTeXFormat	1	
\newblock	439	
\newbox	1489, 1798, 1915	
\newcommand	273, 279,	
	445, 1028, 1095,	
	1144, 1181, 1186,	
	1236, 1257, 1813,	
	1818, 2103, 2474, 2490	
\newcount	1051, 1053, 2070	
\newcounter	2099, 2101	
\newdimen	673, 710,	
	1916, 2187, 2189, 2191	

<code>\newenvironment</code>	171, 173, 175, 177,	1861, 1864, 1867,
. 667, 670, 1480	407, 408, 409, 410,	1870, 1873, 1934,
<code>\newfloat</code> 662	411, 412, 414, 415,	1935, 1937, 1939,
<code>\newif</code> 124, 125, 126, 612,	476, 483, 490, 497,	1983, 2118, 2120,
1174, 1280, 1282, 1284	504, 511, 518, 525,	2122, 2124, 2126,
<code>\newlength</code>	539, 540, 541, 543,	2128, 2130, 2132,
1176, 1178, 1179, 2069	544, 545, 546, 547,	2146, 2153, 2161,
<code>\newsavebox</code> 2068	645, 646, 647, 648,	2196, 2201, 2236,
<code>\newskip</code> 732, 1917	649, 651, 654, 657,	2244, 2252, 2311,
<code>\newtheorem</code>	697, 698, 699, 700,	2312, 2315, 2318,
2419, 2422, 2425,	701, 702, 707, 708,	2321, 2324, 2342,
2427, 2430, 2434, 2437	816, 820, 827, 831,	2346, 2360, 2361,
<code>\newtheoremstyle</code> . . .	835, 839, 843, 847,	2362, 2363, 2364,
. 2373, 2403	850, 856, 862, 868,	2365, 2370, 2371,
<code>\newwrite</code> 386	872, 876, 878, 882,	2390, 2391, 2392,
<code>\nobreak</code> 345, 2046	886, 888, 890, 892,	2393, 2394, 2395,
<code>\noindent</code> . . 571, 1252,	896, 900, 904, 908,	2400, 2401, 2446,
1513, 1611, 1613,	912, 916, 920, 924,	2447, 2448, 2449,
1615, 1617, 1636,	928, 932, 936, 940,	2450, 2451, 2454, 2455
1657, 1744, 1751,	944, 948, 952, 956,	<code>\orcid</code> 10, 1118
1754, 1778, 1792,	960, 965, 969, 973,	<code>\outer@nobreak</code> 688
1793, 1795, 1878,	977, 981, 985, 989,	
1911, 1912, 1971,	993, 997, 1001,	
2015, 2024, 2025,	1005, 1009, 1013,	P
2031, 2046, 2047, 2453	1162, 1163, 1164,	<code>\p@</code> 390,
<code>\nolinkurl</code>	1335, 1337, 1340,	535, 542, 550, 551,
1955, 1957, 1998, 2000	1342, 1343, 1345,	557, 558, 2281,
<code>\normalcolor</code> 564	1347, 1349, 1352,	2285, 2289, 2290,
<code>\normalfont</code> 596, 1252,	1355, 1358, 1360,	2293, 2294, 2297,
1508, 1851, 1856,	1367, 1378, 1389,	2298, 2328, 2333,
1865, 1866, 1868,	1397, 1403, 1409,	2334, 2338, 2339, 2459
1869, 2369, 2384,	1423, 1435, 1442,	<code>\PackageError</code> . 54, 62,
2396, 2399, 2459, 2497	1456, 1463, 1469,	70, 78, 86, 94, 102, 112
<code>\normalparindent</code> . . . 549	1612, 1614, 1616,	<code>\PackageInfo</code> 51,
<code>\normalsize</code> 1713, 1851,	1618, 1620, 1622,	53, 59, 61, 67, 69,
1865, 1866, 1869, 2497	1624, 1626, 1640,	75, 77, 83, 85, 91,
<code>\num@authorgroups</code> . .	1642, 1644, 1646,	93, 99, 101, 107,
1051, 1058, 1493,	1648, 1650, 1652,	111, 826, 855, 861, 867
1932, 1936, 1938, 1981	1654, 1674, 1676,	<code>\PageIndex</code> 16
<code>\num@authors</code> . . 1053, 1056	1678, 1680, 1682,	<code>\pageref</code> 2107
<code>\number</code> 304	1684, 1686, 1688,	<code>\pagestyle</code> 2186
<code>\numberline</code> 324, 337	1696, 1698, 1700,	<code>\par</code> . 289, 345, 381, 560,
<code>\numexpr</code> . 2098, 2100, 2102	1702, 1704, 1706,	686, 1252, 1516,
	1708, 1710, 1717,	1522, 1535, 1539,
	1719, 1721, 1723,	1582, 1591, 1611,
O	1725, 1727, 1729,	1613, 1615, 1617,
<code>\onehalfspacing</code> 190	1731, 1831, 1833,	1639, 1641, 1643,
<code>\openout</code> 387	1835, 1837, 1839,	1655, 1754, 1761,
<code>\or</code> . . 141, 143, 145, 147,	1841, 1843, 1845,	1778, 1789, 1792,
149, 151, 153, 155,	1854, 1857, 1858,	1795, 1797, 1816,
163, 165, 167, 169,		1817, 1819, 1820,

1878, 1882, 1911,	Q	207, 209, 211, 213,
1913, 1919, 1921,	<code>\qed</code>	215, 265, 632, 750,
1949, 1951, 1957,	<code>\quad</code>	1055, 1114, 1482,
1964, 1972, 1974,	2158, 2163, 2167, 2265	1498, 2137, 2138,
1992, 1994, 2000,		2229, 2230, 2280,
2007, 2014, 2016,	R	2284, 2288, 2292,
2022, 2023, 2024,	<code>\raggedright</code>	2296, 2327, 2332, 2337
2025, 2035, 2046,	. . . 1750, 1791, 2014	<code>\renewenvironment</code> . .
2062, 2063, 2064, 2457	<code>\raisebox</code> 664, 751, 1197, 2457
<code>\paragraph</code> 1623, 2292, 2332	1528, 1746, 1758,	<code>\repeat</code>
<code>\parbox</code> 467, 1750, 1768,	1770, 1785, 2218, 2220	2078, 2212
1775, 1783, 2073, 2222	<code>\received</code>	<code>\RequirePackage</code> . .
<code>\parindent</code> <u>535</u> , 549, 719,	<code>\RecordChanges</code>	30,
1516, 1522, 1533,	<code>\ref</code>	31, 183, 184, 185,
2292, 2303, 2355, 2385	<code>\refname</code>	186, 187, 189, 192,
<code>\parskip</code>	<code>\refstepcounter</code>	194, 397, 454, 464,
<u>535</u> , 1533	<code>\relax</code> . .	471, 552, 599, 611,
<code>\part</code>	127, 132, 139,	623, 624, 625, 626,
2296	161, 246, 247, 290,	634, 1254, 1259, 2066
<code>\PassOptionsToClass</code>	309, 311, 315, 329,	<code>\reset@font</code>
.	343, 358, 368, 376,	574, 587
<code>\pdfgentounicode</code> . . .	387, 406, 473, 538,	<code>\reversemarginpar</code> . .
<code>\pdfglyphtounicode</code> .	598, 644, 696, 812,	533
.	1052, 1054, 1056,	<code>\rightskip</code>
602, 603,	1058, 1144, 1145,	2301
604, 605, 606, 607, 608	1261, 1270, 1295,	<code>\rlap</code>
<code>\pdfstringdefDisableCommands</code>	1300, 1303, 1307,	2219
.	1313, 1316, 1319,	<code>\rule</code>
<code>\phantomsection</code>	1322, 1325, 1328,	581, 594, 2221
. . . .	1334, 1366, 1512,	
<code>\popQED</code>	1610, 1638, 1672,	S
2464	1694, 1715, 1829,	<code>\savebox</code>
<code>\position</code>	1853, 1918, 1927,	2073
11,	1928, 1929, 1930,	screenonly (environ-
1104, 1108, 1109,	1933, 1936, 1938,	ment)
1110, 1111, 1112, <u>1806</u>	1940, 1942, 1945,	21
<code>\postcode</code> . . . <u>11</u> , <u>1111</u> , <u>1806</u>	1973, 1976, 1977,	<code>\scriptsize</code> . . .
printonly (environment) <u>21</u>	1978, 1979, 1982,	2075, 2079
<code>\ProcessOptionsX</code> . . .	1985, 1988, 2018,	<code>\scshape</code>
122	2038, 2071, 2100,	2356, 2442
<code>\proof</code>	2102, 2108, 2116,	<code>\section</code>
2457	2140, 2195, 2197,	196,
<code>\proofname</code>	2198, 2199, 2202,	1619, 1621, 1625,
2457	2203, 2204, 2207,	1627, 2033, 2280, 2468
<code>\protect</code>	2208, 2210, 2213,	<code>\section@raggedright</code>
324, 337	2214, 2215, 2216,
<code>\protected@edef</code>	2232, 2264, 2310,	<u>2300</u> , 2304,
.	2359, 2389, 2445, 2459	2305, 2313, 2314,
309, 576, 590	<code>\removelastskip</code>	2316, 2317, 2319,
<code>\providecommand</code>	381	2320, 2322, 2323,
.	<code>\renewcommand</code> . .	2325, 2326, 2331,
439, 443, 2353	195,	2344, 2345, 2348, 2349
<code>\ProvidesClass</code>	199, 200, 203, 205,	<code>\SelectFootnoteRule</code>
<code>\ProvidesFile</code>
<code>\ps@headings</code> . .		553, 555
2274, 2278		<code>\setbox</code>
<code>\ps@myheadings</code> 2273, 2277		354,
<code>\ps@plain</code>		585, 691, 1744,
2272, 2276		1763, 1791, 1802,
<code>\pushQED</code>		1911, 1920, 1971, 2024
2458		<code>\setcitestyle</code>
<code>\put</code>
2086, 2093		23, 200, 274, 280
		<code>\setcopyright</code> . .
		17, 1331

	Z		
\z@	229, 292, 312,	1501, 1516, 1522,	2230, 2280, 2284,
	344, 354, 369, 382,	1528, 1533, 1746,	2296, 2303, 2327,
	536, 581, 594, 597,	1758, 1770, 1785,	2332, 2337, 2367, 2397
	638, 642, 653, 718,	2014, 2137, 2138,	\z@skip 381, 686, 741, 2302
	724, 736, 1499,	2188, 2190, 2192,	
		2218, 2220, 2229,	