

The `lipics` Class*

Schloss Dagstuhl

Printed January 9, 2018

1 Introduction

The `lipics` class assists in preparing articles for *Leibniz International Proceedings in Informatics* with L^AT_EX. It adapts L^AT_EX's standard `article` class to meet some requirements for LIPIcs and provides a specific layout.

The package consists of the following files:

`lipics.pdf` this documentation

`article.tex` the L^AT_EX master file, to be used as a template

`lipics.cls` the L^AT_EX class file, providing adaptations for LIPIcs and producing the layout

logos for LIPIcs, Creative Commons, and ORCID

This documentation is not intended to give an introduction to L^AT_EX. For questions concerning T_EX systems/installations or the L^AT_EX mark-up language in general please visit www.tug.org, www.dante.de, uk.tug.org or any other T_EX user group worldwide. The essential reference for L^AT_EX is *Mittelbach F., Goossens M. (2004) The L^AT_EX Companion. 2nd edn.*, but there are many other good books delivering insight into L^AT_EX.

`lipics` tries to benefit as far as possible from standard L^AT_EX packages. (Have a look at `lipics.cls` to see which packages are used.) Therefore, it should also be easy to compile an already written manuscript with the `lipics` layout. To learn more about the underlying packages we refer to their documentations (try e.g. `texdoc [package name]` at your shell prompt or visit tug.ctan.org).

2 How to use the package

We suggest to employ a recent T_EX installation: the most important distributions, T_EX Live, MiK_TE_X/proT_EXt and MacT_EX, all provide at least 2017 versions. But older versions should (in principle) work as well.

To use `lipics`, put “`article.tex`” and “`lipics.cls`” in your working directory, edit the file “`article.tex`” in your preferred text editor and run L^AT_EX as usual. (See the following section for more detailed advises.)

*This file has version number v1.3, last revised 2017/12/20.

3 Some important settings and commands

3.1 Paper format

You can choose between the A4 format and the US-letter format. The respective options “`a4paper`” or “`letterpaper`” must be inserted in the optional argument of `\documentclass`.

3.2 Language

The document language is chosen in the optional argument of the `\documentclass` command in the L^AT_EX master file. Possible values are `USenglish`, `UKenglish` and many others.

3.3 Input encoding

`lipics` preselects UTF-8 as input encoding. Please do not change the input encoding because otherwise the volume compilation might become difficult.

3.4 Fonts

`lipics` uses the Latin Modern font family. This is a recent redesign of the good old Computer Modern fonts. Latin Modern provides a lot of characters and all necessary math fonts. If your T_EX installation does not provide the Latin Modern family, Computer Modern is used as a fallback.

`lipics` preloads the package “`amssymb`” to make additional mathematical symbols available. Other symbol packages, e.g. `stmaryrd`, may be added, of course. Moreover, the script math alphabet is provided by loading the `euca1` package. – But please avoid loading the `MnSymbol` package. (Note that the `lipics` removes all symbol re-definitions done by `MnSymbol` anyhow, but would retain its newly introduced symbol definitions.)

3.5 Titles

The prelims of a LIPICs article is the only part where some specific commands are required:

- The title is tagged as usual with the `\title{...}` command. If you need a short form for the running head, use the optional `\titlerunning{...}`.
- Authors and their affiliations are rendered blockwise for LIPICs¹. The information for each author is to be tagged with a re-define `\author` macro which has the structure: `\author{name}{affil}{email}{orcid}{funding}`. – There is an additional `\authorrunning{...}` for the running header; it must be used.
- `\Copyright{...}` has just one argument for the copyright holder.

¹This has changed in 2017; the formerly used “`authblk`” mechanism to output authors and affiliations in footnote style is deprecated; the `\affil` command is now obsolete for the `lipics` class.

- `\subjclass{...}` is for classification information following the ACM 2012 Computing Classification System; it is required, too.
- `\keywords{...}` must be used to capture keywords.
- `\category{...}` may be used to provide category information.
- `\relatedversion{...}` may be used to denote a related version.
- `\supplement{...}` may be used to denote supplements.
- `\funding{...}` may be used to capture a funding statement.
- `\acknowledgements{...}` may be used to capture an acknowledgement.

The commands mentioned so far should be used in the document preamble of the \LaTeX file. Providing a title, at least one author, copyright information, subject classification, and keywords is required.

To typeset an abstract use `\begin{abstract}... \end{abstract}`. The environment must be placed after `\begin{document}` and `\maketitle`!

Note that subject classifications, keywords, ..., and acknowledgements will be rendered together with the abstract. So it is necessary to use the `abstract` environment in order to get the output for `\subjclass` etc.

The `\hideLIPIcs` command is to mask all copyright information (and a possible DOI specification) on the first page.

3.6 Mathematical formulas

The `amsmath` package is preloaded, and you are encouraged to use the mark-up it provides instead of old-style standards like the `eqnarray` environment or the `\over` command.

3.7 Theorem-like environments

The `amsthm` package is preloaded, and the following environments are already introduced: `theorem`, `lemma`, `corollary`, `definition`, `example` and `remark`.

Setting up additional environments works with the `\newtheorem` mechanism from the `amsthm` package. For example, add to your document preamble

```
\theoremstyle{plain}
\newtheorem{conjecture}[theorem]{Conjecture}
```

See also the `amsthm` package documentation.

Available `\theoremstyles` are: `plain`, `definition`, and `remark` (all from the `amsthm` package, but slightly modified for LIPIcs).

Note that for LIPIcs all numbered theorem-like environments should use one and the same counter, i. e. the counter of the default environment "`theorem`".

By default, theorem-like environments are numbered consecutively throughout the document. To number the environments subordinately within sections use the class option "`numberwithinsect`".

3.8 Lists

List labels are set flush left. For enumerations with more than 9 items please insert `\addtolength\leftmargini{0.5em}` before `\begin{enumerate}`.

The `enumerate` package is preloaded, so you can use `\begin{enumerate}[(a)]` or the like.

Moreover, some enumerate environments are pre-defined: `{romanenumerate}`, `{alphaenumerate}`, and `{bracketenumerate}`.

3.9 Listings

The `listings` package is preloaded. It provides the `lstlisting` environment to typeset displayed code. Here, the package is configured to get a grey background for listings.

The following example shows how to use captions and labels with the `lstlisting` environment:

```
\begin{lstlisting}[caption={Useless code},label=list:8-6,float,
                    abovecaptionskip=-\medskipamount]
for i:=maxint to 0 do
begin
  j:=square(root(i));
end;
\end{lstlisting}
```

Note also the `float` option to make the listing floating. Instead of the `caption` option one might prefer the `title` option which outputs the argument without the “Listing” label. To globally change the label name from “Listing”, add to your document preamble e.g.

```
\renewcommand*\lstlistingname{Algorithm}
```

Please read the package documentation for more information on the `lstlisting` environment and how to adapt it locally.

3.10 Graphics

The standard interface for graphic inclusion is the `\includegraphics` command provided by the `graphicx` package. Note that the `\graphicspath` command allows to declare one or more folders where the `graphicx` package looks for the image files; so providing the path with each `\includegraphics` command is not necessary.

3.11 Tables

Preloaded packages are: the `array` package (for introducing new column types), the `multirow` package (row spanning cells) and the `tabularx` package (automatic column width calculation).

In order to allow easy use of table footnotes, the `threeparttable` package is preloaded. Please read the short documentation in `threeparttables.sty` to see how the related commands are applied.

3.12 Rotating floats

The preloaded `rotating` package provides the two environments “`sidewaysfigure`” and “`sidewaystable`”. They allow the rotation of floating objects.

3.13 Sub-captions

The preloaded `subcaption` package provides the `\subcaption` command to add sub-captions. Please do not load the aged `subfig` package.

3.14 The `\ccsdesc` macro

Use `ccsdesc` to enter information according to the ACM Computing Classification System (CCS), e.g.
`\ccsdesc[500]{Information systems~Database management system engines}`.

3.15 Bibliography

It is recommended to use the standard bibliography mechanism. You might copy and paste your bibliography entries from elsewhere into the `thebibliography` environment or, more elegant, use `BIBTEX`. For `BIBTEX`, the standard bibliography style “`plain`” is sufficient. You might also use a similar bibliography style but please note that `LIPICs` only allows numerical citation and forbids author-year citations. (So the `natbib` package is not used by `lipics`.)

3.16 Line numbers

The `lineno` package is loaded, and line numbering is switched on by default. To switch line numbering (globally) off, use `\nolinenumbers` (in the document preamble).

3.17 Adding further packages and new macros

Feel free to add further packages if you need extra structural mark-up. But keep in mind that you should not change the general layout of the article.

Happy `TEX`ing!