

STROBE-X	
Total Mass	4998 kg
Orbit	LEO, 550 km altitude, 10° inclination
Total Power	3141 W
Attitude Control	3-axis stabilized, slew 15°/min
Solar Avoidance	45 deg
Total Cost (FY18 \$)	\$880M
Wide Field Monitor (WFM)	
# of Camera Pairs	4
FOV/Camera Pair	70° × 70° FWHM
Energy Range	2–50 keV
Energy Resolution	300 eV FWHM
Sensitivity (1 s)	600 mcrab
Sensitivity (1 day)	2 mcrab
Sky Coverage (Instantaneous)	4.1 sr
Angular Resolution	4.3 arcmin
Position Accuracy	1 arcmin

X-ray Concentrator Array (XRCA)	
Energy Range	0.2–12 keV
Effective Area (cm^2 @ 1.5 keV)	21,760 cm2
Energy Resolution	85 – 175 eV FWHM
Time Resolution	100 ns
Collimator	4 arcmin FWHM
Background Rate	2.2 c/s
Count Rate on Crab (0.2-10 keV)	148,000
Large Area Detector (LAD)	
Energy Range	2–30 keV
Effective Area (cm^2 @ 10 keV)	51,000 cm2
Energy Resolution	200 – 300 eV FWHM
Time Resolution	10 μs
Collimator	1° FWHM
Count Rate on Crab (2-30 keV)	156,000
Background Rate	822 c/s (5 mcrab)