

Dynamic Data Structures for Interval Coloring [☆]

Girish Raguvir J^a, Manas Jyoti Kashyop^a, N. S. Narayanaswamy^a

^a*Department of Computer Science and Engineering, Indian Institute of Technology Madras, Chennai 600036, India*

Abstract

We consider the dynamic graph coloring problem restricted to the class of interval graphs in the incremental and fully dynamic setting. The input consists of a sequence of intervals that are to be either colored, or deleted, if previously colored. For the incremental setting, we consider the well studied optimal online algorithm (KT-algorithm) for interval coloring due to Kierstead and Trotter [1]. We present the following results on the dynamic interval coloring problem.

- Any *direct* implementation of the KT-algorithm requires $\Omega(\Delta^2)$ time per interval in the worst case.
- There exists an incremental algorithm which supports insertion of an interval in amortized $O(\log n + \Delta)$ time per update and maintains a proper coloring using at most $3\omega - 2$ colors.
- There exists a fully dynamic algorithm which supports insertion of an interval in $O(\log n + \Delta \log \omega)$ update time and deletion of an interval in $O(\Delta^2 \log n)$ update time in the worst case and maintains a proper coloring using at most $3\omega - 2$ colors.

The KT-algorithm crucially uses the maximum clique size in an induced subgraph in the neighborhood of a given vertex. We show that the problem of computing the induced subgraph among the neighbors of a given vertex has the same hardness as the online boolean matrix vector multiplication problem [2]. We show that

- Any algorithm that computes the induced subgraph among the neighbors of a given vertex requires at least quadratic time unless the OMv conjecture [2] is false.

Finally, we obtain the following result on the OMv conjecture.

- the OMv conjecture [2] is false if the matrix and the vectors in the online sequence have the consecutive ones property.

References

- [1] H. A. Kierstead, W. T. Trotter, An extremal problem in recursive combinatorics, *Congressus Numerantium* 33 (143-153) (1981) 98.
- [2] M. Henzinger, S. Krinninger, D. Nanongkai, T. Saranurak, Unifying and strengthening hardness for dynamic problems via the online matrix-vector multiplication conjecture, in: *Proceedings of the Forty-Seventh Annual ACM on Symposium on Theory of Computing, STOC, 2015*, pp. 21–30.

[☆]Preliminary version of this work appeared in 25th International Computing and Combinatorics Conference(COCOON), pages 478-489, 2019

Email addresses: girishraguvir@gmail.com (Girish Raguvir J), manasjk@cse.iitm.ac.in (Manas Jyoti Kashyop), swamy@cse.iitm.ac.in (N. S. Narayanaswamy)