SuperCDMS Data Release for Dark Absorption

SuperCDMS Collaboration

This document is an updated version of the original data release document. For details on the changes from the original data release, see Section 3.

This document describes the public release of data pertinent to the SuperCDMS publication titled "Constraints on dark photons and axionlike particles from the SuperCDMS Soudan experiment" [1]. This release includes electron recoil data from four iZIP detectors, taken between October 2012 and July 2013 [2], as well as data from CDMSlite runs 2 and 3. The CDMSlite runs are described in [3] and [4] respectively, but here are used with an extended energy range.

The files are described in Section 1. The use of these data in setting limits on dark photon kinetic mixing and the axioelectric coupling constant is described in Section 2.

For both detector types, the total measured phonon signal is calibrated with electron recoil events to determine the energy scale. We use the standard unit of keV throughout, as here this is equivalent to keV_{ee}, which is sometimes used to avoid ambiguity; details about the keV_{ee} energy scale are described in [3] (especially Eq. 3) and the accompanying data release ¹.

Questions about the data or the extracted limits should be directed to the SuperCDMS publications chair at supercdms-publications@fnal.gov.

1 Description of the Files

The 17 text files accompanying this data release are located in the data_files directory of the .zip file and are described in this section.

1.1 iZIP Data

- eventEnergy_T#Z#.txt: This refers to four different files, one for each of the iZIP detectors T1Z1, T2Z1, T2Z2, and T4Z3; the '#' signs in the file name here are placeholders for the corresponding numbers. Each of these files contains a single column with a sorted list of event energies in keV. This list includes all events for that detector with reconstructed energy between 2 and 510 keV that pass the data quality and fiducial volume selection criteria. There are 10723, 11035, 7838, and 26254 events for T1Z1, T2Z1, T2Z2, and T4Z3, respectively. The event energy spectra are shown in Figure 1.
- efficiency_iZIP.txt: This file contains information on the energy-dependent efficiency function in the analysis range from 2 to 510 keV for the four iZIP detectors. There are thirteen columns. The first column corresponds to the energy in keV. Columns two to four correspond to T1Z1: column two gives the T1Z1 detection efficiency at that energy, and columns three and four give the lower and upper 1σ (68%) uncertainties on the efficiency, respectively. The

¹See "Public Release #1 of CDMSlite Run 2 Data (July 9, 2017)" at https://supercdms.slac.stanford.edu/publicdata or the arXiv ancillary files of Ref. [5].

uncertainties are given as the difference from the central efficiency. The remaining columns correspond to the other three detectors, following the same pattern (columns 5-7 for T2Z1, columns 8-10 for T2Z2, and columns 11-13 for T4Z3). The efficiencies are shown in Figure 2.



Figure 1: The iZIP event rate from 2 to 510 keV for T1Z1, T2Z1, T2Z2, and T4Z3. The spectra are shown in 10-keV bins and normalized by the detector exposure in g·days as listed in Tab. III of [1]. The spectra correspond to the event lists in eventEnergy_T1Z1.txt and the respective files for the other detectors.



Figure 2: The iZIP signal efficiency (black line) from 2 to 510 keV, with 1σ uncertainty band (orange). Data are from the efficiency_iZIP.txt file.

1.2 CDMSlite Run 2 Data

- eventEnergy_CDMSliteR2.txt: This file contains a single column with a sorted list of event energies in keV. This list includes all 2408 events with reconstructed energy of less than 25.5 keV that pass the data quality and fiducial volume selection criteria. The event energy spectrum is shown in Figure 3 (blue).
- efficiency_CDMSliteR2.txt: This file contains information on the energy-dependent efficiency function in the analysis range from 0 to 25.5 keV (as for Run 2, we will use keV in this document). There are four columns: the first column corresponds to the energy in keV, column two gives the detection efficiency at that energy, and columns three and four give the lower and upper 1σ (68%) uncertainties on the efficiency, respectively. The uncertainties are given as the difference from the central efficiency. The efficiency is shown in the top panel of Figure 4.

1.3 CDMSlite Run 3 Data

eventEnergy_CDMSliteR3-#.txt: This refers to two different files, one for each of the measurement periods of CDMSlite Run 3; the '#' signs in the file name here is a placeholder for '1' or '2'

indicating the corresponding measurement period. Each of these files contains a single column with a sorted list of event energies in keV. This list includes all events with reconstructed energy of less than 25.5 keV that pass the data quality and fiducial volume selection criteria. There are 1482 and 1255 events in Periods 1 and 2, respectively. The event energy spectra are shown in Figure 3 (orange and black for Periods 1 and 2 respectively).

efficiency_CDMSliteR3.txt: This file contains information on the energy-dependent efficiency function in the analysis range from 0 to 25.5 keV. There are seven columns: the first column corresponds to the energy in keV; columns two to four refer to CDMSlite Run 3 Period 1 and columns five to seven refer to CDMSlite Run 3 Period 2. Columns two and five give the detection efficiency at that energy; columns three/six and four/seven give the lower and upper 1σ (68%) uncertainties on the efficiency, respectively. The uncertainties are given as the difference from the central efficiency. The efficiencies are shown in the middle and bottom panels of Figure 4.



Figure 3: The CDMSlite event rate up to 25.5 keV for CDMSlite Run 2, Run 3 Period 1, and Run 3 Period 2. The spectra are shown in 0.75 keV bins and normalized by the detector exposure in g·days as listed in Tab. I of [1]. The spectra correspond to the event lists in eventEnergy_CDMSliteR3-1.txt, and eventEnergy_CDMSliteR3-2.txt, respectively.



Figure 4: The CDMSlite signal efficiency (black line) up to 25.5 keV, with 1σ uncertainty band (orange). Data are from the efficiency_CDMSliteR2.txt and efficiency_CDMSliteR3.txt files.

1.4 Supplementary Data

Some additional information is required to reproduce the results reported in [1]. The files containing the respective information are described in this subsection.

The final limits for both dark photon and axionlike particles (ALPs) are dependent on the photoelectric cross section; the corresponding information is found in the following file:

photoelectric_cross-section.txt: This file provides information on the photoelectric cross section for Ge in three columns. The first column is the energy in keV. The second column is the nominal photoelectric cross section in units of cm²/g, and the third column is the conservative photoelectric cross section, also in cm²/g. Both photoelectric cross sections are shown in Figure 5. For more information on the different cross section data, including the difference between the nominal and the conservative cross sections, see [1].



Figure 5: Photoelectric cross section (σ_{pe}) for Ge, in units of cm²/g, as a function of energy. Data are from the photoelectric_cross-section.txt file.

A selection process detailed in the corresponding publication [1] was used to determine which datasets to use to calculate the final limit at a given mass. The chosen method avoids bias introduced by simply picking the overall best limit without allowing datasets with a significantly higher background rate to artificially worsen our result. The following files list which datasets were included in the calculation of the different limits.

- dataset_selection_iZIP.txt: This file indicates which iZIP detectors are used to produce the iZIP limit at each mass. There are five columns. The first column is the dark matter candidate mass in keV/c^2 . The following four columns correspond to the four iZIP detectors in the order T1Z1, T2Z1, T2Z2, T4Z3. If a detector is used in the limit calculation at a given mass, the value in its respective row and column is 1. If not, the value is 0.
- dataset_selection_CDMSlite.txt: This file indicates which CDMSlite runs are used to produce the CDMSlite limit at each mass. There are four columns. The first column is the dark matter candidate mass in keV/c^2 . The following three columns correspond to the two CDMSlite runs in the order 2, 3-1, 3-2. If a dataset is used in the limit calculation at a given mass, the value in its respective row and column is 1. If not, the value is 0.
- dataset_selection_combined.txt: This file indicates which datasets are used to produce the combined limit at each mass. There are eight columns. The first column is the dark matter candidate mass in keV/ c^2 . The following four columns correspond to the four iZIP detectors in the order T1Z1, T2Z1, T2Z2, T4Z3. The final three columns correspond to the two CDMSlite runs in the order 2, 3-1, 3-2. If a dataset is used in the limit calculation at a given mass, the value in its respective row and column is 1. If not, the value is 0.

1.5 Exclusion Limits

- exclusion_limits_iZIP.txt: This file includes the exclusion limits determined using the iZIP detectors. There are ten columns. The first column is the energy in keV (for columns 2-4) or the dark matter mass in units of keV/ c^2 (for columns 5-10). The following three columns are the 90% CL upper limit on the event rate (in events/(g day)) and the respective lower and upper uncertainty on that limit. The next three columns are the 90% CL upper limit on the respective uncertainty band. The final three columns are the 90% CL upper limit on ϵ , describing the kinetic mixing between dark photon and standard model photon, and the respective uncertainty band. The ALP and dark photon upper uncertainty bands are calculated using the conservative photoelectric cross section, and are referred to as the conservative limits. The three limit types are shown in Figure 6.
- exclusion_limits_CDMSlite.txt: This file includes the exclusion limits determined using the CDMSlite data sets. It follows the same format as exclusion_limits_iZIP.txt. The three limit types are shown in Figure 7.
- exclusion_limits_combined.txt: This file includes exclusion limits determined using both iZIP and CDMSlite data. It follows the same format as exclusion_limits_iZIP.txt. In Ref. [1] these limits are referred to as the "Soudan upper limits" or the "combined limits". The three limit types are shown in Figure 8.



Figure 6: The 90% CL upper limit from the iZIP detectors used in this analysis on the event rate (top panel), the ALP coupling constant g_{ae} (middle panel) and the dark photon/standard photon mixing parameter ϵ (bottom panel). The respective uncertainty bands are shown in orange. Data are from the exclusion_limits_iZIP.txt file.



Figure 7: The 90% CL upper limit from the CDMSlite datasets on the event rate (top panel), the ALP coupling constant g_{ae} (middle panel) and the dark photon/standard photon mixing parameter ϵ (bottom panel). The respective uncertainty bands are shown in orange. Data are from the exclusion_limits_CDMSlite.txt file.



Figure 8: The 90% CL upper limit from the combined iZIP and CDMSlite data on the event rate (top panel), the ALP coupling constant g_{ae} (middle panel) and the dark photon/standard photon mixing parameter ϵ (bottom panel). The respective uncertainty bands are shown in orange. Data are from the exclusion_limits_combined.txt file.

2 Description of Limit Setting Calculation

2.1 Limit Calculation

Limits on the event rate are calculated for each detector using the corresponding spectrum, exposure, resolution model, and efficiency. Spectra and efficiencies are found in the eventEnergy_*.txt and efficiency_*.txt files respectively. For the exposure and the resolution models used in this analysis, see Ref. [1]. Limits on the parameters of interest (ϵ and g_{ae}) are calculated using the rate limit and the photoelectric cross section curves. Photoelectric cross section data used are found in the file: photoelectric_cross-section.txt. Here the procedure for calculating the rate limits, combining the data sets, and converting to the physical quantities is described.

The process for calculating the rate for a particular detector at a given energy E is as follows:

- Calculate the energy resolution σ at energy E for that detector.
- Count the number of observed events N with a reconstructed energy larger than $E \sigma$ and smaller than $E + \sigma$, or, in the case of CDMSlite near threshold, smaller than the threshold described at the end of this section.
- Calculate the 90% Poisson upper limit N_{90} on the number of observed events. Note: the 90% Poisson upper limit corresponds to the mean of a Poisson distribution whose integral from 0 to N equals 0.1. This means that 90% of random numbers drawn from this Poisson distribution will return a number equal to or larger than the observed number of events.
- Convert N_{90} to the 90% upper limit on the rate, R_{90} , by dividing by the exposure-weighted efficiency at energy E. The efficiency is calculated by multiplying the signal shape (a normalized Gaussian with width σ centered on E) bin-wise by the detection efficiency given in the efficiency_*.txt files and integrating between the window edges $(E \pm \sigma)$.
- Convert R_{90} to the 90% upper limit on the relevant parameter of interest $(g_{ae} \text{ or } \epsilon)$ by using Eq. 2 and Eq. 4 in Ref. [1]. Note: these equations depend on the photoelectric cross section. For the results given in [1], we linearly interpolated the photoelectric cross section as found in the photoelectric_cross-section.txt file to the required masses. Other interpolation techniques (e.g. a cubic spline or a logarithmic interpolation) would produce a slightly more conservative result at some masses above around $400 \text{ eV}/c^2$.

For CDMSlite near threshold, the efficiency drops off strongly, thus the effective signal distribution becomes very non-Gaussian. In this situation, instead of cutting of at $+1\sigma$ of the primary Gaussian signal distribution, the cutoff is set at the $+1\sigma$ -equivalent point on the effective signal distribution, i.e. the Gaussian distribution multiplied by the efficiency curve given in the efficiency_*.txt files. The $+1\sigma$ -equivalent point is determined as the point where the tail end of the normalized signal (Gaussian distribution multiplied by the efficiency curve) is the same as the tail end of a normalized Gaussian curve from $+1\sigma$ to infinity, which is roughly 15.9%. On the left we keep the original -1σ cutoff. The rest of the rate calculation is the same as described above. This modified choice of window size is applied to CDMSlite Run 2 for particle masses below 100 eV/c² and for CDMSlite Run 3 below 200 eV/c².

The uncertainty band on the rate limit is calculated with different combinations of the upper and lower bounds of the resolution model and detection efficiency, selecting whichever gives the highest or lowest rate, respectively. In the conversion to the physical quantities, the upper edge of the uncertainty band is calculated using the upper edge of the rate uncertainty band and the conservative photoelectric cross section data, found in the third column of photoelectric_cross-section.txt. The lower edge of the uncertainty band is calculated using the lower edge of the rate uncertainty band and the nominal cross section data.

2.2 Combining Datasets

The method of combining data sets is described in [1]. For the iZIP-only and CDMSlite-only limits this method is applied separately for iZIP and CDMSlite. For the combined limit, all detectors and data sets are included. Here we reiterate the main steps:

- For each dark matter particle mass, count the events within the analysis window in each detector that covers the respective mass (as described above).
- Calculate the rate for each detector by dividing the above number by the energy-dependent efficiency at that energy and by the exposure of this detector.
- Pick the detector with the lowest resulting rate; this detector will always be part of the final analysis.
- Compare each other detector to this detector. If their rates differ by more than 3σ (based on simple counting statistics), discard the detector with the higher background for this mass, otherwise keep it.
- Once the comparison is complete, combine the data from all detectors that were kept: add the event numbers from all detectors included, calculate the Poisson upper limit on this sum, and then convert this limit into a rate limit by dividing by the sum of the efficiency corrected exposures of all included detectors.

3 Corrections in this Data Release

This data release differs from the original data release, correcting for the following:

- An error was found in the implementation of the method for calculating the iZIP limits in the original publication. While the efficiencies given in the publication and the original data release were correct, a wrong efficiency (differing from the correct one by a factor of ~ 0.68) was used in the algorithm calculating the limits.
- For the original data release, a similar error also occurred for the CDMSlite data, though in this case the deviation was only of the order of 1%.
- The selected mass points for which limits were calculated for the data release were slightly different from the mass points used in the calculation of the limits for the original publication.

A correction has been submitted to the Journal and the arXiv for the error in the original publication [1] and all three points are addressed in this current data release. Figures 6, 7, and 8 in this document are affected by these changes. The affected data files are the exclusion_limits*.txt and dataset_selection*.txt files. All file names have been appended with Updated_08_2020 for clarity.

References

- T. Aralis *et al.* (SuperCDMS Collaboration), Phys. Rev. D **101**, 052008 (2020), arXiv:1911.11905 [hep-ex].
- [2] R. Agnese *et al.* (SuperCDMS Collaboration), Phys. Rev. Lett. **112**, 241302 (2014), arXiv:1402.7137 [hep-ex].
- [3] R. Agnese *et al.* (SuperCDMS Collaboration), Phys. Rev. Lett. **116**, 071301 (2016), arXiv:1509.02448 [astro-ph.CO] .
- [4] R. Agnese *et al.* (SuperCDMS Collaboration), Phys. Rev. D 99, 062001 (2019), arXiv:1808.09098
 [astro-ph.CO] .
- [5] R. Agnese *et al.* (SuperCDMS Collaboration), Phys. Rev. D 97, 022002 (2018), arXiv:1707.01632
 [astro-ph.CO] .