

**Task:** [1 2 3] → [2 4 6]  
[4 3 4] → [8 6 8]

Wake: program search

```
(Y (λ (r l) (if (nil? l) nil  
  (cons (+ (car l) (car l))  
    (r (cdr l))))))
```

**Task:** [1 2 3] → [0 1 2]  
[4 3 4] → [3 2 3]

Wake: program search

```
(Y (λ (r l) (if (nil? l) nil  
  (cons (- (car l) 1)  
    (r (cdr l))))))
```

## Sleep: Abstraction

refactor  
(10<sup>14</sup> refactorings)

```
((λ (f) (Y (λ (r l) (if (nil? l)  
  nil  
  (cons (f (car l))  
    (r (cdr l)))))))  
(λ (z) (+ z z)))
```

refactor  
(10<sup>14</sup> refactorings)

```
((λ (f) (Y (λ (r l) (if (nil? l)  
  nil  
  (cons (f (car l))  
    (r (cdr l)))))))  
(λ (z) (- z 1)))
```

## Compress (MDL/Bayes objective)

(MAP (λ (z) (+ z z))) (MAP (λ (z) (- z 1)))

(MAP = (λ (f) (Y (λ (r l) (if (nil? l) nil  
 (cons (f (car l))  
 (r (cdr l)))))))