

Wake

Objective: For each task x in X , find best program ρ_x solving x under current library L


Library L

$f_1(x) = (+ x 1)$
 $f_2(z) = (\text{fold cons}$
 $(\text{cons } z \text{ nil}))$
.....

Task x

$[7\ 2\ 3] \rightarrow [4\ 3\ 8]$
 $[3\ 8] \rightarrow [9\ 4]$
 $[4\ 3\ 2] \rightarrow [3\ 4\ 5]$

Recognition
Model $Q(\cdot|x)$



Neurally guided search

Propose programs ρ in decreasing order under $Q(\cdot|x)$ until timeout

Best program ρ_x for task x
 $(\text{map } f_1 (\text{fold } f_2 \text{ nil } x))$


Choose ρ_x that maximizes:
 $P[\rho|x, L] \propto P[x|\rho] P[\rho|L]$

Sleep: Abstraction

Objective: Grow library L to compress programs found during waking

program for task 1

$(\text{cons } (+ 1 1))$



program for task 2

$(+ (\text{car } z) 1)$



Refactoring

Propose new library routines from subtrees of refactorings of programs


New library L

w/ routine $(+ x 1)$



Expand L w/
the routine that
maximizes:

$$P[L] \prod_{x \in X} \max_{\rho: \text{refactorings of } \rho_x} P[x|\rho] P[\rho|L]$$



Repeat
until no
increase
in score

Sleep: Dreaming

Objective: Train recognition model $Q(\rho|x)$ to predict best programs ρ_x for typical tasks x and current library L


Fantasies

1. draw programs ρ from library L
2. set task x to output of executing ρ

Replays

1. recall tasks x solved in waking
2. set program ρ to retrieved solution ρ_x

Train network on x, ρ pairs



Gradient step in parameters of Q
to maximize $\log Q(\rho|x)$

Train
until
converged