

Algorithm

Variables:

$\mathbf{X} = \{x_1, \dots, x_{N_r}\} \in R^D$: X-vectors sequence of recording r
 $\mathbf{Y} = \{y_1, \dots, y_{N_r}\} \in R^d$: lower dimensional representations
 $\mathbf{z} = \{z_1, \dots, z_{N_r}\} \in R$: segment labels
 θ : NN parameters
 $(\mathbf{Y}^p, \mathbf{z}^p, \theta^p)$: refer to variables at iteration p
 N^p : Number of clusters at iteration p
 N^* : target number of clusters

Initialize: ($p = 0$)

$\theta^0 \rightarrow$ (Whitening + length norm + PCA)
 $\mathbf{Y}^0 \rightarrow$ PCA outputs
 $\mathbf{z}^0 \rightarrow$ Initial AHC (N^0 clusters) labels

Steps:

While continue

1. $p = p + 1$
2. Sample triplets based on \mathbf{z}^{p-1}
3. $\theta^{p-1} \xrightarrow{\text{NN with triplet loss}} \theta^p$
4. $\mathbf{X} \xrightarrow{\theta^p} \mathbf{Y}^p$
5. $\mathbf{Y}^p \xrightarrow{\text{AHC}(N^p \text{ clusters})} \mathbf{z}^p = \{z_1^p, \dots, z_{N_r}^p\}$
6. **If stop:**
7. break

Termination: $\{y_1^p, \dots, y_{N_r}^p\} \xrightarrow{\text{AHC}(N^* \text{ clusters})} \{z_1^*, \dots, z_{N_r}^*\}$
(Diarization output)
