

## Algorithm

---

### Variables:

$X = \{x_1, \dots, x_{N_r}\} \in R^D$ : X-vectors sequence of recording  $r$

$Y = \{y_1, \dots, y_{N_r}\} \in R^d$ : lower dimensional representations

$\mathbf{z} = \{z_1, \dots, z_{N_r}\} \in R$ : segment labels

$\theta$ : NN parameters

$(Y^p, \mathbf{z}^p, \theta^p)$ : refer to variables at iteration  $p$

$N^p$ : Number of clusters(speakers) at iteration  $p$

$N^*$ : target number of clusters(speakers)

### Initialize: ( $p = 0$ )

$\theta^0 \rightarrow$  (Whitening + length norm + PCA)

$Y^0 \rightarrow$  PCA outputs

$\mathbf{z}^0 \rightarrow$  Initial AHC ( $N^0$  clusters) output labels

### Steps:

#### While continue

1.  $p = p + 1$
2. Sample triplets based on  $\mathbf{z}^{p-1}$
3.  $\theta^{p-1} \xrightarrow{\text{NN with triplet loss}} \theta^p$
4.  $Y^{p-1} \xrightarrow{\theta^p} Y^p$
5.  $Y^p \xrightarrow{\text{AHC}(N^p \text{ clusters})} \mathbf{z}^p = \{z_1^p, \dots, z_{N_r}^p\}$
6. **If stop:**
7. break

**Termination:**  $\{y_1^p, \dots, y_{N_r}^p\} \xrightarrow{\text{AHC}(N^* \text{ clusters})} \{z_1^*, \dots, z_{N_r}^*\}$   
(Diarization output)

---