

Input: Point cloud \mathbb{P} represented as an octree;

1 Mesh \mathbb{M} constructed from \mathbb{P} ;

2 UV map \mathbb{U} unwrapped from \mathbb{M} .

Result: Texture map \mathbb{T} ; Normal map \mathbb{N} .

3 **function** **TRANSFER**($\mathbb{P}, \mathbb{M}, \mathbb{U}$)

4 **foreach** *Triangle* m **in** \mathbb{M} **do**

 // Find points in \mathbb{P} that are likely on m

5 $P \leftarrow$ **FINDPOINTSINPOINTCLOUD**(\mathbb{P}, m);

 // Map P to the UV map \mathbb{U}

6 **foreach** *Point* p **in** P **do**

7 $c \leftarrow$ project p to m and return the barycentric
 coordinates of p w.r.t. m ;

8 $q \leftarrow$ the point in t whose barycentric coordinates
 are the same as c ;

9 $Q += q$;

10 **end**

11 $t \leftarrow$ triangle in \mathbb{U} corresponding to m ;

12 $S \leftarrow$ Triangulate($Q, t.vertices$);

 // Rasterize t by triangular interpolation

13 **foreach** *Pixel* x **in** *Triangle* t **do**

14 $s \leftarrow$ the triangle in S that bounds x ;

15 $\mathbb{N}[x] \leftarrow$ interpolating x 's normal from s ;

16 $\mathbb{T}[x] \leftarrow$ interpolating x 's color from s ;

17 **end**

18 **end**

19 **return** \mathbb{T}, \mathbb{N} ;

20 **function** **FINDPOINTSINPOINTCLOUD**(\mathbb{P}, m)

21 $P = \emptyset$;

22 $N \leftarrow$ the octree node in \mathbb{P} that bounds m ;

23 **foreach** *Point* p **in** N **do**

24 **if** $distance(p, m) \leq threshold_d$ &&

$angle(p.normal, m.normal) \leq threshold_n$ **then**

25 $P.add(p)$;

26 **end**

27 **end**

28 **return** P ;