

## An example GMS use case: accelerating the Bron-Kerbosch algorithm for maximal clique listing

S

Selecting relevant baselines & input graphs (enabled by the **GMS benchmark specification**).  
Baselines: Das et al., Eppstein et al., Input: graphs with various skews in triangle counts per vertex.


P

I

Experimenting with different algorithmic parts (facilitated by the **GMS benchmarking platform**), such as graph representations, vertex reorderings, loop scheduling, and other optimizations. The key optimizations in the BK algorithm enhanced in GMS are approximate degeneracy reordering of vertices, and an optimization where results of various operations on sets of vertices are cached. Benchmarking is further simplified by providing **reference implementations** of graph mining algorithms.

M

Insightful evaluation (facilitated by the **GMS metrics**, such as algorithmic throughput). *The variants of BK provided in GMS are able to mine up to 9x more cliques per second than the competition.*



BK with the **GMS** code, OpenMP BK with the **GMS** code, Intel TBB BK by Das et al. (a recent baseline)

GMS-DGR : BK with degeneracy reordering (a variant by Eppstein et al.) GMS-DEG : BK with simple degree reordering

GMS-ADG : BK with approximate degeneracy reordering (a baseline obtained with GMS)

GMS-ADG-S : BK-GMS-ADG plus subgraph optimization (a baseline obtained with GMS)

C

Delivering theoretical performance bounds (facilitated by the **GMS concurrency analysis**). *The BK in GMS offers the best work bound among poly-logarithmic depth maximal clique listing algorithms*