

**Figure 11.3** Two graph representations. (a) A directed graph. (b) The adjacency matrix for the graph of (a). (c) The adjacency list for the graph of (a).

to Vertex 1 and one going to Vertex 4. The list for Vertex 2 stores an entry for Vertex 4 because there is an edge from Vertex 2 to Vertex 4, but no entry for Vertex 3 because this edge comes into Vertex 2 rather than going out.

The storage requirements for the adjacency list depend on both the number of edges and the number of vertices in the graph. There must be an array entry for each vertex (even if the vertex is not adjacent to any other vertex and thus has no elements on its linked list), and each edge must appear on one of the lists. Thus, the cost is  $\Theta(|V| + |E|)$ .


Both the adjacency matrix and the adjacency list can be used to store directed or undirected graphs. Each edge of an undirected graph connecting Vertices  $U$  and  $V$  is represented by two directed edges: one from  $U$  to  $V$  and one from  $V$  to  $U$ . Figure 11.4 illustrates the use of the adjacency matrix and the adjacency list for undirected graphs.

Which graph representation is more space efficient depends on the number of edges in the graph. The adjacency list stores information only for those edges that actually appear in the graph, while the adjacency matrix requires space for each potential edge, whether it exists or not. However, the adjacency matrix requires no overhead for pointers, which can be a substantial cost, especially if the only

Discrete Mathematics > Graph Theory > Directed Graphs >  
Interactive Entries > Interactive Demonstrations >

## Directed Graph

EXPLORE THIS TOPIC IN  
The MathWorld Classroom



A graph in which each graph edge is replaced by a directed graph edge, also called a digraph. A directed graph having no multiple edges or loops (corresponding to a binary adjacency matrix with 0s on the diagonal) is called a simple directed graph. A complete graph in which each edge is bidirected is called a complete directed graph. A directed graph having no symmetric pair of directed edges (i.e., no bidirected edges) is called an oriented graph. A complete oriented graph (i.e., a directed graph in which each pair of nodes is joined by a single edge having a unique direction) is called a tournament.

If  $G$  is an undirected connected graph, then one can always direct the circuit graph edges of  $G$  and leave the separating edges undirected so that there is a directed path from any node to another. Such a graph is said to be transitive if the adjacency relation is transitive.

A graph may be tested in the Wolfram Language to see if it is a directed graph using `DirectedGraphQ[g]`.

### SEE ALSO:

Acyclic Digraph, Arborescence, Cayley Graph, Digraph Sink, Digraph Topology, Graph, Indegree, Mixed Graph, Multigraph, Network, Oriented Graph, Outdegree, Source, Strongly Connected Digraph, Tournament, Undirected Graph, Weakly Connected Digraph

### REFERENCES:

- Chartrand, G. "Directed Graphs as Mathematical Models." §1.5 in *Introductory Graph Theory*. New York: Dover, pp. 16-19, 1985.
- Harary, F. and Palmer, E. M. "Digraphs." Ch. 5 in *Graphical Enumeration*. New York: Academic Press, pp. 120-134, 1973.
- Saaty, T. L. and Kainen, P. C. *The Four-Color Problem: Assaults and Conquest*. New York: Dover, p. 122, 1986.

Referenced on Wolfram|Alpha: Directed Graph

### CITE THIS AS:

Weissstein, Eric W. "Directed Graph." From *MathWorld*--A Wolfram Web Resource.  
<https://mathworld.wolfram.com/DirectedGraph.html>

Wolfram Web Resources

Mathematica »  
The #1 tool for creating

Wolfram|Alpha »  
Explore anything with the first

Wolfram Demonstrations Project »  
Explore thousands of free applications



WIKIPEDIA  
The Free Encyclopedia

Main page  
Contents  
Current events  
Random article  
About Wikipedia  
Contact us  
Donate

Contribute

Help  
Learn to edit  
Community portal  
Recent changes  
Upload file

Tools

What links here  
Related changes  
Special pages  
Permanent link  
Page information  
Cite this page  
Wikidata item

Print/export

Download as PDF  
Printable version

In other projects

Wikimedia Commons

Languages

العربية  
Deutsch  
Español  
Français  
한국어  
Italiano  
Русский  
Tiếng Việt  
中文

22 more

Edit links

Not logged in Talk Contributions Create account Log in

Article Talk

Read Edit View history

Search Wikipedia

## Binary search tree

From Wikipedia, the free encyclopedia

In computer science, a **binary search tree** (**BST**), also called an **ordered** or **sorted binary tree**, is a **rooted binary tree** whose internal nodes each store a key greater than all the keys in the node's left subtree and less than those in its right subtree. A binary tree is a type of **data structure** for storing data such as numbers in an organized way. Binary search trees allow **binary search** for fast lookup, addition and removal of data items, and can be used to implement **dynamic sets** and **lookup tables**. The order of nodes in a BST means that each comparison skips about half of the remaining tree, so the whole lookup takes **time proportional** to the **binary logarithm** of the number of items stored in the tree. This is much better than the **linear time** required to find items by key in an (unsorted) array, but slower than the corresponding operations on **hash tables**. Several variants of the binary search tree have been studied.

Contents [hide]

- Definition
  - Order relation
- Operations
  - Searching
  - Searching with duplicates allowed
  - Insertion
  - Deletion
  - Traversal
  - Verification
  - Parallel algorithms
- Examples of applications
  - Sort
  - Priority queue operations
- Types
  - Performance comparisons
  - Optimal binary search trees
- See also
- Notes
- References
- Further reading
- External links


### Definition [ edit ]

A binary search tree is a **rooted binary tree**, whose internal nodes each store a key (and optionally, an associated value), and each has two distinguished sub-trees, commonly denoted *left* and *right*. The tree additionally satisfies the **binary search** property: the key in each node is greater than or equal to any key stored in the left sub-tree, and less than or equal to any key stored in the right sub-tree.<sup>[1]:287</sup> The leaves (final nodes) of the tree contain no key and have no structure to distinguish them from one another.

Often, the information represented by each node is a record rather than a single data element. However, for sequencing purposes, nodes are compared according to their keys rather than any part of their associated records. The major advantage of binary search trees over other data structures is that the related **sorting algorithms** and **search algorithms** such as **in-order traversal** can be very efficient.

Binary search trees are a fundamental **data structure** used to construct more abstract data structures such as **sets**, **multisets**, and **associative arrays**.

Binary search tree
Type
tree
Invented
1960
Invented
P.F. Windley, A.D. Booth, A.J.T.
by
Colin, and T.N. Hibbard
Time complexity in big O notation
Algorithm
Average
Worst case
Space
$O(n)$
$O(n)$
Search
$O(\log n)$
$O(n)$
Insert
$O(\log n)$
$O(n)$
Delete
$O(\log n)$
$O(n)$



A binary search tree of size 9 and depth 3, with 8 at the root. The leaves are not drawn.

### Binary tree