
∇sID
1 Byte
u_t^l (decompressed)
2 Bytes
Effectual O Finder
$\nabla\tilde{s}_t^l$
ID Decoder
∇sID
u_t^l (compressed)
Decompress u_t^l
u_t^l (decompressed)
Example
Spike Gradient Mask:$\nabla\tilde{s}_t^l$
Output ID Buffer 0
Output ID Buffer 1
row
col
Output ID Buffer: ∇sID
Decompress u_t^l
(a)
$\nabla\tilde{u}_t^{l+1}$
Effectual I∩O Finder
ID & Tag
Priority Encoder
∇uID Decoder
Task Queue
Potential Gradient Mask: $\nabla\tilde{u}_t^{l+1}$
(2,3)
0 1 0 1
ID
Tag
Valid Conv ID
∇sID
wID
∇uID
Cycle
Get Valid Conv ID
∇sID (2,3)
Get Valid Input ID
Example
(b)
Valid Operads ID
18 bits
Grad
Phase 2
Phase 1
$\alpha\nabla u_t^l$
∇u_t^l
∇s_t^l
ps_t^l
$\alpha\nabla u_{t+1}^l$
$\nabla\tilde{u}_t^l$
$\neq 0$
s_t^l
β
$\nabla\tilde{s}_t^l$
$-u_t^l$
Eq (2)
$\nabla s_t^l[i] = \nabla u_{t+1}^l[i](-\alpha u_t^l[i]) + \sum_j \nabla u_t^{l+1}[i]\, w^l[i,j]$ Phase 1
ps_t^l
$\nabla u_t^l[i] = \nabla u_{t+1}^l[i]\alpha(1 - s_t^l[i]) + \nabla s_t^l[i] fire'(u_t^l[i])$ Phase 2
Acc
PE Group 0
PE Group 1
PE Group n
Accumulated Partial Sum: ps_t^l
Adder Tree
(d)
Weight: w^l
PE (Floating Point)
Partial Sum: ps_t^l
MAC
0.2
Potential Gradient: ∇u_t^{l+1}
Instruction:
∇sID
wID
∇uID
(2,3)
2
(3,3)
(c)
1 Byte
2 Bytes
(e)
2×(PE group size) Bytes
s_t^l
$\nabla\tilde{s}_t^l$
u_t^l (decompressed)
ps_t^l
$\nabla\tilde{u}_t^l$
∇u_t^l
w^l
∇u_t^{l+1}