Functional Brain Network Construction	SPM 12	AFNI	FSL	Free Surfer	CONN	fMRI Prep	ANTs	Nilearn
Skull-Stripping Remove voxels not necessary for analysis such as bone, dura, air, etc., leaving just the brain	✓	✓	✓	✓		✓	✓	✓
Slice-Timing Correction Adjust for the fact that each slice in the volume is taken at a different time, not all at once	✓	✓	✓		✓	✓		
Motion Correction/Realignment Correct movement made during scanning by aligning all the functional images with one reference	✓	✓	✓		✓	✓	✓	
Co-registration Align participant's functional images with the anatomical structural images for localization	✓	✓	✓	✓	✓	✓	✓	
Normalization Wrap the data across subjects to a template/atlas standardized space	✓	✓	✓		✓	✓		
Smoothing Perform weighted averages of individual voxels with neighboring voxels	✓	✓	✓		✓			✓
Brain Region Parcellation Segment each subject into the regions of interest defined by the given atlas	The parcellation step is usually done separately by choosing an anatomical atlas and apply it to dive the entire brain into units.							
Construct Network Given the ROI parcellation, calculate the edge by the time series activity correlation between different brain regions	The network construction step is usually done separately through pairwise correlation calculation such as Pearson correlation.							