

```
subroutine q_j_stencil(is,ie,js,je,npz,x_area_flux,area_with_x_flux,q,area,fx1,fx2,q_j)
    integer, intent(in):: is, ie, js, je, npz
    real, intent(in):: x_area_flux(is:ie+1, js:je, npz)
    real, intent(in):: area_with_x_flux(is:ie, js:je, npz)
    real, intent(in):: q(isd:ied, js:je, npz)
    real, intent(in):: area(is:ie, js:je)
    real, intent(inout):: fx1(is:ie+1, js:je, npz)
    real, intent(in):: fx2(is:ie+1, js:je, npz)
    real, intent(out):: q_j(is:ie, js:je, npz)
    integer:: i, j, k
    do k = 1, npz
        do j = js, je
            do i = is, ie+1
                fx1(i,j,k) = x_area_flux(i,j,k)*fx2(i,j,k)
            enddo
            do i = is, ie
                area_with_x_flux(i,j,k) = area(i, j)+x_area_flux(i,j,k)-x_area_flux(i+1,j,k)
            enddo
            do i = is, ie
                q_j(i,j,k) = (q(i,j,k)*area(i,j)+fx1(i,j,k)-fx1(i+1,j,k))/area_with_x_flux(i,j,k)
            enddo
        enddo
    enddo
end subroutine q_j_stencil
```

**Type-annotated fields (size-dependent)**

**Static loop structure and explicit ranges**

**Intermediate results hard-coded as arrays**

**Explicit absolute indices**