



Acoustics
Tracer Advection

Remapping
Dynamical Core

Halo Exchange
Unit Tests

Horizontal Stencil

Vertical Solver



Declarative Abstraction (GT4Py)

Backend



Automatic
Callbacks



Local
Optimization


Transfer
Tuning

Full-Program
Optimization

Orchestration (DaCe)

Lines of Code vs. FORTRAN: **0.42x**

Speedup: **3.92x** (P100), **8.48x** (A100)



Backend and target hardware specification


Type-annotated
fields (size-agnostic)

```
@gtscript.stencil(backend='gtc:dace:gpu')
def q_j_stencil(q: FloatField, area: FloatFieldIJ,
                 x_area_flux: FloatField, fx2: FloatField,
                 q_j: FloatField):
    with computation(PARALLEL), interval(...):
        fx1 = x_area_flux * fx2
        area_with_x_flux = area + x_area_flux - x_area_flux[1, 0, 0]
        q_j = (q * area + fx1 - fx1[1, 0, 0]) / area_with_x_flux
```


Computation schedule
and interval abstraction

```
with computation(PARALLEL), interval(...):
```


```
    b = a[0, 1] + a[0, -1] + a[1, 0] + a[-1, 0]
```



```
with computation(FORWARD), interval(...):  
    out = out[0, 0, -1] + out[0, 0, -2]
```



Aligned addresses



Shape: $(I + 2h, J + 2h, K)$


Start offset: $o = a - h$

Strides:


$$s_i = 1$$

$$s_j = a \left\lceil \frac{I + 2h}{a} \right\rceil$$

$$s_k = s_j \cdot (J + 2h)$$



```
glob_b = ...  
class ClassA:  
    def __init__(self, arr):  
        self.q = arr  
  
    @dace.method  
    def __call__(self, a):  
        return a * self.q + glob_b
```



Original arguments

Function closure

```
@dace.program  
def ClassA__call__(a, __g_self_q, __g_glob_b):  
    return a * __g_self_q + __g_glob_b
```

```
glob_b = ...
class ClassA:
    def __init__(self, arr):
        self.q = arr
```

```
@dace.method
def __call__(self, a):
    return a * self.q + glob_b
```



Function closure

```
@dace.program
def ClassA__call__(a, __g_self_q, __g_glob_b):
    return a * __g_self_q + __g_glob_b
```