

L^AT_EX Class for the *Association for Computing Machinery**

Boris Veytsman[†]

2022/08/27, v1.87

Abstract

This package provides a class for typesetting publications of the Association for Computing Machinery.

Contents

1	Introduction	3
2	User's guide	3
2.1	Installation	3
2.2	Invocation and options	6
2.3	Top matter	7
2.4	Top matter of ACM Engage materials	19
2.5	ACM cover page	20
2.6	Internationalization	20
2.7	Algorithms	21
2.8	Figures and tables	21
2.9	Descriptions of images	23
2.10	Theorems	23
2.11	Online-only and offline-only material	24
2.12	Note about anonymous mode	24
2.13	Acknowledgments	24
2.14	Bibliography	25
2.14.1	Processing using BibT _E X	25
2.14.2	Processing using BibL ^A T _E X	28
2.15	Colors	29
2.16	Other notable packages and typographic remarks	30
2.17	Counting words	30
2.18	Creative Commons licenses for ACM publications	30
2.19	Disabled or forbidden commands	31
2.20	Notes for wizards	31
2.21	Currently supported publications	32
2.22	A note about sigchi-a format	33

*©2016–2022, Association for Computing Machinery

[†]borisv@lk.net, boris@varphi.com

3	Implementation	35
3.1	Identification	35
3.2	Preload hook	35
3.3	Options	35
3.4	Setting switches	39
3.5	Loading the base class and package	40
3.6	Citations	41
3.7	Internationalization	43
3.8	Sectioning	45
3.9	Hyperxmp and hyperref	48
3.10	Other packages	50
3.11	Paper size and paragraphing	50
3.12	Fonts	53
3.13	Image descriptions	55
3.14	Floats	56
3.15	Lists	58
3.16	Top-matter data	59
3.17	Concepts system	74
3.18	Copyright system	75
3.19	Maketitle hook	81
3.20	ACM Engage top matter	82
3.21	Typesetting top matter	82
3.22	Headers and Footers	99
3.23	Sectioning	105
3.24	TOC lists	108
3.25	Theorems	108
3.26	Balancing columns	111
3.27	Acknowledgments	112
3.28	Conditional typesetting	113
3.29	Additional bibliography commands	113
3.30	Index	113
3.31	End of Class	114

1 Introduction

The Association for Computing Machinery¹ is the world’s largest educational and scientific computing society, which delivers resources that advance computing as a science and a profession. It was one of the early adopters of \TeX for its typesetting.

It provided several different classes for a number of journals and conference proceedings. Unfortunately during the years since these classes were written, the code was patched many times, and supporting different versions of the classes became difficult.

This package provides the uniform interface for all ACM publications. It is intended to replace all the different classes and packages and provide an up-to-date \LaTeX package.

This package uses only free \TeX packages and fonts included in \TeX Live, Mik \TeX and other popular \TeX distributions. It is intended to be published in these distributions itself, which minimizes users’ efforts in the installation and support of this package.

I am grateful to Michael D. Adams, Leif Andersen, Lawrence Christopher Angrave, Dirk Beyer, Andrew Black, Joachim Breitner, Yegor Bugayenko, Benjamin Byholm, John Collins, Roberto Di Cosmo, Nils Anders Danielsson, Michael Ekstrand, Matthew Fluet, Paolo G. Giarrusso, Ben Greenman, Enrico Gregorio, Jamie Davis, Ulrike Fischer, Jason Hemann, Peter Kemp, Luis Leiva, Ben Liblit, Rholais Lii, LianTze Lim, Kuldeep S. Meel, Kai Mindermann, Frank Mittelbach, Serguei Mokhov, Ross Moore, John Owens, Joel Nider, Scott Pakin, Tobias Pape, Henning Pohl, Philip Quinn, Mathias Rav, Andreas Reichinger, Matteo Riondato, Craig Rodkin, Bernard Rous, Feras Saad, Kerry A. Seitz, Jr., David Shamma, Gabriel Scherer, Kartik Singhal, Christoph Sommer, Stephen Spencer, Shin Hwei Tan, Daniel Thomas, Shari Trewin, Zack Weinberg, John Wickerson and many others for their invaluable help.

The development version of the package is available at <https://github.com/borisveytsman/acmart>.

2 User’s guide

This class uses many commands and customizatón options, so it might appear intimidating for a casual user. Do not panic! Many of these commands and options can be safely left with their default values or the values recommended by your conference or journal editors. If you have problems or questions, do not hesitate to ask me directly or the community at <https://github.com/borisveytsman/acmart>, <https://tex.stackexchange.com> or the closest \TeX Users Group. The world-wide \TeX Users Group is at <https://tug.org/>; please consider joining us if you use \TeX regularly.

2.1 Installation

Most probably, you already have this package installed in your favorite \TeX distribution; if not, you may want to upgrade. You may need to upgrade it anyway since this package uses a number of relatively recent packages, especially the ones related to fonts.

The latest released version of this package can be found on CTAN: <https://www.ctan.org/pkg/acmart>. The development version can be found on GitHub: <https://github.com/borisveytsman/acmart>. At this address you can file a bug report—or even contribute your own enhancement by making a pull request.

¹<http://www.acm.org/>

Please note that the version on Github is a development (or experimental) version: please download it for testing new features. The production version is the one on CTAN and ACM sites.

Most users should not attempt to install this package themselves but should rather rely on their \TeX distributions to provide it. If you decide to install the package yourself, follow the standard rules:

1. Run `latex acmart.ins`. This will produce the file `acmart.cls`
2. Put the files `acmart.cls` and `ACM-Reference-Format.bst` in places where \TeX can find them (see [1] or the documentation for your \TeX system).
3. Update the database of file names. Again, see [1] or the documentation for your \TeX system for the system-specific details.
4. The file `acmart.pdf` provides the documentation for the package. (This is probably the file you are reading now.)

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

This class uses a number of other packages. They are included in all major \TeX distributions (\TeX Live, Mac \TeX , Mik \TeX) of 2015 and later, so you probably have them installed. Just in case here is the list of these packages:

- *amscs*, <http://www.ctan.org/pkg/amscs>
- *amsfonts*, <http://www.ctan.org/pkg/amsfonts>
- *amsmath*, <http://www.ctan.org/pkg/amsmath>
- *binhex*, <http://www.ctan.org/pkg/binhex>
- *balance*, <http://www.ctan.org/pkg/balance>
- *booktabs*, <http://www.ctan.org/pkg/booktabs>
- *caption*, <http://www.ctan.org/pkg/caption>
- *comment*, <http://www.ctan.org/pkg/comment>
- *cm-super*, <http://www.ctan.org/pkg/cm-super>
- *cmap*, <http://www.ctan.org/pkg/cmap>
- *doclicense*, <http://www.ctan.org/pkg/doclicense>
- *draftwatermark*, <http://www.ctan.org/pkg/draftwatermark>
- *environ*, <http://www.ctan.org/pkg/environ>
- *etoolbox*, <http://www.ctan.org/pkg/etoolbox>
- *fancyhdr*, <http://www.ctan.org/pkg/fancyhdr>
- *float*, <http://www.ctan.org/pkg/float>
- *fontaxes*, <http://www.ctan.org/pkg/fontaxes>

- *geometry*, <http://www.ctan.org/pkg/geometry>
- *graphics*, <http://www.ctan.org/pkg/graphics>
- *hyperref*, <http://www.ctan.org/pkg/hyperref>
- *hyperxmp*, <http://www.ctan.org/pkg/hyperxmp>
- *iftex*, <http://www.ctan.org/pkg/iftex>
- *inconsolata*, <http://www.ctan.org/pkg/inconsolata>
- *libertine*, <http://www.ctan.org/pkg/libertine>
- *manyfoot*, <http://www.ctan.org/pkg/manyfoot>
- *microtype*, <http://www.ctan.org/pkg/microtype>
- *mmap*, <http://www.ctan.org/pkg/mmap>
- *ms*, <http://www.ctan.org/pkg/ms>
- *mweights*, <http://www.ctan.org/pkg/mweights>
- *natbib*, <http://www.ctan.org/pkg/natbib>
- *nccfoots*, <http://www.ctan.org/pkg/nccfoots>
- *newtx*, <http://www.ctan.org/pkg/newtx>
- *oberdiek*, <http://www.ctan.org/pkg/oberdiek>
- *pdftex-def*, <http://www.ctan.org/pkg/pdftex-def>
- *refcount*, <http://www.ctan.org/pkg/refcount>
- *setspace*, <http://www.ctan.org/pkg/setspace>
- *textcase*, <http://www.ctan.org/pkg/textcase>
- *totpages*, <http://www.ctan.org/pkg/totpages>
- *trimspaces*, <http://www.ctan.org/pkg/trimspaces>
- *upquote*, <http://www.ctan.org/pkg/upquote>
- *url*, <http://www.ctan.org/pkg/url>
- *xcolor*, <http://www.ctan.org/pkg/xcolor>
- *xkeyval*, <http://www.ctan.org/pkg/xkeyval>
- *xstring*, <http://www.ctan.org/pkg/xstring>

Table 1: The possible values for the format option

Value	Meaning
manuscript	A manuscript. This is the default.
acmsmall	Small single-column format. Used for CIE, CSUR, DLT, FAC, GAMES, JACM, JDIQ, JDS, JEA, JERIC, JETC, JRC, PACMCGIT, PACMHCI, PACMPL, TAAS, TACCESS, TACO, TALG, TALLIP (formerly TALIP), TCPS, TDS, TEAC, TECS, TELO, THRI, TIIS, TIOT, TISSEC, TIST, TKDD, TMIS, TOCE, TOCHI, TOCL, TOCS, TOCT, TODAES, TODS, TOIS, TOIT, TOMACS, TOMM (formerly TOMCCAP), TOMPECS, TOMS, TOPC, TOPLAS, TOPS, TOS, TOSEM, TOSN, TQC, TRETS, TSAS, TSC, TSLP and TWEB, including special issues.
acmlarge	Large single-column format. Used for DTRAP, HEALTH, IMWUT, JOCCH, POMACS and TAP, including special issues.
acmtog	Large double-column format. Used for TOG, including annual conference Technical Papers.
sigconf	Proceedings format for most ACM conferences (with the exception of SIGPLAN) and all ICPS volumes.
sigplan	Proceedings format for SIGPLAN conferences.
acmengage	ACM EngageCSEdu Course materials.
acmcp	ACM cover page.

2.2 Invocation and options

To use this class, put in the preamble of your document

```
\documentclass[<options>]{acmart}
```

There are several options corresponding to the type of the document and its general appearance. They are described below. Generally speaking, the options have key=value forms, for example,

```
\documentclass[format=acmsmall, screen=true, review=false]{acmart}
```

The option `format` describes the format of the output. There are several possible values for this option, for example,

```
\documentclass[format=acmtog]{acmart}
```

Actually the words `format=` can be omitted, e.g.,

```
\documentclass[acmtog, review=false]{acmart}
```

The possible formats are listed in Table 1. Note that formats starting with `acm` are intended for journals, transactions, and course materials, while formats starting with `sig` are intended for proceedings published as books.

Note that sometimes conference proceedings are published as a special issue (or issues) of an ACM journal. In this case, you should use the journal format for a conference paper. Please contact your conference committee if in doubt.

Starting in 2020, ACM retired formats `sigchi` and `sigchi-a`. SIGCHI conferences now use `sigconf` format for their publications. If a file uses `sigchi` format, a warning is issued, and the format is automatically switched to `sigconf`. Format `sigchi-a` can be used for non-ACM documents only (see Section 2.22). The format `acmcp` is used for ACM cover pages discussed in Section 2.5.

There are several Boolean options that can take `true` or `false` values. They are listed in Table 2. The words `=true` can be omitted when setting a Boolean option, so instead of `screen=true` one can write just `screen`, for example,

```
\documentclass[acmsmall, screen, review]{acmart}
```

The option `review` is useful when combined with the `manuscript` format option. It provides a version suitable for reviewers and copy editors.

Two samples in the `samples` directory, `manuscript` and `acmsmall-submission`, show manuscripts formatted for submission to ACM.

The default for the option `screen` depends on the publication. At present it is `false` for all publications *but* PACM, since PACM is now electronic-only. Thus PACM titles (see Table 5) set this option to `true`. In the future this option may involve additional features suitable for on-screen versions of articles.

The option `natbib` is used when the corresponding BibTeX style is based on `natbib`. In most cases you do not need to set it. See Section 2.14.

The option `anonymous` is used for anonymous review processes and causes all author information to be obscured.

The option `timestamp` is used to include a time stamp in the footer of each page. When preparing a document, this can help avoid confusing different revisions. The footer also includes the page range of the document. This helps detect missing pages in hard copies.

The option `authordraft` is intended for author's drafts that are not intended for distribution. It typesets a copyright block to give the author an idea of its size and the overall size of the paper but overprints it with the phrase "Unpublished working draft. Not for distribution.", which is also used as a watermark. This option sets `timestamp` and `review` to `true`, but these can be overridden by setting these options to `false` *after* setting `authordraft` to `true`.

The option `balance` determines whether the last page in the two column mode has balanced columns. By default it is `true`; however, it may lead to problems for some documents. Set it to `false` if you encounter compilation errors. Note that for one page documents `\balance` command might cause problems. An alternative is the (experimental) option `pbalance`, which uses the new package `pbalance` for this end.

The option `urlbreakonhyphens` determines whether URLs can be split between lines after hyphens. By default it is `true`. Set it to `false` to disallow these breaks.

The option `language` is used to define the languages for the multi-language papers. It is discussed in Section 2.6.

2.3 Top matter

A number of commands set up *top matter* or (in computer science jargon) *metadata* for an article. They establish the publication name, article title, authors, DOI and other data. Some of these commands, like `\title` and `\author`, should be put by the authors. Others, like `\acmVolume` and `\acmDOI`—by the editors. Below we describe these commands and mention who should issue them. These macros should be used *before* the

Table 2: Boolean options

Option	Default	Meaning
review	false	A review version: lines are numbered and hyperlinks are colored
screen	see text	A screen version: hyperlinks are colored
natbib	true	Whether to use the natbib package (see Section 2.14)
anonymous	false	Whether to make author(s) anonymous
authorversion	false	Whether to generate a special version for the authors' personal use or posting (see Section 2.3)
nonacm	false	Use the class typesetting options for a non-ACM document, which will not include the conference/journal header and footers. Currently such documents allow only a Creative Commons license.
timestamp	false	Whether to put a time stamp in the footer of each page
authordraft	false	Whether author's-draft mode is enabled
acmthm	true	Whether to define theorem-like environments, see Section 2.10
balance	true	Whether to balance the last page in two column mode
pbalance	false	Whether to balance the last page in two column mode using pbalance package
urlbreakonhyphens	true	Whether to break urls on hyphens

`\maketitle` command. Note that in previous versions of ACM classes some of these commands should be used before `\maketitle`, and some after it. Now they all must be used before `\maketitle`.

This class internally loads the `amsart` class, so many top-matter commands are inherited from `amsart` [2].

`\acmJournal` The macro `\acmJournal{<shortName>}` sets the name of the journal or transaction for journals and transactions. The argument is the short name of the publication *in uppercase*, for example,

```
\acmJournal{TOMS}
```

The currently recognized journals are listed in Table 5. Note that conference proceedings published in *book* form do not set this macro.

`\acmConference` The macro `\acmConference[<short name>]{<name>}{<date>}{<venue>}` is used for conference proceedings published in the book form. The arguments are the following:

short name: the abbreviated name of the conference (optional).

name: the name of the conference.

date: the date(s) of the conference.

venue: the place of the conference.

Examples:

```
\acmConference[TD'15]{Technical Data Conference}{November
12--16}{Dallas, TX, USA}
\acmConference[SA'15 Art Papers]{November 02--06, 2015}{Kobe, Japan}
```

`\acmBooktitle` By default we assume that conference proceedings are published in the book named *Proceedings of CONFERENCE*, where *CONFERENCE* is the name of the conference inferred from the command `\acmConference` above. However, sometimes the book title is different. The command `\acmBooktitle` can be used to set this title, for example,

```
\acmBooktitle{Companion to the first International Conference on the
Art, Science and Engineering of Programming (Programming '17)}
```

An ACM paper should have either `\acmJournal` or `\acmConference` command. If it has both (or more) commands, the last one takes precedence. Note that if you have the command `\acmConference` in a journal format like `acmsmall`, the class will use conference format for `bibstrip` and reference citation formatting. In the samples directory there is a file `sample-acmsmall-conf.tex` with the example of this usage.

An ACM Engage material should *not* use `\acmJournal` or `\acmConference` command. It may use `\acmBooktitle` to override the default *ACM EngageCSEdu*. It should use `\acmYear` to set the date of the material.

`\editor` In most cases, conference proceedings are edited. You can use the command `\editor{<editor>}` to set the editor of the volume. This command can be repeated, for example,

```
\editor{Jennifer B. Sartor}
\editor{Theo D'Hondt}
\editor{Wolfgang De Meuter}
```

`\title` The command `\title`, as in the `amsart` class, has two arguments: one optional, and one mandatory:

```
\title[<ShortTitle>]{<FullTitle>}
```

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

It is expected that this command is inserted by the author of the manuscript.

`\subtitle` Besides title, ACM classes allow a subtitle, set with the `\subtitle{<subtitle>}` macro.

The commands for specifying authors are highly structured. The reason is they serve double duty: the authors' information is typeset in the manuscript *and* is used by the metadata extraction tools for indexing and cataloguing. Therefore it is very important to follow the guidelines exactly.

`\author` The basic commands are `\author`, `\orcid` (for the researchers registered with OR-

`\orcid` CID, <http://www.orcid.org/>), `\affiliation` and `\email`. In the simplest case, you

`\affiliation` enter them in this order:

```
\email
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
```

Do *not* use the \TeX `\and` macro or commas, or `\\` between the authors! Each author deserves his or her own `\author` command. An attempt to list several authors or their e-mails in one command leads to a warning or an error. This is not a bug, but the expected behavior.

Note that some formats do not typeset e-mails or ORCID identifiers. Do not worry: the metadata tools will get them.

Sometimes an author has several affiliations. In this case, the `\affiliation` command should be repeated:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

Similarly you can repeat the `\email` command.

You may have several authors with the same affiliation, different affiliations, or overlapping affiliations (author A_1 is affiliated with institutions I_1 and I_2 , while author A_2 is affiliated with I_2 only, author A_3 is affiliated with I_1 and I_3 , etc.). The recommended solution is to put the `\affiliation` commands after each author, possibly repeating them:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
```

```

\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}

```

In some cases, when several authors share the same affiliation, you can try to save space using the format

```

\author{...}
\email{...}
\author{...}
\email{...}
\affiliation{...}

```

However, this format is not generally recommended.

`\additionalaffiliation` In some cases, too many affiliations can take too much space. The command `\additionalaffiliation{<affiliation>}` creates a footnote after an author's name with the words "Also with {<affiliation>}". You should use this command only as a last resort. An example of usage is:

```

\author{G. Tobin}
\author{Ben Trovato}
\additionalaffiliation{%
  \institution{The Th{\o}rv{\a}ld Group}
  \streetaddress{1 Th{\o}rv{\a}ld Circle}
  \city{Hekla}
  \country{Iceland}}
\affiliation{%
  \institution{Institute for Clarity in Documentation}
  \streetaddress{P.O. Box 1212}
  \city{Dublin}
  \state{Ohio}
  \postcode{43017-6221}}

```

Here Trovato and Tobin share their affiliation with the Institute for Clarity in Documentation, but only Ben Trovato is affiliated with The Thørvöld Group.

`\position` The `\affiliation` and `\additionalaffiliation` commands are further structured to interact with the metadata extraction tools. Inside these commands you should use the `\institution`, `\position`, `\department`, `\city`, `\streetaddress`, `\state`, `\postcode` and `\country` macros to indicate the corresponding parts of the affiliation. Note that in some cases (for example, journals) these parts are not printed in the resulting copy, but they *are* necessary since they are used by the XML metadata extraction programs. Do *not* put commas or `\\` between the elements of `\affiliation`. They will be provided automatically.

The fields `\institution`, `\city` and `\country` are mandatory. If they are not provided, an error or a warning is issued. Currently the absence of `\country` produces an error; ACM may change this in the future.

An example of the author block:

```

\author{A. U. Thor}
\orcid{1234-4564-1234-4565}
\affiliation{%
  \institution{University of New South Wales}
  \department{School of Biomedical Engineering}
  \streetaddress{Samuels Building (F25), Kensington Campus}
  \city{Sidney}
  \state{NSW}
  \postcode{2052}
  \country{Australia}}
\email{author@nsw.au.edu}
\author{A. N. Other}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}
\author{C. O. Respondent}
\orcid{1234-4565-4564-1234}
\affiliation{%
  \institution{University of Pennsylvania}
  \city{Philadelphia}
  \state{PA}
  \country{USA}}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}

```

Note that the old ACM conference formats did not allow more than six authors and required some effort from authors to achieve alignment. The new format is much better in this.

Sometimes an author works in several departments within the same insitution. There could be two situations: the departments are independent, or one department is within another. In the first case, just repeat the command `\department` several times. To handle the second case the command has an optional numerical parameter. The departments with higher numbers are higher in the organizational chart. Compare

```

\affiliation{%
  \department[0]{Department of Lunar Studies} % 0 is the default
  \department[1]{John Doe Institute} % higher than 0
  \institution{University of San Serriffe}
  \country{San Serriffe}}

```

and

```

\affiliation{%
  \department{Department of Lunar Studies} % Not in the John Doe Institute!
  \department{John Doe Institute}
  \institution{University of San Serriffe}
  \country{San Serriffe}}

```

The command `\affiliation` formats its output according to American conventions. This might be wrong for some cases. Consider, for example, a German address. In Germany, the postcode is put before the city and is not separated by a comma. We can handle this order using

```
\affiliation{%
  \institution{Fluginstitut}
  \streetaddress{Sonnenallee 17}
  \postcode{123456}
  \city{Helm}
  \country{Germany}}
```

However, the comma after the postcode is unfortunate: the address will be typeset (in some formats) as

```
Fluginstitut
Sonnenallee 17
123456, Helm, Germany
```

To overcome this problem, the command `\affiliation` has an optional parameter `obeypunctuation`, which can be `false` (the default) or `true`. If this parameter is `true`, `\affiliation` obeys the author's command. Thus

```
\affiliation[obeypunctuation=true]{%
  \institution{Fluginstitut}\\
  \streetaddress{Sonnenallee 17}\\
  \postcode{123456}
  \city{Helm},
  \country{Germany}}
```

will be typeset as

```
Fluginstitut
Sonnenallee 17
123456 Helm, Germany
```

Note that you should *not* use this option for journals.

It is expected that these commands are inserted by the author of the manuscript.

`\thanks` Like `amsart` (and unlike standard \LaTeX), we allow `\thanks` only *outside* of the commands `\title` and `\author`. This command is obsolete and should *not* be used in most cases. Do not list your acknowledgments or grant sponsors here. Put this information in the `acks` environment (see Section 2.13).

`\authorsaddresses` In some formats, addresses are printed as a footnote on the first page. By default \LaTeX typesets them itself using the information you give it. However, you can override its choice using the command `\authorsaddresses{<contact addresses>}`, for example,

```
\authorsaddresses{%
  Authors' addresses: G.~Zhou, Computer Science Department, College of
  William and Mary, 104 Jameson Rd, Williamsburg, PA 23185, US;
  V.~B'eranger, Inria Paris-Rocquencourt, Rocquencourt, France;
  A.~Patel, Rajiv Gandhi University, Rono-Hills, Doimukh, Arunachal
```

Pradesh, India; H.~Chan, Tsinghua University, 30 Shuangqing Rd,
Haidian Qu, Beijing Shi, China; T.~Yan, Eaton Innovation Center,
Prague, Czech Republic; T.~He, C.~Huang, J.~A.~Stankovic University
of Virginia, School of Engineering Charlottesville, VA 22903, USA;
T. F. Abdelzaher, (Current address) NASA Ames Research Center,
Moffett Field, California 94035.}

You can *suppress* printing authors' addresses by setting them to an empty string:
`\authorsaddresses{}`. Please note that authors' addresses are mandatory for journal
articles.

`\titlenote` While the command `\thanks` generates a note without a footnote mark, sometimes
`\subtitlenote` the authors might need notes more tightly connected to the title, subtitle or author. The
`\authornote` commands `\titlenote`, `\subtitlenote` and `\authornote` that follow the correspond-
ing commands (`\title`, `\subtitle` and `\author`) generate such notes. For example,

```
\title{This is a title}
\titlenote{This is a titlenote}
\author{A. U. Thor}
\authornote{This is an authornote}
```

Please never use a `\footnote` inside an `\author` or `\title` command since this con-
fuses the metadata extraction software. (Actually these commands now produce errors.)

`\authornotemark` Sometimes one may need to have the same footnote connected to several authors.
The command `\authornotemark[number]` adds just the footnote mark, for example,

```
\author{A. U. Thor}
\authornote{Both authors contributed equally to the paper}
...
\author{A. N. Other}
\authornotemark[1]
```

The correct numbering of these marks is the responsibility of the user.

`\acmVolume` The macros `\acmVolume`, `\acmNumber`, `\acmArticle`, `\acmYear` and `\acmMonth` are
`\acmNumber` inserted by the editor and set the journal volume, issue, article number, year and month
`\acmArticle` correspondingly. The arguments of all these commands, including `\acmMonth`, is numer-
`\acmYear` ical. For example,

```
\acmMonth
\acmVolume{9}
\acmNumber{4}
\acmArticle{39}
\acmYear{2010}
\acmMonth{3}
```

Note that `\acmArticle` is used not only for journals but also for some conference pro-
ceedings.

`\acmArticleSeq` The articles in the same issue of a journal have a *sequence number*. It is used to
vertically position the black blob on the first page of some formats. By default it is the
same as the article number, but the command `\acmArticleSeq{n}` can be used to
change it:

```
\acmArticle{39} % The sequence number will be 39 by default
```

`\acmArticleSeq{5}` % We redefine it to 5

Setting this number to zero suppresses the blob.

`\acmSubmissionID` If your paper got a Submission ID from the Conference Management System, put it here:

`\acmSubmissionID{123-A56-BU3}`

`\acmPrice` The macro `\acmPrice{<price>}` sets the price for the article, for example,

`\acmPrice{25.00}`

Note that you do not need to put the dollar sign here, just the amount. By default the price is \$15.00, unless the copyright is set to `usgov`, `rightsretained`, `iw3c2w3`, or `iw3c2w3g`, when it is suppressed. Note that to override the defaults you need to set the price *after* the `\setcopyright` command. Also, the command `\acmPrice{}` suppresses the printing of the price.

`\acmISBN` Book-like volumes have ISBN numbers attached to them. The macro `\acmISBN{<ISBN>}` sets it. Normally it is set by the typesetter, for example,

`\acmISBN{978-1-4503-3916-2}`

Setting it to the empty string, as `\acmISBN{}`, suppresses printing the ISBN.

`\acmDOI` The macro `\acmDOI{<DOI>}` sets the DOI of the article, for example,

`\acmDOI{10.1145/9999997.9999999}`

It is normally set by the typesetter. Setting it to the empty string, as `\acmDOI{}`, suppresses the DOI.

`\acmBadgeR` Some conference articles get special distinctions, for example, the artifact evaluation
`\acmBadgeL` for PPOPP 2016 (see <http://ctuning.org/ae/ppopp2016.html>). These articles display special badges supplied by the conference organizers. This class provides commands to add these badges: `\acmBadgeR[<url>]{<graphics>}` and `\acmBadgeL[<url>]{<graphics>}`. The first command puts the badge to the right of the title, and the second one—to the left. The arguments have the following meaning: `[<url>]`, if provided, sets the link to the badge authority in the screen version, while `{<graphics>}` sets the graphics file with the badge image. The file must be a cropped square, which is scaled to a standard size in the output. For example, if the badge image is `ae-logo.pdf`, the command is

`\acmBadgeR[http://ctuning.org/ae/ppopp2016.html]{ae-logo}`

`\startPage` The macro `\startPage{<page>}` sets the first page of the article in a journal or book. It is used by the typesetter.

`\terms` The command `\keywords{<keyword, keyword,...>}` sets keywords for the article.
`\keywords` They must be separated by commas, for example,

`\keywords{wireless sensor networks, media access control,
multi-channel, radio interference, time synchronization}`

CCSXML (*env.*) ACM publications are classified according to the ACM Computing Classification Scheme (CCS). CCS codes are used both in the typeset version of the publications *and* in the metadata in various databases. Therefore you need to provide both \TeX commands and XML metadata with the paper.

The tool at <http://dl.acm.org/ccs.cfm> can be used to generate CCS codes. After you select the topics, click on “Generate CCS codes” to get results like the following:

```
\begin{CCSXML}
<ccs2012>
  <concept>
    <concept_id>10010520.10010553.10010562</concept_id>
    <concept_desc>Computer systems organization~Embedded systems</concept_desc>
    <concept_significance>500</concept_significance>
  </concept>
  <concept>
    <concept_id>10010520.10010575.10010755</concept_id>
    <concept_desc>Computer systems organization~Redundancy</concept_desc>
    <concept_significance>300</concept_significance>
  </concept>
  <concept>
    <concept_id>10010520.10010553.10010554</concept_id>
    <concept_desc>Computer systems organization~Robotics</concept_desc>
    <concept_significance>100</concept_significance>
  </concept>
  <concept>
    <concept_id>10003033.10003083.10003095</concept_id>
    <concept_desc>Networks~Network reliability</concept_desc>
    <concept_significance>100</concept_significance>
  </concept>
</ccs2012>
\end{CCSXML}

\ccsdesc[500]{Computer systems organization~Embedded systems}
\ccsdesc[300]{Computer systems organization~Redundancy}
\ccsdesc{Computer systems organization~Robotics}
\ccsdesc[100]{Networks~Network reliability}
```

You just need to copy this code and paste it in your paper anywhere before `\maketitle`.

CCS Concepts and user-defined keywords are required for all articles over two pages in length, and are optional for one- and two-page articles (or abstracts).

`\setcopyright` There are several possibilities for the copyright of the papers published by the ACM: the authors may transfer the rights to the ACM, license them to the ACM, some or all authors might be employees of the US or Canadian governments, etc. Accordingly the command `\setcopyright{...}` is introduced. Its argument is the copyright status of the paper, for example, `\setcopyright{acmcopyright}`. The possible values for this command are listed in Table 3. This command must be placed in the preamble, before `\begin{document}`. Additional information about ACM copyright rules is discussed in Section ??.

`\setcctype` If Creative Commons license is used, the package by default chooses CC-BY 4.0 Attribution 4.0 International license. You can override this choice by the command `\setcctype[<version>]{<type>}`, where [*<version>*] can be either 3.0 or 4.0 (4.0 by de-

Table 3: Parameters for the `\setcopyright` command

Parameter	Meaning
<code>none</code>	The copyright and permission information is not typeset. (This is the option for some ACM conferences.)
<code>acmcopyright</code>	The authors transfer the copyright to the ACM (the “traditional” choice).
<code>acmlicensed</code>	The authors retain the copyright but license the publication rights to ACM.
<code>rightsretained</code>	The authors retain the copyright and publication rights to themselves or somebody else.
<code>usgov</code>	All the authors are employees of the US government.
<code>usgovmixed</code>	Some authors are employees of the US government.
<code>cagov</code>	All the authors are employees of the Canadian government.
<code>cagovmixed</code>	Some authors are employees of the Canadian government.
<code>licensedusgovmixed</code>	Some authors are employees of the US government, and the publication rights are licensed to ACM.
<code>licensedcagov</code>	All the authors are employees of the Canadian government, and the publication rights are licensed to ACM.
<code>licensedcagovmixed</code>	Some authors are employees of the Canadian government, and the publication rights are licensed to ACM.
<code>othergov</code>	Authors are employees of a government other than the US or Canada.
<code>licensedothergov</code>	Authors are employees of a government other than the US or Canada, and the publication rights are licensed to ACM.
<code>iw3c2w3</code>	Special statement for conferences organized by IW3C2.
<code>iw3c2w3g</code>	Special statement for conferences organized by IW3C2, when some authors are approved Google employees.
<code>cc</code>	Creative Commons license. If this key is set, <i>doclicense</i> images are used to typeset the license. See also <code>\setcctype</code> command. Note that at present this license can be used only for <code>acmengage</code> format or for <code>nonacm</code> publications.

fault), and `{\type}` can be one of zero, by, by-sa, by-nd, by-nc, by-nc-sa, by-nc-nd (see <https://creativecommons.org/licenses/> for the explanation). This command should be used in the preamble only.

Material published under Creative Commons license should include the corresponding icon. A modern T_EX distribution includes these icons in the package *doclicense*. In case your distribution does not have them, ACM provides a file `ccicons.zip` with these icons. Just unzip it in the same directory where your document is.

The ACM submission software should generate the right command for you to paste into your file.

`\copyrightyear` Each copyright statement must have the year of copyright. By default it is the same as `\acmYear`, but you can override this using the macro `\copyrightyear`, e.g.,

```
\acmYear{2016}
\copyrightyear{2015}
```

There is a special case for a personal copy that the authors may be allowed to generate for their use or a posting on a personal site (check the instructions for the specific journal or conference for the details). The document option `authorversion=true` produces a special form of the copyright statement for this case. Note that you still need the `\setcopyright` command and (optionally) `\copyrightyear` command to tell T_EX about the copyright owner and year. Also, you should be aware that due to the different sizes of the permission blocks for the printed version and authors' version, the page breaks might be different between them.

`abstract (env)` The environment `abstract` must *precede* the `\maketitle` command. Again, this is different from the standard L^AT_EX. Putting `abstract` after `\maketitle` will trigger an error.

`teaserfigure (env)` A special kind of figure is used for many two-column conference proceedings. This figure is placed just after the authors but before the main text. The environment `teaserfigure` is used for these figures. This environment must be used *before* `\maketitle`, for example,

```
\begin{teaserfigure}
\includegraphics[width=\textwidth]{sampleteaser}
\caption{This is a teaser}
\label{fig:teaser}
\end{teaserfigure}
```

`\settopmatter` Some information in the top matter is printed for certain journals or proceedings and suppressed for others. You can override these defaults using the command `\settopmatter{<settings>}`. The settings and their meanings are listed in Table 4. For example,

```
\settopmatter{printacmref=false, printccs=true, printfolios=true}
```

The parameter `authorsperrow` requires some explanation. In conference proceedings authors' information is typeset in boxes, several boxes per row (see `sample-sigconf.pdf`, `sample-sigplan.pdf`, etc.). The number of boxes per row is determined automatically. If you want to override this, you can do it using this parameter, for example,

```
\settopmatter{authorsperrow=4}
```

Table 4: Settings for the `\settopmatter` command

Parameter	Values	Meaning
<code>printccs</code>	true/false	Whether to print CCS categories
<code>printacmref</code>	true/false	Whether to print the ACM bibliographic entry
<code>printfolios</code>	true/false	Whether to print page numbers (folios)
<code>authorsperrow</code>	numeric	Number of authors per row for the title page in conference proceedings formats

However, in most cases you should *not* do this and should use the default settings. Setting `authorsperrow` to 0 will revert it to the default settings.

The parameter `printacmref` specifies whether to print the ACM bibliographic entry (default), or not. Note that this entry is required for all articles over one page in length, and is optional for one-page articles (abstracts).

`\received` The command `\received[<stage>]{<date>}` sets the history of the publication. The [*<stage>*] argument is optional; the default is Received for the first date and revised for the subsequent ones. For example,

```
\received{20 February 2007}
\received[revised]{12 March 2009}
\received[accepted]{5 June 2009}
```

`\maketitle` The macro `\maketitle` must be the last command in the top-matter group. That is it must follow the commands defined in this section.

`\shortauthors` After the command `\maketitle`, the macro `\shortauthors` stores the names of the authors for the running head. You can redefine it if the list of author's name is too long, e.g.,

```
\maketitle
\renewcommand{\shortauthors}{Zhou et al.}
```

2.4 Top matter of ACM Engage materials

ACM Engage materials resemble conference proceedings, but have some special features. First, as a rule, they are released under a Creative Commons license. By default CC-BY is used. However, if you want to use another variant of CC license, use `\setccctype` command, for example, `\setccctype{by-nc}`. Second, abstract is called *synopsis*. Third, there are special top matter items used for the materials, such as *Course*, *Resource Type*, *Programming Language*, *CS Topics*.

`\setengagemetadata` These items are set with the command `\setengagemetadata{<name>}{<value>}`, for example,

```
\setengagemetadata{Course}{CS1}
\setengagemetadata{Programming Language}{Python}
\setengagemetadata{Knowledge Unit}{Programming Concepts}
\setengagemetadata{CS Topics}{Functions, Data Types, Expressions,
Mathematical Reasoning}
```

Note that the type of Creative Commons license, if such license is used, is automatically added to the metadata.

2.5 ACM cover page

ACM cover pages are forms of extended abstracts that are added to journals at the late stage. Authors prepare them as separate .tex files using acmcp format. At present only JDS uses them, but in the future this may change.

There are several top matter commands specific for this format.

`\acmArticleType` There are five article types accepted by JDS: *Research* (the default), *Review*, *Discussion*, *Invited*, and *Position*. The command `\acmArticleType{<type>}` sets the article type, for example

```
\acmArticleType{Review}
```

`\acmCodeLink` The commands `\acmCodeDataLink{<link>}` and `\acmDataLink{<link>}` set the links
`\acmDataLink` to the data and code accompanying the paper, for example,

```
\acmCodeLink{https://github.com/repository/code}  
\acmDataLink{https://datadryad.org/stash/dataset/doi:DOI}
```

You may repeat these commands if you have several repositories.

ACM cover page should have the following obligatory sections:

- Problem statement,
- Methods,
- Results,
- Significance.

Sometimes the addresses extracted from the authors' data are too long to fit on the page. In this case the command `\authorsaddresses` can be use to override them, for example,

```
\authorsaddresses{Corresponding author: Ben Trovato,  
\href{mailto:trovato@corporation.com}{trovato@corporation.com};  
Institute for Clarity in Documentation, P.O. Box 1212, Dublin,  
Ohio, USA, 43017-6221}
```

2.6 Internationalization

ACM accepts publications in languages other than English, as well as papers in English with translations of titles, subtitles, keywords and abstracts into other languages. Papers in languages other than English usually have titles, subtitles (if applicable), keywords and abstracts in English. Note that CCS concepts are always typeset in English.

To submit these papers you need to set the option language in the `\documentclass` command. This option can be repeated, for example,

```
\documentclass[sigconf, language=french, language=english]{acmart}
```

The last language in the list is the main language of the paper, i.e. the one for the main title, abstract, body, etc. The other languages are *secondary*, and used for translated titles, keywords, abstracts. Thus the paper above is written in English, and has a secondary abstract and a secondary title in French. On the other hand, a paper in French with secondary titles and abstracts in English and German should use, for example

```
\documentclass[sigconf,
               language=german,
               language=english,
               language=french]{acmart}
```

This key can use any language defined in *babel* package [3] (currently the package is tested with English, French, German and Spanish languages; other languages may require a translation of `\keywordsname` macro). Actually *acmart* loads *babel* internally, so you can use the facilities provided by this package.

If this key is set, you have access to several additional top matter commands.

`\translatedtitle` The commands `\translatedtitle{<language>}title`, `\translatedsubtitle{<language>}subtitle`
`\translatedsubtitle` and `\translatedkeywordlanguagekeywords` are used to set title, subtitle and key-
`\translatedkeywords` words in the secondary language. For example, a paper in English with French title and abstract may set

```
\title{A note on computational complexity}
\translatedtitle{french}{Remarque sur la complexit e de calcul}
```

while a paper in French should set

```
\title{Remarque sur la complexit e de calcul}
\translatedtitle{english}{A note on computational complexity}
```

`translatedabstract (env)` Similarly, `translatedabstract` environment has a mandatory language argument, for example,

```
\begin{translatedabstract}{english}
  This is the English version of the abstract
\end{translatedabstract}
```

You can repeat these commands if a paper has more than one secondary language.

Use the standard commands (`\title`, `\subtitle`, `\keywords`, `abstract`) for the main language of the paper.

2.7 Algorithms

There are now several good packages for typesetting algorithms [4, 5, 6], and the authors are free to choose their favorite one.

2.8 Figures and tables

The new ACM styles use the standard L^AT_EX interface for figures and tables. There are some important items to be aware of, however.

1. The captions for figures must be entered *after* the figure bodies and for tables *before* the table bodies.
2. The ACM uses the standard types for figures and tables and adds several new ones. In total there are the following types:

figure, table: a standard figure or table taking a full text width in one-column formats and one column width in two-column formats.

figure*, table* in two-column formats, a special figure or table taking a full text width.

teaserfigure: a special figure before `\maketitle`.

3. Accordingly, when scaling images, one should use the following sizes:
 - (a) For `teaserfigure`, `figure` in one-column mode or `figure*` in two-column mode, use `\textwidth`. In one-column mode, you can also use `\columnwidth`, which coincides with `\textwidth` in this case.
 - (b) For `figure` in two-column mode, use `\columnwidth`.

It is strongly recommended to use the package `booktabs` [7] and follow its main principles of typography with respect to tables:

1. Never, ever use vertical rules.
2. Never use double rules.

It is also a good idea not to overuse horizontal rules.

For table *footnotes* you have several options described in the TeX FAQ [1]. The simplest one is to use a `\minipage` environment:

```
\begin{table}
\caption{Simulation Configuration}
\label{tab:conf}
\begin{minipage}{\columnwidth}
\begin{center}
\begin{tabular}{ll}
\toprule
TERRAIN\footnote{This is a table footnote. This is a
table footnote. This is a table footnote.} &
(200\,m$\times$200\,m) Square\\
Node Number & 289\\
Node Placement & Uniform\\
Application & Many-to-Many/Gossip CBR Streams\\
Payload Size & 32 bytes\\
Routing Layer & GF\\
MAC Layer & CSMA/MMSN\\
Radio Layer & RADIO-ACCNOISE\\
Radio Bandwidth & 250Kbps\\
Radio Range & 20m--45m\\
\bottomrule
\end{tabular}
\end{center}
\bigskip
\footnotesize\emph{Source:} This is a table
```

```
sourcenote. This is a table sourcenote. This is a table
sourcenote.
```

```
\emph{Note:} This is a table footnote.
\end{minipage}
\end{table}
```

Tables and figures are by default centered. However, in some cases (for example, when you use several subimages per figure) you may need to override this. A good way to do so is to put the contents into a `\minipage` of the width `\columnwidth`.

2.9 Descriptions of images

`\Description` Some readers of ACM publications might be visually challenged. These readers might use a voice-over software to read aloud the papers. It is important to provide them a description of each image used in the paper.

The command `\Description[<short description>]{<long description>}` should be placed inside every figure, `teaserfigure` or `marginfigure` environment to provide a description of the image(s) used in the figure. Unlike `\caption`, which is used alongside the image, `\Description` is intended to be used instead of the image, for example,

```
\begin{figure}
\centering
\includegraphics{voltage}
\Description{A bell-like histogram centered at  $0.5V$  with most
measurements between  $0.2V$  and  $0.8V$ }
\caption{Histogram of the measurements of voltage}
\label{fig:voltage}
\end{figure}
```

At present the lack of descriptions generates a warning at compilation.

2.10 Theorems

The ACM classes define two theorem styles and several pre-defined theorem environments:

acmplain: this is the style used for theorem, conjecture, proposition, lemma and corollary, and

acmdefinition: this is the style used for example and definition.

These environments are defined by default. In the unusual circumstance that a user does not wish to have these environments defined, the option `acmthm=false` in the preamble will suppress them.

Sometimes authors want to define new theorem-like constructs that use theorem counters. These constructs must be defined either after `\begin{document}`, or delayed using `\AtEndPreamble` macro, for example,

```
\AtEndPreamble{%
\theoremstyle{acmdefinition}
\newtheorem{remark}[theorem]{Remark}}
```

2.11 Online-only and offline-only material

`printonly` (*env.*) Some supplementary material in ACM publications is put online but not in the printed version. The text inside the environment `screenonly` will be typeset only when the option `screen` (see Section 2.2) is set to true. Conversely, the text inside the environment `printonly` is typeset only when this option is set to false. For example,

```
\section{Supplementary materials}

\begin{printonly}
  Supplementary materials are available in the online version of this paper.
\end{printonly}

\begin{screenonly}
  (The actual supplementary materials.)
\end{screenonly}
```

We use the `comment` package for typesetting this code, so `\begin` and `\end` should start on a line of their own with no leading or trailing spaces.

2.12 Note about anonymous mode

`anonsuppress` (*env.*) When the option `anonymous` is selected, \TeX suppresses author information (including the number of authors) for a blind review. However, sometimes the information identifying the authors may be present in the body of the paper. For example,

```
\begin{anonsuppress}
  This is the continuation of the previous work by the author
  \cite{prev1, prev2}.
\end{anonsuppress}
```

As for the `printonly` and `screenonly` environments, `\begin{anonsuppress}` and `\end{anonsuppress}` should start on a line of their own with no leading or trailing spaces.

`\anon` To suppress short snippets of information, use the command `\anon[<substitute>]{<suppressed-text>}`. By default [*<substitute>*] is the word ANONYMOUS. Examples:

```
This work was performed at \anon{NSA}.
This work was performed at \anon[No Such Agency]{NSA}.
```

2.13 Acknowledgments

The traditional “Acknowledgments” section is conventionally used to thank persons and granting agencies for their help and support. However, there are several important considerations about this section.

First, in anonymous mode this section must be omitted: it gives too much information to reviewers. Second, data about grants is extracted and stored separately by the postprocessing software. ACM classes provide facilities for both these tasks.

`acks` (*env.*) The environment `acks` starts an unnumbered section “Acknowledgments” unless the anonymous mode is chosen. Put all thanks inside this environment.

As for the `printonly` and `screenonly` environments, `\begin{acks}` and `\end{acks}` should start on a line of their own with no leading or trailing spaces.

`\grantsponsor` All financial support *must* be listed using the commands `\grantsponsor` and `\grantnum`. These commands tell the postprocessing software about the granting organization and grant. The format of these commands is the following:

```
\grantsponsor{\sponsorID}{\name}{\url}
\grantnum[\url]{\sponsorID}{\number}.
```

Here `{\sponsorID}` is the unique ID used to match grants to sponsors, `{\name}` is the name of the sponsor, `{\url}` is its URL, and `{\number}` is the grant number. The `{\sponsorID}` of the `\grantnum` command must correspond to the `{\sponsorID}` of a `\grantsponsor` command. Some awards have their own web pages, which you can include using the optional argument of the `\grantnum` command.

At present `{\sponsorID}` is chosen by the authors and can be an arbitrary key in the same way the label of a `\cite` is arbitrarily chosen. There might be a change to this policy if the ACM decides to create a global database of sponsoring organizations.

Example:

```
\begin{acks}
The authors would like to thank Dr. Yuhua Li for providing the
matlab code of the \textit{BEPS} method.

The authors would also like to thank the anonymous referees for
their valuable comments and helpful suggestions. This work is
supported by the \grantsponsor{GS501100001809}{National Natural
Science Foundation of
China}{https://doi.org/10.13039/501100001809} under Grant
No.: ~\grantnum{GS501100001809}{61273304}
and ~\grantnum[http://www.nnsf.cn/youngscientists]{GS501100001809}{Young
Scientists' Support Program}.
\end{acks}
```

2.14 Bibliography

The ACM lets you use either Bib_{TeX} or Bib_{LaTeX} to process your references: they require slightly different setup of your _{TeX} file, as detailed in the following subsections.

2.14.1 Processing using Bib_{TeX}

This uses the `natbib` package for formatting references and the Bib_{TeX} style file `ACM-Reference-Format.bst` for Bib_{TeX} processing. You can disable loading of `natbib` using the option `natbib=false` in `\documentclass`. However, it is not recommended, as well as the use of Bib_{TeX} styles other than `ACM-Reference-Format.bst`, and may delay the processing of the manuscript.

`\citestyle` If you use `natbib`, you can select one of two predefined citation styles using the command `\citestyle`: the author-year format `acmauthoryear` or the numeric format `acmnumeric`. For example,

```
\citestyle{acmauthoryear}
```

Note that numeric citations are the default mode for most formats.

`\setcitestyle` You can further customize natbib using the `\setcitestyle` command, for example,
`\setcitestyle{numbers,sort&compress}`

One of the more common versions is

`\setcitestyle{nosort}`

It is useful if you do not like the way natbib sorts citation lists.

If you use natbib, then commands like `\citep` and `\citeauthor` are automatically supported. The command `\shortcite` is the same as `\cite` in numerical mode and cites the year in author-date mode.

Note that before version 1.48 the command `\citeyear` put the year in parentheses. In version 1.48 and later it produces just the year; the command `\citeyearpar` can be used to emulate its old behavior.

There are several customized B_BT_EX entry types and fields in the ACM style file `ACM-Reference-Format.bst` that you may want to be aware of.

The style supports the fields `doi` and `url`, for example,

```
doi = "10.1145/1188913.1188915",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.pdf",
```

Normally the printing of URL is suppressed if DOI is present. However, there is a special field `distinctURL`. If it is present and is not zero, URL is printed even if DOI is present.

The style supports the arXiv-recommended fields `eprint` and (optionally) `primaryclass`, for example,

```
eprint = "960935712",
primaryclass = "cs",
```

See the examples at <https://arxiv.org/help/hypertex/bibstyles>.

There are several special entry types. Types `online` and `game` are used for Web pages and games, for example,

```
@online{Thornburg01,
  author = "Harry Thornburg",
  year = "2001",
  title = "Introduction to Bayesian Statistics",
  url = "http://ccrma.stanford.edu/~jos/bayes/bayes.html",
  month = mar,
  lastaccessed = "March 2, 2005",
}
```

Entry types `artifactsoftware`, `artifactdataset` (with synonyms `software` and `dataset`) can be used to cite software artifacts and datasets, for example,

```
@ArtifactSoftware{R,
  title = {R: A Language and Environment for Statistical Computing},
  author = {{R Core Team}},
  organization = {R Foundation for Statistical Computing},
```

```

        address = {Vienna, Austria},
        year = {2019},
        url = {https://www.R-project.org/},
    }
    @ArtifactDataset{UMassCitations,
        author = {Sam Anzaroot and Andrew McCallum},
        title = {{UMass} Citation Field Extraction Dataset},
        year = 2013,
        url =
            {http://www.iesl.cs.umass.edu/data/data-umasscitationfield},
        lastaccessed = {May 27, 2019}
    }

```

For these entry types you can use the `lastaccessed` field to add the access date for the URL.

There are two ways to enter video or audio sources in the bibliography corresponding to two different possibilities. For standalone sources available online, you can use an online entry and set its `howpublished` field. For example,

```

@online{Obama08,
    author = "Barack Obama",
    year = "2008",
    title = "A more perfect union",
    howpublished = "Video",
    day = "5",
    url = "http://video.google.com/videoplay?docid=6528042696351994555",
    month = mar,
    lastaccessed = "March 21, 2008",
}

```

For sources available as attachments to conference proceedings and similar documents, you can use the usual `inproceedings` entry type and set its `howpublished` field:

```

@Inproceedings{Novak03,
    author = "Dave Novak",
    title = "Solder man",
    booktitle = "ACM SIGGRAPH 2003 Video Review on Animation theater Program",
    year = "2003",
    publisher = "ACM Press",
    address = "New York, NY",
    pages = "4",
    month = "March 21, 2008",
    doi = "10.9999/woot07-S422",
    howpublished = "Video",
}

```

Sometimes you need to cite a complete issue of a journal. The periodical entry type is intended for this:

```

@periodical{JCohen96,
    key = "Cohen",
    editor = "Jacques Cohen",
}

```

```

title =      "Special issue: Digital Libraries",
journal =    "Communications of the {ACM}",
volume =     "39",
number =     "11",
month =      nov,
year =       "1996",
}

```

If you do not know the year of publication, the style will add “[n. d.]” (for “no date”) to the entry.

If you do not know the author (this is often the case for online entries), use the key field to add a key for sorting and citations, for example,

```

@online{TUGInstmem,
  key =      {TUG},
  year =     2017,
  title =    "Institutional members of the {\TeX} Users Group",
  url =      "http://wwtug.org/instmem.html",
  lastaccessed = "May 27, 2017",
}

```

A note about sorting. The current ACM bibliography styles always sort the entries according to authors names and publication year. There is a controversy about sorting names with “von” or “van” part: should Ludwig van Beethoven be sorted under “V” or under “B”? The American practice is to use “van” in sorting, i.e. to file van Beethoven under “V”. However, some authorities recommend to sort Dutch persons according to their last names (see e.g. <https://www.ifla.org/files/assets/cataloguing/pubs/names-of-persons.1996.pdf>). While I do not want to take a part in this dispute, I would like to point to the old “noopsort” trick by Oren Patashnik. Add to the .bib file the line

```
@PREAMBLE{"\providecommand{\noopsort}[1]{}}

```

and then encode the author as

```
author = {Ludwig {\noopsort{Beethoven}}van Beethoven},

```

This will make the author to be sorted as “Beethoven” rather than “van Beethoven”.

The current bst style defines a number of macros for common journal names. In particular, all journals listed in Table 5 are included, so you can use strings like `journal = taccess` for *ACM Transactions on Accessible Computing*.

2.14.2 Processing using Bib_{La}T_EX

You will find in this package two sets of style files for Bib_{La}T_EX, `acmnumeric` and `acmauthoryear`, that mimic the behaviour of the `ACM-Reference-Format.bst` Bib_TE_X style. They provide you access to all the power of Bib_{La}T_EX and already include support for advanced citation of software artefact from the `biblatex-software` package, also separately available on CTAN. Look at the `biblatex-software` documentation to learn more about what it offers.

There are a few key differences in how the \LaTeX sources are set up when using Bib \LaTeX instead of Bib \TeX , that we summarize briefly here (please refer to the official Bib \LaTeX documentation for more details).

In the preamble of your document you need to load the Bib \LaTeX package and select the appropriate bibliography style, as follows

```
\RequirePackage[
  datamodel=acmdatamodel,
  style=acmnumeric, % use style=acmauthoryear for publications that require it
]{biblatex}
```

Also in the preamble, you need to declare the bibliography sources files using the `\addbibresource` directive (one `\addbibresource` command per source file), e.g.:

```
\addbibresource{software.bib}
\addbibresource{sample-base.bib}
```

At the end of the document, where you want the bibliography to appear, you need to place the command `\printbibliography`.

Look at the `sample-*-biblatex.tex` files that can be found in the samples directory after running `make` for templates showcasing these Bib \LaTeX styles.

2.15 Colors

While printed ACM publications are usually black and white, screen mode allows the use of colors. The ACM classes pre-define several colors according to [8]: `ACMBlue`, `ACMYellow`, `ACMOrange`, `ACMRed`, `ACMLightBlue`, `ACMGreen`, `ACMPurple` and `ACMDarkBlue`. You can use them in color assignments.

The ACM provides the following recommendation on color use.

The most accessible approach would be to ensure that your article is still readable when printed in greyscale. The most notable reasons for this are:

1. The most common type of inherited Color Vision Deficiency (CVD) is red-green (in which similar-brightness colors that differ only in their amounts of red or green are often confused), and it affects up to 8% of males and 0.5% of females of Northern European descent.
2. The most common type of acquired Color Vision Deficiency (CVD) is blue-yellow (including mild cases for many older adults).
3. Most printing is in black and white.
4. Situational impairments (e.g., bright sunlight shining on a mobile screen) tend to reduce the entire color gamut, reducing color discriminability.

Note: It is *not* safe to encode information using only variations in color (i.e., only differences in hue and/or saturation) as there is bound to be someone affected!

To ensure that you are using the most accessible colors, the ACM recommends that you choose sets of colors to help ensure suitable variations in when printed in greyscale by using either of the following tools:

1. ColourBrewer: <http://colorbrewer2.org/>
2. ACE: The Accessible Colour Evaluator: <http://daprlab.com/ace/> for designing WCAG 2.0 compliant palettes.

2.16 Other notable packages and typographic remarks

Several other packages are recommended for specialized tasks.

The package `subcaption` [9] is recommended for complex figures with several subplots or subfigures that require separate subcaptioning. The packages `nomencl` [10] and `glossaries` [11] can be used for the automatic creation of the lists of symbols and concepts used.

By default `acmart` prevents all widows and orphans (i.e., lonely lines at the beginning or end of the page) and hyphenation at the end of the page. This is done by the rather strict settings

```
\widowpenalty=10000
\clubpenalty=10000
\brokenpenalty=10000
```

However, this may lead to frustrating results when the authors must obey a page limit. Setting these penalties to smaller values may help if you absolutely need to.

Another problem might be the too strict line breaking rules. Again, a strategically placed `\sloppy` command or putting the problematic paragraph inside `sloppypar` environment might help—but beware, the results might be, well, sloppy.

Note that the uppercasing in section titles is done using the `textcase` package [12], so the command `\NoCaseChange` inside the title may help to prevent extraneous uppercasing.

2.17 Counting words

Some ACM conferences use word count limits for papers. The calculation of word number for a paper with math, tables and figures is not a trivial task. Currently the authoritative word count is done by translating the PDF to text and using `wc -w` on the output. Authors can use the package `texcount` (used by Overleaf) to get an estimate of the word count. To facilitate this one adds to the beginning of the package metacomments

```
%TC:macro \cite [option:text,text]
%TC:macro \citep [option:text,text]
%TC:macro \citet [option:text,text]
%TC:envir table 0 1
%TC:envir table* 0 1
%TC:envir tabular [ignore] word
%TC:envir displaymath 0 word
%TC:envir math 0 word
%TC:envir comment 0 0
```

and uses `\begin{math}...\end{math}` instead of dollar signs for math. Note that the count is in any case approximate, and the final decision of editors is based on PDF count.

The script `texcount` provides a report of word count in the document.

2.18 Creative Commons licenses for ACM publications

At present ACM does not allow the authors to typeset Creative Commons license for most ACM publications. These licenses can be used under an agreement with the ACM publishing office. In this case they are inserted by ACM itself.

The exceptions are ACM Engage format, which allows Creative Commons license, and conferences organized and copyrighted by IW3C2. In these cases the authors should use correspondingly `\setcopyright{cc}`, `\setcopyright{iw3c2w3}`, or `\setcopyright{iw3c2w3g}` (the latter should be used by Google employees).

Yet another case is the typesetting of non-ACM materials, when the option `nonacm` is used. This case is somewhat opposite, because for this case *only* Creative Commons licenses are supported.

The command `\setcopyright{cc}` produces an error unless the format is `acmengage` or `nonacm` option is selected. On the other hand, if the option `nonacm` is selected, any argument of `\setcopyright` other than `cc` is treated as `none`.

2.19 Disabled or forbidden commands

The goal of `acmart` package is to provide a uniform look and feel for ACM publications. Accordingly, a number of commands is forbidden or disabled in `acmart`.

You may *not* put several authors or several e-mails into a `\author` or `\email` command. This may lead to errors or warning.

You cannot change `\baselinestretch` in your document: this produces an error.

You should not abuse the command `\vspace`: this command may disturb the typesetting of ACM papers.

You should not load `amssymb` package since the package `acmart` defines the corresponding symbols itself.

2.20 Notes for wizards

Sometimes you need to change the behavior of `acmart`. The usual way to do this is to redefine commands in the preamble. However, these definitions are executed *after* `acmart` is loaded and certain decisions are made. This presents a number of problems.

For example, one may want to use the `titletoc` package with `acmart`. This package should be loaded before `hyperref`. However, since `acmart` loads `hyperref` itself, the line `\usepackage{titletoc}` in the preamble will lead to grief (see <http://tex.stackexchange.com/questions/357265/using-titletoc-with-acm-acmart-style>).

Another example is passing options to a package. Suppose you want to use the `dvipsnames` option of the `xcolor` package. Normally you cannot do this because `acmart` loads this package itself without options.

The file `acmart-preload-hook.tex` can be used to solve these problems. If this file exists, it will be processed before any other package. You can use this file to load packages or pass options to them. For example, if you put in this file

```
\let\LoadClassOrig\LoadClass
\renewcommand\LoadClass[2][\LoadClassOrig[#1]{#2}%
\usepackage{titletoc}}
```

then `titletoc` will be loaded before `hyperref`. If you put in this file

```
\PassOptionsToPackage{dvipsnames}{xcolor}
```

you will pass `dvipsnames` to `xcolor`.

Important note. This hook makes it too easy to create a manuscript that is not acceptable by the ACM. It is even easier to create a file that cannot be compiled. So

please do not use it *unless you know what you are doing*. And if you use it, *do not ask for support*. If you decide to use this hook, you are on your own.

`\AtBeginMaketitle` Another hook is `\AtBeginMaketitle`. The commands in this hook are executed before `\maketitle`, for example,

```
\AtBeginMaketitle{\acmPrice{125.00}}
```

2.21 Currently supported publications

Table 5: ACM publications and arguments of the `\acmJournal` command

Abbreviation	Publication
CIE	ACM Computers in Entertainment
CSUR	ACM Computing Surveys
DLT	Distributed Ledger Technologies: Research and Practice
DGOV	Digital Government: Research and Practice
DTRAP	Digital Threats: Research and Practice
FAC	Formal Aspects of Computing
GAMES	ACM Games: Research and Practice
HEALTH	ACM Transactions on Computing for Healthcare
IMWUT	PACM on Interactive, Mobile, Wearable and Ubiquitous Technologies
JACM	Journal of the ACM
JDIQ	ACM Journal of Data and Information Quality
JDS	ACM/IMS Journal of Data Science
JEA	ACM Journal of Experimental Algorithmics
JERIC	ACM Journal of Educational Resources in Computing
JETC	ACM Journal on Emerging Technologies in Computing Systems
JOCCH	ACM Journal on Computing and Cultural Heritage
JRC	ACM Journal on Responsible Computing
PACMCGIT	Proceedings of the ACM on Computer Graphics and Interactive Techniques
PACMHCI	PACM on Human-Computer Interaction
PACMPL	PACM on Programming Languages
POMACS	PACM on Measurement and Analysis of Computing Systems
TAAS	ACM Transactions on Autonomous and Adaptive Systems
TACCESS	ACM Transactions on Accessible Computing
TACO	ACM Transactions on Architecture and Code Optimization
TALG	ACM Transactions on Algorithms
TALLIP	ACM Transactions on Asian and Low-Resource Language Information Processing
TAP	ACM Transactions on Applied Perception
TCPS	ACM Transactions on Cyber-Physical Systems
TDS	ACM/IMS Transactions on Data Science
TEAC	ACM Transactions on Economics and Computation
TECS	ACM Transactions on Embedded Computing Systems
TELO	ACM Transactions on Evolutionary Learning
THRI	ACM Transactions on Human-Robot Interaction

Table 5: ACM publications and arguments of the \acmJournal command (continued)

Abbreviation	Publication
TIIS	ACM Transactions on Interactive Intelligent Systems
TIOT	ACM Transactions on Internet of Things
TISSEC	ACM Transactions on Information and System Security
TIST	ACM Transactions on Intelligent Systems and Technology
TKDD	ACM Transactions on Knowledge Discovery from Data
TMIS	ACM Transactions on Management Information Systems
TOCE	ACM Transactions on Computing Education
TOCHI	ACM Transactions on Computer-Human Interaction
TOCL	ACM Transactions on Computational Logic
TOCS	ACM Transactions on Computer Systems
TOCT	ACM Transactions on Computation Theory
TODAES	ACM Transactions on Design Automation of Electronic Systems
TODS	ACM Transactions on Database Systems
TOG	ACM Transactions on Graphics
TOIS	ACM Transactions on Information Systems
TOIT	ACM Transactions on Internet Technology
TOMACS	ACM Transactions on Modeling and Computer Simulation
TOMM	ACM Transactions on Multimedia Computing, Communications and Applications
TOMPECS	ACM Transactions on Modeling and Performance Evaluation of Computing Systems
TOMS	ACM Transactions on Mathematical Software
TOPC	ACM Transactions on Parallel Computing
TOPLAS	ACM Transactions on Programming Languages and Systems
TOPS	ACM Transactions on Privacy and Security
TOS	ACM Transactions on Storage
TOSEM	ACM Transactions on Software Engineering and Methodology
TOSN	ACM Transactions on Sensor Networks
TQC	ACM Transactions on Quantum Computing
TRETS	ACM Transactions on Reconfigurable Technology and Systems
TSAS	ACM Transactions on Spatial Algorithms and Systems
TSC	ACM Transactions on Social Computing
TSLP	ACM Transactions on Speech and Language Processing
TWEB	ACM Transactions on the Web

Besides the publications listed in Table 5, there is a special “publication” type FACMP, a forthcoming ACM publication, reserved for new journals which are not assigned an ISSN yet.

2.22 A note about sigchi-a format

Starting in Spring 2020 ACM retired SIGCHI Extended Abstract format (sigchi-a). ACM will not, under any circumstances, accept documents in this format for publication and will not offer technical support to the authors who use this template.

You may use this format in the nonacm mode only, as in

```
\documentclass[sigchi-a, nonacm]{acmart}
```

`sidebar` (*env.*) This format has large margin uses for special figures and tables. This package provides three environments for this with optional captions:
`marginfigure` (*env.*)
`marginfigure` (*env.*)

sidebar: textual information in the margin,

marginfigure: a figure in the margin,

marginfigure: a table in the margin.

The environments `figure` and `table` produce figures and tables with the width of the text column. The environments `figure*` and `table*` produce “wide” figures and tables, which take a large part of the margin.

The horizontal sizes of figures are:

1. `figure`: `\columnwidth`,
2. `marginfigure`: `\marginparwidth`,
3. `figure*`: `\fulltextwidth`.

3 Implementation

3.1 Identification

We start with a declaration of who we are. Most .dtx files put driver code in a separate .drv driver file. We roll this code into the main file and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{acmart.dtx}
4 </gobble>
5 <class>\ProvidesClass{acmart}
6 [2022/08/27 v1.87 Typesetting articles for the Association for Computing Machinery]
```

And the driver code:

```
7 <*gobble>
8 \documentclass{ltxdoc}
9 \usepackage{array,booktabs,amsmath,graphicx,fancyvrb,tabularx, longtable}
10 \usepackage[tt=false, type1=true]{libertine}
11 \usepackage[varqu]{zi4}
12 \usepackage[libertine]{newtxmath}
13 \usepackage[tableposition=top]{caption}
14 \usepackage{hypdoc}
15 \PageIndex
16 \CodelineIndex
17 \RecordChanges
18 \EnableCrossrefs
19 \begin{document}
20   \DocInput{acmart.dtx}
21 \end{document}
22 </gobble>
23 <*class>
24 \def\@classname{acmart}
```

3.2 Preload hook

We preload acmart-preload-hook:

```
25 \InputIfFileExists{acmart-preload-hook.tex}{%
26   \ClassWarning{\@classname}{%
27     I am loading acmart-preload-hook.tex. You are fully responsible
28     for any problems from now on.}}{}
```

3.3 Options

We need xkeyval since some of our options may have values:

```
29 \RequirePackage{xkeyval}
   We use xstring to check whether user input is valid
30 \RequirePackage{xstring}
   We need iftex to check the engine
31 \RequirePackage{iftex}
```

format The possible formats

```
32 \define@choicekey*+{acmart.cls}{format}[\ACM@format\ACM@format@nr]{%
33 manuscript, acmsmall, acmlarge, acmtog, sigconf, siggraph,
34 sigplan, sigchi, sigchi-a, acmengage, acmcp}[manuscript]{}{%
35 \ClassError{\@classname}{The option format must be manuscript,
36 acmsmall, acmlarge, acmtog, sigconf, siggraph,
37 sigplan, sigchi or sigchi-a}}
38 \def\@DeclareACMFormat#1{\DeclareOptionX{#1}{\setkeys{acmart.cls}{format=#1}}}
39 \@DeclareACMFormat{manuscript}
40 \@DeclareACMFormat{acmsmall}
41 \@DeclareACMFormat{acmlarge}
42 \@DeclareACMFormat{acmtog}
43 \@DeclareACMFormat{sigconf}
44 \@DeclareACMFormat{siggraph}
45 \@DeclareACMFormat{sigplan}
46 \@DeclareACMFormat{sigchi}
47 \@DeclareACMFormat{sigchi-a}
48 \@DeclareACMFormat{acmengage}
49 \@DeclareACMFormat{acmcp}
50 \ExecuteOptionsX{format}
```

\if@ACM@screen Whether we use screen mode

```
51 \define@boolkey+{acmart.cls}[@ACM@]{screen}[true]{%
52 \if@ACM@screen
53 \PackageInfo{\@classname}{Using screen mode}%
54 \else
55 \PackageInfo{\@classname}{Not using screen mode}%
56 \fi}{\PackageError{\@classname}{The option screen can be either true or
57 false}}
58 \ExecuteOptionsX{screen=false}
```

\if@ACM@urlbreakonhyphens

```
59 \define@boolkey+{acmart.cls}[@ACM@]{urlbreakonhyphens}[true]{%
60 \if@ACM@urlbreakonhyphens
61 \PackageInfo{\@classname}{Using breaking urls on hyphens}%
62 \else
63 \PackageInfo{\@classname}{Not breaking urls on hyphens}%
64 \fi}{\PackageError{\@classname}{The option urlbreakonhyphens can be either true or
65 false}}
66 \ExecuteOptionsX{urlbreakonhyphens=true}
```

\if@ACM@acmthm Whether we define theorem-like environments.

```
67 \define@boolkey+{acmart.cls}[@ACM@]{acmthm}[true]{%
68 \if@ACM@acmthm
69 \PackageInfo{\@classname}{Requiring acmthm}%
70 \else
71 \PackageInfo{\@classname}{Suppressing acmthm}%
72 \fi}{\PackageError{\@classname}{The option acmthm can be either true or
73 false}}
74 \ExecuteOptionsX{acmthm=true}
```

\if@ACM@review Whether we use review mode

```
75 \define@boolkey+{acmart.cls}[@ACM@]{review}[true]{%
```

```

76 \if@ACM@review
77   \PackageInfo{\@classname}{Using review mode}%
78   \AtBeginDocument{\@ACM@printfoliostrue}%
79 \else
80   \PackageInfo{\@classname}{Not using review mode}%
81 \fi}{\PackageError{\@classname}{The option review can be either true or
82   false}}
83 \ExecuteOptionsX{review=false}

```

\if@ACM@authorversion Whether we use author's-version mode

```

84 \define@boolkey+{acmart.cls}[@ACM@]{authorversion}[true]{%
85   \if@ACM@authorversion
86     \PackageInfo{\@classname}{Using authorversion mode}%
87   \else
88     \PackageInfo{\@classname}{Not using authorversion mode}%
89   \fi}{\PackageError{\@classname}{The option authorversion can be either true or
90     false}}
91 \ExecuteOptionsX{authorversion=false}

```

\if@ACM@nonacm Special option for non-ACM publications using the ACM typesetting options.

```

92 \define@boolkey+{acmart.cls}[@ACM@]{nonacm}[true]{%
93   \if@ACM@nonacm
94     \PackageInfo{\@classname}{Using nonacm mode}%
95     \AtBeginDocument{\@ACM@printacmreffalse}%
96     % in 'nonacm' mode we disable the "ACM Reference Format"
97     % printing by default, but this can be re-enabled by the
98     % user using \settopmatter{printacmref=true}
99   \else
100     \PackageInfo{\@classname}{Not using nonacm mode}%
101   \fi}{\PackageError{\@classname}{The option nonacm can be either true or
102     false}}
103 \ExecuteOptionsX{nonacm=false}

```

\if@ACM@balance Whether to balance the last page

```

104 \define@boolkey+{acmart.cls}[@ACM@]{balance}[true]{%}{%
105   \PackageError{\@classname}{The option balance can be either true or
106     false}}
107 \ExecuteOptionsX{balance}

```

\if@ACM@pbalance Whether to balance the last page

```

108 \define@boolkey+{acmart.cls}[@ACM@]{pbalance}[true]{%}{%
109   \PackageError{\@classname}{The option pbalance can be either true or
110     false}}
111 \ExecuteOptionsX{pbalance=false}

```

\if@ACM@natbib@override This macro is no longer used.

\if@ACM@natbib Whether we use natbib mode

```

112 \define@boolkey+{acmart.cls}[@ACM@]{natbib}[true]{%
113   \if@ACM@natbib
114     \PackageInfo{\@classname}{Explicitly selecting natbib mode}%
115   \else
116     \PackageInfo{\@classname}{Explicitly deselecting natbib mode}%
117   \fi}{\PackageError{\@classname}{The option natbib can be either true or

```

```

118     false}}
119 \ExecuteOptionsX{natbib=true}

\if@ACM@anonymous Whether we use anonymous mode
120 \define@boolkey+{acmart.cls}[@ACM@]{anonymous}[true]{%
121   \if@ACM@anonymous
122     \PackageInfo{\@classname}{Using anonymous mode}%
123   \else
124     \PackageInfo{\@classname}{Not using anonymous mode}%
125   \fi}{\PackageError{\@classname}{The option anonymous can be either true or
126     false}}
127 \ExecuteOptionsX{anonymous=false}

\if@ACM@timestamp Whether we use timestamp mode
128 \define@boolkey+{acmart.cls}[@ACM@]{timestamp}[true]{%
129   \if@ACM@timestamp
130     \PackageInfo{\@classname}{Using timestamp mode}%
131   \else
132     \PackageInfo{\@classname}{Not using timestamp mode}%
133   \fi}{\PackageError{\@classname}{The option timestamp can be either true or
134     false}}
135 \ExecuteOptionsX{timestamp=false}

\if@ACM@authordraft Whether we use author-draft mode
136 \define@boolkey+{acmart.cls}[@ACM@]{authordraft}[true]{%
137   \if@ACM@authordraft
138     \PackageInfo{\@classname}{Using authordraft mode}%
139     \@ACM@timestamptrue
140     \@ACM@reviewtrue
141   \else
142     \PackageInfo{\@classname}{Not using authordraft mode}%
143   \fi}{\PackageError{\@classname}{The option authordraft can be either true or
144     false}}
145 \ExecuteOptionsX{authordraft=false}

\ACM@fontsize The font size to pass to the base class
146 % \changes{v1.87}{2022/08/27}{Added fontsize 8pt}
147 \def\ACM@fontsize{}
148 \DeclareOptionX{8pt}{\edef\ACM@fontsize{\CurrentOption}}
149 \DeclareOptionX{9pt}{\edef\ACM@fontsize{\CurrentOption}}
150 \DeclareOptionX{10pt}{\edef\ACM@fontsize{\CurrentOption}}
151 \DeclareOptionX{11pt}{\edef\ACM@fontsize{\CurrentOption}}
152 \DeclareOptionX{12pt}{\edef\ACM@fontsize{\CurrentOption}}

\ACM@languages The languages of the document
153 \def\ACM@languages{}
154 \DeclareOptionX{language}{%
155   \ifx\ACM@languages\@empty
156     \gdef\ACM@languages{english}\fi
157   \g@addto@macro\ACM@languages{, #1}}

158 \DeclareOptionX{draft}{\PassOptionsToClass{\CurrentOption}{amsart}}
159 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
160 \ProcessOptionsX
161 \ClassInfo{\@classname}{Using format \ACM@format, number \ACM@format@nr}

```

3.4 Setting switches

```

\if@ACM@manuscript Whether we use manuscript mode
162 \newif\if@ACM@manuscript

\if@ACM@journal There are two kinds of publications: journals and books
163 \newif\if@ACM@journal

\if@ACM@journal@bibstrip Sometimes ACM wants a journal-like publication to have conference information in the
bibstrip and vice versa, so we have an additional switch.
164 \newif\if@ACM@journal@bibstrip

\if@ACM@sigchiamode The formatting of SIGCHI extended abstracts is quite unusual. We have a special switch
for them.
165 \newif\if@ACM@sigchiamode

\if@ACM@engage ACM Engage course materials have special formatting
166 \newif\if@ACM@engage
167 \@ACM@engagefalse

\if@ACM@acmcp ACM cover page formatting
168 \newif\if@ACM@acmcp
169 \@ACM@acmcpfalse

```

Setting up switches

```

170 \ifnum\ACM@format@nr=5\relax % siggraph
171 \ClassWarning{\@classname}{%
172   The format siggraph is now obsolete.\MessageBreak
173   I am switching to sigconf.}
174 \setkeys{acmart.cls}{format=sigconf}
175 \fi
176 \ifnum\ACM@format@nr=7\relax % sigchi
177 \ClassWarning{\@classname}{%
178   The format sigchi is now obsolete.\MessageBreak
179   I am switching to sigconf.}
180 \setkeys{acmart.cls}{format=sigconf}
181 \fi
182 \ifnum\ACM@format@nr=8\relax % sigchi
183 \ClassWarning{\@classname}{%
184   ACM SIGCHI has retired the SIGCHI-A template\MessageBreak
185   effective immediately. ACM is keeping this template\MessageBreak
186   option available to authors who are working on legacy\MessageBreak
187   documents only. ACM will not, under any circumstances,\MessageBreak
188   accept documents in this format for publication and\MessageBreak
189   will not offer technical support to the authors who use\MessageBreak
190   this template.\MessageBreak
191   ACM SIGCHI is directing Conference leaders and\MessageBreak
192   authors to publish their articles using the SIGCONF\MessageBreak
193   template call.}
194 \fi
195 \ifnum\ACM@format@nr=0\relax
196   \@ACM@manuscripttrue
197 \else

```

```

198 \ACM@manuscriptfalse
199 \fi
200 \ACM@sigchiamodefalse
201 \ifcase\ACM@format@nr
202 \relax % manuscript
203 \ACM@journaltrue
204 \or % acmsmall
205 \ACM@journaltrue
206 \or % acmlarge
207 \ACM@journaltrue
208 \or % acmtog
209 \ACM@journaltrue
210 \or % sigconf
211 \ACM@journalfalse
212 \or % siggraph
213 \ACM@journalfalse
214 \or % sigplan
215 \ACM@journalfalse
216 \or % sigchi
217 \ACM@journalfalse
218 \or % sigchi-a
219 \ACM@journalfalse
220 \ACM@sigchiamodetrue
221 \or % acmengage
222 \ACM@journalfalse
223 \ACM@engagetrue
224 \or % acmcp
225 \ACM@journaltrue
226 \ACM@acmcptrue
227 \AtBeginDocument{\ACM@printacmreffalse}%
228 \fi
229 \if\ACM@journal
230 \ACM@journal@bibstriptrue
231 \else
232 \ACM@journal@bibstripfalse
233 \fi

```

3.5 Loading the base class and package

At this point we either have \ACM@fontsize or use defaults

```

234 \ifx\ACM@fontsize\@empty
235 \ifcase\ACM@format@nr
236 \relax % manuscript
237 \def\ACM@fontsize{9pt}%
238 \or % acmsmall
239 \def\ACM@fontsize{10pt}%
240 \or % acmlarge
241 \def\ACM@fontsize{10pt}%
242 \or % acmtog
243 \def\ACM@fontsize{9pt}%
244 \or % sigconf
245 \def\ACM@fontsize{9pt}%
246 \or % siggraph
247 \def\ACM@fontsize{9pt}%

```



```

248 \or % sigplan
249 \def\ACM@fontsize{10pt}%
250 \or % sigchi
251 \def\ACM@fontsize{9pt}%
252 \or % sigchi-a
253 \def\ACM@fontsize{10pt}%
254 \or % acmengage
255 \def\ACM@fontsize{10pt}%
256 \or % acmcp
257 \def\ACM@fontsize{9pt}%
258 \fi
259 \fi
260 \ClassInfo{\@classname}{Using fontsize \ACM@fontsize}
261 \LoadClass[\ACM@fontsize, reqno]{amsart}
262 \RequirePackage{microtype}

    We need etoolbox for delayed code
263 \RequirePackage{etoolbox}

    Booktabs is now the default
264 \RequirePackage{booktabs}

    We need totpages to calculate the number of pages and refcount to use that num-
ber
265 \RequirePackage{refcount}
266 \RequirePackage{totpages}

    The \collect@body macro in amsmath is defined using \def. We load environ to
access the \long version of this command
267 \RequirePackage{environ}

    We use setspace for double spacing
268 \if@ACM@manuscript
269 \RequirePackage{setspace}
270 \onehalfspacing
271 \fi

    We need textcase for better upcasing
272 \RequirePackage{textcase}

273 \if@ACM@acmcp
274 \RequirePackage{framed}
275 \fi

```

3.6 Citations

We patch `\setcitestyle` to allow, for example, `\setcitestyle{sort}` and `\setcitestyle{nosort}`. We patch `\citestyle` to warn about undefined citation styles.

```

276 \if@ACM@natbib
277 \RequirePackage{natbib}
278 \renewcommand{\bibsection}{%
279 \section*{\refname}%
280 \phantomsection\addcontentsline{toc}{section}{\refname}%
281 }
282 \renewcommand{\bibfont}{\bibliofont}
283 \renewcommand\setcitestyle[1]{

```

```

284 \@for\@tempa:=#1\do
285 {\def\@tempb{round}\ifx\@tempa\@tempb
286   \renewcommand\NAT@open{()}\renewcommand\NAT@close{)}\fi
287 \def\@tempb{square}\ifx\@tempa\@tempb
288   \renewcommand\NAT@open{[]}\renewcommand\NAT@close{[]}\fi
289 \def\@tempb{angle}\ifx\@tempa\@tempb
290   \renewcommand\NAT@open{<}\renewcommand\NAT@close{>}\fi
291 \def\@tempb{curly}\ifx\@tempa\@tempb
292   \renewcommand\NAT@open{\{}\renewcommand\NAT@close{\}}\fi
293 \def\@tempb{semicolon}\ifx\@tempa\@tempb
294   \renewcommand\NAT@sep{;}\fi
295 \def\@tempb{colon}\ifx\@tempa\@tempb
296   \renewcommand\NAT@sep{:}\fi
297 \def\@tempb{comma}\ifx\@tempa\@tempb
298   \renewcommand\NAT@sep{,}\fi
299 \def\@tempb{authoryear}\ifx\@tempa\@tempb
300   \NAT@numbersfalse\fi
301 \def\@tempb{numbers}\ifx\@tempa\@tempb
302   \NAT@numberstrue\NAT@superfalse\fi
303 \def\@tempb{super}\ifx\@tempa\@tempb
304   \NAT@numberstrue\NAT@supertrue\fi
305 \def\@tempb{nobibstyle}\ifx\@tempa\@tempb
306   \let\bibstyle=\@gobble\fi
307 \def\@tempb{bibstyle}\ifx\@tempa\@tempb
308   \let\bibstyle=\@citestyle\fi
309 \def\@tempb{sort}\ifx\@tempa\@tempb
310   \def\NAT@sort{\@ne}\fi
311 \def\@tempb{nosort}\ifx\@tempa\@tempb
312   \def\NAT@sort{\z@}\fi
313 \def\@tempb{compress}\ifx\@tempa\@tempb
314   \def\NAT@cmprs{\@ne}\fi
315 \def\@tempb{nocompress}\ifx\@tempa\@tempb
316   \def\NAT@cmprs{\z@}\fi
317 \def\@tempb{sort&compress}\ifx\@tempa\@tempb
318   \def\NAT@sort{\@ne}\def\NAT@cmprs{\@ne}\fi
319 \def\@tempb{mcite}\ifx\@tempa\@tempb
320   \let\NAT@merge\@ne\fi
321 \def\@tempb{merge}\ifx\@tempa\@tempb
322   \@ifnum{\NAT@merge<\tw@}{\let\NAT@merge\tw@}{\fi}
323 \def\@tempb{elide}\ifx\@tempa\@tempb
324   \@ifnum{\NAT@merge<\thr@}{\let\NAT@merge\thr@}{\fi}
325 \def\@tempb{longnamesfirst}\ifx\@tempa\@tempb
326   \NAT@longnamestrue\fi
327 \def\@tempb{nonamebreak}\ifx\@tempa\@tempb
328   \def\NAT@nmfmt#1{\mbox{\NAT@up#1}}\fi
329 \expandafter\NAT@find@eq\@tempa=\relax\@nil
330 \if\@tempc\relax\else
331   \expandafter\NAT@rem@eq\@tempc
332   \def\@tempb{open}\ifx\@tempa\@tempb
333     \xdef\NAT@open{\@tempc}\fi
334   \def\@tempb{close}\ifx\@tempa\@tempb
335     \xdef\NAT@close{\@tempc}\fi
336   \def\@tempb{aysep}\ifx\@tempa\@tempb
337     \xdef\NAT@aysep{\@tempc}\fi

```

```

338     \def\@tempb{yysep}\ifx\@tempa\@tempb
339     \xdef\NAT@yrsep{\@tempc}\fi
340     \def\@tempb{notesep}\ifx\@tempa\@tempb
341     \xdef\NAT@cmt{\@tempc}\fi
342     \def\@tempb{citesep}\ifx\@tempa\@tempb
343     \xdef\NAT@sep{\@tempc}\fi
344     \fi
345 }%
346 \NAT@setcites
347 }
348 \renewcommand\citestyle[1]{%
349     \ifcsname bibstyle@#1\endcsname%
350     \csname bibstyle@#1\endcsname\let\bibstyle\gobble%
351     \else%
352     \@latex@error{Undefined ‘#1’ citestyle}%
353     \fi
354 }%
355 \fi

```

`\bibstyle@acmauthoryear` The default author-year format:

```

356 \newcommand{\bibstyle@acmauthoryear}{%
357     \setcitestyle{%
358         authoryear,%
359         open={},close={},citesep={;},%
360         aysep={},yysep={},,%
361         notesep={, }}

```

`\bibstyle@acmnumeric` The default numeric format:

```

362 \newcommand{\bibstyle@acmnumeric}{%
363     \setcitestyle{%
364         numbers,sort&compress,%
365         open={},close={},citesep={,},%
366         notesep={, }}

```

The default is numeric:

```

367 \if@ACM@natbib
368 \citestyle{acmnumeric}
369 \fi

```

3.7 Internationalization

```

370 \if@ACM@journal
371     \renewcommand\keywordsname{Additional Key Words and Phrases}%
372 \else
373     \renewcommand\keywordsname{Keywords}%
374 \fi
375 \if@ACM@engage
376     \renewcommand\abstractname{Synopsis}%
377 \fi
378 \ifx\ACM@languages\@empty
379 \else
380     \RequirePackage[\ACM@languages]{babel}%
381     \addto\captionsenglish{%
382         \if@ACM@journal

```

```

383     \renewcommand\keywordsname{Additional Key Words and Phrases}%
384   \else
385     \renewcommand\keywordsname{Keywords}%
386   \fi
387   \renewcommand\acksname{Acknowledgements}%
388   \if@ACM@engage
389     \renewcommand\abstractname{Synopsis}%
390   \fi
391 }%
392 \addto\captionsfrench{%
393   \if@ACM@journal
394     \renewcommand\keywordsname{Mots Clés et Phrases Supplémentaires}%
395   \else
396     \renewcommand\keywordsname{Mots clés}%
397   \fi
398   \renewcommand\acksname{Remerciements}%
399 }%
400 \addto\captionsgerman{%
401   \if@ACM@journal
402     \renewcommand\keywordsname{Zusätzliche Schlagwörter und Phrasen}%
403   \else
404     \renewcommand\keywordsname{Schlagwörter}%
405   \fi
406   \renewcommand\acksname{Danksagungen}%
407 }%
408 \addto\captionsspanish{%
409   \if@ACM@journal
410     \renewcommand\keywordsname{Palabras y Frases Claves Adicionales}%
411   \else
412     \renewcommand\keywordsname{Palabras claves}%
413   \fi
414   \renewcommand\acksname{Expresiones de gratitud}%
415 }%
416 \fi

```

\ACM@lang@check Some commands should not be used if the document is monlingual

```

417 \newcommand\ACM@lang@check[1]{%
418   \ifx\ACM@languages\@empty\relax
419     \ClassError{\@classname}{%
420       Command \string#1 \MessageBreak is used in monlingual document}{%
421         You used a command (\string#1) \MessageBreak
422         that does not have a meaning \MessageBreak
423         unless are languages are defined. \MessageBreak
424         Please choose the languages in \string\documentclass
425         \MessageBreak
426         (e.g. \string\documentclass[languages={french, english}]{acmart}),
427         \MessageBreak
428         or delete the command.}%
429   \fi}

```

\@translatedtitle

```

430 \def\@translatedtitle{}

```

\translatedtitle The title of the paper in a different language

```

431 \newcommand\translatedtitle[2]{\ACM@lang@check{\translatedtitle}%
432 \g@addto@macro\@translatedtitle{\par\foreignlanguage{#1}{#2}}}

\@translatedsubtitle
433 \def\@translatedsubtitle{}

\translatedsubtitle The subtitle of the paper in a different language
434 \newcommand\translatedsubtitle[2]{\ACM@lang@check{\translatedsubtitle}%
435 \g@addto@macro\@translatedsubtitle{\par\foreignlanguage{#1}{#2}}}

\@translatedkeywords
436 \def\@translatedkeywords{}

\translatedkeywords Add keywords to the paper in the language specified
437 \newcommand\translatedkeywords[2]{\ACM@lang@check{\translatedkeywords}%
438 \g@addto@macro\@translatedkeywords{\@mktranslatedkeywords{#1}{#2}}}

\@translatedabstracts The container for translated abstracts.
439 \def\@translatedabstracts{}

translatedabstract We save translated abstracts into \@translatedabstracts
440 \newenvironment{translatedabstract}[1]{\Collect@Body
441 \@savetranslatedabstract\@mktranslatedabstract{#1}}{}

\@savetranslatedabstract And saving the abstract
442 \long\def\@savetranslatedabstract#1{\if@ACM@maketitle@typeset
443 \ClassError{\@classname}{Abstract must be defined before maketitle
444 command. Please move it!}\fi
445 \ACM@lang@check{translatedabstract}%
446 \g@addto@macro\@translatedabstracts{\bgroup#1\egroup}}

```

3.8 Sectioning

\@startsection Before we call hyperref, we redefine \@startsection commands to their L^AT_EX defaults since the amsart ones are too AMS-specific. We need to do this early since we want hyperref to have a chance to redefine them again:

```

447 \def\@startsection#1#2#3#4#5#6{%
448 \if@noskipsec \leavevmode \fi
449 \par
450 \@tempskipa #4\relax
451 \@afterindenttrue
452 \ifdim \@tempskipa <\z@
453 \@tempskipa -\@tempskipa \@afterindentfalse
454 \fi
455 \if@nobreak
456 \everypar{}%
457 \else
458 \addpenalty\@secpenalty\addvspace\@tempskipa
459 \fi
460 \@ifstar
461 {\@ssect{#3}{#4}{#5}{#6}}%
462 {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}

```

```

463 \def\@sect#1#2#3#4#5#6[#7]#8{%
464 \edef\@toclevel{\ifnum#2=\@m 0\else\number#2\fi}%
465 \ifnum #2>\c@secnumdepth
466 \let\@svsec\@empty
467 \else
468 \refstepcounter{#1}%
469 \protected@edef\@svsec{\@seccntformat{#1}\relax}%
470 \fi
471 \@tempskipa #5\relax
472 \ifdim \@tempskipa>\z@
473 \begingroup
474 #6{%
475 \hangfrom{\hskip #3\relax\@svsec}%
476 \interlinepenalty \@M #8\@par}%
477 \endgroup
478 \csname #1mark\endcsname{#7}%
479 \ifnum #2>\c@secnumdepth \else
480 \tochangmeasure{\csname the#1\endcsname}%
481 \fi
482 \addcontentsline{toc}{#1}{%
483 \ifnum #2>\c@secnumdepth \else
484 \protect\numberline{\csname the#1\endcsname}%
485 \fi
486 #7}%
487 \else
488 \def\@svsechd{%
489 #6{\hskip #3\relax
490 \@svsec #8}%
491 \csname #1mark\endcsname{#7}%
492 \ifnum #2>\c@secnumdepth \else
493 \tochangmeasure{\csname the#1\endcsname\space}%
494 \fi
495 \addcontentsline{toc}{#1}{%
496 \ifnum #2>\c@secnumdepth \else
497 \protect\numberline{\csname the#1\endcsname}%
498 \fi
499 #7}}%
500 \fi
501 \@xsect{#5}}
502 \def\@xsect#1{%
503 \@tempskipa #1\relax
504 \ifdim \@tempskipa>\z@
505 \par \nobreak
506 \vskip \@tempskipa
507 \afterheading
508 \else
509 \@nobreakfalse
510 \global\@noskipsectrue
511 \everypar{%
512 \if@noskipsec
513 \global\@noskipsecfalse
514 {\setbox\z@\lastbox}%
515 \clubpenalty\@M
516 \begingroup \@svsechd \endgroup

```

```

517     \unskip
518     \@tempskipa #1\relax
519     \hskip -\@tempskipa
520   \else
521     \clubpenalty \@clubpenalty
522     \everypar{}%
523   \fi}%
524 \fi
525 \ignorespaces}
526 \def\@secntformat#1{\csname the#1\endcsname\quad}
527 \def\@ssect#1#2#3#4#5{%
528   \@tempskipa #3\relax
529   \ifdim \@tempskipa>\z@
530     \begingroup
531       #4{%
532         \@hangfrom{\hskip #1}%
533         \interlinepenalty \@M #5\@par}%
534     \endgroup
535   \else
536     \def\@svsechd{#4{\hskip #1\relax #5}}%
537   \fi
538   \@xsect{#3}}

```

\@startsection The amsart package redefines \@startsection. Here we redefine it again to make the table of contents work.

```

539 \def\@starttoc#1#2{\begingroup\makeatletter
540   \setTrue{#1}%
541   \par\removelastskip\vskip\z@skip
542   \@startsection{section}\@M\z@{\linespacing\@plus\linespacing}%
543     {.5\linespacing}{\centering\contentsnamefont}{#2}%
544   \@input{\jobname.#1}%
545   \if@filesw
546     \xp\newwrite\csname tf@#1\endcsname
547     \immediate\xp\openout\csname tf@#1\endcsname \jobname.#1\relax
548   \fi
549   \global\@nobeckfalse \endgroup
550   \addvspace{32\p@\@plus14\p@}%
551 }

```

\l@section Section spacing is more generous than for amsart

```

552 \def\l@section{\@tocline{1}{0pt}{1pc}{2pc}{}}

```

\l@subsection The spacing in amsart is too large

```

553 \def\l@subsection{\@tocline{2}{0pt}{1pc}{3pc}{}}

```

\l@subsubsection The spacing in amsart is too large

```

554 \def\l@subsubsection{\@tocline{3}{0pt}{1pc}{5pc}{}}

```

We need to define footnote-related stuff before the call to hyperref (Ross Moore)

\@makefnmark We do not use indentation for footnotes

```

555 \def\@makefnmark{\noindent\@makefnmark}

```

\@footnotetext In sigchi-a mode our footnotes are in the margin!

```
556 \if@ACM@sigchiamode
557 \long\def\@footnotetext#1{\marginpar{%
558   \reset@font\small
559   \interlinepenalty\interfootnotelinepenalty
560   \protected@edef\@currentlabel{%
561     \csname p@footnote\endcsname\@thefnmark
562   }%
563   \color@begingroup
564     \@makefnmark{%
565       \rule{z@footnotesep}{\ignorespaces#1}\@finalstrut\strutbox}%
566   \color@endgroup}}%
567 \fi
```

\@mpfootnotetext We want the footnotes in minipages centered:

```
568 \long\def\@mpfootnotetext#1{%
569   \global\setbox\@mpfootins\vbox{%
570     \unvbox\@mpfootins
571     \reset@font\footnotesize
572     \hsize\columnwidth
573     \@parboxrestore
574     \protected@edef\@currentlabel
575       {\csname p@mpfootnote\endcsname\@thefnmark}%
576     \color@begingroup\centering
577       \@makefnmark{%
578         \rule{z@footnotesep}{\ignorespaces#1}\@finalstrut\strutbox}%
579     \color@endgroup}}
```

\@makefnmark AMS classes use a buggy definition of \@makefnmark. We revert to the standard one.

```
580 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}
```

3.9 Hyperxmp and hyperref

Adding hyperxmp

```
581 \RequirePackage{hyperxmp}
```

And now, hyperref

```
582 \let\@footnotemark@nolink\@footnotemark
583 \let\@footnotetext@nolink\@footnotetext
584 \RequirePackage[bookmarksnumbered,unicode]{hyperref}
585 \pdfstringdefDisableCommands{%
586   \def\addtocounter#1#2{%
587     \def\unskip{}}%
588   \def\textbullet{- }%
589   \def\textrightarrow{-> }%
590   \def\footnotemark{}}%
591 }
592 \urlstyle{rm}
593 \ifcase\ACM@format@nr
594 \relax % manuscript
595 \or % acmsmall
596 \or % acmlarge
597 \or % acmtog
598 \or % sigconf
```



```

599 \or % siggraph
600 \or % sigplan
601 \urlstyle{sf}
602 \or % sigchi
603 \or % sigchi-a
604 \urlstyle{sf}
605 \or % acmengage
606 \or % acmcp
607 \fi
608 \AtEndPreamble{%
609 \if@ACM@urlbreakonhyphens
610 \def\do@url@hyp{\do\~}%
611 \fi
612 \if@ACM@screen
613 \hypersetup{colorlinks,
614 linkcolor=ACMPurple,
615 citecolor=ACMPurple,
616 urlcolor=ACMDarkBlue,
617 filecolor=ACMDarkBlue}
618 \else
619 \hypersetup{hidelinks}
620 \fi
621 \hypersetup{pdflang={en},
622 pdfdisplaydoctitle}}
    Bibliography mangling.
623 \if@ACM@natbib
624 \let\citeN\cite
625 \let\cite\citep
626 \let\citeANP\citeauthor
627 \let\citeNN\citeyearpar
628 \let\citeyearNP\citeyear
629 \let\citeNP\citealt
630 \DeclareRobustCommand\citeA
631 {\begingroup\NAT@swafalse
632 \let\NAT@ctype\@ne\NAT@partrue\NAT@fullfalse\NAT@open\NAT@citetp}%
633 \providecommand\newblock{}%
634 \else
635 \AtBeginDocument{%
636 \let\shortcite\cite%
637 \providecommand\citename[1]{#1}}
638 \fi
639 \newcommand\shortcite[2][]{%
640 \ifNAT@numbers\cite[#1]{#2}\else\citeyearpar[#1]{#2}\fi}

```

`\bibliographystyle` The `amsart` package redefines `\bibliographystyle` since it prefers the AMS bibliography style. We turn it back to the \LaTeX definition:

```

641 \def\bibliographystyle#1{%
642 \ifx\@begindocumenthook\@undefined\else
643 \expandafter\AtBeginDocument
644 \fi
645 {\if@filesw
646 \immediate\write\@auxout{\string\bibstyle{#1}}%
647 \fi}}

```

3.10 Other packages

Graphics and color.

```
648 \RequirePackage{graphicx}
649 \RequirePackage[prologue]{xcolor}
```

We define ACM colors according to [8]:

```
650 \definecolor[named]{ACMBlue}{cmyk}{1,0.1,0,0.1}
651 \definecolor[named]{ACMYellow}{cmyk}{0,0.16,1,0}
652 \definecolor[named]{ACMOrange}{cmyk}{0,0.42,1,0.01}
653 \definecolor[named]{ACMRed}{cmyk}{0,0.90,0.86,0}
654 \definecolor[named]{ACMLightBlue}{cmyk}{0.49,0.01,0,0}
655 \definecolor[named]{ACMGreen}{cmyk}{0.20,0,1,0.19}
656 \definecolor[named]{ACMPurple}{cmyk}{0.55,1,0,0.15}
657 \definecolor[named]{ACMDarkBlue}{cmyk}{1,0.58,0,0.21}
```

Author-draft mode or sigchi-a mode

```
658 \if@ACM@authordraft
659   \RequirePackage{draftwatermark}
660   \SetWatermarkFontSize{0.5in}
661   \SetWatermarkColor[gray]{.9}
662   \SetWatermarkText{\parbox{12em}{\centering
663     Unpublished working draft.\\
664     Not for distribution.}}
665 \else
666   \if@ACM@sigchi-mode
667     \if@ACM@nonacm\else
668       \RequirePackage{draftwatermark}
669       \SetWatermarkFontSize{0.5in}
670       \SetWatermarkColor[gray]{.9}
671       \SetWatermarkText{\parbox{12em}{\centering
672         Legacy document. \\
673         Not for publication in an ACM venue}}
674     \fi
675   \fi
676 \fi
```

3.11 Paper size and paragraphing

We use geometry for dimensions. Note that the present margins do not depend on the font size option—we might need to change this. See <https://github.com/borisveytsman/acmart/issues/5#issuecomment-272881329>.

```
677 \RequirePackage{geometry}
678 \ifcase\ACM@format@nr
679 \relax % manuscript
680   \geometry{letterpaper,head=13pt,
681     marginparwidth=6pc,heightrounded}%
682 \or % acmsmall
683   \geometry{twoside=true,
684     includeheadfoot, head=13pt, foot=2pc,
685     paperwidth=6.75in, paperheight=10in,
686     top=58pt, bottom=44pt, inner=46pt, outer=46pt,
687     marginparwidth=2pc,heightrounded
688   }%
```

```

689 \or % acmlarge
690 \geometry{twoside=true, head=13pt, foot=2pc,
691     paperwidth=8.5in, paperheight=11in,
692     includeheadfoot,
693     top=78pt, bottom=114pt, inner=81pt, outer=81pt,
694     marginparwidth=4pc,heightrounded
695 }%
696 \or % acmtog
697 \geometry{twoside=true, head=13pt, foot=2pc,
698     paperwidth=8.5in, paperheight=11in,
699     includeheadfoot, columnsep=24pt,
700     top=52pt, bottom=75pt, inner=52pt, outer=52pt,
701     marginparwidth=2pc,heightrounded
702 }%
703 \or % sigconf
704 \geometry{twoside=true, head=13pt,
705     paperwidth=8.5in, paperheight=11in,
706     includeheadfoot, columnsep=2pc,
707     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
708     marginparwidth=2pc,heightrounded
709 }%
710 \or % siggraph
711 \geometry{twoside=true, head=13pt,
712     paperwidth=8.5in, paperheight=11in,
713     includeheadfoot, columnsep=2pc,
714     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
715     marginparwidth=2pc,heightrounded
716 }%
717 \or % sigplan
718 \geometry{twoside=true, head=13pt,
719     paperwidth=8.5in, paperheight=11in,
720     includeheadfoot=false, columnsep=2pc,
721     top=1in, bottom=1in, inner=0.75in, outer=0.75in,
722     marginparwidth=2pc,heightrounded
723 }%
724 \or % sigchi
725 \geometry{twoside=true, head=13pt,
726     paperwidth=8.5in, paperheight=11in,
727     includeheadfoot, columnsep=2pc,
728     top=66pt, bottom=73pt, inner=54pt, outer=54pt,
729     marginparwidth=2pc,heightrounded
730 }%
731 \or % sigchi-a
732 \geometry{twoside=false, head=13pt,
733     paperwidth=11in, paperheight=8.5in,
734     includeheadfoot, marginparsep=72pt,
735     marginparwidth=170pt, columnsep=20pt,
736     top=72pt, bottom=72pt, left=314pt, right=72pt
737 }%
738 \@mparswitchfalse
739 \reversemarginpar
740 \or % acmengage
741 \geometry{twoside=true, head=13pt,
742     paperwidth=8.5in, paperheight=11in,

```

```

743     includeheadfoot, columnsep=2pc,
744     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
745     marginparwidth=2pc,heightrounded
746   }%
747 \or % acmcp
748   \geometry{twoside=true,
749     includeheadfoot, head=13pt, foot=2pc,
750     paperwidth=6.75in, paperheight=10in,
751     top=58pt, bottom=44pt, inner=46pt, outer=46pt,
752     marginparwidth=2pc,heightrounded
753   }%
754 \fi

```

`\parindent` Paragraphing

```

\parskip 755 \setlength\parindent{10\p@}
756 \setlength\parskip{\z@}
757 \ifcase\ACM@format@nr
758 \relax % manuscript
759 \or % acmsmall
760 \or % acmlarge
761 \or % acmtog
762   \setlength\parindent{9\p@}%
763 \or % sigconf
764 \or % siggraph
765 \or % sigplan
766 \or % sigchi
767 \or % sigchi-a
768 \or % acmengage
769 \or % acmcp
770 \fi

```

`\normalparindent` The `amsart` package defines the `\normalparindent` length and initializes it to 12pt (the value of `\parindent` in `amsart`). It is later used to set the `\listparindent` length in the quotation environment and the `\parindent` length in the `\@footnotetext` command. We set `\normalparindent` to the value of `\parindent` as selected by `acmart` for consistent paragraph indents.

```
771 \setlength\normalparindent{\parindent}
```

Footnotes require some consideration. We have several layers of footnotes: front-matter footnotes, “regular” footnotes and the special insert for the bibstrip. In the old ACM classes, the bibstrip was a `\@float`. The problem with floats is that they tend to, well, float—and we want the guarantee they stay.

We use `manyfoot` for layered footnotes instead.

`copyrightpermissionfootnoterule` This is the footnote rule that separates the bibstrip from the rest of the paper. It is a full width rule.

```

772 \def\copyrightpermissionfootnoterule{\kern-3\p@
773   \hrule \@width \columnwidth \kern 2.6\p@}

774 \RequirePackage{manyfoot}
775 \SelectFootnoteRule[2]{copyrightpermission}
776 \DeclareNewFootnote{authorsaddresses}
777 \SelectFootnoteRule[2]{copyrightpermission}
778 \DeclareNewFootnote{copyrightpermission}

```

`\footnoterule` Tschichold's rules:

```
779 \def\footnoterule{\kern-3\p@
780 \hrule \@width 4pc \kern 2.6\p@}
```

`\endminipage` We do not use footnote rules in minipages

```
781 \def\endminipage{%
782   \par
783   \unskip
784   \ifvoid\@mpfootins\else
785     \vskip\skip\@mpfootins
786     \normalcolor
787     \unvbox\@mpfootins
788   \fi
789   \@minipagefalse
790   \color@endgroup
791   \egroup
792   \expandafter\@iiparbox\@mpargs{\unvbox\@tempboxa}}
```

`\@textbottom` Add some stretch according to David Carlisle's advice at <http://tex.stackexchange.com/a/62318/5522>

```
793 \def\@textbottom{\vskip \z@ \@plus 1pt}
794 \let\@texttop\relax
```

In two-column layouts, force both columns to be the same height by inserting extra internal vertical space to fill out the page.

```
795 \ifcase\ACM@format@nr
796 \relax % manuscript
797 \or % acmsmall
798 \or % acmlarge
799 \or % acmtog
800 \flushbottom
801 \or % sigconf
802 \flushbottom
803 \or % siggraph
804 \flushbottom
805 \or % sigplan
806 \flushbottom
807 \or % sigchi
808 \flushbottom
809 \or % sigchi-a
810 \or % acmengage
811 \flushbottom
812 \or % acmcp
813 \flushbottom
814 \fi
```

3.12 Fonts

Somehow PDF_TEX and Xe_TEX require different incantations to make a PDF compliant with the current Acrobat bugs. Xpdf is much better.

The code below is by Ross Moore.

```
815 \ifPDFTeX
816 \input{glyhtounicode}
```

```

817 \pdfglyphtounicode{f_f}{FB00}
818 \pdfglyphtounicode{f_f_i}{FB03}
819 \pdfglyphtounicode{f_f_l}{FB04}
820 \pdfglyphtounicode{f_i}{FB01}
821 \pdfglyphtounicode{t_t}{0074 0074}
822 \pdfglyphtounicode{f_t}{0066 0074}
823 \pdfglyphtounicode{T_h}{0054 0068}
824 \pdfgentounicode=1
825 \RequirePackage{cmap}
826 \fi

```

`\if@ACM@newfonts` Whether we load the new fonts

```

827 \newif\if@ACM@newfonts
828 \@ACM@newfontstrue
829 \IfFileExists{libertine.sty}{\ClassWarning{\@classname}{You do not
830   have the libertine package installed. Please upgrade your
831   TeX}\@ACM@newfontsfalse}
832 \IfFileExists{zi4.sty}{\ClassWarning{\@classname}{You do not
833   have the inconsolata (zi4.sty) package installed. Please upgrade your
834   TeX}\@ACM@newfontsfalse}
835 \IfFileExists{newtxmath.sty}{\ClassWarning{\@classname}{You do not
836   have the newtxmath package installed. Please upgrade your
837   TeX}\@ACM@newfontsfalse}

```

We use Libertine throughout.

```

838 \if@ACM@newfonts
839   \RequirePackage[T1]{fontenc}
840   % Note that the order in which packages are loaded matters,
841   % and the correct order depends on the LaTeX engine used.
842   % See https://github.com/borisveytsman/acmart/issues/402
843   % and https://github.com/borisveytsman/acmart/issues/410
844   \ifxetex
845     \RequirePackage[libertine]{newtxmath}
846     \RequirePackage[tt=false]{libertine}
847     \setmonofont[StylisticSet=3]{inconsolata}
848   \else
849     \ifluatex
850       \RequirePackage[libertine]{newtxmath}
851       \RequirePackage[tt=false]{libertine}
852       \setmonofont[StylisticSet=3]{inconsolata}
853     \else
854       \RequirePackage[tt=false, type1=true]{libertine}
855       \RequirePackage[varqu]{zi4}
856       \RequirePackage[libertine]{newtxmath}
857     \fi
858   \fi
859 \fi

```

`\liningnums` Libertine defines `\liningnums`, which makes `fontspec` unhappy. While we do not use `fontspec`, some users do.

```

860 \let\liningnums\@undefined
861 \AtEndPreamble{%
862   \DeclareTextFontCommand{\liningnums}{\libertineLF}}

```

The SIGCHI extended abstracts are sans serif:

```
863 \if@ACM@sigchiamode
864   \renewcommand{\familydefault}{\sfdefault}
865 \fi
```

3.13 Image descriptions

`\if@Description@present` A local switch: whether there is a description in the given figure

```
866 \newif\if@Description@present
867 \@Description@presenttrue
```

`\if@undescribed@images` A global switch whether some images were *not* described

```
868 \newif\if@undescribed@images
869 \@undescribed@imagesfalse
```

`\Description` The Description macro right now just sets switches

```
870 \newcommand\Description[2][\global\@Description@presenttrue\ignorespaces]
```

The global warning

```
871 \AtEndDocument{\if@undescribed@images
872   \ClassWarningNoLine{\@classname}{Some images may lack descriptions}\fi}
```

Hooks for figures and tables. We also patch algorithm and algorithm* in case somebody uses them.

```
873 \AtBeginEnvironment{figure}{\@Description@presentfalse
874   \let\@vspace\@vspace@orig
875   \let\@vspacer\@vspacer@orig}
876 \AtBeginEnvironment{figure*}{\@Description@presentfalse
877   \let\@vspace\@vspace@orig
878   \let\@vspacer\@vspacer@orig}
879 \AtEndEnvironment{figure}{\if@Description@present\else
880   \global\@undescribed@imagestrue
881   \ClassWarning{\@classname}{A possible image without description}\fi}
882 \AtEndEnvironment{figure*}{\if@Description@present\else
883   \global\@undescribed@imagestrue
884   \ClassWarning{\@classname}{A possible image without description}\fi}
885 \AtBeginEnvironment{table}{\let\@vspace\@vspace@orig
886   \let\@vspacer\@vspacer@orig}
887 \AtBeginEnvironment{table*}{\let\@vspace\@vspace@orig
888   \let\@vspacer\@vspacer@orig}
889 \AtBeginEnvironment{algorithm}{\let\@vspace\@vspace@orig
890   \let\@vspacer\@vspacer@orig}
891 \AtBeginEnvironment{algorithm*}{\let\@vspace\@vspace@orig
892   \let\@vspacer\@vspacer@orig}
893 \AtBeginEnvironment{lstlisting}{\let\@vspace\@vspace@orig
894   \let\@vspacer\@vspacer@orig}
895 \AtBeginEnvironment{lstlisting*}{\let\@vspace\@vspace@orig
896   \let\@vspacer\@vspacer@orig}
897 \AtBeginEnvironment{minted}{\let\@vspace\@vspace@orig
898   \let\@vspacer\@vspacer@orig}
899 \AtBeginEnvironment{minted*}{\let\@vspace\@vspace@orig
900   \let\@vspacer\@vspacer@orig}
901 \AtBeginEnvironment{listing}{\let\@vspace\@vspace@orig
```

```

902 \let\@vspacer\@vspacer@orig}
903 \AtBeginEnvironment{listing*}{\let\@vspace\@vspace@orig
904 \let\@vspacer\@vspacer@orig}
905

```

3.14 Floats

We use the caption package

```

906 \RequirePackage{caption, float}
907 \captionsetup[table]{position=top}
908 \if@ACM@journal
909   \captionsetup{labelfont={sf, small},
910     textfont={sf, small}, margin=\z@}
911   \captionsetup[figure]{name={Fig.}}
912 \else
913   \captionsetup{labelfont={bf},
914     textfont={bf}, labelsep=colon, margin=\z@}
915   \ifcase\ACM@format@nr
916     \relax % manuscript
917     \or % acmsmall
918     \or % acmlarge
919     \or % acmtog
920     \or % sigconf
921     \or % siggraph
922     \captionsetup{textfont={it}}
923     \or % sigplan
924     \captionsetup{labelfont={bf},
925       textfont={normalfont}, labelsep=period, margin=\z@}
926     \or % sigchi
927       \captionsetup[figure]{labelfont={bf, small},
928         textfont={bf, small}}
929       \captionsetup[table]{labelfont={bf, small},
930         textfont={bf, small}}
931     \or % sigchi-a
932       \captionsetup[figure]{labelfont={bf, small},
933         textfont={bf, small}}
934       \captionsetup[table]{labelfont={bf, small},
935         textfont={bf, small}}
936     \or % acmengage
937     \or % acmcp
938     \fi
939 \fi

```

sidebar The sidebar environment:

```

940 \newfloat{sidebar}{}{sbar}
941 \floatname{sidebar}{Sidebar}
942 \renewenvironment{sidebar}{}{\Collect@Body\@sidebar}{}

```

\@sidebar The processing of the saved text

```

943 \long\def\@sidebar#1{\bgroup\let\@vspace\@vspace@orig
944 \let\@vspacer\@vspacer@orig\captionsetup{type=sidebar}%
945 \marginpar{\small#1}\egroup}

```


marginfigure The marginfigure environment:

```
946 \newenvironment{marginfigure}{\Collect@Body\@marginfigure}{}
```

\@marginfigure The processing of the saved text

```
947 \long\def\@marginfigure#1{\bgroup
948   \let\@vspace\@vspace@orig
949   \let\@vspacer\@vspacer@orig
950   \captionsetup{type=figure}%
951   \marginpar{\@Description@presentfalse\centering
952     \small#1\if@Description@present\else
953       \global\@undescribed@imagestrue
954       \ClassWarning{\@classname}{A possible image without description}
955     \fi}%
956   \egroup}
```

marginfigure The marginfigure environment:

```
957 \newenvironment{marginfigure}{\Collect@Body\@marginfigure}{}
```

\@marginfigure The processing of the saved text

```
958 \long\def\@marginfigure#1{\bgroup\let\@vspace\@vspace@orig
959   \let\@vspacer\@vspacer@orig\captionsetup{type=table}%
960   \marginpar{\centering\small#1}\egroup}
```

SIGCHI extended abstracts provide an interesting possibility to push into the margin. Here we use figure* and table* for this.

\fulltextwidth We define the width of the boxes as

```
961 \newdimen\fulltextwidth
962 \fulltextwidth=\dimexpr(\textwidth+\marginparwidth+\marginparsep)
```

\@dblfloat We redefine the double-float command. First, we make the size bigger. Second, our default position is going to be tp (to give marginalia a chance)

```
963 \if@ACM@sigchiamode
964 \def\@dblfloat{\bgroup\let\@vspace\@vspace@orig
965   \let\@vspacer\@vspacer@orig\columnwidth=\fulltextwidth
966   \let\@endfloatbox\@endwidefloatbox
967   \def\@fpsadddefault{\def\@fps{tp}}%
968   \@float}
969 \fi
```

\end@dblfloat And the end. Just adding a \bgroup.

```
970 \if@ACM@sigchiamode
971 \def\end@dblfloat{%
972   \end@float\egroup}
973 \fi
```

\@endwidefloatbox This is the end of a wide box—we basically move everything to the left

```
974 \def\@endwidefloatbox{%
975   \par\vskip\z@skip
976   \@minipagefalse
977   \outer@nobreak
978   \egroup
979   \color@endbox}
```

```

980 \global\setbox\@currbox=\vbox{\moveleft
981   \dimexpr(\fulltextwidth-\textwidth)\box\@currbox}%
982   \wd\@currbox=\textwidth
983 }

```

3.15 Lists

```

984 \ifcase\ACM@format@nr
985 \relax % manuscript
986 \or % acmsmall
987 \or % acmlarge
988 \or % acmtog
989 \or % sigconf
990 \or % siggraph
991 \or % sigplan
992 \def\labelenumi{\theenumi.}
993 \def\labelenumii{\theenumii.}
994 \def\labelenumiii{\theenumiii.}
995 \def\labelenumiv{\theenumiv.}
996 \or % sigchi
997 \or % sigchi-a
998 \or % acmengage
999 \or % acmcp
1000 \fi

```

The AMS uses generous margins for lists. Note that `amsart` defines `\leftmargin` values for list levels at the beginning of the document, so we must redefine them in the same manner. Also, note that `amsart` redefines the `enumerate` and `itemize` environments with a `\makelabel` command that uses `\llap`, so the `\labelwidth` value is (effectively) irrelevant; nonetheless, we follow `amsart` and set `\labelwidth` to `\leftmargin` minus `\labelsep`.

```

1001 \newdimen\@ACM@labelwidth
1002 \AtBeginDocument{%
1003   \setlength\labelsep{4pt}
1004   \setlength{\@ACM@labelwidth}{6.5pt}
1005
1006   %% First-level list: when beginning after the first line of an
1007   %% indented paragraph or ending before an indented paragraph, labels
1008   %% should not hang to the left of the preceding/following text.
1009   \setlength\leftmargini{\z@}
1010   \addtolength\leftmargini{\parindent}
1011   \addtolength\leftmargini{2\labelsep}
1012   \addtolength\leftmargini{\@ACM@labelwidth}
1013
1014   %% Second-level and higher lists.
1015   \setlength\leftmarginii{\z@}
1016   \addtolength\leftmarginii{0.5\labelsep}
1017   \addtolength\leftmarginii{\@ACM@labelwidth}
1018   \setlength\leftmarginiii{\leftmarginii}
1019   \setlength\leftmarginiv{\leftmarginiii}
1020   \setlength\leftmarginv{\leftmarginiv}
1021   \setlength\leftmarginvi{\leftmarginv}
1022   \@listi}
1023 \newskip\listisep

```

```

1024 \listisep\smallskipamount
1025 \def\@listI{\leftmargin\leftmarginI
1026 \labelwidth\leftmarginI \advance\labelwidth-\labelsep
1027 \listparindent\z@
1028 \topsep\listisep}
1029 \let\@listi\@listI
1030 \def\@listii{\leftmargin\leftmarginii
1031 \labelwidth\leftmarginii \advance\labelwidth-\labelsep
1032 \topsep\z@skip}
1033 \def\@listiii{\leftmargin\leftmarginiii
1034 \labelwidth\leftmarginiii \advance\labelwidth-\labelsep}
1035 \def\@listiv{\leftmargin\leftmarginiv
1036 \labelwidth\leftmarginiv \advance\labelwidth-\labelsep}
1037 \def\@listv{\leftmargin\leftmarginv
1038 \labelwidth\leftmarginv \advance\labelwidth-\labelsep}
1039 \def\@listvi{\leftmargin\leftmarginvi
1040 \labelwidth\leftmarginvi \advance\labelwidth-\labelsep}
\descriptionlabel We do not use a colon by default like amsart does:
1041 \renewcommand{\descriptionlabel}[1]{\upshape\bfseries #1}

\description Make the description environment indentation consistent with that of the itemize
and enumerate environments.
1042 \renewenvironment{description}{\list{}{%
1043 \labelwidth\@ACM@labelwidth
1044 \let\makelabel\descriptionlabel}%
1045 }{
1046 \endlist
1047 }
1048 \let\enddescription=\endlist % for efficiency

```

3.16 Top-matter data

`\if@ACM@maketitle@typeset` The switch to check whether `\maketitle` is already typeset. It is initially false, and setting top matter when it is true is wrong.

```

1049 \newif\if@ACM@maketitle@typeset
1050 \@ACM@maketitle@typesetfalse

```

We use the `xkeyval` interface to define journal titles and the relevant information

```

1051 \define@choicekey*+{ACM}{acmJournal}[\@journalCode\@journalCode@nr]{%
1052 CIE,%
1053 CSUR,%
1054 DGOV,%
1055 DLT,%
1056 DTRAP,%
1057 FAC,%
1058 GAMES,%
1059 HEALTH,%
1060 IMWUT,%
1061 JACM,%
1062 JDIQ,%
1063 JDS,%
1064 JEA,%
1065 JERIC,%

```

1066 JETC,%
1067 JOCCH,%
1068 JRC,%
1069 PACMCGIT,%
1070 PACMHCI,%
1071 PACMPL,%
1072 POMACS,%
1073 TAAS,%
1074 TACCESS,%
1075 TACO,%
1076 TALG,%
1077 TALLIP,%
1078 TAP,%
1079 TCPS,%
1080 TDS,%
1081 TEAC,%
1082 TECS,%
1083 TELO,%
1084 THRI,%
1085 TIIS,%
1086 TIOT,%
1087 TISSEC,%
1088 TIST,%
1089 TKDD,%
1090 TMIS,%
1091 TOCE,%
1092 TOCHI,%
1093 TOCL,%
1094 TOCS,%
1095 TOCT,%
1096 TODAES,%
1097 TODS,%
1098 TOG,%
1099 TOIS,%
1100 TOIT,%
1101 TOMACS,%
1102 TOMM,%
1103 TOMPECS,%
1104 TOMS,%
1105 TOPC,%
1106 TOPS,%
1107 TOPLAS,%
1108 TOS,%
1109 TOSEM,%
1110 TOSN,%
1111 TQC,%
1112 TRETs,%
1113 TSAS,%
1114 TSC,%
1115 TSLP,%
1116 TWEB,%
1117 FACMP%
1118 }{ %
1119 \ifcase \@journalCode@nr

```

1120 \relax % CIE
1121 \def\@journalName{ACM Computers in Entertainment}%
1122 \def\@journalNameShort{ACM Comput. Entertain.}%
1123 \def\@permissionCodeOne{1544-3574}%
1124 \or % CSUR
1125 \def\@journalName{ACM Computing Surveys}%
1126 \def\@journalNameShort{ACM Comput. Surv.}%
1127 \def\@permissionCodeOne{0360-0300}%
1128 \or % DGOV
1129 \def\@journalName{Digital Government: Research and Practice}%
1130 \def\@journalNameShort{Digit. Gov. Res. Pract.}%
1131 \def\@permissionCodeOne{2639-0175}%
1132 \or % DLT
1133 \def\@journalName{Distributed Ledger Technologies: Research and Practice}%
1134 \def\@journalNameShort{Distrib. Ledger Technol.}%
1135 \def\@permissionCodeOne{2769-6472}%
1136 \or % DTRAP
1137 \def\@journalName{Digital Threats: Research and Practice}%
1138 \def\@journalNameShort{Digit. Threat. Res. Pract.}%
1139 \def\@permissionCodeOne{2576-5337}%
1140 \or % FAC
1141 \def\@journalName{Formal Aspects of Computing}%
1142 \def\@journalNameShort{Form. Asp. Comput.}%
1143 \def\@permissionCodeOne{0934-5043}%
1144 \def\@permissionCodeTwo{1433-299X}%
1145 \or % GAMES
1146 \def\@journalName{ACM Games: Research and Practice}%
1147 \def\@journalNameShort{ACM Games}%
1148 \or % HEALTH
1149 \def\@journalName{ACM Transactions on Computing for Healthcare}%
1150 \def\@journalNameShort{ACM Trans. Comput. Healthcare}%
1151 \def\@permissionCodeOne{2637-8051}%
1152 \or % IMWUT
1153 \def\@journalName{Proceedings of the ACM on Interactive, Mobile,
1154 Wearable and Ubiquitous Technologies}%
1155 \def\@journalNameShort{Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.}%
1156 \def\@permissionCodeOne{2474-9567}%
1157 \@ACM@screentruer
1158 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1159 \or % JACM
1160 \def\@journalName{Journal of the ACM}%
1161 \def\@journalNameShort{J. ACM}%
1162 \def\@permissionCodeOne{0004-5411}%
1163 \or % JDIQ
1164 \def\@journalName{ACM Journal of Data and Information Quality}%
1165 \def\@journalNameShort{ACM J. Data Inform. Quality}%
1166 \def\@permissionCodeOne{1936-1955}%
1167 \or % JDS
1168 \def\@journalName{ACM/JMS Journal of Data Science}%
1169 \def\@journalNameShort{ACM/IMS J. Data Sci.}%
1170 \def\@permissionCodeOne{2831-3194}%
1171 \def\@permissionCodeTwo{2831-3194}%
1172 \or % JEA
1173 \def\@journalName{ACM Journal of Experimental Algorithmics}%

```

```

1174 \def\@journalNameShort{ACM J. Exp. Algor.}%
1175 \def\@permissionCodeOne{1084-6654}%
1176 \or % JERIC
1177 \def\@journalName{ACM Journal of Educational Resources in Computing}%
1178 \def\@journalNameShort{ACM J. Edu. Resources in Comput.}%
1179 \def\@permissionCodeOne{1073-0516}%
1180 \or % JETC
1181 \def\@journalName{ACM Journal on Emerging Technologies in Computing Systems}%
1182 \def\@journalNameShort{ACM J. Emerg. Technol. Comput. Syst.}%
1183 \def\@permissionCodeOne{1550-4832}%
1184 \or % JOCCH
1185 \def\@journalName{ACM Journal on Computing and Cultural Heritage}%
1186 \def\@journalNameShort{ACM J. Comput. Cult. Herit.}%
1187 \def\@permissionCodeOne{1556-4673}%
1188 \def\@permissionCodeTwo{1556-4711}%
1189 \or % JRC
1190 \def\@journalName{ACM Journal on Responsible Computing}%
1191 \def\@journalNameShort{ACM J. Responsib. Comput.}%
1192 \def\@permissionCodeOne{2832-0565}%
1193 \or % PACMCGIT
1194 \def\@journalName{Proceedings of the ACM on Computer Graphics and Interactive Techniques}%
1195 \def\@journalNameShort{Proc. ACM Comput. Graph. Interact. Tech.}%
1196 \def\@permissionCodeOne{2577-6193}%
1197 \@ACM@screentruer
1198 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1199 \or % PACMHCI
1200 \def\@journalName{Proceedings of the ACM on Human-Computer Interaction}%
1201 \def\@journalNameShort{Proc. ACM Hum.-Comput. Interact.}%
1202 \def\@permissionCodeOne{2573-0142}%
1203 \@ACM@screentruer
1204 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1205 \or % PACMPL
1206 \def\@journalName{Proceedings of the ACM on Programming Languages}%
1207 \def\@journalNameShort{Proc. ACM Program. Lang.}%
1208 \def\@permissionCodeOne{2475-1421}%
1209 \@ACM@screentruer
1210 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1211 \or % POMACS
1212 \def\@journalName{Proceedings of the ACM on Measurement and Analysis of Computing Systems}%
1213 \def\@journalNameShort{Proc. ACM Meas. Anal. Comput. Syst.}%
1214 \def\@permissionCodeOne{2476-1249}%
1215 \@ACM@screentruer
1216 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1217 \or % TAAS
1218 \def\@journalName{ACM Transactions on Autonomous and Adaptive Systems}%
1219 \def\@journalNameShort{ACM Trans. Autonom. Adapt. Syst.}%
1220 \def\@permissionCodeOne{1556-4665}%
1221 \or % TACCESS
1222 \def\@journalName{ACM Transactions on Accessible Computing}%
1223 \def\@journalNameShort{ACM Trans. Access. Comput.}%
1224 \def\@permissionCodeOne{1936-7228}%
1225 \or % TACO
1226 \def\@journalName{ACM Transactions on Architecture and Code Optimization}%
1227 \def\@journalNameShort{ACM Trans. Arch. Code Optim.}%

```

```

1228 \def\@permissionCodeOne{1544-3566}%
1229 \def\@permissionCodeTwo{1544-3973}%
1230 \or % TALG
1231 \def\@journalName{ACM Transactions on Algorithms}%
1232 \def\@journalNameShort{ACM Trans. Algor.}%
1233 \def\@permissionCodeOne{1549-6325}%
1234 \or % TALLIP
1235 \def\@journalName{ACM Transactions on Asian and Low-Resource Language Information Processing}%
1236 \def\@journalNameShort{ACM Trans. Asian Low-Resour. Lang. Inf. Process.}%
1237 \def\@permissionCodeOne{2375-4699}%
1238 \or % TAP
1239 \def\@journalName{ACM Transactions on Applied Perception}%
1240 \def\@journalNameShort{ACM Trans. Appl. Percept.}%
1241 \def\@permissionCodeOne{1544-3558}%
1242 \or % TCPS
1243 \def\@journalName{ACM Transactions on Cyber-Physical Systems}%
1244 \def\@journalNameShort{ACM Trans. Cyber-Phys. Syst.}%
1245 \def\@permissionCodeOne{2378-962X}%
1246 \or % TDS
1247 \def\@journalName{ACM/IMS Transactions on Data Science}%
1248 \def\@journalNameShort{ACM/IMS Trans. Data Sci.}%
1249 \def\@permissionCodeOne{2577-3224}%
1250 \or % TEAC
1251 \def\@journalName{ACM Transactions on Economics and Computation}%
1252 \def\@journalNameShort{ACM Trans. Econ. Comput.}%
1253 \def\@permissionCodeOne{2167-8375}%
1254 \or % TECS
1255 \def\@journalName{ACM Transactions on Embedded Computing Systems}%
1256 \def\@journalNameShort{ACM Trans. Embedd. Comput. Syst.}%
1257 \def\@permissionCodeOne{1539-9087}%
1258 \or % TELO
1259 \def\@journalName{ACM Transactions on Evolutionary Learning}%
1260 \def\@journalNameShort{ACM Trans. Evol. Learn.}%
1261 \def\@permissionCodeOne{2688-3007}%
1262 \or % THRI
1263 \def\@journalName{ACM Transactions on Human-Robot Interaction}%
1264 \def\@journalNameShort{ACM Trans. Hum.-Robot Interact.}%
1265 \def\@permissionCodeOne{2573-9522}%
1266 \or % TIIS
1267 \def\@journalName{ACM Transactions on Interactive Intelligent Systems}%
1268 \def\@journalNameShort{ACM Trans. Interact. Intell. Syst.}%
1269 \def\@permissionCodeOne{2160-6455}%
1270 \or % TIOT
1271 \def\@journalName{ACM Transactions on Internet of Things}%
1272 \def\@journalNameShort{ACM Trans. Internet Things}%
1273 \def\@permissionCodeOne{2577-6207}%
1274 \or % TISSEC
1275 \def\@journalName{ACM Transactions on Information and System Security}%
1276 \def\@journalNameShort{ACM Trans. Info. Syst. Sec.}%
1277 \def\@permissionCodeOne{1094-9224}%
1278 \or % TIST
1279 \def\@journalName{ACM Transactions on Intelligent Systems and Technology}%
1280 \def\@journalNameShort{ACM Trans. Intell. Syst. Technol.}%
1281 \def\@permissionCodeOne{2157-6904}%

```

```

1282 \or % TKDD
1283 \def\@journalName{ACM Transactions on Knowledge Discovery from Data}%
1284 \def\@journalNameShort{ACM Trans. Knowl. Discov. Data.}%
1285 \def\@permissionCodeOne{1556-4681}%
1286 \or % TMIS
1287 \def\@journalName{ACM Transactions on Management Information Systems}%
1288 \def\@journalNameShort{ACM Trans. Manag. Inform. Syst.}%
1289 \def\@permissionCodeOne{2158-656X}%
1290 \or % TOCE
1291 \def\@journalName{ACM Transactions on Computing Education}%
1292 \def\@journalNameShort{ACM Trans. Comput. Educ.}%
1293 \def\@permissionCodeOne{1946-6226}%
1294 \or % TOCHI
1295 \def\@journalName{ACM Transactions on Computer-Human Interaction}%
1296 \def\@journalNameShort{ACM Trans. Comput.-Hum. Interact.}%
1297 \def\@permissionCodeOne{1073-0516}%
1298 \or % TOCL
1299 \def\@journalName{ACM Transactions on Computational Logic}%
1300 \def\@journalNameShort{ACM Trans. Comput. Logic}%
1301 \def\@permissionCodeOne{1529-3785}%
1302 \or % TOCS
1303 \def\@journalName{ACM Transactions on Computer Systems}%
1304 \def\@journalNameShort{ACM Trans. Comput. Syst.}%
1305 \def\@permissionCodeOne{0734-2071}%
1306 \or % TOCT
1307 \def\@journalName{ACM Transactions on Computation Theory}%
1308 \def\@journalNameShort{ACM Trans. Comput. Theory}%
1309 \def\@permissionCodeOne{1942-3454}%
1310 \or % TODAES
1311 \def\@journalName{ACM Transactions on Design Automation of Electronic Systems}%
1312 \def\@journalNameShort{ACM Trans. Des. Autom. Electron. Syst.}%
1313 \def\@permissionCodeOne{1084-4309}%
1314 \or % TODS
1315 \def\@journalName{ACM Transactions on Database Systems}%
1316 \def\@journalNameShort{ACM Trans. Datab. Syst.}%
1317 \def\@permissionCodeOne{0362-5915}%
1318 \or % TOG
1319 \def\@journalName{ACM Transactions on Graphics}%
1320 \def\@journalNameShort{ACM Trans. Graph.}%
1321 \def\@permissionCodeOne{0730-0301}%
1322 \or % TOIS
1323 \def\@journalName{ACM Transactions on Information Systems}%
1324 \def\@journalNameShort{ACM Trans. Inf. Syst.}%
1325 \def\@permissionCodeOne{1046-8188}%
1326 \or % TOIT
1327 \def\@journalName{ACM Transactions on Internet Technology}%
1328 \def\@journalNameShort{ACM Trans. Internet Technol.}%
1329 \def\@permissionCodeOne{1533-5399}%
1330 \or % TOMACS
1331 \def\@journalName{ACM Transactions on Modeling and Computer Simulation}%
1332 \def\@journalNameShort{ACM Trans. Model. Comput. Simul.}%
1333 \def\@permissionCodeOne{1049-3301}%
1334 \def\@permissionCodeTwo{1558-1195}%
1335 \or % TOMM

```



```

1336 \def\@journalName{ACM Transactions on Multimedia Computing, Communications and Applications}%
1337 \def\@journalNameShort{ACM Trans. Multimedia Comput. Commun. Appl.}%
1338 \def\@permissionCodeOne{1551-6857}%
1339 \def\@permissionCodeTwo{1551-6865}%
1340 \or % TOMPECS
1341 \def\@journalName{ACM Transactions on Modeling and Performance Evaluation of Computing Systems}%
1342 \def\@journalNameShort{ACM Trans. Model. Perform. Eval. Comput. Syst.}%
1343 \def\@permissionCodeOne{2376-3639}%
1344 \or % TOMS
1345 \def\@journalName{ACM Transactions on Mathematical Software}%
1346 \def\@journalNameShort{ACM Trans. Math. Softw.}%
1347 \def\@permissionCodeOne{0098-3500}%
1348 \or % TOPC
1349 \def\@journalName{ACM Transactions on Parallel Computing}%
1350 \def\@journalNameShort{ACM Trans. Parallel Comput.}%
1351 \def\@permissionCodeOne{1539-9087}%
1352 \or % TOPS
1353 \def\@journalName{ACM Transactions on Privacy and Security}%
1354 \def\@journalNameShort{ACM Trans. Priv. Sec.}%
1355 \def\@permissionCodeOne{2471-2566}%
1356 \or % TOPLAS
1357 \def\@journalName{ACM Transactions on Programming Languages and Systems}%
1358 \def\@journalNameShort{ACM Trans. Program. Lang. Syst.}%
1359 \def\@permissionCodeOne{0164-0925}%
1360 \or % TOS
1361 \def\@journalName{ACM Transactions on Storage}%
1362 \def\@journalNameShort{ACM Trans. Storage}%
1363 \def\@permissionCodeOne{1553-3077}%
1364 \or % TOSEM
1365 \def\@journalName{ACM Transactions on Software Engineering and Methodology}%
1366 \def\@journalNameShort{ACM Trans. Softw. Eng. Methodol.}%
1367 \def\@permissionCodeOne{1049-331X}%
1368 \or % TOSN
1369 \def\@journalName{ACM Transactions on Sensor Networks}%
1370 \def\@journalNameShort{ACM Trans. Sensor Netw.}%
1371 \def\@permissionCodeOne{1550-4859}%
1372 \or % TQC
1373 \def\@journalName{ACM Transactions on Quantum Computing}%
1374 \def\@journalNameShort{ACM Trans. Quantum Comput.}%
1375 \def\@permissionCodeOne{2643-6817}%
1376 \or % TRET
1377 \def\@journalName{ACM Transactions on Reconfigurable Technology and Systems}%
1378 \def\@journalNameShort{ACM Trans. Reconfig. Technol. Syst.}%
1379 \def\@permissionCodeOne{1936-7406}%
1380 \or % TSAS
1381 \def\@journalName{ACM Transactions on Spatial Algorithms and Systems}%
1382 \def\@journalNameShort{ACM Trans. Spatial Algorithms Syst.}%
1383 \def\@permissionCodeOne{2374-0353}%
1384 \or % TSC
1385 \def\@journalName{ACM Transactions on Social Computing}%
1386 \def\@journalNameShort{ACM Trans. Soc. Comput.}%
1387 \def\@permissionCodeOne{2469-7818}%
1388 \or % TSLP
1389 \def\@journalName{ACM Transactions on Speech and Language Processing}%

```

```

1390 \def\@journalNameShort{ACM Trans. Speech Lang. Process.}%
1391 \def\@permissionCodeOne{1550-4875}%
1392 \or % TWEB
1393 \def\@journalName{ACM Transactions on the Web}%
1394 \def\@journalNameShort{ACM Trans. Web}%
1395 \def\@permissionCodeOne{1559-1131}%
1396 \else % FACMP, a dummy journal
1397 \def\@journalName{ACM Just Accepted}%
1398 \def\@journalNameShort{ACM Accepted}%
1399 \def\@permissionCodeOne{XXXX-XXXX}%
1400 \fi
1401 \ClassInfo{\@classname}{Using journal code \@journalCode}%
1402 }{%
1403 \ClassError{\@classname}{Incorrect journal #1}%
1404 }%

```

`\acmJournal` And the syntactic sugar around it

```

1405 \def\acmJournal#1{\setkeys{ACM}{acmJournal=#1}%
1406 \global\@ACM@journal@bibstriptrue}

```

The defaults:

```

1407 \def\@journalCode@nr{0}
1408 \def\@journalName{}%
1409 \def\@journalNameShort{\@journalName}%
1410 \def\@permissionCodeOne{XXXX-XXXX}%
1411 \def\@permissionCodeTwo{}%

```

`\acmConference` This is the conference command

```

1412 \newcommand\acmConference[4][{}%
1413 \gdef\acmConference@shortname{#1}%
1414 \gdef\acmConference@name{#2}%
1415 \gdef\acmConference@date{#3}%
1416 \gdef\acmConference@venue{#4}%
1417 \ifx\acmConference@shortname\@empty
1418 \gdef\acmConference@shortname{#2}%
1419 \fi
1420 \global\@ACM@journal@bibstripfalse
1421 }
1422 \if@ACM@journal\else
1423 \acmConference[Conference'17]{ACM Conference}{July 2017}{Washington,
1424 DC, USA}%
1425 \fi

```

`\acmBooktitle` The book title of the conference:

```

\@acmBooktitle 1426 \def\acmBooktitle#1{\gdef\@acmBooktitle{#1}}
1427 \acmBooktitle{}
1428 \ifx\acmConference@name\undefined\else
1429 \acmBooktitle{Proceedings of \acmConference@name
1430 \ifx\acmConference@name\acmConference@shortname\else
1431 \ (\acmConference@shortname)\fi}
1432 \fi

```

`\@editorsAbbrev` How to abbreviate editors

```

1433 \def\@editorsAbbrev{(Ed.)}

```

```

\@acmEditors The list of editors
1434 \def\@acmEditors{}

\editor Add a new editor to the list
1435 \def\editor#1{\ifx\@acmEditors\@empty
1436     \gdef\@acmEditors{#1}%
1437 \else
1438     \gdef\@editorsAbbrev{(Eds.)}%
1439     \g@addto@macro\@acmEditors{\and#1}%
1440 \fi}

\subtitle The subtitle macro
1441 \def\subtitle#1{\def\@subtitle{#1}}
1442 \subtitle{}

\num@authorgroups The total number of “groups”. Each group is several authors with the same affiliations(s)
1443 \newcount\num@authorgroups
1444 \num@authorgroups=0\relax

\num@author The total number of authors
1445 \newcount\num@author The total number of authors
1446 \num@author=0\relax

\if@insideauthorgroup Whether we are continuing an author group
1447 \newif\if@insideauthorgroup
1448 \@insideauthorgroupfalse

\author Adding an author to the list of authors and addresses.
    Note that we want to typeset the link to the author’s orcid if known. The problem
    is, we know the orcid only after the author is entered. The trick is based on the idea
    that \csname... \endcsname is \relax unless defined. Therefore we typeset authors by
    the special macro \csname typeset@author\the\num@author The total number of authors \endcsname, which is
    defined by \orcid command.
1449 \renewcommand\author[2][{}%
1450 \IfSubStr{\detokenize{#2}}{,}{\ClassWarning{\@classname}{Do not put several
1451     authors in the same \string\author\space macro!}}{}%
1452 \global\advance\num@author The total number of authors by 1\relax
1453 \if@insideauthorgroup\else
1454     \global\advance\num@authorgroups by 1\relax
1455     \global\@insideauthorgrouptrue
1456 \fi
1457 \ifx\addresses\@empty
1458     \if@ACM@anonymous
1459         \gdef\addresses{\@author{Anonymous Author(s)}%
1460             \ifx\@acmSubmissionID\@empty\else\Submission Id:
1461                 \@acmSubmissionID\fi}}%
1462         \gdef\authors{Anonymous Author(s)}%
1463     \else
1464         \expandafter\gdef\expandafter\addresses\expandafter{%
1465             \expandafter\@author\expandafter{%
1466                 \csname typeset@author\the\num@author The total number of authors \endcsname{#2}}}%
1467         \gdef\authors{#2}%
1468     \fi

```

```

1469 \else
1470   \if@ACM@anonymous\else
1471     \expandafter\g@addto@macro\expandafter\addresses\expandafter{%
1472       \expandafter\and\expandafter\@author\expandafter{%
1473         \csname typeset@author\the\num@authors\endcsname{#2}}}%
1474     \g@addto@macro\authors{\and#2}%
1475   \fi
1476 \fi
1477 \if@ACM@anonymous
1478   \ifx\shortauthors\@empty
1479     \gdef\shortauthors{Anon.
1480       \ifx\@acmSubmissionID\@empty\else Submission Id:
1481         \@acmSubmissionID\fi}%
1482   \fi
1483 \else
1484   \def\@tempa{#1}%
1485   \ifx\@tempa\@empty
1486     \ifx\shortauthors\@empty
1487       \gdef\shortauthors{#2}%
1488     \else
1489       \g@addto@macro\shortauthors{\and#2}%
1490     \fi
1491   \else
1492     \ifx\shortauthors\@empty
1493       \gdef\shortauthors{#1}%
1494     \else
1495       \g@addto@macro\shortauthors{\and#1}%
1496     \fi
1497   \fi
1498 \fi}

```

`\affiliation` The macro `\affiliation` mimics `\address` from `amsart`. Note that it has an optional argument, which we use differently from `amsart`.

```

1499 \newcommand{\affiliation}[2][{}]{%
1500   \global\@insideauthorgroupfalse
1501   \if@ACM@anonymous\else
1502     \g@addto@macro\addresses{\affiliation{#1}{#2}}%
1503   \fi}

```

`\ACM@affiliation@obeypunctuation` Whether to use the author's punctuation (false by default, which adds American-style address punctuation)

```

1504 \define@boolkey+{@ACM@affiliation@}[@ACM@affiliation@]{obeypunctuation}%
1505 [true]{\ClassError{\@classname}{The option obeypunctuation can be either true or false}}

```

`\additionalaffiliation` Additional affiliations go to footnotes

```

1506 \def\additionalaffiliation#1{\authornote{\@additionalaffiliation{#1}}}

```

`\@additionalaffiliation` Process `\additionalaffiliation` inside `\authornote`

```

1507 \def\@additionalaffiliation#1{\bgroup
1508   \def\position##1{\ignorespaces}%
1509   \def\institution##1{##1\ignorespaces}%
1510   \def\department{\@ifnextchar[{\@department}{\@department[]}}%
1511   \def\@department[##1]##2{\unskip, ##2\ignorespaces}%

```

```

1512 \let\streetaddress\position
1513 \let\city\position
1514 \let\state\position
1515 \let\postcode\position
1516 \let\country\position
1517 Also with #1\unskip.\egroup}

```

`\email` The macro `\email` mimics `\email` from `amsart`. Again, it has an optional argument that we do not currently need but keep for possible future use.

```

1518 \renewcommand{\email}[2][]{%
1519 \IfSubStr{#2}{,}{\ClassWarning{\@classname}{Do not put several
1520 addresses in the same \string\email\space macro!}}{%
1521 \if@ACM@anonymous\else
1522 \g@addto@macro\addresses{\email{#1}{#2}}%
1523 \fi}

```

`\orcid` We redefine the command to typeset the current author

```

1524 \def\orcid#1{\unskip\ignorespaces%
1525 \IfBeginWith{#1}{http}{%
1526 \expandafter\gdef\csname
1527 typeset@author\the\num@authors\endcsname##1{%
1528 \href{#1}{##1}}}%
1529 \expandafter\gdef\csname
1530 typeset@author\the\num@authors\endcsname##1{%
1531 \href{https://orcid.org/#1}{##1}}}

```

`\authorsaddresses` Setting up authors' addresses

```

1532 \def\authorsaddresses#1{\def\@authorsaddresses{#1}}
1533 \authorsaddresses{\@mkauthorsaddresses}

```

`\@mktranslatedkeywords` We have two argument: the language to typeset keywords and the keywords.

```

1534 \newcommand{\@mktranslatedkeywords}[2]{\bgroup
1535 \selectlanguage{#1}%
1536 {\@specialsection{\keywordsname}%
1537 \noindent#2\par}\egroup}

```

`\@titlenotes` The title notes

```

1538 \def\@titlenotes{}

```

`\titlenote` Adding a note to the title

```

1539 \def\titlenote#1{%
1540 \g@addto@macro\@title{\footnotemark}%
1541 \if@ACM@anonymous
1542 \g@addto@macro\@titlenotes{%
1543 \stepcounter{footnote}\footnotetext{Title note}}%
1544 \else
1545 \g@addto@macro\@titlenotes{\stepcounter{footnote}\footnotetext{#1}}%
1546 \fi}

```

`\@subtitlenotes` The subtitle notes

```

1547 \def\@subtitlenotes{}

```

`\subtitlenote` Adding a note to the subtitle

```
1548 \def\subtitlenote#1{%
1549   \g@addto@macro\@subtitle{\footnotemark}%
1550   \if@ACM@anonymous
1551     \g@addto@macro\@subtitlenotes{%
1552       \stepcounter{footnote}\footnotetext{Subtitle note}}%
1553   \else
1554     \g@addto@macro\@subtitlenotes{%
1555       \stepcounter{footnote}\footnotetext{#1}}%
1556   \fi}
```

`\@authornotes` The author notes

```
1557 \def\@authornotes{}
```

`\authornote` Adding a note to the author

```
1558 \def\authornote#1{%
1559   \if@ACM@anonymous\else
1560     \g@addto@macro\addresses{\@authornotemark}%
1561     \g@addto@macro\@authornotes{%
1562       \stepcounter{footnote}\footnotetext{#1}}%
1563   \fi}
```

`\authornotemark` Adding a footnote mark to the authors

```
1564 \newcommand\authornotemark[1][\relax]{%
1565   \ifx#1\relax\relax\relax
1566     \g@addto@macro\addresses{\@authornotemark}%
1567   \else
1568     \g@addto@macro\addresses{\@authornotemark{#1}}%
1569   \fi}
```

`\acmVolume` The current volume

```
1570 \def\acmVolume#1{\def\@acmVolume{#1}}
1571 \acmVolume{1}
```

`\acmNumber` The current number

```
1572 \def\acmNumber#1{\def\@acmNumber{#1}}
1573 \acmNumber{1}
```

`\acmArticle` The current article

```
1574 \def\acmArticle#1{\def\@acmArticle{#1}}
1575 \acmArticle{}
```

`\acmArticleSeq` The sequence number

```
1576 \def\acmArticleSeq#1{\def\@acmArticleSeq{#1}}
1577 \acmArticleSeq{\@acmArticle}
```

`\acmYear` The current year

```
1578 \def\acmYear#1{\def\@acmYear{#1}}
1579 \acmYear{\the\year}
```

`\acmMonth` The current month

```
1580 \def\acmMonth#1{\def\@acmMonth{#1}}
1581 \acmMonth{\the\month}
```

`\acmPubDate` The publication date

```

1582 \def\acmPubDate{\ifcase\acmMonth\or
1583   January\or February\or March\or April\or May\or June\or
1584   July\or August\or September\or October\or November\or
1585   December\fi~\acmYear}

```

`\acmPrice` The price

```

1586 \def\acmPrice#1{\def\acmPrice{#1}}
1587 \acmPrice{15.00}

```

`\acmSubmissionID` The submission ID

```

1588 \def\acmSubmissionID#1{\def\acmSubmissionID{#1}}
1589 \acmSubmissionID{}

```

`\acmISBN` The book ISBN

```

1590 \def\acmISBN#1{\def\acmISBN{#1}}
1591 \acmISBN{978-x-xxxx-xxxx-x/YY/MM}

```

`\acmDOI` The paper DOI

```

1592 \def\acmDOI#1{\def\acmDOI{#1}}
1593 \acmDOI{10.1145/nnnnnnn.nnnnnnn}

```

`\if@ACM@badge` Whether to print a badge. Note that either a left or right badge triggers it:

```

1594 \newif\if@ACM@badge
1595 \@ACM@badgefalse

```

`\@ACM@badge@width` The width of the badge

```

1596 \newlength\@ACM@badge@width
1597 \setlength\@ACM@badge@width{5pc}

```

`\@ACM@title@width` The width of the badge

```

1598 \newlength\@ACM@title@width

```

`\@ACM@badge@skip` The space between the badge and the title

```

1599 \newlength\@ACM@badge@skip
1600 \setlength\@ACM@badge@skip{1pc}

```

`\acmBadgeR` Setting the right badge

```

1601 \newcommand\acmBadgeR[2][\@ACM@badgetrue
1602   \def\acmBadgeR@url{#1}%
1603   \def\acmBadgeR@image{#2}}
1604 \def\acmBadgeR@url{}
1605 \def\acmBadgeR@image{}

```

`\acmBadgeL` Setting the left badge

```

1606 \newcommand\acmBadgeL[2][\@ACM@badgetrue
1607   \def\acmBadgeL@url{#1}%
1608   \def\acmBadgeL@image{#2}}
1609 \def\acmBadgeL@url{}
1610 \def\acmBadgeL@image{}

```

`\startPage` The start page of the paper

```
1611 \def\startPage#1{\def\@startPage{#1}}
1612 \startPage{}
```

`\terms` Terms are obsolete. We use CCS now.

```
1613 \def\terms#1{\ClassWarning{\@classname}{The command \string\terms{} is
1614   obsolete. I am going to ignore it}}
```

`\keywords` Keywords are mostly obsolete. We use CCS now. Still it makes sense to keep them for compatibility.

```
1615 \def\keywords#1{\def\@keywords{#1}}
1616 \let\@keywords\@empty

1617 \AtEndDocument{\if@ACM@nonacm\else\ifx\@keywords\@empty
1618   \ifnum\getrefnumber{TotPages}>2\relax
1619   \ClassWarningNoLine{\@classname}{ACM keywords are mandatory
1620     for papers over two pages}%
1621   \fi\fi\fi}
```

`abstract` The amsart package puts abstract in a box. Since we do not know whether we will use two-column mode, we prefer to save the text

```
1622 \renewenvironment{abstract}{\Collect@Body\@saveabstract}{}
```

`\@saveabstract` And saving the abstract

```
1623 \long\def\@saveabstract#1{\if@ACM@maketitle@typeset
1624   \ClassError{\@classname}{Abstract must be defined before maketitle
1625     command. Please move it!}\fi
1626   \long\gdef\@abstract{#1}}
1627 \@saveabstract{}
```

`\@empty` The long version of `\@empty` (to compare with `\@abstract`)

```
1628 \long\def\@empty{}
```

`\if@ACM@printccs` Whether to print CCS

```
1629 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printccs}[true]{%
1630   \if@ACM@printccs
1631     \ClassInfo{\@classname}{Printing CCS}%
1632   \else
1633     \ClassInfo{\@classname}{Suppressing CCS}%
1634   \fi}{\ClassError{\@classname}{The option printccs can be either true or false}}
```

`\if@ACM@printacmref` Whether to print the ACM bibstrip

```
1635 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printacmref}[true]{%
1636   \if@ACM@printacmref
1637     \ClassInfo{\@classname}{Printing bibformat}%
1638   \else
1639     \ClassInfo{\@classname}{Suppressing bibformat}%
1640   \fi}{\ClassError{\@classname}{The option printacmref can be either true or false}}

1641 \AtEndDocument{\if@ACM@nonacm\else\if@ACM@printacmref\else
1642   \ifnum\getrefnumber{TotPages}>1\relax
1643   \ClassWarningNoLine{\@classname}{%
1644     ACM reference format is mandatory \MessageBreak
```



```

1645     for papers over one page. \MessageBreak
1646     Please add printacmref=true to the \MessageBreak
1647     \string\settopmatter\space command.}%
1648 \fi\fi\fi}

```

`\if@ACM@printfolios` Whether to print folios

```

1649 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printfolios}[true]{%
1650 \if@ACM@printfolios
1651 \ClassInfo{\@classname}{Printing folios}%
1652 \else
1653 \ClassInfo{\@classname}{Suppressing folios}%
1654 \fi}{\ClassError{\@classname}{The option printfolios can be either true or false}}

```

`\@ACM@authorssperrow` The number of authors per row. 0 means use the default algorithm.

```

1655 \define@cmdkey{@ACM@topmatter@}[@ACM@]{authorssperrow}[0]{%
1656 \IfInteger{#1}{\ClassInfo{\@classname}{Setting authorssperrow to
1657 #1}}{\ClassWarning{\@classname}{The parameter authorssperrow must be
1658 numerical. Ignoring the input #1}}\gdef\@ACM@authorssperrow{0}}

```

`\settopmatter` The usual syntactic sugar

```

1659 \def\settopmatter#1{\setkeys{@ACM@topmatter@}{#1}}

```

Now the settings

```

1660 \settopmatter{printccs=true, printacmref=true}
1661 \if@ACM@manuscript
1662 \settopmatter{printfolios=true}
1663 \else
1664 \if@ACM@journal
1665 \settopmatter{printfolios=true}
1666 \else
1667 \settopmatter{printfolios=false}
1668 \fi
1669 \fi
1670 \settopmatter{authorssperrow=0}

```

`\@received` The container for the paper history

```

1671 \def\@received{}

```

`\received` The `\received` command

```

1672 \newcommand\received[2][\def\@tempa{#1}%
1673 \ifx\@tempa\@empty
1674 \ifx\@received\@empty
1675 \gdef\@received{Received #2}%
1676 \else
1677 \g@addto@macro{\@received}{; revised #2}%
1678 \fi
1679 \else
1680 \ifx\@received\@empty
1681 \gdef\@received{#1 #2}%
1682 \else
1683 \g@addto@macro{\@received}{; #1 #2}%
1684 \fi
1685 \fi}

```

```

1686 \AtEndDocument{%
1687   \ifx\@received\@empty\else
1688     \par\bigskip\noindent\small\normalfont\@received\par
1689   \fi}

```

\acmArticleType Article type. We set up the color.

```

1690 \define@choicekey+{ACM}{articletype}[\ACM@ArticleType\ACM@ArticleType@nr]{%
1691   Research,Review,Discussion,Invited,Position}[Review]{%
1692   \ifcase\ACM@ArticleType@nr
1693     \relax % Research
1694     \colorlet{@ACM@Article@color}{ACMBlue}%
1695     \or % Review
1696     \colorlet{@ACM@Article@color}{ACMOrange}%
1697     \or % Discussion
1698     \colorlet{@ACM@Article@color}{ACMGreen}%
1699     \or % Invited
1700     \colorlet{@ACM@Article@color}{ACMPurple}%
1701     \or % Position
1702     \colorlet{@ACM@Article@color}{ACMRed}%
1703   \fi
1704 }{%
1705 \ClassError{\@classname}{Article Type must be Research, Review,\MessageBreak
1706   Discussion, Invited, or Position}}
1707 \def\acmArticleType#1{\setkeys{ACM}{articletype=#1}}
1708 \newenvironment{@ACM@color@frame}{%
1709   \def\FrameCommand{\hspace*{-6.5pc}}%
1710   \colorbox{@ACM@Article@color!10!white}}%
1711   \MakeFramed {\advance\hsize -6.5pc\relax\FrameRestore}}{\endMakeFramed}
1712 \if@ACM@acmcp
1713 \acmArticleType{Research}%
1714 \fi

```

\acmCodeLink The code link

```

1715 \def\acmCodeLink#1{%
1716   \ifx\@acmCodeDataLink\@empty
1717     \gdef\@acmCodeDataLink{\url{#1}}%
1718   \else
1719     \g@addto@macro{\@acmCodeDataLink}{\ \url{#1}}%
1720   \fi}
1721 \def\@acmCodeDataLink{}

```

\acmDataLink The code link

```

1722 \let\acmDataLink\acmCodeLink

```

3.17 Concepts system

We exclude CCSXML stuff generated by the ACM system:

```

1723 \RequirePackage{comment}
1724 \excludecomment{CCSXML}

```

\@concepts This is the storage macro and counter for concepts

```

1725 \let\@concepts\@empty
1726 \newcounter{@concepts}

```

\ccsdesc The first argument is the significance, the second is the concept(s)

```
1727 \newcommand\ccsdesc[2][100]{%
1728   \ccsdesc@parse#1~#2~~\ccsdesc@parse@end}
```

\ccsdesc@parse The parser of the expression Significance~General~Specific (we need textcomp for \textrightarrow). Note that Specific can be empty!

```
1729 \def\textrightarrow{$\rightarrow$}
1730 \def\ccsdesc@parse#1~#2~#3~{%
1731   \stepcounter{@concepts}%
1732   \expandafter\ifx\csname CCS@General@#2\endcsname\relax
1733     \expandafter\gdef\csname CCS@General@#2\endcsname{\textbullet\
1734       \textbf{#2}}%
1735     \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{;}%
1736     \expandafter\gdef\csname CCS@Specific@#2\endcsname{}%
1737     \g@addto@macro{\@concepts}{\csname CCS@General@#2\endcsname
1738       \csname CCS@Punctuation@#2\endcsname
1739       \csname CCS@Specific@#2\endcsname}%
1740     \fi
1741     \ifx#3\relax\relax\else
1742       \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{
1743         \textrightarrow\ }%
1744       \expandafter\g@addto@macro\expandafter{\csname CCS@Specific@#2\endcsname}{%
1745         \addtocounter{@concepts}{-1}%
1746         \ifnum#1>499\textbf{#3}\else
1747         \ifnum#1>299\textit{#3}\else
1748         #3\fi\fi\ifnum\value{@concepts}=0.\else; \fi}%
1749       \fi
1750 \ccsdesc@parse@finish}

1751 \AtEndDocument{\if@ACM@nonacm\else\ifx\@concepts\empty\relax
1752   \ifnum\getrefnumber{TotPages}>2\relax
1753   \ClassWarningNoLine{\@classname}{CCS concepts are mandatory
1754     for papers over two pages}%
1755   \fi\fi\fi}
```

\ccdesc@parse@finish Gobble everything to \ccsdesc@parse@end

```
1756 \def\ccsdesc@parse@finish#1\ccsdesc@parse@end{}
```

3.18 Copyright system

This is from acmcopyright.sty

\if@printcopyright Whether to print a copyright symbol

```
1757 \newif\if@printcopyright
1758 \@printcopyrighttrue
```

\if@printpermission Whether to print the permission block

```
1759 \newif\if@printpermission
1760 \@printpermissiontrue
```

\if@acmowned Whether the ACM owns the rights to the paper

```
1761 \newif\if@acmowned
1762 \@acmownedtrue
```

Keys:

```

1763 \define@choicekey*{ACM@}{acmcopyrightmode}[%
1764   \acm@copyrightinput\acm@copyrightmode]{none,%
1765     acmcopyright,acmlicensed,rightsretained,%
1766     usgov,usgovmixed,cagov,cagovmixed,licensedusgovmixed,%
1767     licensedcagov,licensedcagovmixed,othergov,licensedothergov,%
1768     iw3c2w3,iw3c2w3g,cc}{%
1769   \@printpermissiontrue
1770   \@printcopyrighttrue
1771   \@acmownedtrue
1772   \ifnum\acm@copyrightmode=0\relax % none
1773     \@printpermissionfalse
1774     \@printcopyrightfalse
1775     \@acmownedfalse
1776   \fi
1777   \ifnum\acm@copyrightmode=2\relax % acmlicensed
1778     \@acmownedfalse
1779   \fi
1780   \ifnum\acm@copyrightmode=3\relax % rightsretained
1781     \@acmownedfalse
1782     \AtBeginDocument{\acmPrice{}}%
1783   \fi
1784   \ifnum\acm@copyrightmode=4\relax % usgov
1785     \@printpermissiontrue
1786     \@printcopyrightfalse
1787     \@acmownedfalse
1788     \AtBeginDocument{\acmPrice{}}%
1789   \fi
1790   \ifnum\acm@copyrightmode=6\relax % cagov
1791     \@acmownedfalse
1792   \fi
1793   \ifnum\acm@copyrightmode=8\relax % licensedusgovmixed
1794     \@acmownedfalse
1795   \fi
1796   \ifnum\acm@copyrightmode=9\relax % licensedcagov
1797     \@acmownedfalse
1798   \fi
1799   \ifnum\acm@copyrightmode=10\relax % licensedcagovmixed
1800     \@acmownedfalse
1801   \fi
1802   \ifnum\acm@copyrightmode=11\relax % othergov
1803     \@acmownedtrue
1804   \fi
1805   \ifnum\acm@copyrightmode=12\relax % licensedothergov
1806     \@acmownedfalse
1807   \fi
1808   \ifnum\acm@copyrightmode=13\relax % iw3c2w3
1809     \@acmownedfalse
1810     \AtBeginDocument{\acmPrice{}}%
1811   \fi
1812   \ifnum\acm@copyrightmode=14\relax % iw3c2w3g
1813     \@acmownedfalse
1814     \AtBeginDocument{\acmPrice{}}%
1815   \fi

```

```

1816 \ifnum\acm@copyrightmode=15\relax % cc
1817 \@acmownedfalse
1818 \AtBeginDocument{\acmPrice{}}%
1819 \fi}

```

\setcopyright This is the syntactic sugar around setting keys.

```

1820 \def\setcopyright#1{\setkeys{ACM@}{acmcopyrightmode=#1}}
1821 \setcopyright{acmcopyright}

```

\setcctype The type of Creative Commons license used

```

1822 \newcommand\setcctype[2][4.0]{%
1823 \def\ACM@cc@version{#1}%
1824 \def\ACM@cc@type{#2}}
1825 \setcctype{by}

```

\@copyrightowner Here is the owner of the copyright

```

1826 \def\@copyrightowner{%
1827 \ifcase\acm@copyrightmode\relax % none
1828 \or % acmcopyright
1829 Association for Computing Machinery.
1830 \or % acmlicensed
1831 Copyright held by the owner/author(s). Publication rights licensed to
1832 ACM\@.
1833 \or % rightsretained
1834 Copyright held by the owner/author(s).
1835 \or % usgov
1836 \or % usgovmixed
1837 Association for Computing Machinery.
1838 \or % cagov
1839 Crown in Right of Canada.
1840 \or %cagovmixed
1841 Association for Computing Machinery.
1842 \or %licensedusgovmixed
1843 Copyright held by the owner/author(s). Publication rights licensed to
1844 ACM\@.
1845 \or % licensedcagov
1846 Crown in Right of Canada. Publication rights licensed to
1847 ACM\@.
1848 \or %licensedcagovmixed
1849 Copyright held by the owner/author(s). Publication rights licensed to
1850 ACM\@.
1851 \or % othergov
1852 Association for Computing Machinery.
1853 \or % licensedothergov
1854 Copyright held by the owner/author(s). Publication rights licensed to
1855 ACM\@.
1856 \or % ic2w3www
1857 IW3C2 (International World Wide Web Conference Committee), published
1858 under Creative Commons CC-BY~4.0 License.
1859 \or % ic2w3wwwgoogle
1860 IW3C2 (International World Wide Web Conference Committee), published
1861 under Creative Commons CC-BY-NC-ND~4.0 License.
1862 \or % cc
1863 Copyright held by the owner/author(s).

```

1864 \fi}

\@formatdoi Print a clickable DOI

1865 \def\@formatdoi#1{\url{https://doi.org/#1}}

\@ACM@copyright@check@cc At present cC licenses can be used only for acmengage format or for non-acm stuff. This macro checks whether the CC license is applicable and generates an error if not.

```
1866 \def\@ACM@copyright@check@cc{%
1867   \if@ACM@nonacm
1868     \ClassInfo{\@classname}{Using CC license with a non-acm
1869       material}%
1870   \else
1871     \if@ACM@engage
1872       \ClassInfo{\@classname}{Using CC license with ACM Engage
1873         material}%
1874     \else
1875       \ClassError{\@classname}{%
1876         Sorry, Creative Commons licenses are\MessageBreak
1877         currently not used with ACM publications\MessageBreak
1878         typeset by the authors}{Please use nonacm
1879         option or ACM Engage class to enable CC licenses}%
1880     \fi
1881 \fi}
```

\@copyrightpermission The canned permission block.

```
1882 \def\@copyrightpermission{%
1883   \ifcase\acm@copyrightmode\relax % none
1884   \or % acmcopyright
1885     Permission to make digital or hard copies of all or part of this
1886     work for personal or classroom use is granted without fee provided
1887     that copies are not made or distributed for profit or commercial
1888     advantage and that copies bear this notice and the full citation on
1889     the first page. Copyrights for components of this work owned by
1890     others than ACM must be honored. Abstracting with credit is
1891     permitted. To copy otherwise, or republish, to post on servers or to
1892     redistribute to lists, requires prior specific permission
1893     and\hspace*{.5pt}/or a fee. Request permissions from
1894     permissions@acm.org.
1895   \or % acmlicensed
1896     Permission to make digital or hard copies of all or part of this
1897     work for personal or classroom use is granted without fee provided
1898     that copies are not made or distributed for profit or commercial
1899     advantage and that copies bear this notice and the full citation on
1900     the first page. Copyrights for components of this work owned by
1901     others than the author(s) must be honored. Abstracting with credit
1902     is permitted. To copy otherwise, or republish, to post on servers
1903     or to redistribute to lists, requires prior specific permission
1904     and\hspace*{.5pt}/or a fee. Request permissions from
1905     permissions@acm.org.
1906   \or % rightsretained
1907     Permission to make digital or hard copies of part or all of this work
1908     for personal or classroom use is granted without fee provided that
1909     copies are not made or distributed for profit or commercial advantage
1910     and that copies bear this notice and the full citation on the first
```

1911 page. Copyrights for third-party components of this work must be
 1912 honored. For all other uses, contact the
 1913 owner\hspace*{.5pt}/author(s).
 1914 \or % usgov
 1915 This paper is authored by an employee(s) of the United States
 1916 Government and is in the public domain. Non-exclusive copying or
 1917 redistribution is allowed, provided that the article citation is
 1918 given and the authors and agency are clearly identified as its
 1919 source.
 1920 \or % usgovmixed
 1921 ACM acknowledges that this contribution was authored or co-authored
 1922 by an employee, contractor, or affiliate of the United States
 1923 government. As such, the United States government retains a
 1924 nonexclusive, royalty-free right to publish or reproduce this
 1925 article, or to allow others to do so, for government purposes only.
 1926 \or % cagov
 1927 This article was authored by employees of the Government of Canada.
 1928 As such, the Canadian government retains all interest in the
 1929 copyright to this work and grants to ACM a nonexclusive,
 1930 royalty-free right to publish or reproduce this article, or to allow
 1931 others to do so, provided that clear attribution is given both to
 1932 the authors and the Canadian government agency employing them.
 1933 Permission to make digital or hard copies for personal or classroom
 1934 use is granted. Copies must bear this notice and the full citation
 1935 on the first page. Copyrights for components of this work owned by
 1936 others than the Canadian Government must be honored. To copy
 1937 otherwise, distribute, republish, or post, requires prior specific
 1938 permission and\hspace*{.5pt}/or a fee. Request permissions from
 1939 permissions@acm.org.
 1940 \or % cagovmixed
 1941 ACM acknowledges that this contribution was co-authored by an
 1942 affiliate of the national government of Canada. As such, the Crown
 1943 in Right of Canada retains an equal interest in the copyright.
 1944 Reprints must include clear attribution to ACM and the author's
 1945 government agency affiliation. Permission to make digital or hard
 1946 copies for personal or classroom use is granted. Copies must bear
 1947 this notice and the full citation on the first page. Copyrights for
 1948 components of this work owned by others than ACM must be honored.
 1949 To copy otherwise, distribute, republish, or post, requires prior
 1950 specific permission and\hspace*{.5pt}/or a fee. Request permissions
 1951 from permissions@acm.org.
 1952 \or % licensedusgovmixed
 1953 Publication rights licensed to ACM\@. ACM acknowledges that this
 1954 contribution was authored or co-authored by an employee, contractor
 1955 or affiliate of the United States government. As such, the
 1956 Government retains a nonexclusive, royalty-free right to publish or
 1957 reproduce this article, or to allow others to do so, for Government
 1958 purposes only.
 1959 \or % licensedcagov
 1960 This article was authored by employees of the Government of Canada.
 1961 As such, the Canadian government retains all interest in the
 1962 copyright to this work and grants to ACM a nonexclusive,
 1963 royalty-free right to publish or reproduce this article, or to allow
 1964 others to do so, provided that clear attribution is given both to

1965 the authors and the Canadian government agency employing them.

1966 Permission to make digital or hard copies for personal or classroom

1967 use is granted. Copies must bear this notice and the full citation

1968 on the first page. Copyrights for components of this work owned by

1969 others than the Canadian Government must be honored. To copy

1970 otherwise, distribute, republish, or post, requires prior specific

1971 permission and\hspace*{.5pt}/or a fee. Request permissions from

1972 permissions@acm.org.

1973 \or % licensedcagovmixed

1974 Publication rights licensed to ACM\@. ACM acknowledges that this

1975 contribution was authored or co-authored by an employee, contractor

1976 or affiliate of the national government of Canada. As such, the

1977 Government retains a nonexclusive, royalty-free right to publish or

1978 reproduce this article, or to allow others to do so, for Government

1979 purposes only.

1980 \or % othergov

1981 ACM acknowledges that this contribution was authored or co-authored

1982 by an employee, contractor or affiliate of a national government. As

1983 such, the Government retains a nonexclusive, royalty-free right to

1984 publish or reproduce this article, or to allow others to do so, for

1985 Government purposes only.

1986 \or % licensedothergov

1987 Publication rights licensed to ACM\@. ACM acknowledges that this

1988 contribution was authored or co-authored by an employee, contractor

1989 or affiliate of a national government. As such, the Government

1990 retains a nonexclusive, royalty-free right to publish or reproduce

1991 this article, or to allow others to do so, for Government purposes

1992 only.

1993 \or % iw3c2w3

1994 This paper is published under the Creative Commons Attribution~4.0

1995 International (CC-BY~4.0) license. Authors reserve their rights to

1996 disseminate the work on their personal and corporate Web sites with

1997 the appropriate attribution.

1998 \or % iw3c2w3g

1999 This paper is published under the Creative Commons

2000 Attribution-NonCommercial-NoDerivs~4.0 International

2001 (CC-BY-NC-ND~4.0) license. Authors reserve their rights to

2002 disseminate the work on their personal and corporate Web sites with

2003 the appropriate attribution.

2004 \or % CC

2005 \@ACM@copyright@check@cc

2006 \IfEq{\ACM@cc@type}{zero}{%

2007 \def\ACM@CC@Url{https://creativecommons.org/publicdomain/zero/1.0/legalcode}}{%

2008 \edef\ACM@CC@Url{https://creativecommons.org/licenses/\ACM@cc@type/\ACM@cc@version/legalcode}}%

2009 \href{\ACM@CC@Url}{\includegraphics[height=5ex]{doclicense-CC-\ACM@cc@type-88x31}}\%

2010 \href{\ACM@CC@Url}{%

2011 This work is licensed under a Creative Commons

2012 \IfEq{\ACM@cc@type}{zero}{CC0 1.0 Universal}{%

2013 \IfEq{\ACM@cc@type}{by}{Attribution}{}%

2014 \IfEq{\ACM@cc@type}{by-sa}{Attribution-ShareAlike}{}%

2015 \IfEq{\ACM@cc@type}{by-nd}{Attribution-NoDerivatives}{}%

2016 \IfEq{\ACM@cc@type}{by-nc}{Attribution-NonCommercial}{}%

2017 \IfEq{\ACM@cc@type}{by-nc-sa}{Attribution-NonCommercial-ShareAlike}{}%

2018 \IfEq{\ACM@cc@type}{by-nc-nd}{Attribution-NonCommercial-NoDerivatives}{}%


```

2019 ~\IfEq{\ACM@cc@version}{4.0}{4.0 International}{3.0 Unported}%
2020 }
2021 License.}%
2022 \fi}

```

`\copyrightyear` By default, the copyright year is the same as `\acmYear`, but one can override this:

```

2023 \def\copyrightyear#1{\def\@copyrightyear{#1}}
2024 \copyrightyear{\@acmYear}

```

`\@teaserfigures` The teaser figures container

```

2025 \def\@teaserfigures{}

```

`teaserfigure` The teaser figure

```

2026 \newenvironment{teaserfigure}{\Collect@Body\@saveteaser}{}

```

`\@saveteaser` Saving the teaser

```

2027 \long\def\@saveteaser#1{\g@addto@macro\@teaserfigures{\@teaser{#1}}}

```

`\thanks` We redefine `amsart \thanks` so the anonymous key works

```

2028 \renewcommand{\thanks}[1]{%
2029   \ifnotempty{#1}{%
2030     \if@ACM@anonymous
2031       \g@addto@macro\thankses{\thanks{A note}}%
2032     \else
2033       \g@addto@macro\thankses{\thanks{#1}}%
2034     \fi}}

```

`\anon` We provide `\anon` command, which blinds parts of the text if the package option `anonymous` is set

```

2035 \newcommand{\anon}[2][ANONYMIZED]{%
2036   \if@ACM@anonymous%
2037     {\color{ACMOrange}#1}%
2038   \else%
2039     #2%
2040   \fi}

```

3.19 Maketitle hook

The current \LaTeX provides a nice `lthooks` mechanism. However, since it is relatively new, we will use oldfashioned approach—at least for now.

`\@beginmaketitlehook` The hook

```

2041 \ifx\@beginmaketitlehook\undefined
2042   \let\@beginmaketitlehook\empty
2043 \fi

```

`\AtBeginMaketitle` Adding to the hook

```

2044 \def\AtBeginMaketitle{\g@addto@macro\@beginmaketitlehook}

```

3.20 ACM Engage top matter

\@acmengagemetadata The special metadata for ACM engage course materials

```
2045 \def\@acmengagemetadata{}
```

\setengagemetadata Adding topic to engage metadata

```
2046 \def\setengagemetadata#1#2{%
2047   \g@addto@macro{\@acmengagemetadata}{%
2048     \@setengagemetadata{#1}{#2}}}
```

3.21 Typesetting top matter

\mktitle@bx Some of our formats use a two-column design. Some use a one-column design. In all cases we use a wide title. Thus we typeset the top matter in a special box to be used in the construction \@twocolumn[*box*].

```
2049 \newbox\mktitle@bx
```

\maketitle The (in)famous \maketitle. Note that in sigchi-a mode, authors are *not* in the title box.

Another note: there is a subtle difference between author notes, title notes and thanks. The latter two refer to the paper itself and therefore belong to the copy-right/permission block. By the way, this was the default behavior of the old ACM classes.

```
2050 \def\maketitle{\@beginmaketitlehook
2051   \@ACM@maketitle@typesettrue
2052   \if@ACM@anonymous
2053     % Anonymize omission of \author-s
2054     \ifnum\num@authorgroups=0\author{}\fi
2055   \fi
2056   \begingroup
2057   \let\@vspace\@vspace@orig
2058   \let\@vspacer\@vspacer@orig
2059   \let\@footnotemark\@footnotemark@nolink
2060   \let\@footnotetext\@footnotetext@nolink
2061   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
2062   \hsize=\textwidth
2063   \def\@makefnmark{\hbox{\@textsuperscript{\@thefnmark}}}%
2064   \@mktitle\if@ACM@sigchiamode\else\@mkauthors\fi\@mkteasers
2065   \@printtopmatter
2066   \if@ACM@sigchiamode\@mkauthors\fi
2067   \setcounter{footnote}{0}%
2068   \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}%
2069   \@titlenotes
2070   \@subtitlenotes
2071   \@authornotes
2072   \let\@makefnmark\relax
2073   \let\@thefnmark\relax
2074   \let\@makefntext\noindent
2075   \ifx\@empty\thankses\else
2076     \footnotetextauthorsaddresses{%
2077       \def\par{\let\par\@par}\parindent\z@\@setthanks}%
2078   \fi
2079   \if@ACM@acmcp\else
2080     \ifx\@empty\authorsaddresses\else
```

```

2081     \if@ACM@anonymous\else
2082     \if@ACM@journal@bibstrip
2083     \footnotetextauthorsaddresses{%
2084     \def\par{\let\par\@par}\parindent\z@\setauthorsaddresses}%
2085     \fi
2086     \fi
2087     \fi
2088     \fi
2089     \if@ACM@nonacm
2090     \ifnum\acm@copyrightmode=15\relax % cc
2091     \footnotetextcopyrightpermission{\@copyrightpermission}%
2092     \fi
2093     \else
2094     \if@ACM@acmcp\else
2095     \footnotetextcopyrightpermission{%
2096     \if@ACM@authordraft
2097     \raisebox{-2ex}[\z@][\z@]{\makebox[0pt][l]{\large\bfseries
2098     Unpublished working draft. Not for distribution.}}%
2099     \color[gray]{0.9}%
2100     \fi
2101     \parindent\z@\parskip0.1\baselineskip
2102     \if@ACM@authorversion\else
2103     \if@printpermission\@copyrightpermission\par\fi
2104     \fi
2105     \if@ACM@manuscript\else
2106     \if@ACM@journal@bibstrip\else % Print the conference information
2107     \if@ACM@engage
2108     {\itshape \@acmBooktitle, \@acmYear.}\par
2109     \else
2110     {\itshape \acmConference@shortname, \acmConference@date, \acmConference@venue}\par
2111     \fi
2112     \fi
2113     \fi
2114     \if@printcopyright
2115     \copyright\ \@copyrightyear\ \@copyrightowner\
2116     \else
2117     \@copyrightyear.\
2118     \fi
2119     \if@ACM@manuscript
2120     Manuscript submitted to ACM\
2121     \else
2122     \if@ACM@authorversion
2123     This is the author's version of the work. It is posted here for
2124     your personal use. Not for redistribution. The definitive Version
2125     of Record was published in
2126     \if@ACM@journal@bibstrip
2127     \emph{\@journalName}%
2128     \else
2129     \emph{\@acmBooktitle}%
2130     \fi
2131     \ifx\@acmDOI\@empty
2132     .
2133     \else
2134     , \@formatdoi{\@acmDOI}.

```

```

2135         \fi\\
2136     \else
2137         \if@ACM@nonacm\else
2138             \if@ACM@journal@bibstrip
2139                 \@permissionCodeOne/\@acmYear/\@acmMonth-ART\@acmArticle
2140                 \ifx\@acmPrice\@empty\else\ $\@acmPrice\fi\\
2141                 \@formatdoi{\@acmDOI}%
2142             \else % Conference
2143                 \ifx\@acmISBN\@empty\else ACM~ISBN~\@acmISBN
2144                 \ifx\@acmPrice\@empty.\else\dots\$\@acmPrice\fi\\\fi
2145                 \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi%
2146             \fi
2147         \fi
2148     \fi
2149 \fi}%
2150 \fi
2151 \fi
2152 \endgroup
2153 \if@ACM@engage\@typesetengagemetadata\fi
2154 \setcounter{footnote}{0}%
2155 \@mkabstract
2156 \ifx\@translatedabstracts\@empty\else
2157 \@translatedabstracts\fi
2158 \if@ACM@printccs
2159 \ifx\@concepts\@empty\else\bgroup
2160     {\@specialsection{CCS Concepts}%
2161     \noindent\@concepts\par}\egroup
2162 \fi
2163 \fi
2164 \if@ACM@acmcp\else
2165     \ifx\@keywords\@empty\else\bgroup
2166         {\@specialsection{\keywordsname}%
2167         \noindent\@keywords\par}\egroup
2168     \fi
2169     \ifx\@translatedkeywords\@empty\else
2170     \@translatedkeywords
2171     \fi
2172 \fi
2173 \let\metadata@authors=\authors
2174 \nxandlist{, }, {, } \metadata@authors
2175 \def\@ACM@checkaffil{%
2176 \hypersetup{
2177     pdfauthor={\metadata@authors},
2178     pdftitle={\@title},
2179     pdfsubject={\@concepts},
2180     pdfkeywords={\@keywords},
2181     pdfcreator={LaTeX with acmart
2182         \csname ver@acmart.cls\endcsname\space
2183         and hyperref
2184         \csname ver@hyperref.sty\endcsname}}%
2185 \andify\authors
2186 \andify\shortauthors
2187 \global\let\authors=\authors
2188 \global\let\shortauthors=\shortauthors

```

```

2189 \if@ACM@printacmref
2190 \mkbibcitation
2191 \fi
2192 \global\@topnum\z@ % this prevents floats from falling
2193 % at the top of page 1
2194 \global\@botnum\z@ % we do not want them to be on the bottom either
2195 \@printendtopmatter
2196 \@afterindentfalse
2197 \@afterheading
2198 \if@ACM@acmcp
2199 \set@ACM@acmcpbox
2200 \AtEndDocument{\end@ACM@color@frame}%
2201 \@ACM@color@frame
2202 \fi
2203 }

```

\set@ACM@acmcpbox Setting infobox for acmcp

```

2204 \newbox\@ACM@acmcpbox
2205 \def\set@ACM@acmcpbox{%
2206 \bgroup
2207 \hsize=5pc
2208 \global\setbox\@ACM@acmcpbox=\vtop to \textheight{%
2209 \setlength{\parindent}{\z@}%
2210 {\Large LOGO\par}%
2211 \scriptsize
2212 \vfill
2213 \ifx\@acmCodeDataLink\@empty\else
2214 Code and data links:\\ \@acmCodeDataLink\par\vfill
2215 \fi
2216 \ifx\@keywords\@empty\else Keywords:
2217 \@keywords\par\vfill
2218 \fi
2219 \ifx\@empty\@authorsaddresses\else\@setauthorsaddresses\vfill\fi
2220 }
2221 \egroup}

```

\@specialsection This macro starts sections for proceedings and uses \small for journals

```

2222 \def\@specialsection#1{%
2223 \let\@vspace\@vspace@orig
2224 \let\@vspacer\@vspacer@orig
2225 \ifcase\ACM@format@nr
2226 \relax % manuscript
2227 \par\medskip\small\noindent#1: %
2228 \or % acmsmall
2229 \par\medskip\small\noindent#1: %
2230 \or % acmlarge
2231 \par\medskip\small\noindent#1: %
2232 \or % acmtog
2233 \par\medskip\small\noindent#1: %
2234 \or % sigconf
2235 \section*{#1}%
2236 \or % siggraph
2237 \section*{#1}%
2238 \or % sigplan

```

```

2239 \noindentparagraph*{#1:~}%
2240 \or % sigchi
2241 \section*{#1}%
2242 \or % sigchi-a
2243 \section*{#1}%
2244 \or % acmengage
2245 \section*{#1}%
2246 \or % acmcp
2247 \section*{#1}%
2248 \fi
2249 \let\@vspace\@vspace@acm
2250 \let\@vspacer\@vspacer@acm
2251 }

```

\@printtopmatter The printing of top matter starts a new page and uses the given title box. Note that for sigchi-a we print badges here rather than in \mkttitle since we want them in the margins.

Note that if there are too many authors, \mkttitle@bx might overflow the page. Therefore we start with checking this and if this happens, we split the box and print it page by page.

```

2252 \def\@printtopmatter{%
2253 \ifx\@startPage\@empty
2254 \gdef\@startPage{1}%
2255 \else
2256 \setcounter{page}{\@startPage}%
2257 \fi
2258 \@tempdima=\ht\mkttitle@bx
2259 \advance\@tempdima by \dp\mkttitle@bx
2260 \ifdim\@tempdima>0.9\textheight
2261 \loop
2262 \setbox\@tempboxa=\vsplit \mkttitle@bx to 0.9\textheight
2263 \thispagestyle{firstpagestyle}%
2264 \noindent\unvbox\@tempboxa
2265 \clearpage
2266 \@tempdima=\ht\mkttitle@bx
2267 \advance\@tempdima by \dp\mkttitle@bx
2268 \ifdim\@tempdima>0.9\textheight\repeat
2269 \fi
2270 \thispagestyle{firstpagestyle}%
2271 \noindent
2272 \ifcase\ACM@format@nr
2273 \relax % manuscript
2274 \box\mkttitle@bx\par
2275 \or % acmsmall
2276 \box\mkttitle@bx\par
2277 \or % acmlarge
2278 \box\mkttitle@bx\par
2279 \or % acmtog
2280 \twocolumn[\box\mkttitle@bx]%
2281 \or % sigconf
2282 \twocolumn[\box\mkttitle@bx]%
2283 \or % siggraph
2284 \twocolumn[\box\mkttitle@bx]%
2285 \or % sigplan

```

```

2286 \twocolumn[\box\mktitle@bx]%
2287 \or % sigchi
2288 \twocolumn[\box\mktitle@bx]%
2289 \or % sigchi-a
2290 \par\box\mktitle@bx\par\bigskip
2291 \if@ACM@badge
2292 \marginpar{\noindent
2293 \ifx\@acmBadgeL@image\empty\else
2294 \href{\@acmBadgeL@url}{%
2295 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}%
2296 \hskip\@ACM@badge@skip
2297 \fi
2298 \ifx\@acmBadgeR@image\empty\else
2299 \href{\@acmBadgeR@url}{%
2300 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}%
2301 \fi}%
2302 \fi
2303 \or % acmengage
2304 \twocolumn[\box\mktitle@bx]%
2305 \or % acmcp
2306 \box\mktitle@bx\par
2307 \fi
2308 }

```

\@mktitle The title of the article

```

2309 \def\@mktitle{%
2310 \ifcase\ACM@format@nr
2311 \relax % manuscript
2312 \@mktitle@i
2313 \or % acmsmall
2314 \@mktitle@i
2315 \or % acmlarge
2316 \@mktitle@i
2317 \or % acmtog
2318 \@mktitle@i
2319 \or % sigconf
2320 \@mktitle@iii
2321 \or % siggraph
2322 \@mktitle@iii
2323 \or % sigplan
2324 \@mktitle@iii
2325 \or % sigchi
2326 \@mktitle@iii
2327 \or % sigchi-a
2328 \@mktitle@iv
2329 \or % acmengage
2330 \@mktitle@iii
2331 \or % acmcp
2332 \@mktitle@i
2333 \fi
2334 }

```

\@titlefont The font to typeset the title

```

2335 \def\@titlefont{%

```

```

2336 \ifcase\ACM@format@nr
2337 \relax % manuscript
2338 \LARGE\sffamily\bfseries
2339 \or % acmsmall
2340 \LARGE\sffamily\bfseries
2341 \or % acmlarge
2342 \LARGE\sffamily\bfseries
2343 \or % acmtog
2344 \Huge\sffamily
2345 \or % sigconf
2346 \Huge\sffamily\bfseries
2347 \or % siggraph
2348 \Huge\sffamily\bfseries
2349 \or % sigplan
2350 \Huge\bfseries
2351 \or % sigchi
2352 \Huge\sffamily\bfseries
2353 \or % sigchi-a
2354 \Huge\bfseries
2355 \or % acmengage
2356 \Huge\sffamily\bfseries
2357 \or % acmcp
2358 \LARGE\sffamily\bfseries
2359 \fi}

```

`\@subtitlefont` The font to typeset the subtitle

```

2360 \def\@subtitlefont{\normalsize
2361 \ifcase\ACM@format@nr
2362 \relax % manuscript
2363 \mdseries
2364 \or % acmsmall
2365 \mdseries
2366 \or % acmlarge
2367 \mdseries
2368 \or % acmtog
2369 \LARGE
2370 \or % sigconf
2371 \LARGE\mdseries
2372 \or % siggraph
2373 \LARGE\mdseries
2374 \or % sigplan
2375 \LARGE\mdseries
2376 \or % sigchi
2377 \LARGE\mdseries
2378 \or % sigchi-a
2379 \mdseries
2380 \or % acmengage
2381 \LARGE\mdseries
2382 \or % acmcp
2383 \mdseries
2384 \fi}

```

`\@mkttitle@i` The version of `\mkttitle` for most journals

```

2385 \def\@mkttitle@i{\hsize=\textwidth

```



```

2386 \if@ACM@acmcp
2387 \advance\hsize by -6pc%
2388 \fi
2389 \@ACM@title@width=\hsize
2390 \ifx\@acmBadgeL@image\@empty\else
2391 \advance\@ACM@title@width by -\@ACM@badge@width
2392 \advance\@ACM@title@width by -\@ACM@badge@skip
2393 \fi
2394 \ifx\@acmBadgeR@image\@empty\else
2395 \advance\@ACM@title@width by -\@ACM@badge@width
2396 \advance\@ACM@title@width by -\@ACM@badge@skip
2397 \fi
2398 \setbox\mktitle@bx=\vbox{\noindent\@titlefont
2399 \ifx\@acmBadgeL@image\@empty\else
2400 \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeL@url}{%
2401 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}%
2402 \hskip\@ACM@badge@skip
2403 \fi
2404 \parbox[t]{\@ACM@title@width}{\raggedright
2405 \@titlefont\noindent
2406 \@title\@translatedtitle%
2407 \ifx\@subtitle\@empty\else
2408 \par\noindent{\@subtitlefont\@subtitle\@translatedsubtitle}%
2409 \fi}%
2410 \ifx\@acmBadgeR@image\@empty\else
2411 \hskip\@ACM@badge@skip
2412 \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
2413 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}%
2414 \fi
2415 \par\bigskip}}%

```

`\@mktitle@ii` The version of `\mktitle` for TOG. Since v1.06, this is subsumed by the `\mktitle@i` macro

`\@mktitle@iii` The version of `\mktitle` for SIG proceedings. Note that since the title is centered, we leave space for the left badge even if only the right badge is defined.

```

2416 \def\@mktitle@iii{\hsize=\textwidth
2417 \setbox\mktitle@bx=\vbox{\@titlefont\centering
2418 \@ACM@title@width=\hsize
2419 \if@ACM@badge
2420 \advance\@ACM@title@width by -2\@ACM@badge@width
2421 \advance\@ACM@title@width by -2\@ACM@badge@skip
2422 \parbox[b]{\@ACM@badge@width}{\strut
2423 \ifx\@acmBadgeL@image\@empty\else
2424 \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeL@url}{%
2425 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}%
2426 \fi}%
2427 \hskip\@ACM@badge@skip
2428 \fi
2429 \parbox[t]{\@ACM@title@width}{\centering\@titlefont
2430 \@title\@translatedtitle%
2431 \ifx\@subtitle\@empty\else
2432 \par\noindent{\@subtitlefont\@subtitle\@translatedsubtitle}
2433 \fi

```

```

2434 }%
2435 \if@ACM@badge
2436   \hskip\@ACM@badge@skip
2437   \parbox[b]{\@ACM@badge@width}{\strut
2438     \ifx\@acmBadgeR@image\@empty\else
2439       \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
2440         \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}%
2441     \fi}%
2442 \fi
2443 \par\bigskip}}%

```

\@mktitle@iv The version of \@mktitle for sigchi-a

```

2444 \def\@mktitle@iv{\hsize=\textwidth
2445   \setbox\mktitle@bx=\vbox{\raggedright\leftskip5pc\@titlefont
2446     \noindent\leavevmode\leaders\hrule height 2pt\hfill\kern0pt\par
2447     \noindent\@title\@translatedtitle%
2448     \ifx\@subtitle\@empty\else
2449       \par\noindent\@subtitlefont\@subtitle\@translatedsubtitle%
2450     \fi
2451     \par\bigskip}}%

```

\@ACM@addtoaddress This macro adds an item to the address using the following rules:

1. If we start a paragraph, add the item
2. Otherwise, add a comma and the item
3. However, the comma is deleted if it is at the end of a line. We use the magic \cleaders trick for this.

```

2452 \newbox\@ACM@commabox
2453 \def\@ACM@addtoaddress#1{%
2454   \ifvmode\else
2455     \if@ACM@affiliation@obeypunctuation\else
2456       \setbox\@ACM@commabox=\hbox{, }%
2457       \unskip\cleaders\copy\@ACM@commabox\hskip\wd\@ACM@commabox
2458     \fi\fi
2459   #1}

```

\institution Theoretically we can define the macros for \affiliation inside the \@mkauthors-style commands. However, this would lead to a strange error if an author uses them outside \department \affiliation. Of course we can make them produce an error message, but...

```

\streetaddress 2460 \def\streetaddress#1{\unskip\ignorespaces}
\city 2461 \def\postcode#1{\unskip\ignorespaces}
\state 2462 \if@ACM@journal
\postcode 2463 \def\position#1{\unskip\ignorespaces}
\country 2464 \def\institution#1{\global\@ACM@instpresenttrue
2465   \unskip~#1\ignorespaces}
2466 \def\city#1{\global\@ACM@citypresenttrue\unskip\ignorespaces}
2467 \def\state#1{\unskip\ignorespaces}
2468 \newcommand\department[2][0]{\unskip\ignorespaces}
2469 \def\country#1{\StrDel{#1}{ }[\@tempa]}%
2470 \ifx\@tempa\@empty\else
2471   \global\@ACM@countrypresenttrue\fi
2472   \if@ACM@affiliation@obeypunctuation\else, \fi#1\ignorespaces}

```

```

2473 \else
2474 \def\position#1{\if@ACM@affiliation@obexpunctuation#1\else#1\par\fi}%
2475 \def\institution#1{\global\@ACM@instpresenttrue
2476 \if@ACM@affiliation@obexpunctuation#1\else#1\par\fi}%
2477 \newcommand\department[2][0]{\if@ACM@affiliation@obexpunctuation
2478 #2\else#2\par\fi}%
2479 % \def\streetaddress#1{\if@ACM@affiliation@obexpunctuation#1\else#1\par\fi}%
2480 \def\city#1{\global\@ACM@citypresenttrue\@ACM@addtoaddress{#1}}%
2481 \let\state\@ACM@addtoaddress
2482 % \def\postcode#1{\if@ACM@affiliation@obexpunctuation#1\else\unskip\space#1\fi}%
2483 \def\country#1{\global\@ACM@countrypresenttrue\@ACM@addtoaddress{#1}}%
2484 \fi

```

\mkauthors Typesetting the authors

```

2485 \def\mkauthors{\begingroup
2486 \hsize=\textwidth
2487 \ifcase\ACM@format@nr
2488 \relax % manuscript
2489 \mkauthors@i
2490 \or % acmsmall
2491 \mkauthors@i
2492 \or % acmlarge
2493 \mkauthors@i
2494 \or % acmtog
2495 \mkauthors@i
2496 \or % sigconf
2497 \mkauthors@iii
2498 \or % siggraph
2499 \mkauthors@iii
2500 \or % sigplan
2501 \mkauthors@iii
2502 \or % sigchi
2503 \mkauthors@iii
2504 \or % sigchi-a
2505 \mkauthors@iv
2506 \or % acmengage
2507 \mkauthors@iii
2508 \or % acmcp
2509 \mkauthors@i
2510 \fi
2511 \endgroup
2512 }

```

\authorfont Somehow different conferences use different fonts for author names. Why?

```

2513 \def\authorfont{\Large\sffamily}

```

\affiliationfont Font for affiliations

```

2514 \def\affiliationfont{\normalsize\normalfont}

```

Adjusting fonts for different formats

```

2515 \ifcase\ACM@format@nr
2516 \relax % manuscript
2517 \or % acmsmall
2518 \def\authorfont{\large\sffamily}

```

```

2519 \def\@affiliationfont{\small\normalfont}
2520 \or % acmlarge
2521 \or % acmtog
2522 \def\@authorfont{\LARGE\sffamily}
2523 \def\@affiliationfont{\large}
2524 \or % sigconf
2525 \def\@authorfont{\LARGE}
2526 \def\@affiliationfont{\large}
2527 \or % siggraph
2528 \def\@authorfont{\normalsize\normalfont}
2529 \def\@affiliationfont{\normalsize\normalfont}
2530 \or % sigplan
2531 \def\@authorfont{\Large\normalfont}
2532 \def\@affiliationfont{\normalsize\normalfont}
2533 \or % sigchi
2534 \def\@authorfont{\bfseries}
2535 \def\@affiliationfont{\mdseries}
2536 \or % sigchi-a
2537 \def\@authorfont{\bfseries}
2538 \def\@affiliationfont{\mdseries}
2539 \or % acmengage
2540 \def\@authorfont{\LARGE}
2541 \def\@affiliationfont{\large}
2542 \or % acmcp
2543 \def\@authorfont{\large\sffamily}
2544 \def\@affiliationfont{\small\normalfont}
2545 \fi

```

\typeset@author@line At this point we have \@currentauthors and \@currentaffiliations. We typeset them in the journal style

```

2546 \def\@typeset@author@line{%
2547 \andify\@currentauthors\par\noindent
2548 \@currentauthors\def\@currentauthors{}%
2549 \ifx\@currentaffiliations\empty\else
2550 \andify\@currentaffiliations
2551 \unskip, {\@currentaffiliations}\par
2552 \fi
2553 \def\@currentaffiliations{}}

```

\if@ACM@instpresent Whether the given affiliation has institution

```

2554 \newif\if@ACM@instpresent
2555 \@ACM@instpresenttrue

```

\if@ACM@citypresent Whether the given affiliation has city

```

2556 \newif\if@ACM@citypresent
2557 \@ACM@citypresenttrue

```

\if@ACM@countrypresent Whether the given affiliation has country

```

2558 \newif\if@ACM@countrypresent
2559 \@ACM@countrypresenttrue

```

\@ACM@resetaffil Reset affiliation flags

```

2560 \def\@ACM@resetaffil{%

```

```

2561 \global\@ACM@instpresentfalse
2562 \global\@ACM@citypresentfalse
2563 \global\@ACM@countrypresentfalse
2564 }

```

\@ACM@checkaffil Check affiliation flags

```

2565 \def\@ACM@checkaffil{%
2566   \if@ACM@instpresent\else
2567     \ClassWarningNoLine{\@classname}{No institution present for an affiliation}%
2568   \fi
2569   \if@ACM@citypresent\else
2570     \ClassWarningNoLine{\@classname}{No city present for an affiliation}%
2571   \fi
2572   \if@ACM@countrypresent\else
2573     \ClassError{\@classname}{No country present for an affiliation}{ACM
2574       requires each author to indicate their country using country macro.}%
2575   \fi
2576 }

```

\@mkauthors@i This version is used in most journal formats. Note that \and between authors with the same affiliation becomes _and_:

```

2577 \def\@mkauthors@i{%
2578   \def\@currentauthors{}%
2579   \def\@currentaffiliations{}%
2580   \global\let\and\@typeset@author@line
2581   \def\@author##1{%
2582     \ifx\@currentauthors\@empty
2583       \gdef\@currentauthors{\@authorfont\MakeTextUppercase{##1}}%
2584     \else
2585       \g@addto@macro{\@currentauthors}{\and\MakeTextUppercase{##1}}%
2586     \fi
2587     \gdef\and{}}%
2588   \def\email##1##2{%
2589     \def\affiliation##1##2{%
2590       \def\@tempa{##2}\ifx\@tempa\@empty\else
2591         \ifx\@currentaffiliations\@empty
2592           \gdef\@currentaffiliations{%
2593             \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2594             \setkeys{@ACM@affiliation@}{##1}%
2595             \@ACM@resetaffil
2596             \@affiliationfont##2\@ACM@checkaffil}%
2597           \else
2598             \g@addto@macro{\@currentaffiliations}{\and
2599               \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2600               \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2601               ##2\@ACM@checkaffil}%
2602             \fi
2603             \fi
2604             \global\let\and\@typeset@author@line}%
2605     \if@ACM@acmcp
2606       \advance\hsize by -6pc%
2607     \fi
2608     \global\setbox\mktitle@bx=\vbox{\noindent\unvbox\mktitle@bx\par\medskip
2609       \noindent\addresses\@typeset@author@line

```

```
2610 \par\medskip}%
2611 }
```

\mkauthors@ii The \mkauthors@ii command was the version used in acmtog. It is no longer necessary.

\author@bx The box to put an individual author in

```
2612 \newbox\author@bx
```

\author@bx@wd The width of the author box

```
2613 \newdimen\author@bx@wd
```

\author@bx@sep The separation between author boxes

```
2614 \newskip\author@bx@sep
2615 \author@bx@sep=1pc\relax
```

\typeset@author@bx Typesetting the box with authors. Note that in sigchi-a the box is not centered.

```
2616 \def\typeset@author@bx{\bgroup\hsize=\author@bx@wd
2617 \def\and{\par}\normalbaselines
2618 \global\setbox\author@bx=\vtop{\if@ACM@sigchiamode\else\centering\fi
2619 \@authorfont\@currentauthors\par\@affiliationfont
2620 \@currentaffiliation}\egroup
2621 \box\author@bx\hspace{\author@bx@sep}%
2622 \gdef\@currentauthors{}}%
2623 \gdef\@currentaffiliation{}}
```

\mkauthors@iii The sigconf version. Here we use a centered design with each author in a separate box.

```
2624 \def\mkauthors@iii{%
```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width $(\text{textwidth} - \text{author@bx@sep})/N - \text{author@bx@sep}$, where N is the number of boxes per row.

```
2625 \author@bx@wd=\textwidth\relax
2626 \advance\author@bx@wd by -\author@bx@sep\relax
2627 \ifnum\@ACM@authorsperrow>0\relax
2628 \divide\author@bx@wd by \@ACM@authorsperrow\relax
2629 \else
2630 \ifcase\@num@authorgroups
2631 \relax % 0?
2632 \or % 1=one author per row
2633 \or % 2=two authors per row
2634 \divide\author@bx@wd by \@num@authorgroups\relax
2635 \or % 3=three authors per row
2636 \divide\author@bx@wd by \@num@authorgroups\relax
2637 \or % 4=two authors per row (!)
2638 \divide\author@bx@wd by 2\relax
2639 \else % three authors per row
2640 \divide\author@bx@wd by 3\relax
2641 \fi
2642 \fi
2643 \advance\author@bx@wd by -\author@bx@sep\relax
```

Now, parsing of \addresses:

```

2644 \gdef\@currentauthors{}%
2645 \gdef\@currentaffiliation{}%
2646 \def\@author##1{\ifx\@currentauthors\@empty
2647   \gdef\@currentauthors{\par##1}%
2648   \else
2649     \g@addto@macro\@currentauthors{\par##1}%
2650   \fi
2651 \gdef\and{}}%
2652 \def\email##1##2{\ifx\@currentaffiliation\@empty
2653   \gdef\@currentaffiliation{\bgroup
2654     \mathchardef\UrlBreakPenalty=10000\nolinkurl{##2}\egroup}%
2655   \else
2656     \g@addto@macro\@currentaffiliation{\par\bgroup
2657       \mathchardef\UrlBreakPenalty=10000\nolinkurl{##2}\egroup}%
2658   \fi}%
2659 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
2660   \gdef\@currentaffiliation{%
2661     \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2662     \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2663     ##2\@ACM@checkaffil}%
2664   \else
2665     \g@addto@macro\@currentaffiliation{\par
2666       \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2667       \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2668       ##2\@ACM@checkaffil}%
2669   \fi
2670 \global\let\and\@typeset@author@bx
2671 }%

```

Actual typesetting is done by the \and macro:

```

2672 \hsize=\textwidth
2673 \global\setbox\mktitle@bx=\vbox{\noindent
2674   \unvbox\mktitle@bx\par\medskip\leavevmode
2675   \lineskip=1pc\relax\centering\hspace*{-1em}%
2676   \addresses\let\and\@typeset@author@bx\and\par\bigskip}}

```

\@mkauthors@iv The sigchi-a version. We put authors in the main text with no more than 2 authors per line, unless overridden.

```

2677 \def\@mkauthors@iv{%

```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width $(\text{\textwidth} - \text{\author@bx@sep})/N - \text{\author@bx@sep}$, where N is the number of boxes per row.

```

2678 \author@bx@wd=\columnwidth\relax
2679 \advance\author@bx@wd by -\author@bx@sep\relax
2680 \ifnum\@ACM@authorsperrrow>0\relax
2681   \divide\author@bx@wd by \@ACM@authorsperrrow\relax
2682 \else
2683   \ifcase\@num@authorgroups
2684     \relax % 0?
2685     \or % 1=one author per row
2686     \else % 2=two authors per row

```

```

2687 \divide\author@bx@wd by 2\relax
2688 \fi
2689 \fi
2690 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

2691 \gdef\@currentauthors{}%
2692 \gdef\@currentaffiliation{}%
2693 \def\@author##1{\ifx\@currentauthors\@empty
2694 \gdef\@currentauthors{\par##1}%
2695 \else
2696 \g@addto@macro\@currentauthors{\par##1}%
2697 \fi
2698 \gdef\and{}}%
2699 \def\email##1##2{\ifx\@currentaffiliation\@empty
2700 \gdef\@currentaffiliation{\nolinkurl{##2}}%
2701 \else
2702 \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
2703 \fi}%
2704 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
2705 \gdef\@currentaffiliation{%
2706 \setkeys{@ACM@affiliation@}{obexpunctuation=false}%
2707 \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2708 ##2\@ACM@checkaffil}%
2709 \else
2710 \g@addto@macro\@currentaffiliation{\par
2711 \setkeys{@ACM@affiliation@}{obexpunctuation=false}%
2712 \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2713 ##2\@ACM@checkaffil}%
2714 \fi
2715 \global\let\and\@typeset@author@bx}%
2716 %

```

Actual typesetting is done by the \and macro

```

2717 \bgroup\hsize=\columnwidth
2718 \par\raggedright\leftskip=\z@
2719 \lineskip=1pc\noindent
2720 \addresses\let\and\@typeset@author@bx\and\par\bigskip\egroup}

```

\@mkauthorsaddresses Typesetting authors' addresses in the footnote style

```

2721 \def\@mkauthorsaddresses{%
2722 \ifnum\num@authors>1\relax
2723 Authors' \else Author's \fi
2724 \ifnum\num@authorgroups>1\relax
2725 addresses: \else address: \fi
2726 \bgroup
2727 \def\streetaddress##1{\unskip, ##1}%
2728 \def\postcode##1{\unskip, ##1}%
2729 \def\position##1{\unskip\ignorespaces}%
2730 \gdef\@ACM@institution@separator{,}%
2731 \def\institution##1{\unskip\@ACM@institution@separator ##1\gdef\@ACM@institution@separator{ and }}
2732 \def\city##1{\unskip, ##1}%
2733 \def\state##1{\unskip, ##1}%
2734 \renewcommand\department[2][0]{\unskip\@addpunct, ##2}%
2735 \def\country##1{\unskip, ##1}%

```



```

2736 \def\and{\unskip; \gdef\@ACM@institution@separator{, }}%
2737 \def\@author##1{##1}%
2738 \def\email##1##2{\unskip, \nolinkurl{##2}}%
2739 \addresses
2740 \egroup}

2741 \AtEndDocument{\if@ACM@nonacm\else\if@ACM@journal
2742 \ifx\@authorsaddresses\@empty
2743 \ClassWarningNoLine{\@classname}{Authors'
2744 addresses are mandatory for ACM journals}%
2745 \fi\fi\fi}

```

\@setaddresses This is an amsart macro that we do not need.

```
2746 \def\@setaddresses{}
```

\@authornotemark Adding a footnote mark to authors. This version adds a “normal” footnote mark.

```
2747 \def\@authornotemark{\g@addto@macro\@currentauthors{\footnotemark\relax}}
```

\@@authornotemark Adding a footnote mark to authors with a given number

```
2748 \def\@@authornotemark#1{\g@addto@macro\@currentauthors{\footnotemark[#1]}}
```

\@mkteasers Typesetting the teasers

```

2749 \def\@mkteasers{%
2750 \ifx\@teaserfigures\@empty\else
2751 \def\@teaser##1{\par\bigskip\bgroup
2752 \captionsetup{type=figure}##1\egroup\par}
2753 \global\setbox\mktitle@bx=\vbox{\noindent\unvbox\mktitle@bx\par
2754 \noindent\@Description@presentfalse
2755 \@teaserfigures\par\if@Description@present\else
2756 \global\@undescribed@imagestrue
2757 \ClassWarning{\@classname}{A possible image without
2758 description}\fi
2759 \medskip}%
2760 \fi}

```

\@mkabstract Typesetting the abstract

```

2761 \def\@mkabstract{\bgroup
2762 \ifx\@abstract\@empty\else
2763 {\phantomsection\addcontentsline{toc}{section}{\@abstractname}%
2764 \if@ACM@journal
2765 \everypar{\setbox\z@\lastbox\everypar{}}\small
2766 \else
2767 \section*{\@abstractname}%
2768 \fi
2769 \ignorespaces\@abstract\par}%
2770 \fi\egroup}

```

\@mktranslatedabstract Typesetting a translated abstract

```

2771 \def\@mktranslatedabstract#1{\selectlanguage{#1}%
2772 \if@ACM@journal
2773 \everypar{\setbox\z@\lastbox\everypar{}}\small
2774 \else
2775 \section*{\@abstractname}%
2776 \fi
2777 \ignorespaces}

```

\@mkbibcitation Print the bibcitation format

```
2778 \def\@mkbibcitation{\bgroup
2779   \let\@vspace\@vspace@orig
2780   \let\@vspacer\@vspacer@orig
2781   \def\@pages@word{\ifnum\getrefnumber{TotPages}=1\relax page\else pages\fi}%
2782   \def\footnotemark{}%
2783   \def\{\unskip\} \ignorespaces}%
2784   \def\footnote{\ClassError{\@classname}{Please do not use footnotes
2785     inside a \string\title{} or \string\author{} command! Use
2786     \string\titlenote{} or \string\authornote{} instead!}}%
2787   \def\@article@string{\ifx\@acmArticle\@empty{\ }else,
2788     Article~\@acmArticle\ \fi}%
2789   \par\medskip\small\noindent{\bfseries ACM Reference Format:}\par\nobreak
2790   \noindent\bgroup
2791   \def\{\unskip\}, \ignorespaces\authors\egroup. \@acmYear. \@title
2792   \ifx\@subtitle\@empty. \else: \@subtitle. \fi
2793   \if@ACM@nonacm\else
2794     % The 'nonacm' option disables 'printacmref' by default,
2795     % and the present \@mkbibcitation definition is never used
2796     % in this case. The conditional remains useful if the user
2797     % explicitly sets \settopmatter{printacmref=true}.
2798     \if@ACM@journal@bibstrip
2799       \textit{\@journalNameShort}
2800       \@acmVolume, \@acmNumber \@article@string (\@acmPubDate),
2801       \ref{TotPages}~\@pages@word.
2802     \else
2803       In \textit{\@acmBooktitle}%
2804       \ifx\@acmEditors\@empty\textit{.}\else
2805         \andify\@acmEditors\textit{, }\@acmEditors~\@editorsAbbrev.%
2806       \fi\
2807       ACM, New York, NY, USA%
2808       \@article@string\unskip, \ref{TotPages}~\@pages@word.
2809     \fi
2810   \fi
2811   \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi
2812 \par\egroup}
```

\@printendtopmatter End the top matter

```
2813 \def\@printendtopmatter{%
2814   \let\@vspace\@vspace@orig
2815   \let\@vspacer\@vspacer@orig
2816   \par\bigskip
2817   \let\@vspace\@vspace@acm
2818   \let\@vspacer\@vspacer@acm
2819 }
```

\@setthanks We redefine \@setthanks using \long

```
2820 \def\@setthanks{\long\def\thanks##1{\par##1\@addpunct.}\thankses}
```

\@setauthorsaddresses

```
2821 \def\@setauthorsaddresses{\@authorsaddresses\unskip\@addpunct.}
```

\@typesetengagemetadata Typesetting special metadata for ACM Engage

```

2822 \def\@typesetengagemetadata{%
2823   \def\@setengagemetadata##1##2{\par\noindent\textbf{##1} ##2\par}%
2824   \@acmengagemetadata}

```

3.22 Headers and Footers

We use fancyhdr for our headers and footers:

```

2825 \RequirePackage{fancyhdr}

```

\ACM@restore@pagestyle The following code by Ross Moore protects against changes by the totpages package:

```

2826 \let\ACM@ps@plain\ps@plain
2827 \let\ACM@ps@myheadings\ps@myheadings
2828 \let\ACM@ps@headings\ps@headings
2829 \def\ACM@restore@pagestyle{%
2830   \let\ps@plain\ACM@ps@plain
2831   \let\ps@myheadings\ACM@ps@myheadings
2832   \let\ps@headings\ACM@ps@headings}
2833 \AtBeginDocument{\ACM@restore@pagestyle}

```

\ACM@linecount@bx This is the box displayed in review mode

```

2834 \if@ACM@review
2835   \newsavebox{\ACM@linecount@bx}
2836   \newlength\ACM@linecount@bxht
2837   \newcount\ACM@linecount
2838   \ACM@linecount\@ne\relax
2839   \def\ACM@mk@linecount{%
2840     \savebox{\ACM@linecount@bx}[4em][t]{\parbox[t]{4em}{\normalfont
2841       \normalsize
2842       \setlength{\ACM@linecount@bxht}{0pt}%
2843       \loop{\color{red}\scriptsize\the\ACM@linecount}}\
2844       \global\advance\ACM@linecount by \@ne
2845       \addtolength{\ACM@linecount@bxht}{\baselineskip}%
2846       \ifdim\ACM@linecount@bxht<\textheight\repeat
2847       {\color{red}\scriptsize\the\ACM@linecount}\hfill
2848       \global\advance\ACM@linecount by \@ne}}}
2849 \fi

```

\ACM@linecountL How to display the box on the left

```

2850 \def\ACM@linecountL{%
2851   \if@ACM@review
2852     \ACM@mk@linecount
2853     \begin{picture}(0,0)%
2854       \put(-26,-22){\usebox{\ACM@linecount@bx}}%
2855     \end{picture}%
2856   \fi}

```

\ACM@linecountR How to display the box on the right. In one column formats we do not step the numbers.

```

2857 \def\ACM@linecountR{%
2858   \if@ACM@review
2859     \ifcase\ACM@format@nr
2860       \relax % manuscript
2861       \relax
2862     \or % acmsmall

```

```

2863         \relax
2864     \or % acmlarge
2865         \relax
2866     \or % acmtog
2867         \ACM@mk@linecount
2868     \or % sigconf
2869         \ACM@mk@linecount
2870     \or % siggraph
2871         \ACM@mk@linecount
2872     \or % sigplan
2873         \ACM@mk@linecount
2874     \or % sigchi
2875         \ACM@mk@linecount
2876     \or % sigchi-a
2877         \ACM@mk@linecount
2878     \or % acmengage
2879         \ACM@mk@linecount
2880     \or % acmcp
2881         \relax
2882 \fi
2883 \begin{picture}(0,0)%
2884     \put(20,-22){\usebox{\ACM@linecount@bx}}%
2885 \end{picture}%
2886 \fi}

```

\ACM@timestamp The timestamp system

```

2887 \if@ACM@timestamp
2888 % Subtracting 30 from \time gives us the effect of rounding down despite
2889 % \numexpr rounding to nearest
2890 \newcounter{ACM@time@hours}
2891 \setcounter{ACM@time@hours}{\numexpr (\time - 30) / 60 \relax}
2892 \newcounter{ACM@time@minutes}
2893 \setcounter{ACM@time@minutes}{\numexpr \time - \theACM@time@hours * 60 \relax}
2894 \newcommand\ACM@timestamp{%
2895     \footnotesize%
2896     \ifx\@acmSubmissionID\@empty\relax\else
2897     Submission ID: \@acmSubmissionID.{ }%
2898 \fi
2899 \the\year-\two@digits{\the\month}-\two@digits{\the\day}{ }%
2900 \two@digits{\theACM@time@hours}:\two@digits{\theACM@time@minutes}{. }%
2901 Page \thepage of \@startPage--\pageref*{TotPages}.%
2902 }
2903 \fi

```

\@shortauthors Even if the author redefined \shortauthors, we do not print it in the headers when in anonymous mode:

```

2904 \def\@shortauthors{%
2905     \if@ACM@anonymous
2906     Anon.
2907     \ifx\@acmSubmissionID\@empty\else Submission Id: \@acmSubmissionID\fi
2908 \else\shortauthors\fi}

```

\@headfootfont The font to typeset header and footer text.

```

2909 \def\@headfootfont{\sffamily\footnotesize}

```

standardpagestyle The page style for all pages but the first one The page style for all pages but the first one

```

2910 \AtBeginDocument{%
2911 \fancypagestyle{standardpagestyle}{%
2912   \fancyhf{}%
2913   \renewcommand{\headrulewidth}{\z@}%
2914   \renewcommand{\footrulewidth}{\z@}%
2915   \def\@acmArticlePage{%
2916     \ifx\@acmArticle\empty%
2917       \if@ACM@printfolios\thepage\fi%
2918     \else%
2919       \@acmArticle\if@ACM@printfolios:\thepage\fi%
2920     \fi%
2921   }%
2922   \if@ACM@journal@bibstrip
2923     \ifcase\ACM@format@nr
2924     \relax % manuscript
2925     \fancyhead[LE]{\ACM@linecountL\if@ACM@printfolios\thepage\fi}%
2926     \fancyhead[RO]{\if@ACM@printfolios\thepage\fi}%
2927     \fancyhead[RE]{\@shortauthors}%
2928     \fancyhead[LO]{\ACM@linecountL\shorttitle}%
2929     \if@ACM@nonacm\else%
2930       \fancyfoot[RO,LE]{\footnotesize Manuscript submitted to ACM}
2931     \fi%
2932   \or % acmsmall
2933     \fancyhead[LE]{\ACM@linecountL\@headfootfont\@acmArticlePage}%
2934     \fancyhead[RO]{\@headfootfont\@acmArticlePage}%
2935     \fancyhead[RE]{\@headfootfont\@shortauthors}%
2936     \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2937     \if@ACM@nonacm\else%
2938       \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2939         \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2940     \fi
2941   \or % acmlarge
2942     \fancyhead[LE]{\ACM@linecountL\@headfootfont
2943       \@acmArticlePage\quad\textbullet\quad\@shortauthors}%
2944     \fancyhead[LO]{\ACM@linecountL}%
2945     \fancyhead[RO]{\@headfootfont
2946       \shorttitle\quad\textbullet\quad\@acmArticlePage}%
2947     \if@ACM@nonacm\else%
2948       \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2949         \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2950     \fi
2951   \or % acmtog
2952     \fancyhead[LE]{\ACM@linecountL\@headfootfont
2953       \@acmArticlePage\quad\textbullet\quad\@shortauthors}%
2954     \fancyhead[LO]{\ACM@linecountL}%
2955     \fancyhead[RE]{\ACM@linecountR}%
2956     \fancyhead[RO]{\@headfootfont
2957       \shorttitle\quad\textbullet\quad\@acmArticlePage\ACM@linecountR}%
2958     \if@ACM@nonacm\else%
2959       \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2960         \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2961     \fi

```

```

2962 \else % Proceedings
2963 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2964 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2965 \fancyhead[RE]{\@headfootfont\@shortauthors\ACM@linecountR}%
2966 \if@ACM@nonacm
2967 \fancyhead[LE]{\ACM@linecountL}%
2968 \fancyhead[RO]{\ACM@linecountR}%
2969 \else%
2970 \if@ACM@engage
2971 \fancyhead[LE]{\ACM@linecountL\@headfootfont\footnotesize
2972 EngageCSEdu. \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi}%
2973 \fancyhead[RO]{\@headfootfont
2974 EngageCSEdu. \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi
2975 \ACM@linecountR}%
2976 \else
2977 \fancyhead[LE]{\ACM@linecountL\@headfootfont\footnotesize
2978 \acmConference@shortname,
2979 \acmConference@date, \acmConference@venue}%
2980 \fancyhead[RO]{\@headfootfont
2981 \acmConference@shortname,
2982 \acmConference@date, \acmConference@venue\ACM@linecountR}%
2983 \fi
2984 \fi
2985 \fi
2986 \else % Proceedings
2987 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2988 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2989 \fancyhead[RE]{\@headfootfont\@shortauthors\ACM@linecountR}%
2990 \if@ACM@nonacm
2991 \fancyhead[LE]{\ACM@linecountL}%
2992 \fancyhead[RO]{\ACM@linecountR}%
2993 \else%
2994 \if@ACM@engage
2995 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2996 EngageCSEdu. \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi}%
2997 \fancyhead[RO]{\@headfootfont
2998 EngageCSEdu. \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi
2999 \ACM@linecountR}%
3000 \else
3001 \fancyhead[LE]{\ACM@linecountL\@headfootfont
3002 \acmConference@shortname,
3003 \acmConference@date, \acmConference@venue}%
3004 \fancyhead[RO]{\@headfootfont
3005 \acmConference@shortname,
3006 \acmConference@date, \acmConference@venue\ACM@linecountR}%
3007 \fi
3008 \fi
3009 \fi
3010 \if@ACM@sigchiamode
3011 \fancyheadoffset[L]{\dimexpr(\marginparsep+\marginparwidth)}%
3012 \fi
3013 \if@ACM@timestamp
3014 \fancyfoot[LO,RE]{\ACM@timestamp}
3015 \fi

```

```

3016 \if@ACM@acmcp
3017 \renewcommand{\footrulewidth}{0.1\p@}%
3018 \fancyheadoffset[L]{46pt}%
3019 \fancyhead[L]{\makebox[\z@][l]{%
3020   \raisebox{-\dimexpr(0.25\textheight*\ACM@ArticleType@nr)}{%
3021     \rotatebox{90}{\colorbox{@ACM@Article@color}{\color{white}%
3022       \strut\ACM@ArticleType~Article}}}%
3023   \ACM@linecountL}%
3024 \fancyhead[R]{\makebox[\z@][r]{\box\@ACM@acmcpbox}}%
3025 \fancyfoot[L,C]{}%
3026 \fancyfoot[R]{\footnotesize
3027   \@journalName, Volume~\@acmVolume, Issue~\@acmNumber,
3028   \ifx\@acmArticle\@empty\else Article~\@acmArticle\fi\space
3029   (\@acmPubDate)\ifx\@acmDOI\@empty\else\\@formatdoi{\@acmDOI}\fi}
3030 \fi
3031 }%
3032 \pagestyle{standardpagestyle}
3033 }

\@folio@wd Folio blob width, height, offsets and max number
\@folio@ht 3034 \newdimen\@folio@wd
\@folio@voffset 3035 \@folio@wd=\z@
\@folio@max 3036 \newdimen\@folio@ht
3037 \@folio@ht=\z@
3038 \newdimen\@folio@voffset
3039 \@folio@voffset=\z@
3040 \def\@folio@max{1}
3041 \ifcase\ACM@format@nr
3042 \relax % manuscript
3043 \or % acmsmall
3044 \@folio@wd=45.75pt\relax
3045 \@folio@ht=1.25in\relax
3046 \@folio@voffset=.2in\relax
3047 \def\@folio@max{8}
3048 \or % acmlarge
3049 \@folio@wd=43.25pt\relax
3050 \@folio@ht=79pt\relax
3051 \@folio@voffset=.55in\relax
3052 \def\@folio@max{10}
3053 \fi

\@folioblob The macro to typeset the folio blob.
3054 \def\@folioblob{\@tempcnta=0\@acmArticleSeq\relax
3055   \ifnum\@tempcnta=0\relax\else
First, we calculate \@acmArticleSeq modulo \@folio@max
3056   \loop
3057     \ifnum\@tempcnta>\@folio@max\relax
3058       \advance\@tempcnta by - \@folio@max
3059   \repeat
3060   \advance\@tempcnta by -1\relax
3061   \@tempdima=\@folio@ht\relax
3062   \multiply\@tempdima by \the\@tempcnta\relax
3063   \advance\@tempdima by -\@folio@voffset\relax

```

```

3064 \begin{picture}(0,0)
3065 \makebox[\z@]{\raisebox{-\@tempdima}{%
3066   \rlap{%
3067     \raisebox{-0.45\@folio@ht}{\z@}{\z@}{%
3068       \rule{\@folio@wd}{\@folio@ht}}}%
3069   \parbox{\@folio@wd}{%
3070     \centering
3071     \textcolor{white}{\LARGE\sffamily\bfseries\@acmArticle}}}}
3072 \end{picture}\fi}
3073

```

firstpagestyle The page style for the first page only.

```

3074 \AtBeginDocument{%
3075 \fancypagestyle{firstpagestyle}{%
3076   \fancyhf{}%
3077   \renewcommand{\headrulewidth}{\z@}%
3078   \renewcommand{\footrulewidth}{\z@}%
3079   \if@ACM@journal@bibstrip
3080     \ifcase\ACM@format@nr
3081       \relax % manuscript
3082       \fancyhead[L]{\ACM@linecountL}%
3083       \fancyfoot[RO,LE]{\if@ACM@printfolios\small\thepage\fi}%
3084       \if@ACM@nonacm\else%
3085         \fancyfoot[RE,LO]{\footnotesize Manuscript submitted to ACM}%
3086       \fi%
3087     \or % acmsmall
3088       \if@ACM@nonacm\else%
3089         \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
3090           \@acmNumber, Article \@acmArticle. Publication date:
3091           \@acmPubDate.}%
3092       \fi%
3093       \fancyhead[LE]{\ACM@linecountL\@folioblob}%
3094       \fancyhead[LO]{\ACM@linecountL}%
3095       \fancyhead[RO]{\@folioblob}%
3096       \fancyheadoffset[RO,LE]{0.6\@folio@wd}%
3097     \or % acmlarge
3098       \if@ACM@nonacm\else%
3099         \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
3100           \@acmNumber, Article \@acmArticle. Publication date:
3101           \@acmPubDate.}%
3102       \fi%
3103       \fancyhead[RO]{\@folioblob}%
3104       \fancyhead[LE]{\ACM@linecountL\@folioblob}%
3105       \fancyhead[LO]{\ACM@linecountL}%
3106       \fancyheadoffset[RO,LE]{1.4\@folio@wd}%
3107     \or % acmtog
3108       \if@ACM@nonacm\else%
3109         \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
3110           \@acmNumber, Article \@acmArticle. Publication date:
3111           \@acmPubDate.}%
3112       \fi%
3113       \fancyhead[L]{\ACM@linecountL}%
3114       \fancyhead[R]{\ACM@linecountR}%
3115     \else % Conference proceedings

```



```

3116 \fancyhead[L]{\ACM@linecountL}%
3117 \fancyhead[R]{\ACM@linecountR}%
3118 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
3119 \fi
3120 \else
3121 \fancyhead[L]{\ACM@linecountL}%
3122 \fancyhead[R]{\ACM@linecountR}%
3123 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
3124 \fi
3125 \if@ACM@timestamp
3126 \ifnum\ACM@format@nr=0\relax % Manuscript
3127 \fancyfoot[LO,RE]{\ACM@timestamp\quad
3128 \if@ACM@nonacm\else
3129 \footnotesize Manuscript submitted to ACM
3130 \fi}
3131 \else
3132 \fancyfoot[LO,RE]{\ACM@timestamp}
3133 \fi
3134 \fi
3135 \if@ACM@acmcp
3136 \renewcommand{\footrulewidth}{0.1\p@}%
3137 \fancyheadoffset[L]{46pt}%
3138 \fancyhead[L]{\makebox[\z@][l]{%
3139 \raisebox{-\dimexpr(0.25\textheight*\ACM@ArticleType@nr)}{%
3140 \rotatebox{90}{\colorbox{@ACM@Article@color}{\color{white}%
3141 \strut\ACM@ArticleType~Article}}}%
3142 \ACM@linecountL}%
3143 \fancyhead[R]{\makebox[\z@][r]{\box\@ACM@acmcpbox}}%
3144 \fancyfoot[L,C]{}%
3145 \fancyfoot[R]{\footnotesize
3146 \@journalName, Volume~\@acmVolume, Issue~\@acmNumber,
3147 \ifx\@acmArticle\empty\else Article~\@acmArticle\fi\space
3148 (\@acmPubDate)\ifx\@acmDOI\empty\else\\@formatdoi{\@acmDOI}\fi}
3149 \fi
3150 }}

```

3.23 Sectioning

\ACM@NRadjust Ross Moore's macro.

Initially \ACM@sect@format@ just passes through its #1 argument unchanged. When a sectioning macro such as \section occurs, the \ACM@NRadjust redefines \ACM@sect@format@ to expand into the styling commands; e.g., \@secfont. Then \Sectionformat is temporarily redefined to produce \realSectionformat{\ACM@sect@format{#1}}{#2}, which ultimately becomes \Sectionformat{@secfont{#1}}{#2}. This is done to allow \Sectionformat to be variable, as may be needed in particular circumstances. Its current expansion is saved as \realSectionformat which is used with the modified 1st argument, then \Sectionformat is reverted to its former expansion.

To style the section-number, the line #1{} is used at the end of \ACM@NRadjust. This imposes style-changing commands for fonts and sizes, but any \MakeUppercase acts on just the {}. It's a bit hacky, by essentially assuming that only numbers occur here, not letters to be case-changed. (This should be acceptable

in a class-file, as it ought to be possible to change the case elsewhere, if that was ever desired.) Also, it can result in \@adddotafter being called too soon, so a slight adjustment is made, via \ACM@adddotafter, which now tests whether its argument is empty. But the coding has to allow for other packages to have also patched \@adddotafter.

```

3151 \def\ACM@NRadjust#1{%
3152   \begingroup
3153   \expandafter\ifx\csname Sectionformat\endcsname\relax
3154   % do nothing when \Sectionformat is unknown
3155   \def\next{\endgroup #1}%
3156   \else
3157   \def\next{\endgroup
3158     \let\realSectionformat\Sectionformat
3159     \def\ACM@sect@format@{#1}%
3160     \let\Sectionformat\ACM@NR@adjustedSectionformat
3161     %% next lines added 2018-06-17 to ensure section number is styled
3162     \let\real@adddotafter\@adddotafter
3163     \let\@adddotafter\ACM@adddotafter
3164     #1}% imposes the styles, but nullifies \MakeUppercase
3165     \let\@adddotafter\real@adddotafter
3166   }%
3167   \fi \next
3168 }

```

\ACM@NR@adjustedSectionformat

```

3169 \def\ACM@NR@adjustedSectionformat#1#2{%
3170   \realSectionformat{\ACM@sect@format@{#1}}{#2}%
3171   \let\Sectionformat\realSectionformat}
3172 \DeclareRobustCommand{\ACM@sect@format@}{\ACM@sect@format@}
3173 \def\ACM@sect@format@null#1{#1}
3174 \let\ACM@sect@format@\ACM@sect@format@null
3175 \AtBeginDocument{%
3176   \expandafter\ifx\csname LTX@adddotafter\endcsname\relax
3177   \let\LTX@adddotafter\@adddotafter
3178   \fi
3179 }

```

\ACM@adddotafter

```

3180 \def\ACM@adddotafter#1{\ifx\relax#1\relax\else\LTX@adddotafter{#1}\fi}

```

Sectioning is different for different levels

```

3181 \renewcommand\section{\@startsection{section}{1}{\z@}%
3182   {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3183   {.25\baselineskip}%
3184   {\ACM@NRadjust\@secfont}}
3185 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
3186   {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3187   {.25\baselineskip}%
3188   {\ACM@NRadjust\@subsecfont}}
3189 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
3190   {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3191   {-3.5\p@}%
3192   {\ACM@NRadjust{\@subsubsecfont\@adddotafter}}}

```

```

3193 \renewcommand\paragraph{\@startsection{paragraph}{4}{\parindent}%
3194 {-1\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3195 {-3.5\p@}%
3196 {\ACM@NRadjust{\@parfont\@adddotafter}}}}
3197 \newcommand\noindentparagraph{\@startsection{paragraph}{4}{\z@}%
3198 {-1\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3199 {-3.5\p@}%
3200 {\ACM@NRadjust{\@parfont}}}}
3201
3202 \renewcommand\part{\@startsection{part}{9}{\z@}%
3203 {-10\p@ \@plus -4\p@ \@minus -2\p@}%
3204 {4\p@}%
3205 {\ACM@NRadjust{\@parfont}}}

```

\section@raggedright Special version of \raggedright compatible with \MakeUppercase

```

3206 \def\section@raggedright{\@rightskip\@flushglue
3207 \rightskip\@rightskip
3208 \leftskip\z@skip
3209 \parindent\z@}

```

\@secfont Fonts for sections etc. are different for different formats.

```

\@subsecfont 3210 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
\@subsubsecfont 3211 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
\@parfont 3212 \def\@subsubsecfont{\sffamily\itshape}
3213 \def\@parfont{\itshape}
3214 \setcounter{secnumdepth}{3}
3215 \ifcase\ACM@format@nr
3216 \relax % manuscript
3217 \or % acmsmall
3218 \or % acmlarge
3219 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
3220 \def\@subsecfont{\sffamily\large\section@raggedright}
3221 \or % acmtog
3222 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
3223 \def\@subsecfont{\sffamily\large\section@raggedright}
3224 \or % sigconf
3225 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
3226 \def\@subsecfont{\bfseries\Large\section@raggedright}
3227 \or % siggraph
3228 \def\@secfont{\sffamily\bfseries\Large\section@raggedright\MakeTextUppercase}
3229 \def\@subsecfont{\sffamily\bfseries\Large\section@raggedright}
3230 \or % sigplan
3231 \def\@secfont{\bfseries\Large\section@raggedright}
3232 \def\@subsecfont{\bfseries\section@raggedright}
3233 \def\@subsubsecfont{\bfseries\section@raggedright}
3234 \def\@parfont{\bfseries\itshape}
3235 \def\@subparfont{\itshape}
3236 \or % sigchi
3237 \setcounter{secnumdepth}{1}
3238 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
3239 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
3240 \or % sigchi-a
3241 \setcounter{secnumdepth}{0}
3242 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}

```

```

3243 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
3244 \or % acmengage
3245 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
3246 \def\@subsecfont{\bfseries\Large\section@raggedright}
3247 \or %acmcp
3248 \fi

```

`\@adddotafter` Add punctuation after a sectioning command

```

3249 \def\@adddotafter#1{#1\@addpunct{.}}

```

`\@addspaceafter` Add space after a sectioning command

```

3250 \def\@addspaceafter#1{#1\@addpunct{\enspace}}

```

```

3251 \if@ACM@acmcp
3252   \setcounter{secnumdepth}{-1}%
3253 \fi

```

3.24 TOC lists

`\@dotsep` Related to the `\tableofcontents` are all the horizontal fillers. Base \LaTeX defines `\@dottedtocline`, which we should not disable. Yet, this command expects `\@dotsep` to be defined but leaves this to the class implementation. Since `amsart` does not provide this, we copy the standard variant from `article` here.

```

3254 \providecommand*\@dotsep{4.5}

```

3.25 Theorems

`\acmplainbodyfont` The font to typeset the body of the `acmplain` theorem style.

```

3255 \def\acmplainbodyfont{\itshape}

```

`\acmplainindent` The amount to indent the `acmplain` theorem style.

```

3256 \def\acmplainindent{\parindent}

```

`\acmplainheadfont` The font to typeset the head of the `acmplain` theorem style.

```

3257 \def\acmplainheadfont{\scshape}

```

`\acmplainnotefont` The font to typeset the note of the `acmplain` theorem style.

```

3258 \def\acmplainnotefont{\@empty}

```

Customization of the `acmplain` theorem style:

```

3259 \ifcase\ACM@format@nr
3260 \relax % manuscript
3261 \or % acmsmall
3262 \or % acmlarge
3263 \or % acmtog
3264 \or % sigconf
3265 \or % siggraph
3266 \or % sigplan
3267   \def\acmplainbodyfont{\itshape}
3268   \def\acmplainindent{\z@}
3269   \def\acmplainheadfont{\bfseries}
3270   \def\acmplainnotefont{\normalfont}

```

```

3271 \or % sigchi
3272 \or % sigchi-a
3273 \or % acmengage
3274 \or % acmcp
3275 \fi

```

acmplain The acmplain theorem style

```

3276 \newtheoremstyle{acmplain}%
3277   {.5\baselineskip\@plus.2\baselineskip
3278     \@minus.2\baselineskip}% space above
3279   {.5\baselineskip\@plus.2\baselineskip
3280     \@minus.2\baselineskip}% space below
3281   {\@acmplainbodyfont}% body font
3282   {\@acmplainindent}% indent amount
3283   {\@acmplainheadfont}% head font
3284   {.}% punctuation after head
3285   {.5em}% spacing after head
3286   {\thmname{#1}\thmnumber{#2}\thmnote{ {\@acmplainnotefont{#3}}}}% head spec

```

\@acmdefinitionbodyfont The font to typeset the body of the acmdefinition theorem style.

```

3287 \def\@acmdefinitionbodyfont{\normalfont}

```

\@acmdefinitionindent The amount to indent the acmdefinition theorem style.

```

3288 \def\@acmdefinitionindent{\parindent}

```

\@acmdefinitionheadfont The font to typeset the head of the acmdefinition theorem style.

```

3289 \def\@acmdefinitionheadfont{\itshape}

```

\@acmdefinitionnotefont The font to typeset the note of the acmdefinition theorem style.

```

3290 \def\@acmdefinitionnotefont{\@empty}

```

Customization of the acmdefinition theorem style:

```

3291 \ifcase\ACM@format@nr
3292 \relax % manuscript
3293 \or % acmsmall
3294 \or % acmlarge
3295 \or % acmtog
3296 \or % sigconf
3297 \or % siggraph
3298 \or % sigplan
3299 \def\@acmdefinitionbodyfont{\normalfont}
3300 \def\@acmdefinitionindent{\z@}
3301 \def\@acmdefinitionheadfont{\bfseries}
3302 \def\@acmdefinitionnotefont{\normalfont}
3303 \or % sigchi
3304 \or % sigchi-a
3305 \or % acmengage
3306 \or % acmcp
3307 \fi

```

acmdefinition The acmdefinition theorem style

```

3308 \newtheoremstyle{acmdefinition}%
3309   {.5\baselineskip\@plus.2\baselineskip

```

```

3310 \@minus.2\baselineskip}% space above
3311 {.5\baselineskip\@plus.2\baselineskip
3312 \@minus.2\baselineskip}% space below
3313 {\@acmdefinitionbodyfont}% body font
3314 {\@acmdefinitionindent}% indent amount
3315 {\@acmdefinitionheadfont}% head font
3316 {.}% punctuation after head
3317 {.5em}% spacing after head
3318 {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmdefinitionnotefont(#3)}}}% head spec

```

Make acmplain the default theorem style.

```

3319 \theoremstyle{acmplain}

```

Delay defining the theorem environments until after other packages have been loaded. In particular, the `cleveref` package must be loaded before the theorem environments are defined in order to show the correct environment name (see <https://github.com/borisveytsman/acmart/issues/138>). The `acmthm` option is used to suppress the definition of any theorem environments. Also, to avoid obscure errors arising from these environment definitions conflicting with environments defined by the user or by user-loaded packages, we only define environments that have not yet been defined.

```

3320 \AtEndPreamble{%
3321 \if@ACM@acmthm
3322 \theoremstyle{acmplain}
3323 \@ifundefined{theorem}{%
3324 \newtheorem{theorem}{Theorem}[section]
3325 }{}
3326 \@ifundefined{conjecture}{%
3327 \newtheorem{conjecture}[theorem]{Conjecture}
3328 }{}
3329 \@ifundefined{proposition}{%
3330 \newtheorem{proposition}[theorem]{Proposition}
3331 }{}
3332 \@ifundefined{lemma}{%
3333 \newtheorem{lemma}[theorem]{Lemma}
3334 }{}
3335 \@ifundefined{corollary}{%
3336 \newtheorem{corollary}[theorem]{Corollary}
3337 }{}
3338 \theoremstyle{acmdefinition}
3339 \@ifundefined{example}{%
3340 \newtheorem{example}[theorem]{Example}
3341 }{}
3342 \@ifundefined{definition}{%
3343 \newtheorem{definition}[theorem]{Definition}
3344 }{}
3345 \fi
3346 \theoremstyle{acmplain}
3347 }

```

`\@proofnamefont` The font to typeset the proof name.

```

3348 \def\@proofnamefont{\scshape}

```

`\@proofindent` Whether or not to indent proofs.

```
3349 \def\@proofindent{\indent}
```

Customization of the proof environment.

```
3350 \ifcase\ACM@format@nr
3351 \relax % manuscript
3352 \or % acmsmall
3353 \or % acmlarge
3354 \or % acmtog
3355 \or % sigconf
3356 \or % siggraph
3357 \or % sigplan
3358 \def\@proofnamefont{\itshape}
3359 \def\@proofindent{\noindent}
3360 \or % sigchi
3361 \or % sigchi-a
3362 \or % acmengage
3363 \or % acmcp
3364 \fi
```

proof We want some customization of the proof environment.

```
3365 \renewenvironment{proof}[1][\proofname]{\par
3366 \pushQED{\qed}%
3367 \normalfont \topsep6\p@\@plus6\p@\relax
3368 \trivlist
3369 \item[\@proofindent\hskip\labelsep
3370 {\@proofnamefont #1\@addpunct{.}}]\ignorespaces
3371 }{%
3372 \popQED\endtrivlist\endpfalse
3373 }
```

3.26 Balancing columns

We need balancing only if the user did not disable it, and we use a two column format. Note that pbalance uses a different mechanism.

```
3374 \AtEndPreamble{%
3375 \if@ACM@pbalance
3376 \global\@ACM@balancefalse
3377 \ifcase\ACM@format@nr
3378 \relax % manuscript
3379 \or % acmsmall
3380 \or % acmlarge
3381 \or % acmtog
3382 \RequirePackage{pbalance}%
3383 \or % sigconf
3384 \RequirePackage{pbalance}%
3385 \or % siggraph
3386 \RequirePackage{pbalance}%
3387 \or % sigplan
3388 \RequirePackage{pbalance}%
3389 \or % sigchi
3390 \RequirePackage{pbalance}%
3391 \or % sigchi-a
3392 \or % acmengage
```

```

3393         \RequirePackage{pbalance}%
3394         \or % acmcp
3395     \fi
3396 \fi
3397 \if@ACM@balance
3398     \ifcase\ACM@format@nr
3399     \relax % manuscript
3400         \global\@ACM@balancefalse
3401     \or % acmsmall
3402         \global\@ACM@balancefalse
3403     \or % acmlarge
3404         \global\@ACM@balancefalse
3405     \or % acmtog
3406         \RequirePackage{balance}%
3407     \or % sigconf
3408         \RequirePackage{balance}%
3409     \or % siggraph
3410         \RequirePackage{balance}%
3411     \or % sigplan
3412         \RequirePackage{balance}%
3413     \or % sigchi
3414         \RequirePackage{balance}%
3415     \or % sigchi-a
3416         \global\@ACM@balancefalse
3417     \or % acmengage
3418         \RequirePackage{balance}%
3419     \or % acmcp
3420         \global\@ACM@balancefalse
3421 \fi
3422 \fi
3423 }
3424 \AtEndDocument{%
3425     \if@ACM@balance
3426     \if@twocolumn
3427     \balance
3428     \fi\fi}

```

3.27 Acknowledgments

\acksname

```

3429 \newcommand\acksname{Acknowledgments}

```

\acks This is a comment-like structure

```

3430 \specialcomment{acks}{%
3431     \begin{group}
3432     \section*{\acksname}
3433     \phantomsection\addcontentsline{toc}{section}{\acksname}
3434 }{%
3435     \end{group}
3436 }

```

\grantsponsor We just typeset the name of the sponsor

```

3437 \def\grantsponsor#1#2#3{#2}

```


`\grantnum`

```
3438 \newcommand\grantnum[3][\]{#3%
3439 \def\@tempa{#1}\ifx\@tempa\@empty\else\space(\url{#1})\fi}
```

3.28 Conditional typesetting

We use the comment package for conditional typesetting:

```
3440 \AtEndPreamble{%
3441 \if@ACM@screen
3442 \includecomment{screenonly}
3443 \excludecomment{printonly}
3444 \else
3445 \excludecomment{screenonly}
3446 \includecomment{printonly}
3447 \fi
3448 \if@ACM@anonymous
3449 \excludecomment{anonsuppress}
3450 \excludecomment{acks}
3451 \else
3452 \includecomment{anonsuppress}
3453 \fi}
```

3.29 Additional bibliography commands

`\showeprint` The command `\showeprint` has two arguments: the (optional) prefix and the eprint number. Right now the only prefix we understand is the (lowercase) word ‘arxiv’.

```
3454 \newcommand\showeprint[2][arxiv]{%
3455 \def\@tempa{#1}%
3456 \ifx\@tempa\@empty\def\@tempa{arxiv}\fi
3457 \def\@tempb{arxiv}%
3458 \ifx\@tempa\@tempb\relax
3459 \arXiv:\href{https://arxiv.org/abs/#2}{#2}%
3460 \else
3461 \def\@tempb{arXiv}%
3462 \ifx\@tempa\@tempb\relax
3463 \arXiv:\href{https://arxiv.org/abs/#2}{#2}%
3464 \else
3465 #1:#2%
3466 \fi
3467 \fi}
```

3.30 Index

`\theindex` Standard amsart uses plain page style in index pages. This clashes with line numbering for review option, so we redefine it.

```
3468 \def\theindex{\@restonecoltrue\if@twocolumn\@restonecolfalse\fi
3469 \columnseprule\z@ \columnsep 35\p@
3470 \@indextitlestyle
3471 \let\item\@idxitem
3472 \parindent\z@ \parskip\z@\@plus.3\p@\relax
3473 \raggedright
3474 \hyphenpenalty\@M
3475 \footnotesize}
```

3.31 End of Class

`\vspace` We do not disable `\vspace`, but add warning to it

```
3476 \let\@vspace@orig=\@vspace
3477 \let\@vspacer@orig=\@vspacer
3478 \apptocmd{\@vspace}{\ClassWarning{\@classname}{\string\vspace\space should
3479     only be used to provide space above/below surrounding
3480     objects}}{}{}
3481 \apptocmd{\@vspacer}{\ClassWarning{\@classname}{\string\vspace\space should
3482     only be used to provide space above/below surrounding
3483     objects}}{}{}
3484 \let\@vspace@acm=\@vspace
3485 \let\@vspacer@acm=\@vspacer
```

`\ACM@origbaselinestretch` We produce an error if the user tries to change `\baselinestretch`

```
3486 \let\ACM@origbaselinestretch\baselinestretch
3487 \AtEndDocument{\ifx\baselinestretch\ACM@origbaselinestretch\else
3488   \ClassError{\@classname}{An attempt to redefine
3489     \string\baselinestretch\space detected. Please do not do this for
3490     ACM submissions!}\fi}

3491 \normalsize\normalfont\frenchspacing
3492 </class>
```

References

- [1] UK T_EX Users Group. UK list of T_EX frequently asked questions. <https://texfaq.org>, 2019.
- [2] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://www.ctan.org/pkg/amslatex>.
- [3] Johannes L. Braams and Javier Bezos. *Babel*, 2022. <http://www.ctan.org/pkg/babel>.
- [4] Cristophe Fiorio. *algorithm2e.sty—package for algorithms*, October 2015. <http://www.ctan.org/pkg/algorithm2e>.
- [5] Rogério Brito. *The algorithms bundle*, August 2009. <http://www.ctan.org/pkg/algorithms>.
- [6] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*, June 2015. <http://www.ctan.org/pkg/listings>.
- [7] Simon Fear. *Publication quality tables in L^AT_EX*, April 2005. <http://www.ctan.org/pkg/booktabs>.
- [8] Association for Computing Machinery. *ACM Visual Identity Standards*, 2007. <http://identitystandards.acm.org>.
- [9] Axel Sommerfeldt. *The subcaption package*, April 2013. <http://www.ctan.org/pkg/subcaption>.
- [10] Boris Veytsman, Bern Schandl, Lee Netherton, and C. V. Radhakrishnan. *A package to create a nomenclature*, September 2005. <http://www.ctan.org/pkg/nomenc1>.
- [11] Nicola L. C. Talbot. *User Manual for glossaries.sty v4.44*, December 2019. <http://www.ctan.org/pkg/glossaries>.
- [12] David Carlisle. *The textcase package*, October 2004. <http://www.ctan.org/pkg/textcase>.

Change History

1.48	General: Added prologue option to xcolor	50	\ccsdesc@parse: Added warning for missing concepts	75
	Bib code cleanup (Zack Weinberg)	35	\if@ACM@printacmref: Added warning for longer papers	72
	Documentation update (siggraph) .	35	\keywords: Added warning for missing keywords	72
1.49	General: New journal: DTRAP	35	1.69	\vspace: Added the changed command to avoid grouping
1.53	General: New journals: PACMCGIT, TIOT, TDSCI	35	1.70	General: Name change for TDS
	Rearranged docs	35	1.71	General: Bibliography change: volume for @inproceedings is now in brackets together with series
1.54	General: Moved footnote stuff before hyperref call (Ross Moore)	35		LuaTeX now uses the OTF versions of fonts
1.56	General: Documented \Description	35		Retired sigchi and sigchi-a
1.57	General: Booktabs package is now the default	35	1.75	General: Documentation update
1.58	General: Changes in samples (Enrico Gregorio)	35	1.78	General: Documentation update: Word count
	New journal: HEALTH. TDS is renamed to TDSCI	35	1.79	General: Updated indormation for TAP, TCPS, TEAC
1.60	General: New option: urlbreakonhyphens	35	1.80	General: Added DLT and FAC
	\if@ACM@urlbreakonhyphens: introduced macro	36	1.82	General: Updated abbreviations and codes for several journals
1.62	General: New journal: TELO	35	1.84	General: New journals: JDS, GAMES
1.63	General: New journal: FACMP	35		
	New journal: TQUANT	35	1.85	General: Added CC licenses
1.63a	General: Move: TQUANT to TQC	35		Added: acmengage
1.64	General: Putting abstract after \maketitle now causes an error .	35		New journal: JRC
1.65	General: New journal: DGOV	35		\@mkauthors: Added: acmengage
1.66	General: ACM reference format is now mandatory for papers over one page; CCS concepts and keywords are now mandatory for papers over two pages	35		\@mktitle: Added: acmengage
	Authors' addresses are mandatory for journal articles	35		\@parfont: Added: acmengage
	\@mkauthorsaddresses: Added warning for missing addresses	97		\@printtopmatter: Added: acmengage
				\@specialsection: Added: acmengage
				\@subtitlefont: Added: acmengage
				\@titlefont: Added: acmengage
				\ACM@linecountR: Added: acmengage
				format: New format: acmengage
				\parskip: Added: acmengage

1.87	Patched \setcitestyle command; closes https: //github.com/borisveytsman/ acmart/issues/19	36	35
format: New format: acmcp			
v1.00	General: First released version	35	
v1.01	General: Changed hyperref colors in screen mode (closes https: //github.com/borisveytsman/ acmart/issues/1)	35	
	Defined ACM colors	35	
	Explicitly put draft option (closes https: //github.com/borisveytsman/ acmart/issues/4)	38	
	Set headheight to 1pc for all formats (closes https: //github.com/borisveytsman/ acmart/issues/5)	35	
v1.02	General: Added TOPS and TSC (closes https: //github.com/borisveytsman/ acmart/issues/12)	35	
	Documentation changes (closes https: //github.com/borisveytsman/ acmart/issues/13)	35	
v1.03	General: Added anonsuppress environment	35	
	Added authorversion option (closes https: //github.com/borisveytsman/ acmart/issues/9)	35	
	\@formatdoi: Added macro	78	
	\if@ACM@authorversion: Added macro	37	
	\maketitle: Added special case of authorversion	82	
v1.04	General: Updated bibliography for siggraph	35	
	\acmArticleSeq: Name change by Matthew Fluet	70	
	\acmDOI: Name change by Matthew Fluet	71	
	\acmISBN: Name change by Matthew Fluet	71	
v1.05	General: Added processing doi numbers for acmsiggraph and doi numbers for sigproc.bib	35	
v1.06	\@ACM@badge@skip: Added macro	71	
	\@ACM@badge@width: Added macro	71	
	\@ACM@title@width: Added macro	71	
	\@mktitle@i: Added processing badges	88	
	Made generic	88	
	\@mktitle@ii: Now this macro is obsolete	89	
	\@mktitle@iii: Added processing badges	89	
	Made more generic	89	
	\@mktitle@iv: Made more generic	90	
	\@printtopmatter: Added processing badges	86	
	\@subtitlefont: Added macro	88	
	\@titlefont: Added macro	87	
	\acmBadgeL: Added macro	71	
	\acmBadgeR: Added macro	71	
	\if@ACM@badge: Added macro	71	
v1.07	\maketitle: Corrected a bug with abstract footnotes	82	
	Corrected a bug with permssion and footnotes order	82	
v1.08	General: SIGPLAN reformatting by Matthew Fluet	35	
	Typos corrected (Tobias Pape)	35	
v1.09	General: Revert SIGPLAN caption rules	35	
v1.10	General: Changes of 'licensedothergov' wording	76	
	\maketitle: Corrected a bug with doi in manuscript and author version, https: //github.com/borisveytsman/ acmart/issues/36	82	
	standardpagestyle: Reversed folios location	101	
v1.11	General: Customization of ACM theorem styles and proof environment by Matthew Fluet	35	
v1.12	General: Added graceful behavior when libertine fonts are absent	53	
	Documentation updates	35	

\@marginfigure: Now centering by default	57	\affiliation: Added code for author groups	68
\@margintable: Now centering by default	57	\author: Added code for author groups	67
\@parfont: Moved to \section@raggedright	107	\city: Added macro	90
\copyrightpermissionfootnoterule: Added macro	52	\country: Added macro	90
\descriptionlabel: Redefined	59	\department: Added macro	90
\footnoterule: Made shorter	53	\grantnum: Added macro	113
\if@ACM@natbib@override: Added macro	37	\grantsponsor: Added macro	112
\if@ACM@newfonts: Added macro	54	\if@insideauthorgroup: Introduced macro	67
\maketitle: Moved thankses to copyrightpermission box	82	\institution: Added macro	90
\section@raggedright: Introduced macro	107	\num@authorgroups: Renamed	67
v1.13		\orcid: Introduced macro	69
General: Font adjustments for acmsmall	91	\position: Added macro	90
Increased font size for ACM Large	40	\postcode: Added macro	90
Print bibliographic information by default for the proceedings	73	\state: Added macro	90
\empfootnotetext: Made minipage footnotes centered	48	\streetaddress: Added macro	90
\bibliographystyle: Redefined macro	49	standardpagestyle: Better handling of anonymous mode	101
\bibstyle@acmauthoryear: Added macro	43	v1.16	
\bibstyle@acmnumeric: Added macro	43	General: Formatting header/footer (Matthew Fluet)	35
\if@ACM@printfolios: Added macro	73	\@headfootfont: Added macro	100
standardpagestyle: Added headers for sigs	101	standardpagestyle: Customize header/footer text font	101
Expanded headers for sigchi-a	101	v1.17	
Suppressed folios if sig	101	General: Slightly decreased margins for sigs	50
v1.14		\@makefnmark: Redefined	48
General: \citestyle updates (Matthew Fluet)	35	\@mkauthors: TOG now uses the same authors block as other journals	91
Patched \citestyle	41	\@mkauthors@ii: Deleted	94
\bibstyle@acmauthoryear: Moved def of \bibstyle@acmauthoryear before use	43	\@mkbibcitation: Added \nobreak	98
\bibstyle@acmnumeric: Moved def of \bibstyle@numeric before use	43	Changed format for sigs	98
v1.15		\acmArticle: The default is now numerical	70
\@ACM@addtoaddress: Added macro	90	\acmMonth: The default must be numerical. Closes #50.	70
\@mkauthors@iii: New authors system	94	\acmNumber: The default is now numerical	70
\@shortauthors: Introduced macro	100	\acmVolume: The default is now numerical	70
\@typeset@author@bx: Moved to separate macro	94	\acmYear: The default is now numerical	70
\acks: Added macro	112	\description: Decreased indent	59
		\grantnum: Added url	113
		\grantsponsor: Renamed	112
		\if@ACM@printacmref: Renamed from \if@ACM@printbib	72
		standardpagestyle: Added paper title to sigs	101

v1.18	General: Natbib is now the default for all formats	35	standardpagestyle: Corrected printfolios (Matthew Fluet)	101
	\@mkauthors@i: Now we andify affiliations	93	v1.30 General: Added \frenchspacing . . .	114
	\@typeset@author@line: Added macro	92	Bibtex style now recognizes https:// in doi	35
v1.19	General: Include 'Abstract', 'Acknowledgements', and 'References' in PDF bookmarks (Matthew Fluet)	35	Switched to T1: looks like libertine has problems with \l in OT1 . . .	54
	Include 'References' in PDF bookmarks (Matthew Fluet)	41	Updated IMWUT and PACMPL . . .	59
	\@mkabstract: Include 'Abstract' in PDF bookmarks (Matthew Fluet) . .	97	\department: Added optional parameter	90
	\acks: Include 'Acknowledgements' in PDF bookmarks (Matthew Fluet) . .	112	v1.31 General: Documentation changes . . .	35
v1.20	General: Bug fixes for bst	35	\@additionalaffiliation: Added macro	68
	\@mkabstract: Deleted spurious space	97	\@mkbibcitation: Disabled linebreak	98
v1.21	\showeprint: Added macro	113	\@startsection: Added \tochangmeasure	45
v1.22	General: More bibliography changes for Aptara	35	Redefined macro	47
v1.23	General: Add PACMPL journal option	35	\@textbottom: Redefined	53
v1.24	General: Add IMWUT journal option	59	\acmMonth: The default now is the current month (Matteo Riondato)	70
v1.25	General: Updated PACMPL	59	\acmYear: The default now is the current year (Matteo Riondato) . .	70
v1.26	General: Corrected \shortcite bug . .	35	\additionalaffiliation: Added macro	68
	Documentation typos fixed (thanks to Stephen Spencer)	35	\l@section: Redefined macro . . .	47
v1.27	\if@ACM@printccs: Typo corrected . .	72	\l@subsubsection: Redefined macro	47
v1.28	General: Corrected option natbib behavior	43	v1.32 General: Added POMACS journal option	35
	Got rid of warnings in pdf keywords	48	Format siggraph is now obsolete . .	35
	\ccsdesc@parse: Change from \to to \textrightarrow (Matteo Riondato)	75	\@formatdoi: New doi format	78
v1.29	General: Increased head to 13pt	50	v1.33 General: Added acmart-preload-hook	35
	\@mkabstract: Removed spurious indentation (John Wickerson) . . .	97	Added cmap and glyphtounicode . .	53
	\ccsdesc@parse: Add spacing after bullet and around rightrightarrow; semicolon separators no longer in bold/italic (John Wickerson)	75	BibTeX comma before articleno bug corrected	35
			BibTeX crossref bug corrected . . .	35
			BibTeX numpages bug corrected . .	35
			Documentation updates	35
			Moved \citename definition for non-natbib bibliography, so a package may redefine it	49
			Switched to Type 1 fonts for libertine even if OTF-capable engine is used (Kai Mindermann) .	54
			\@ACM@addtoaddress: Added obeypunctuation code	90
			\@mkauthors@i: Added obeypunctuation code	93
			\@mkauthors@iii: Added obeypunctuation code	94

\@mkauthors@iv: Added	Deleted ‘DOI’ from doi numbers	82
obeypunctuation code	Rearranged bibstrip	82
\@subtitlefont: Added	The \terms command is now	
\normalsize	obsolete	82
\ACM@linecountL: Renamed macro	\terms: The \terms command now	
\ACM@linecountR: Added macro	just produces a warning	72
\ACM@timestamp: Added current page		
number	v1.35	
Added macro (Michael D. Adams)	General: BibTeX bug fixed: et al.	35
Added submission id	If the copyright is set to usgov or	
\acmSubmissionID: Added macro	rightsretained, the price is	
\city: Added obeypunctuation code	suppressed	76
\country: Added obeypunctuation	\bibstyle@acmauthoryear: Square	
code	brackets for author-year style	43
\department: Added obeypunctuation		
code	v1.36	
\if@ACM@affiliation@obeypunctuation:	General: Added PACMHCI journal	
Added macro	options	59
\if@ACM@authordraft: Added macro	Added the possibility to adjust	
\if@ACM@natbib@override: Deleted	number of author boxes per row	
macro	in conference formats	35
\if@ACM@timestamp: Added macro	\@ACM@authorsperrrow: Added macro	73
(Michael D. Adams)	\@mkauthors@iii: Added	
\institution: Added	authorsperrrow override	94
obeypunctuation code	\@mkauthors@iv: Added	
firstpagestyle: Added right	authorsperrrow override	95
linecount for two-column formats	\if@ACM@authordraft: Corrected	
Added timestamp (Michael	typo, thanks to bargteil	38
D. Adams)		
\maketitle: Fixed the bug with	v1.37	
figures on top and bottom of the	General: Reduce list indentation	
title page, thanks to David Epstein	(Matthew Fluet)	58
\position: Added obeypunctuation	Set \normalparindent; Reduce list	
code	indentation (Matthew Fluet)	35
\postcode: Added obeypunctuation	\description: Reduce list	
code	indentation (Matthew Fluet)	59
\state: Added obeypunctuation code	\descriptionlabel: Reduce list	
\streetaddress: Added	indentation (Matthew Fluet)	59
obeypunctuation code	\normalparindent: Set	
standardpagestyle: Added right	\normalparindent (Matthew	
linecount for two-column formats	Fluet)	52
Added timestamp (Michael	v1.38	
D. Adams)	General: Increase default font size for	
v1.34	SIGPLAN	35, 40
\@mkbibcitation: Deleted DOI from	v1.39	
doi numbers	\@authornotemark: Added macro	97
\ACM@linecount@bx: Rulers now are	\authornotemark: Added macro	70
continuous	v1.40	
\ACM@linecountL: Rulers now are	General: Added ‘textcase’ package	41
continuous	Added heightrounded to geometry	50
\ACM@linecountR: Rulers now are	Added new copyright version:	
continuous	licensedcagov	35
\maketitle: Added date to the	Added package cleveref	35
bibstrip in conf proceedings	Added Ross Moore code for	
	glyphtounicode	53
	Bibliography changes	35

\@copyrightowner: Added new copyright version: licensedcagov	77	\maketitle: Empty DOI or ISBN are not printed (by Michael Ekstrand)	82
\@copyrightpermission: Added new copyright version: licensedcagov	78	v1.45	
\@mkauthors@i: Switched to MakeTextUppercase	93	\@folioblob: Switched \bfseries\sffamily to \sffamily\bfseries	103
\@parfont: Switched to MakeTextUppercase	107	\@parfont: Switched \bfseries\sffamily to \sffamily\bfseries	107
\ACM@linecount@bx: Work around a bug in xcolor: looks like cmyk colors in boxes do not work	99	\@titlefont: Switched \bfseries\sffamily to \sffamily\bfseries	87
\ccdesc@parse@finish: Added macro	75	v1.46	
\city: We now do not print this even in SIG	90	General: Added etoolbox	35
\country: Fixed bugs with extra spaces	90	Bst file bug fixes: label width is calculated correctly	35
\l@section: Redefined macro	47	Delayed hypersetup since journal options may change screen mode	48
\postcode: We now do not print this even in SIG	90	PACM now set screen to true	59
\state: We now do not print this even in SIG	90	Restore theorem defs to class file	35
\streetaddress: We now do not print this even in SIG	90	\@mkauthorsaddresses: Introduced macro	96
v1.41		\@mkbibcitation: Added subtitle	98
General: Added new badges	35	\@printendtopmatter: Made it \par\bigskip uniformly	98
v1.42		\@printtopmatter: Deleted rule	86
General: Deleted ACM badges	35	\@setauthorsaddresses: Introduced macro	98
v1.43		\ACM@linecount@bx: Rearranged the code to get rid of spurious underfull messages (Benjamin Byholm)	99
\@startsection: Added \makeatletter	47	\author: Started counting authors	67
\country: Added comma before country for journals	90	\authorsaddresses: Introduced macro	69
v1.44		\country: Corrected spacing for institution	90
General: Added package refcount	35	\if@ACM@acmthm: Modified description	36
Deleted package cleveref	35	\liningnums: Workaround for compatibility with fontspec	54
Put theorem defs in a separate style	35	\maketitle: Added authors' addresses 'Thankses go before authors' addresses	82
\@acmBooktitle: Added macro	66	\num@authors: Introduced macro	67
\@acmEditors: Added macro	67	v1.47	
\@editorsAbbrev: Added macro	66	General: New journal: THRI	35
\@folioblob: Suppress the blob if acmArticleSeq is empty	103	v1.48	
\@mkbibcitation: If the paper has just one page, use 'page' instead of 'pages'	98	General: \citeyear no longer behaves like \citeyearpar	49
\ACM@restore@pagestyle: Added macro	99	Code prettying (Michael D. Adams)	35
\acmArticle: The default is now empty	70	Initial support for Biblatex (Daniel Thomas)	35
\acmArticleSeq: Now acmArticle might be empty	70		
\acmBooktitle: Added macro	66		
\editor: Added macro	67		
\if@ACM@acmthm: Added macro	36		

Misc entries in the bibliography no longer produce a separate date . . .	35	\ACM@NR@adjustedSectionformat: Added macro	106
Typos fixed (Jamie Davis)	35	\ACM@NRadjust: Added macro	105
\@headfootfont: Deleted unnecessary switch (Michael D. Adams)	100	\author: Added submission id in anonymous mode	67
\@mkabstract: Removed spurious indentation if abstract is followed by an empty line	97	\if@ACM@nonacm: Added macro	37
\ACM@timestamp: Formatting change (Michael D. Adams)	100	v1.55	
\if@ACM@review: Review mode now switches on folios	36	General: Now we use purple color for links	48
\maketitle: Added acmart and version info to pdfcreator tag . . .	82	Table captions for SIGCHI now use the same font size as figure captions (Luis Leiva)	56
Added language and doctitle attributes to PDF (Andreas Reichinger)	82	Typo corrected (Zack Weinberg) . .	41
Suppressed empty DOI (Serguei Mokhov)	82	\@mkbibcitation: Bug corrected . . .	98
v1.50		\maketitle: Fixes topnum	82
\@copyrightpermission: New copyright statements for iw3c2w3[g]	78	v1.56	
v1.51		General: Looks like XeTeX requires explicit monotype font declaration	54
General: Corrected the bug with price suppression	76	Make two-column layouts flush (Philip Quinn)	50
Suppress price if the copyright is set to iw3c2w3 or iw3c2w3g	76	\@marginfigure: Added checking for description	57
XeTeX now uses OTF fonts (Joachim Breitner)	54	\@mkteasers: Added check for description	97
firstpagestyle: We now use journal abbreviation for footers	104	\acksname: Added macro (Philip Quinn)	112
standardpagestyle: We now use journal abbreviation for footers .	101	\ccsdesc@parse: End the concepts list with a period (Philip Quinn) .	75
v1.52		\Description: Added macro	55
\@copyrightowner: Rewording of licenses	77	\if@Description@present: Added macro	55
\@copyrightpermission: Another rewording of copyright statements for iw3c2w3[g]	78	\if@undescribed@images: Added macro	55
v1.53		v1.57	
General: Added PACMCGIT, TIOT, TDSCI	59	\ACM@origbaselinestretch: Added check whether the user changed \baselinestretch	114
v1.54		\author: Added warning if \author has comma	67
General: Added Ross's patch for sectioning	106	\email: Added warning if \author has comma	69
Deleted indent for subsubsection .	106	\if@ACM@balance: Added macro . . .	37
XeTeX now uses T1 encoding . . .	54	\vspace: Added warning	114
\@mkbibcitation: Bug corrected (Ross Moore)	98	v1.58	
\@shortauthors: Added submission id in anonymous mode	100	General: Added HEALTH. TDSCI is renamed to TDS	59
\ACM@adddotafter: Added macro . .	106	Suppressed \addtocounter in pdf subject	48
		\@dblfloat: Deleted spurious \vspace warning	57
		\@marginfigure: Deleted spurious \vspace warning	57
		\@margintable: Deleted spurious \vspace warning	57

\mkbibcitation: Deleted spurious		space warnings	55
\vspace warning	98	\@parfont: Deleted redefinitions of	
\@printendtopmatter: Deleted		sections	107
spurious \vspace warning	98	\@specialsection: Paragraph inside	
\@sidebar: Deleted spurious \vspace		group does not print its argument.	
warning	56	Added a bugfix	85
\maketitle: Original \vspace inside		v1.68	
\maketitle	82	General: New command for unindent	
\vspace: Preserved old versions as		paras	106
\@vspace@orig and		\@specialsection: Deleted grouping	
\@vspace@orig	114	altogether	85
v1.59		v1.69	
\acmConference: Setting		General: No dots for unindented	
\@ACM@journal@bibstrip	66	paragraphs	106
\acmJournal: Setting		\@printendtopmatter: Deleted	
\@ACM@journal@bibstrip	66	grouping	98
\if@ACM@journal@bibstrip:		\@specialsection: Changed dot to	
Introduced macro	39	colon for sigplan	85
firstpagestyle: Added logic for		\ACM@linecountR: Do not increase	
conference papers using journal		numbers in one column format . .	99
format	104	\ccsdesc@parse: Use math right	
Moved page styles to		arrow in text	75
\AtBeginDocument	104	v1.71	
standardpagestyle: Added logic for		\l@subsubsection: Bug fixed (thanks	
conference papers using journal		to Andrew Black)	47
format	101	v1.72	
Moved page styles to		General: Added hyperxmp	48
\AtBeginDocument	101	\author: Added \detokenize	
v1.60		(Kuldeep S. Meel)	67
\@headfootfont: Moved to		\maketitle: Do not andify authors	
footnotesize	100	for pdf metadata (Scott Pakin) . .	82
v1.61		v1.73	
\@typeset@author@bx: Added		General: Patching minted and minted*	
\normalbaselines	94	to prevent spurious space	
v1.64		warnings	55
\ACM@linecount@bx: Bug fix: made		\@ACM@checkaffil: Added macro . .	93
the spacing on the left and the		\@ACM@resetaffil: Added macro . .	92
right size equal	99	\mkauthors@i: Check the presence	
\if@ACM@maketitle@typeset:		of required elements for	
Introduced macro	59	affiliations	93
\maketitle: Added a switch setting to		\mkauthors@iii: Check the	
show that \maketitle is typeset .	82	presence of required elements for	
v1.65		affiliations	94
\mkauthorsaddresses: Deleted		\mkauthors@iv: Check the presence	
cs@addpunct	96	of required elements for	
v1.66		affiliations	95
General: Patching algorithm and		\city: Check the presence in affil . .	90
algorithm* to prevent spurious		\country: Check the presence in affil	90
space warnings	55	\if@ACM@citypresent: Added macro	92
\@specialsection: Suppress		\if@ACM@countrypresent: Added	
warnings about \vspace	85	macro	92
v1.67		\if@ACM@instpresent: Added macro	92
General: Patching lstlisting and		\institution: Check the presence in	
lstlisting* to prevent spurious		affil	90

\maketitle: Do not check again the presense of address fields	82	\mktranslatedabstract: Added macro	97
v1.74		\mktranslatedkeywords: Added macro	69
General: Changed the order of font loading	54	\@translatedabstracts: Added macro	45
v1.75		\@translatedkeywords: Added macro	45
\@ACM@checkaffil: Changed warning to error for country	93	\@translatedsubtitle: Added macro	45
\@beginmaketitlehook: Introduced macro	81	\@translatedtitle: Added macro	44
\AtBeginMaketitle: Introduced macro	81	\ACM@lang@check: Added macro	44
\maketitle: Added \@beginmaketitlehook	82	\ACM@languages: Introduced macro	38
v1.76		\maketitle: I13n	82
General: Moved hyperxmp before hyperref, see https://github.com/borisveytsman/ acmart/issues/425	48	translatedabstract: Added macro	45
\author: Added code for orcid links	67	\translatedkeywords: Added macro	45
\if@ACM@pbalance: Added macro	37	\translatedsubtitle: Added macro	45
\maketitle: Put \par inside group for keywords	82	\translatedtitle: Added macro	44
\orcid: Added code for orcid links	69	v1.85	
standardpagestyle: Fixed bug with no line numbers for nonacm	101	General: Added CC licenses	76
v1.77		\@acmengagemetadata: Introduced macro	82
\@mkauthorsaddresses: New separator of institutions	96	\@copyrightowner: Added CC licenses	77
v1.78		\@copyrightpermission: Added CC licenses	78
\@mkauthors@i: Unboxing \mktitle@bx	93	\@typesetengagemetadata: Introduced macro	98
\@mkauthors@iii: Unboxing \mktitle@bx	94	\if@ACM@engage: Introduced macro	39
\@mkteasers: Unboxing \mktitle@bx	97	\maketitle: acmengage	82
\@printtopmatter: Added processing the overflowing title box	86	\setccctype: Added macro	77
\@specialsection: Again suppressed \vspace warning	85	\setengagemetadata: Introduced macro	82
v1.82		v1.86	
\anon: Introduced macro	81	\country: Error if country is empty	90
v1.83		standardpagestyle: Special treatment of ACM Engage materials	101
General: Use babel for multilanguage papers	43	v1.87	
\@mkabstract: I13n	97	General: Added ‘framed’ package for acmcp	41
\@mktitle@i: Added \translatedtitle and \translatedsubtitle	88	No numbering sections for ACMCP	108
\@mktitle@iii: Added \translatedtitle and \translatedsubtitle	89	\@ACM@copyright@check@cc: Added macro	78
\@mktitle@iv: Added \translatedtitle and \translatedsubtitle	90	\@copyrightpermission: CC licenses now are allowed only for non-acm or ACM engage publications	78
		\@mkauthors@i: Special treatment for acmcp	93
		\@mktitle@i: Special treatment for acmcp	88
		\acmArticleType: Introduced macro	74
		\acmCodeLink: Added possibility to have several links	74

Introduced macro	74	\maketitle: CC license are allowed	
\acmDataLink: Introduced macro . .	74	for non-acm publications	82
Now this is the same as the code link	74		
\if@ACM@acmcp: Introduced macro . .	39	\set@ACM@acmcpbox: Added macro . .	85
firstpagestyle: Special treatment		standardpagestyle: Special	
for acmcp	104	treatment of ACMCP	101

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		
\\$	2140, 2144	\@ACM@engagetrue . . . 223
\-	610	\@ACM@institution@separator . . . 873, 876, 951, 2754
\@ 1832, 1844, 1847, 1850, 1855, 1953, 1974, 1987		. . . 2730, 2731, 2736
\@authornotemark	1568, <u>2748</u>	\@ACM@instpresentfalse 867, 870
\@par	476, 533 2561
\@ACM@acmcpbox	2204, 2208, 3024, 3143	\@ACM@instpresenttrue 2464, 2475, 2555
\@ACM@acmcpfalse	169	\@ACM@journal@bibstripfalse 1574, 1577, 2139,
\@ACM@acmcptrue	226 232, 1420
\@ACM@addtoaddress	2452, 2480, 2481, 2483	\@ACM@journal@bibstriptrue 2919, 2939, 2949,
\@ACM@authorsperrrow	1655, 2627, 2628, 2680, 2681 230, 1406
\@ACM@badge@skip	1599, 2296, 2392, 2396, 2402, 2411, 2421, 2427, 2436	\@ACM@journalfalse 3090, 3100, 3110, 3147
\@ACM@badge@width	1596, 2295, 2300, 2391, 2395, 2401, 2413, 2420, 2422, 2425, 2437, 2440 211, 213, 215, 217, 219, 222
\@ACM@badgefalse	1595	\@ACM@journaltrue 2943, 2946, 2953, 2957
\@ACM@badgetrue	1601, 1606 203, 205, 207, 209, 225
\@ACM@balancefalse	3376, 3400, 3402, 3404, 3416, 3420	\@ACM@labelwidth 1001, 1004, 1012, 1017, 1043
\@ACM@checkaffil	2175, 2565, 2596, 2601, 2663, 2668, 2708, 2713	\@ACM@maketitle@typesetfalse 2293, 2295, 2390,
\@ACM@citypresentfalse	2562 1050
\@ACM@citypresenttrue	2466, 2480, 2557	\@ACM@maketitle@typesettrue 1607, 1609, 2294, 2400, 2424
\@ACM@color@frame	2201	\@ACM@manuscriptfalse 198
\@ACM@commabox	2452, 2456, 2457	\@ACM@manuscripttrue 196
\@ACM@copyright@check@cc	1866, 2005	\@ACM@newfontsfalse 2298, 2300, 2394,
\@ACM@countrypresentfalse	2563 831, 834, 837
\@ACM@countrypresenttrue	2471, 2483, 2559	\@ACM@newfontstrue 828
\@ACM@engagefalse	167	\@ACM@printacmreffalse 95, 227
		\@ACM@printfoliostrue 78
		\@ACM@resetaffil 2560, 2595, 2600,
	 2662, 2667, 2707, 2712
		\@ACM@reviewtrue 140
		\@ACM@screentrue 1157, 1197, 1203, 1209, 1215
		\@ACM@sigchiamodeffalse 200
		\@ACM@sigchiamodetrue 220
		\@ACM@timestamptrue 139
		\@ACM@title@width 1598,
	 2389, 2391, 2392,
	 2395, 2396, 2404,
	 2418, 2420, 2421, 2429
		\@DeclareACMFormat 38,
	 39, 40, 41, 42, 43,
	 44, 45, 46, 47, 48, 49
		\@Description@presentfalse 873, 876, 951, 2754
		\@Description@presenttrue 476, 515, 533, 542, 3474
		\@M 476, 515, 533, 542, 3474
		\@abstract 1626, 2762, 2769
		\@acmArticle
		\@acmArticlePage 2915, 2933, 2934,
		\@acmArticleSeq 1576, 3054
		\@acmBadgeL@image 1608, 1610,
		\@acmBadgeL@url 1607,
		\@acmBadgeR@image 1603, 1605,
		\@acmBadgeR@url 1602,
		\@acmBooktitle 1426, 2108, 2129, 2803
		\@acmCodeDataLink 1716, 1717,
		\@acmDOI 1592, 2131,
		\@acmEditors 1434, 1435, 1436, 1439, 2804, 2805
		\@acmISBN 1590, 2143
		\@acmMonth 1580, 1582, 2139
		\@acmNumber 1572, 2800, 2939,
		\@acmPrice 1586, 2140, 2144
		\@acmPubDate 1582, 2800, 2939,

2949, 2960, 3029, 3091, 3101, 3111, 3148	\@article@string 2787, 2800, 2808	\@copyrightyear 2023, 2115, 2117
\@acmSubmissionID 1460, 1461, 1480, 1481, 1588, 2896, 2897, 2907	\@author 1459, 1465, 1472, 2581, 2646, 2693, 2737	\@currbox 980, 981, 982
\@acmVolume 1570, 2800, 2938, 2948, 2959, 3027, 3089, 3099, 3109, 3146	\@authorfont 2513, 2518, 2522, 2525, 2528, 2531, 2534, 2537, 2540, 2543, 2583, 2619	\@currentaffiliation 2620, 2623, 2645, 2652, 2653, 2656, 2659, 2660, 2665, 2692, 2699, 2700, 2702, 2704, 2705, 2710
\@acmYear .. 1578, 1585, 2024, 2108, 2139, 2791	\@authornotemark 1560, 1566, 2747	\@currentaffiliations 2549, 2550, 2551, 2553, 2579, 2591, 2592, 2598
\@acmdefinitionbodyfont ... 3287, 3299, 3313	\@authornotes 1557, 1561, 2071	\@currentauthors 2547, 2548, 2578, 2582, 2583, 2585, 2619, 2622, 2644, 2646, 2647, 2649, 2691, 2693, 2694, 2696, 2747, 2748
\@acmdefinitionheadfont ... 3289, 3301, 3315	\@authorsaddresses 1532, 2080, 2219, 2742, 2821	\@currentlabel . 560, 574
\@acmdefinitionindent ... 3288, 3300, 3314	\@auxout 646	\@dblarg 462
\@acmdefinitionnotefont ... 3290, 3302, 3318	\@begindocumenthook 642	\@dblfloat 963
\@acmengagemetadata ... 2045, 2047, 2824	\@beginmaketitlehook ... 2041, 2044, 2050	\@department .. 1510, 1511
\@acmownedfalse 1775, 1778, 1781, 1787, 1791, 1794, 1797, 1800, 1806, 1809, 1813, 1817	\@botnum 2194	\@dotsep 3254
\@acmownedtrue 1762, 1771, 1803	\@citestyle 308	\@editorsAbbrev 1433, 1438, 2805
\@acmplainbodyfont 3255, 3267, 3281	\@classname 24, 26, 35, 53, 55, 56, 61, 63, 64, 69, 71, 72, 77, 80, 81, 86, 88, 89, 94, 100, 101, 105, 109, 114, 116, 117, 122, 124, 125, 130, 132, 133, 138, 142, 143, 161, 171, 177, 183, 260, 419, 443, 829, 832, 835, 872, 881, 884, 954, 1158, 1198, 1204, 1210, 1216, 1401, 1403, 1450, 1505, 1519, 1613, 1619, 1624, 1631, 1633, 1634, 1637, 1639, 1640, 1643, 1651, 1653, 1654, 1656, 1657, 1705, 1753, 1868, 1872, 1875, 2567, 2570, 2573, 2743, 2757, 2784, 3478, 3481, 3488	\@empty 155, 234, 378, 418, 466, 1417, 1435, 1457, 1460, 1478, 1480, 1485, 1486, 1492, 1616, 1617, 1673, 1674, 1680, 1687, 1716, 1725, 1751, 2042, 2075, 2080, 2131, 2140, 2143, 2144, 2145, 2156, 2159, 2165, 2169, 2213, 2216, 2219, 2253, 2293, 2298, 2390, 2394, 2399, 2407, 2410, 2423, 2431, 2438, 2448, 2470, 2549, 2582, 2590, 2591, 2646, 2652, 2659, 2693, 2699, 2704, 2742, 2750, 2787, 2792, 2804, 2811, 2896, 2907, 2972, 2974, 2996, 2998, 3028, 3029, 3147, 3148, 3258, 3290, 3439, 3456
\@acmplainheadfont 3257, 3269, 3283	\@clubpenalty 521	
\@acmplainindent 3256, 3268, 3282	\@concepts . 1725, 1737, 1751, 2159, 2161, 2179	
\@acmplainnotefont 3258, 3270, 3286	\@copyrightowner 1826, 2115	
\@adddotafter 3162, 3163, 3165, 3177, 3192, 3196, 3249	\@copyrightpermission ... 1882, 2091, 2103	
\@additionalaffiliation 1506, 1507		
\@addpunct . 2734, 2820, 2821, 3249, 3250, 3370		
\@addspaceafter 3250		
\@affiliationfont 2514, 2519, 2523, 2526, 2529, 2532, 2535, 2538, 2541, 2544, 2596, 2619		
\@afterheading . 507, 2197		
\@afterindentfalse 453, 2196		
\@afterindenttrue .. 451		

\@endfloatbox	966	\@journalCode	2959, 3089, 3099, 3109	
\@endpfalse	3372	1051, 1158, 1198,	\@keywords	1615,
\@endwfloatbox	966, 974	1204, 1210, 1216, 1401	1616, 1617, 2165,	
\@finalstrut	565, 578	\@journalCode@nr	2167, 2180, 2216, 2217	
\@float	968	1051, 1119, 1407	\@latex@error	352
\@flushglue	3206	\@journalName	1121,	
\@fnsymbol	2061	1125, 1129, 1133,	\@empty	1628, 2762
\@folio@ht	3034, 3061, 3067, 3068	1137, 1141, 1146,	\@listI	1025, 1029
\@folio@max	3034, 3057, 3058	1149, 1153, 1160,	\@listi	1022, 1029
\@folio@voffset	3034, 3063	1164, 1168, 1173,	\@listii	1030
\@folio@wd	3034,	1177, 1181, 1185,	\@listiii	1033
3068, 3069, 3096, 3106		1190, 1194, 1200,	\@listiv	1035
\@folioblob	3054,	1206, 1212, 1218,	\@listv	1037
3093, 3095, 3103, 3104		1222, 1226, 1231,	\@listvi	1039
\@footnotemark	582, 2059	1235, 1239, 1243,	\@m	464
\@footnotemark@nolink	582, 2059	1247, 1251, 1255,	\@makefnmark	555,
\@footnotetext	556, 583, 2060	1259, 1263, 1267,	580, 2063, 2068, 2072	
\@footnotetext@nolink	583, 2060	1271, 1275, 1279,	\@makefntext	555, 564, 577, 2074
\@for	284	1283, 1287, 1291,	\@marginfigure	946, 947
\@formatdoi	1865,	1295, 1299, 1303,	\@margintable	957, 958
2134, 2141, 2145,		1307, 1311, 1315,	\@minipagefalse	789, 976
2811, 2972, 2974,		1319, 1323, 1327,	\@minus	3182, 3186, 3190,
2996, 2998, 3029, 3148		1331, 1336, 1341,	3194, 3198, 3203,	
\@fps	967	1345, 1349, 1353,	3278, 3280, 3310, 3312	
\@fpsaddefault	967	1357, 1361, 1365,	\@mkabstract	2155, 2761
\@gobble	306, 350	1369, 1373, 1377,	\@mkauthors	2064, 2066, 2485
\@hangfrom	475, 532	1381, 1385, 1389,	\@mkauthors@i	2489, 2491,
\@headfootfont	2909, 2933,	1393, 1397, 1408,	2493, 2495, 2509, 2577	
2934, 2935, 2936,		1409, 1217, 3027, 3146	\@mkauthors@ii	2612
2942, 2945, 2952,		\@journalNameShort	2497, 2499,	
2956, 2964, 2965,		1122,	2501, 2503, 2507, 2624	
2971, 2973, 2977,		1126, 1130, 1134,	\@mkauthors@iv	2505, 2677
2980, 2988, 2989,		1138, 1142, 1147,	\@mkauthorsaddresses	1533, 2721
2995, 2997, 3001, 3004		1150, 1155, 1161,	\@mkbibcitation	2190, 2778
\@idxitem	3471	1165, 1169, 1174,	\@mkteasers	2064, 2749
\@ifnextchar	1510	1178, 1182, 1186,	\@mkttitle	2064, 2309
\@ifnotempty	2029	1191, 1195, 1201,	\@mkttitle@i	2312, 2314,
\@ifnum	322, 324	1207, 1213, 1219,	2316, 2318, 2332, 2385	
\@ifstar	460	1223, 1227, 1232,	\@mkttitle@ii	2416
\@ifundefined	3323, 3326, 3329,	1236, 1240, 1244,	\@mkttitle@iii	2320, 2322,
3332, 3335, 3339, 3342		1248, 1252, 1256,	2324, 2326, 2330, 2416	
\@iiiparbox	792	1260, 1264, 1268,	\@mkttitle@iv	2328, 2444
\@indextitlestyle	3470	1272, 1276, 1280,	\@mktranslatedabstract	441, 2771
\@input	544	1284, 1288, 1292,	\@mktranslatedkeywords	438, 1534
\@insideauthorgroupfalse	1448, 1500	1296, 1300, 1304,	\@mpargs	792
\@insideauthorgrouptue	1455	1308, 1312, 1316,	\@mparswitchfalse	738
		1320, 1324, 1328,	\@mpfootins	569, 570, 784, 785, 787
		1332, 1337, 1342,		
		1346, 1350, 1354,		
		1358, 1362, 1366,		
		1370, 1374, 1378,		
		1382, 1386, 1390,		
		1394, 1398, 1409,		
		2799, 2938, 2948,		

\@mpfootnotetext . . .	568	\@printtopmatter . . .		\@tempa	284 ,
\@ne . . .	310 , 314 , 318 , 320 ,		2065 , 2252		285 , 287 , 289 , 291 ,
	632 , 2838 , 2844 , 2848	\@proofindent			293 , 295 , 297 , 299 ,
\@nil	329		3349 , 3359 , 3369		301 , 303 , 305 , 307 ,
\@nobreakfalse . . .	509 , 549	\@proofnamefont			309 , 311 , 313 , 315 ,
\@noskipsecfalse . . .	513		3348 , 3358 , 3370		317 , 319 , 321 , 323 ,
\@noskipsectrue	510	\@received . .	1671 , 1674 ,		325 , 327 , 329 , 332 ,
\@pages@word			1675 , 1677 , 1680 ,		334 , 336 , 338 , 340 ,
	2781 , 2801 , 2808		1681 , 1683 , 1687 , 1688		342 , 1484 , 1485 ,
\@par	2077 , 2084	\@restonecolfalse . .	3468		1672 , 1673 , 2469 ,
\@parboxrestore	573	\@restonecoltrue . . .	3468		2470 , 2590 , 3439 ,
\@parfont		\@rightskip . . .	3206 , 3207		3455 , 3456 , 3458 , 3462
	3196 , 3200 , 3205 , 3210	\@saveabstract . .	1622 , 1623	\@tempb	
\@permissionCodeOne		\@saveteaser . .	2026 , 2027		285 , 287 , 289 , 291 ,
	1123 , 1127 , 1131 ,	\@savetranslatedabstract			293 , 295 , 297 , 299 ,
	1135 , 1139 , 1143 ,		441 , 442		301 , 303 , 305 , 307 ,
	1151 , 1156 , 1162 ,	\@secntformat . .	469 , 526		309 , 311 , 313 , 315 ,
	1166 , 1170 , 1175 ,	\@secfont	3184 , 3210		317 , 319 , 321 , 323 ,
	1179 , 1183 , 1187 ,	\@secpenalty	458		325 , 327 , 332 , 334 ,
	1192 , 1196 , 1202 ,	\@sect	462 , 463		336 , 338 , 340 , 342 ,
	1208 , 1214 , 1220 ,	\@setaddresses	2746		3457 , 3458 , 3461 , 3462
	1224 , 1228 , 1233 ,	\@setauthorsaddresses		\@tempboxa . .	792 , 2262 , 2264
	1237 , 1241 , 1245 ,		2084 , 2219 , 2821	\@tempc . .	330 , 331 , 333 ,
	1249 , 1253 , 1257 ,	\@setengagemetadata			335 , 337 , 339 , 341 , 343
	1261 , 1265 , 1269 ,		2048 , 2823	\@tempcnta . .	3054 , 3055 ,
	1273 , 1277 , 1281 ,	\@setthanks . . .	2077 , 2820		3057 , 3058 , 3060 , 3062
	1285 , 1289 , 1293 ,	\@shortauthors		\@tempdima	
	1297 , 1301 , 1305 ,		2904 , 2927 , 2935 ,		2258 , 2259 , 2260 ,
	1309 , 1313 , 1317 ,		2943 , 2953 , 2965 , 2989		2266 , 2267 , 2268 ,
	1321 , 1325 , 1329 ,	\@sidebar	942 , 943		3061 , 3062 , 3063 , 3065
	1333 , 1338 , 1343 ,	\@specialsection . . .		\@tempskipa	
	1347 , 1351 , 1355 ,		1536 , 2160 , 2166 , 2222		450 , 452 , 453 , 458 ,
	1359 , 1363 , 1367 ,	\@sssect	461 , 527		471 , 472 , 503 , 504 ,
	1371 , 1375 , 1379 ,	\@startPage	1611 ,		506 , 518 , 519 , 528 , 529
	1383 , 1387 , 1391 ,		2253 , 2254 , 2256 , 2901	\@textbottom	793
	1395 , 1399 , 1410 , 2139	\@startsection . .	447 ,	\@textsuperscript . .	
\@permissionCodeTwo			539 , 3181 , 3185 ,		580 , 2063 , 2068
	1144 , 1171 , 1188 ,		3189 , 3193 , 3197 , 3202	\@texttop	794
	1229 , 1334 , 1339 , 1411	\@starttoc	539	\@thefnmark . .	561 , 575 ,
\@plus	542 , 550 ,	\@subparfont	3235		580 , 2063 , 2068 , 2073
	793 , 3182 , 3186 ,	\@subsecfont . .	3188 , 3210	\@title . . .	1540 , 2178 ,
	3190 , 3194 , 3198 ,	\@subsubsecfont	3192 , 3210		2406 , 2430 , 2447 , 2791
	3203 , 3277 , 3279 ,	\@subtitle . .	1441 , 1549 ,	\@titlefont	2335 , 2398 ,
	3309 , 3311 , 3367 , 3472		2407 , 2408 , 2431 ,		2405 , 2417 , 2429 , 2445
\@printcopyrightfalse			2432 , 2448 , 2449 , 2792	\@titlenotes	
	1774 , 1786	\@subtitlefont			1538 , 1542 , 1545 , 2069
\@printcopyrighttrue			2360 , 2408 , 2432 , 2449	\@tochangmeasure	480 , 493
	1758 , 1770	\@subtitlenotes		\@toclevel	464
\@printendtopmatter			1547 , 1551 , 1554 , 2070	\@tocline . . .	552 , 553 , 554
	2195 , 2813	\@svsec . .	466 , 469 , 475 , 490	\@topnum	2192
\@printpermissionfalse		\@svsechd . . .	488 , 516 , 536	\@translatedabstracts	
	1773	\@teaser	2027 , 2751		439 , 446 , 2156 , 2157
\@printpermissiontrue		\@teaserfigures		\@translatedkeywords	
	1760 , 1769 , 1785		2025 , 2027 , 2750 , 2755		436 , 438 , 2169 , 2170

\@translatedsubtitle	2120, 2135, 2140,	3126, 3215, 3259,
..... 433,	2144, 2214, 2783,	3291, 3350, 3377, 3398
435, 2408, 2432, 2449	2791, 2843, 3029, 3148	\ACM@lang@check
\@translatedtitle 430,	\{ 292	417, 431, 434, 437, 445
432, 2406, 2430, 2447	\} 292	\ACM@languages
\@typeset@author@bx	_ ... 1431, 1733, 1743,	... 153, 378, 380, 418
..... 2616,	2115, 2117, 2140,	\ACM@linecount
2670, 2676, 2715, 2720	2787, 2788, 2806, 2901 2837, 2838,
\@typeset@author@line		2843, 2844, 2847, 2848
2546, 2580, 2604, 2609	A	\ACM@linecount@bx ..
\@typesetengagemetadata	\abstract 1622	... 2834, 2854, 2884
..... 2153, 2822	abstract (env.) 18	\ACM@linecount@bxht
\@undefined 642, 860, 1428, 2041	\abstractname .. 376,	2836, 2842, 2845, 2846
\@undescribed@imagesfalse	389, 2763, 2767, 2775	\ACM@linecountL
..... 869	\acks 3430 2850, 2925,
\@undescribed@imagetrue	acks (env.) 24	2928, 2933, 2936,
.. 880, 883, 953, 2756	\acksname 387, 398, 406,	2942, 2944, 2952,
\@vspace 874, 877, 885,	414, 3429, 3432, 3433	2954, 2964, 2967,
887, 889, 891, 893,	\ACM@adddotafter ...	2971, 2977, 2988,
895, 897, 899, 901, 3163, 3180	2991, 2995, 3001,
903, 943, 948, 958,	\ACM@ArticleType ...	3023, 3082, 3093,
964, 2057, 2223,	... 1690, 3022, 3141	3094, 3104, 3105,
2249, 2779, 2814,	\ACM@ArticleType@nr	3113, 3116, 3121, 3142
2817, 3476, 3478, 3484	1690, 1692, 3020, 3139	\ACM@linecountR . 2857,
\@vspace@acm 2249, 2817, 3484	\ACM@cc@type ... 1824,	2955, 2957, 2965,
\@vspace@orig 874, 877,	2006, 2008, 2009,	2968, 2975, 2982,
885, 887, 889, 891,	2012, 2013, 2014,	2989, 2992, 2999,
893, 895, 897, 899,	2015, 2016, 2017, 2018	3006, 3114, 3117, 3122
901, 903, 943, 948,	\ACM@CC@Url 2007, 2008, 2009, 2010	\ACM@mk@linecount ..
958, 964, 2057,	\ACM@cc@version 1823, 2008, 2019 2839, 2852,
2223, 2779, 2814, 3476	\acm@copyrightinput 1764	2867, 2869, 2871,
\@vspacer 875, 878, 886,	\acm@copyrightmode .	2873, 2875, 2877, 2879
888, 890, 892, 894, 1764,	\ACM@NR@adjustedSectionformat
896, 898, 900, 902,	1772, 1777, 1780, 3160, 3169
904, 944, 949, 959,	1784, 1790, 1793,	\ACM@NRadjust 3151, 3184, 3188,
965, 2058, 2224,	1796, 1799, 1802,	3192, 3196, 3200, 3205
2250, 2780, 2815,	1805, 1808, 1812,	\ACM@origbaselinestretch
2818, 3477, 3481, 3485	1816, 1827, 1883, 2090 3486
\@vspacer@acm 2250, 2818, 3485	\ACM@fontsize 146, 234,	\ACM@ps@headings ...
\@vspacer@orig . 875,	237, 239, 241, 243, 2828, 2832
878, 886, 888, 890,	245, 247, 249, 251,	\ACM@ps@myheadings .
892, 894, 896,	253, 255, 257, 260, 261 2827, 2831
898, 900, 902,	\ACM@format 32, 161	\ACM@ps@plain . 2826, 2830
904, 944, 949,	\ACM@format@nr .. 32,	\ACM@restore@pagestyle
959, 965, 2058,	161, 170, 176, 182, 2826
2224, 2780, 2815, 3477	195, 201, 235, 593,	\ACM@sect@format ...
\@width 773, 780	678, 757, 795, 915, 3170, 3172
\@xp 546, 547	984, 2225, 2272,	\ACM@sect@format@ ..
\@xsect 501, 502, 538	2310, 2336, 2361,	... 3159, 3172, 3174
\\ 663, 672, 1460,	2487, 2515, 2859,	\ACM@sect@format@null
1719, 2009, 2115,	2923, 3041, 3080, 3173, 3174
		\ACM@timestamp
		2887, 3014, 3127, 3132

\acmArticle	14 , 1574	2396, 2420, 2421,	B
\acmArticleSeq . .	14 , 1576	2606, 2626, 2643,	\balance 3427
\acmArticleType . .	20 , 1690	2679, 2690, 2844,	\baselineskip
\acmBadgeL	15 , 1606	2848, 3058, 3060, 3063 2101, 2400,
\acmBadgeR	15 , 1601	\affiliation 10,	2412, 2424, 2439,
\acmBooktitle . . .	9 , 1426	1499 , 2589, 2659, 2704	2845, 3182, 3183,
\acmCodeLink 20 , 1715 , 1722		\and 1439, 1472,	3186, 3187, 3190,
\acmConference . . .	9 , 1412	1474, 1489, 1495,	3194, 3198, 3277,
\acmConference@date		2580, 2585, 2587,	3278, 3279, 3280,
. 1415, 2110,		2598, 2604, 2617,	3309, 3310, 3311, 3312
2979, 2982, 3003, 3006		2651, 2670, 2676,	\baselinestretch . . .
\acmConference@name		2698, 2715, 2720, 2736	. . . 3486, 3487, 3489
1414, 1428, 1429, 1430		\andify 2185,	\begin . 19, 2853, 2883, 3064
\acmConference@shortname		2186, 2547, 2550, 2805	\beginingroup 473,
1413, 1417, 1418,		\anon 24, 2035	516, 530, 539, 631,
1430, 1431, 2110,		anonsuppress (env.) . . . 24	2056, 2485, 3152, 3431
2978, 2981, 3002, 3005		\apptocmd 3478, 3481	\bfseries
\acmConference@venue		\AtBeginDocument . 78,	1041, 2097, 2338,
. 1416, 2110,		95, 227, 635, 643,	2340, 2342, 2346,
2979, 2982, 3003, 3006		1002, 1782, 1788,	2348, 2350, 2352,
\acmDataLink	20 , 1722	1810, 1814, 1818,	2354, 2356, 2358,
\acmdefinition	3308	2833, 2910, 3074, 3175	2534, 2537, 2789,
\acmDOI	15 , 1592	\AtBeginEnvironment	3071, 3210, 3211,
\acmISBN	15 , 1590	. . . 873, 876, 885,	3225, 3226, 3228,
\acmJournal	9 , 1405	887, 889, 891, 893,	3229, 3231, 3232,
\acmMonth	14 , 1580	895, 897, 899, 901, 903	3233, 3234, 3238,
\acmNumber	14 , 1572	\AtBeginMaketitle 32 , 2044	3239, 3242, 3243,
\acmplain	3276	\AtEndDocument	3245, 3246, 3269, 3301
\acmPrice 15 , 1586 , 1782,	 871, 1617,	\bgroup . 446, 943, 947,
1788, 1810, 1814, 1818		1641, 1686, 1751,	958, 964, 1507,
\acmSubmissionID 15 , 1588		2200, 2741, 3424, 3487	1534, 2159, 2165,
\acmVolume	14 , 1570	\AtEndEnvironment 879, 882	2206, 2616, 2653,
\acmYear	14 , 1578	\AtEndPreamble . 608,	2656, 2717, 2726,
\addcontentsline 280,		861, 3320, 3374, 3440	2751, 2761, 2778, 2790
482, 495, 2763, 3433		\author 10,	\bibfont 282
\additionalaffiliation		1449 , 2053, 2054, 2785	\bibliofont 282
. 11 , 1506		\author@bx 2612 , 2618, 2621	\bibliographystyle . 641
\addpenalty 458		\author@bx@sep	\bibsection 278
\addresses 2614, 2621,	\bibstyle 306, 308, 350, 646
1457, 1459, 1464,		2626, 2643, 2679, 2690	\bibstyle@acmauthoryear
1471, 1502, 1522,		\author@bx@wd 356
1560, 1566, 1568,	 2613 , 2616,	\bibstyle@acmnumeric 362
2609, 2676, 2720, 2739		2625, 2626, 2628,	\bigskip . . 1688, 2290,
\addto . . 381, 392, 400, 408		2634, 2636, 2638,	2415, 2443, 2451,
\addtocounter . . 586, 1745		2640, 2643, 2678,	2676, 2720, 2751, 2816
\addtolength 1010, 1011,		2679, 2681, 2687, 2690	\box 981, 2274,
1012, 1016, 1017, 2845		\authornote	2276, 2278, 2280,
\addvspace 458, 550		. 14, 1506, 1558 , 2786	2282, 2284, 2286,
\advance		\authornotemark . 14, 1564	2288, 2290, 2304,
1026, 1031, 1034,		\authors	2306, 2621, 3024, 3143
1036, 1038, 1040,		1462, 1467, 1474,	
1452, 1454, 1711,		2173, 2185, 2187, 2791	C
2259, 2267, 2387,		\authorsaddresses 13 , 1532	\c@footnote 2061
2391, 2392, 2395,			

<code>\c@secnumdepth</code>	<code>\ClassWarningNoLine</code>	<code>\def</code>
465, 479, 483, 492, 496	. 872, 1619, 1643,	24, 38,
<code>\captionenglish</code> . . . 381	1753, 2567, 2570, 2743	147, 153, 237, 239,
<code>\captionsetup</code> . . 907,	<code>\cleaders</code> 2457	241, 243, 245, 247,
909, 911, 913, 922,	<code>\clearpage</code> 2265	249, 251, 253, 255,
924, 927, 929, 932,	<code>\clubpenalty</code> . . . 515, 521	257, 285, 287, 289,
934, 944, 950, 959, 2752	<code>\CodelineIndex</code> 16	291, 293, 295, 297,
<code>\captionfrench</code> 392	<code>\Collect@Body</code> 440, 942,	299, 301, 303, 305,
<code>\captionsgerman</code> 400	946, 957, 1622, 2026	307, 309, 310, 311,
<code>\captionsspanish</code> . . . 408	<code>\color</code> 2037, 2099,	312, 313, 314, 315,
<code>\ccdesc@parse@finish</code> 1756	2843, 2847, 3021, 3140	316, 317, 318, 319,
<code>\ccsdesc</code> 16, 1727	<code>\color@begingroup</code> 563, 576	321, 323, 325, 327,
<code>\ccsdesc@parse</code> 1728, 1729	<code>\color@endbox</code> 979	328, 332, 334, 336,
<code>\ccsdesc@parse@end</code> .	<code>\color@endgroup</code>	338, 340, 342, 430,
. 1728, 1756 566, 579, 790	433, 436, 439, 442,
<code>\ccsdesc@parse@finish</code>	<code>\colorbox</code> . 1710, 3021, 3140	447, 463, 488, 502,
. 1750, 1756	<code>\colorlet</code> 1694,	526, 527, 536, 539,
CCSXML (env.) 16	1696, 1698, 1700, 1702	552, 553, 554, 555,
<code>\centering</code> 543,	<code>\columnsep</code> 3469	557, 568, 580, 586,
576, 662, 671,	<code>\columnseprule</code> 3469	587, 588, 589, 590,
951, 960, 2417,	<code>\columnwidth</code> . . . 572,	610, 641, 772, 779,
2429, 2618, 2675, 3070	773, 965, 2678, 2717	781, 793, 943, 947,
<code>\changes</code> 146	<code>\contentsnamefont</code> . . 543	958, 964, 967, 971,
<code>\cite</code> . . . 624, 625, 636, 640	<code>\copy</code> 2457	974, 992, 993, 994,
<code>\citeA</code> 630	<code>\copyright</code> 2115	995, 1025, 1030,
<code>\citealt</code> 629	<code>\copyrightpermissionfootnoterule</code>	1033, 1035, 1037,
<code>\citeANP</code> 626 772	1039, 1121, 1122,
<code>\citeauthor</code> 626	<code>\copyrightyear</code> . 18, 2023	1123, 1125, 1126,
<code>\citeN</code> 624	<code>\country</code> 11, 1516, 2460, 2735	1127, 1129, 1130,
<code>\citename</code> 637	<code>\csname</code> 350, 478,	1131, 1133, 1134,
<code>\citeNN</code> 627	480, 484, 491, 493,	1135, 1137, 1138,
<code>\citeNP</code> 629	497, 526, 546, 547,	1139, 1141, 1142,
<code>\citet</code> 625	561, 575, 1466,	1143, 1144, 1146,
<code>\citestyle</code> . . . 25, 348, 368	1473, 1526, 1529,	1147, 1149, 1150,
<code>\citeyear</code> 628	1732, 1733, 1735,	1151, 1153, 1155,
<code>\citeyearNP</code> 628	1736, 1737, 1738,	1156, 1160, 1161,
<code>\citeyearpar</code> . . . 627, 640	1739, 1742, 1744,	1162, 1164, 1165,
<code>\city</code> . . 11, 1513, 2460, 2732	2182, 2184, 3153, 3176	1166, 1168, 1169,
<code>\ClassError</code>	<code>\CurrentOption</code>	1170, 1171, 1173,
35, 419, 443, 1403, 148, 149,	1174, 1175, 1177,
1505, 1624, 1634,	150, 151, 152, 158, 159	1178, 1179, 1181,
1640, 1654, 1705,		1182, 1183, 1185,
1875, 2573, 2784, 3488		1186, 1187, 1188,
<code>\ClassInfo</code> . . 161, 260,		1190, 1191, 1192,
1401, 1631, 1633,		1194, 1195, 1196,
1637, 1639, 1651,		1200, 1201, 1202,
1653, 1656, 1868, 1872		1206, 1207, 1208,
<code>\ClassWarning</code> 26, 171,		1212, 1213, 1214,
177, 183, 829, 832,		1218, 1219, 1220,
835, 881, 884, 954,		1222, 1223, 1224,
1450, 1519, 1613,		1226, 1227, 1228,
1657, 2757, 3478, 3481		1229, 1231, 1232,
		1233, 1235, 1236,
		1237, 1239, 1240,
		1241, 1243, 1244,

1245, 1247, 1248,	1611, 1613, 1615,	3231, 3232, 3233,
1249, 1251, 1252,	1623, 1628, 1659,	3234, 3235, 3238,
1253, 1255, 1256,	1671, 1672, 1707,	3239, 3242, 3243,
1257, 1259, 1260,	1709, 1715, 1721,	3245, 3246, 3249,
1261, 1263, 1264,	1729, 1730, 1756,	3250, 3255, 3256,
1265, 1267, 1268,	1820, 1823, 1824,	3257, 3258, 3267,
1269, 1271, 1272,	1826, 1865, 1866,	3268, 3269, 3270,
1273, 1275, 1276,	1882, 2007, 2023,	3287, 3288, 3289,
1277, 1279, 1280,	2025, 2027, 2044,	3290, 3299, 3300,
1281, 1283, 1284,	2045, 2046, 2050,	3301, 3302, 3348,
1285, 1287, 1288,	2063, 2068, 2077,	3349, 3358, 3359,
1289, 1291, 1292,	2084, 2175, 2205,	3437, 3439, 3455,
1293, 1295, 1296,	2222, 2252, 2309,	3456, 3457, 3461, 3468
1297, 1299, 1300,	2335, 2360, 2385,	\define@boolkey
1301, 1303, 1304,	2416, 2444, 2453,	. . . 51, 59, 67, 75,
1305, 1307, 1308,	2460, 2461, 2463,	84, 92, 104, 108,
1309, 1311, 1312,	2464, 2466, 2467,	112, 120, 128, 136,
1313, 1315, 1316,	2469, 2474, 2475,	1504, 1629, 1635, 1649
1317, 1319, 1320,	2479, 2480, 2482,	\define@choicekey ..
1321, 1323, 1324,	2483, 2485, 2513,	. 32, 1051, 1690, 1763
1325, 1327, 1328,	2514, 2518, 2519,	\define@cmdkey 1655
1329, 1331, 1332,	2522, 2523, 2525,	\definecolor
1333, 1334, 1336,	2526, 2528, 2529,	. . . 650, 651, 652,
1337, 1338, 1339,	2531, 2532, 2534,	653, 654, 655, 656, 657
1341, 1342, 1343,	2535, 2537, 2538,	\department
1345, 1346, 1347,	2540, 2541, 2543,	. 11, 1510, 2460, 2734
1349, 1350, 1351,	2544, 2546, 2548,	\Description 23, 870
1353, 1354, 1355,	2553, 2560, 2565,	\description 1042
1357, 1358, 1359,	2577, 2578, 2579,	\descriptionlabel ..
1361, 1362, 1363,	2581, 2588, 2589, 1041, 1044
1365, 1366, 1367,	2590, 2616, 2617,	\detokenize 1450
1369, 1370, 1371,	2624, 2646, 2652,	\dimexpr 962,
1373, 1374, 1375,	2659, 2677, 2693,	981, 3011, 3020, 3139
1377, 1378, 1379,	2699, 2704, 2721,	\divide 2628, 2634, 2636,
1381, 1382, 1383,	2727, 2728, 2729,	2638, 2640, 2681, 2687
1385, 1386, 1387,	2731, 2732, 2733,	\do 284, 610
1389, 1390, 1391,	2735, 2736, 2737,	\do@url@hyp 610
1393, 1394, 1395,	2738, 2746, 2747,	\DocInput 20
1397, 1398, 1399,	2748, 2749, 2751,	\documentclass 8, 424, 426
1405, 1407, 1408,	2761, 2771, 2778,	\dots 2144
1409, 1410, 1411,	2781, 2782, 2783,	\dp 2259, 2267
1426, 1433, 1434,	2784, 2787, 2791,	
1435, 1441, 1484,	2813, 2820, 2821,	
1506, 1507, 1508,	2822, 2823, 2829,	
1509, 1510, 1511,	2839, 2850, 2857,	E
1524, 1532, 1538,	2904, 2909, 2915,	\edef 148, 149,
1539, 1547, 1548,	3040, 3047, 3052,	150, 151, 152, 464, 2008
1557, 1558, 1570,	3054, 3151, 3155,	\editor 9, 1435
1572, 1574, 1576,	3157, 3159, 3169,	\egroup 446,
1578, 1580, 1582,	3173, 3180, 3206,	791, 945, 956, 960,
1586, 1588, 1590,	3210, 3211, 3212,	972, 978, 1517,
1592, 1602, 1603,	3213, 3219, 3220,	1537, 2161, 2167,
1604, 1605, 1607,	3222, 3223, 3225,	2221, 2620, 2654,
1608, 1609, 1610,	3226, 3228, 3229,	2657, 2720, 2740,
		2752, 2770, 2791, 2812

<code>\else</code> . . .	54, 62, 70, 79,	2908, 2918, 2929,	<code>\excludecomment</code> .	1724,
	87, 99, 115, 123,	2937, 2947, 2958,		3443, 3445, 3449, 3450
	131, 141, 197, 231,	2962, 2969, 2972,	<code>\ExecuteOptionsX</code> . . .	
	330, 351, 372, 379,	2974, 2976, 2986,		. . . 50, 58, 66, 74,
	384, 395, 403, 411,	2993, 2996, 2998,		83, 91, 103, 107,
	457, 464, 467, 479,	3000, 3028, 3029,		111, 119, 127, 135, 145
	483, 487, 492, 496,	3055, 3084, 3088,	<code>\expandafter</code>	329, 331,
	508, 520, 535, 618,	3098, 3108, 3115,		643, 792, 1464,
	634, 640, 642, 665,	3120, 3128, 3131,		1465, 1471, 1472,
	667, 784, 848, 853,	3147, 3148, 3156,		1526, 1529, 1732,
	879, 882, 912, 952,	3180, 3439, 3444,		1733, 1735, 1736,
	1396, 1422, 1428,	3451, 3460, 3464, 3487		1742, 1744, 3153, 3176
	1430, 1437, 1453,			
	1460, 1463, 1469,	<code>\email</code>		
	1470, 1480, 1483,	10, 1518,		
	1488, 1491, 1494,	2588, 2652, 2699, 2738		
	1501, 1521, 1544,		F	
	1553, 1559, 1567,	<code>\emph</code>	<code>\familydefault</code>	864
	1617, 1632, 1638,	2127, 2129	<code>\fancyfoot</code>	2930,
	1641, 1652, 1663,	<code>\empty</code>		2938, 2948, 2959,
	1666, 1676, 1679,	2916		2963, 2987, 3014,
	1682, 1687, 1718,	<code>\EnableCrossrefs</code>		3025, 3026, 3083,
	1741, 1746, 1747,	18		3085, 3089, 3099,
	1748, 1751, 1870,	<code>\end</code> . . . 21, 2855, 2885, 3072		3109, 3118, 3123,
	1874, 2032, 2038,	<code>\end@ACM@color@frame</code>		3127, 3132, 3144, 3145
	2064, 2075, 2079,	2200	<code>\fancyhead</code> .	2925, 2926,
	2080, 2081, 2093,	<code>\end@dblfloat</code>		2927, 2928, 2933,
	2094, 2102, 2105,	970		2934, 2935, 2936,
	2106, 2109, 2116,	<code>\end@float</code>		2942, 2944, 2945,
	2121, 2128, 2133,	972		2952, 2954, 2955,
	2136, 2137, 2140,	<code>\endcsname</code>		2956, 2964, 2965,
	2142, 2143, 2144,	349, 350, 478,		2967, 2968, 2971,
	2145, 2156, 2159,	480, 484, 491, 493,		2973, 2977, 2980,
	2164, 2165, 2169,	497, 526, 546, 547,		2988, 2989, 2991,
	2213, 2216, 2219,	561, 575, 1466,		2992, 2995, 2997,
	2255, 2293, 2298,	1473, 1527, 1530,		3001, 3004, 3019,
	2390, 2394, 2399,	1732, 1733, 1735,		3024, 3082, 3093,
	2407, 2410, 2423,	1736, 1737, 1738,		3094, 3095, 3103,
	2431, 2438, 2448,	1739, 1742, 1744,		3104, 3105, 3113,
	2454, 2455, 2470,	2182, 2184, 3153, 3176		3114, 3116, 3117,
	2472, 2473, 2474,	<code>\enddescription</code>		3121, 3122, 3138, 3143
	2476, 2478, 2479,	1048	<code>\fancyheadoffset</code>	3011,
	2482, 2549, 2566,	<code>\endgroup</code> . . . 477, 516,		3018, 3096, 3106, 3137
	2569, 2572, 2584,	534, 549, 2152,	<code>\fancyhf</code>	2912, 3076
	2590, 2597, 2618,	2511, 3155, 3157, 3435		<code>\fancypagestyle</code>
	2629, 2639, 2648,	<code>\endlist</code>		2911, 3075
	2655, 2664, 2682,	1046, 1048	<code>\fi</code> . . . 56, 64, 72, 81, 89,	
	2686, 2695, 2701,	<code>\endMakeFramed</code>		101, 117, 125, 133,
	2709, 2723, 2725,	1711		143, 156, 175, 181,
	2741, 2750, 2755,	<code>\endminipage</code>		194, 199, 228, 233,
	2762, 2766, 2774,	781		258, 259, 271, 275,
	2781, 2787, 2792,	<code>\endtrivlist</code>		286, 288, 290, 292,
	2793, 2802, 2804,	3372		294, 296, 298, 300,
	2811, 2896, 2907,	<code>\enspace</code>		302, 304, 306, 308,
		3250		310, 312, 314, 316,
		environments:		318, 320, 322, 324,
		abstract		326, 328, 333, 335,
		acks		337, 339, 341, 343,
		anonsuppress		
		CCSXML		
		marginfigure		
		marginfigure		
		printonly		
		screenonly		
		sidebar		
		teaserfigure		
		translatedabstract		
			
		<code>\everypar</code>		
		456,		
		511, 522, 2765, 2773		

344, 353, 355, 369,	2426, 2428, 2433,	3026, 3085, 3089,
374, 377, 386, 390,	2441, 2442, 2450,	3099, 3109, 3118,
397, 405, 413, 416,	2458, 2471, 2472,	3123, 3129, 3145, 3475
429, 444, 448, 454,	2474, 2476, 2478,	<code>\footnotetext</code> . . 1543,
459, 464, 470, 481,	2479, 2482, 2484,	1545, 1552, 1555, 1562
485, 494, 498, 500,	2510, 2545, 2552,	<code>\footnotetextauthorsaddresses</code>
523, 524, 537, 548,	2568, 2571, 2575, 2076, 2083
567, 607, 611, 620,	2586, 2602, 2603,	<code>\footnotetextcopyrightpermission</code>
638, 640, 644, 647,	2607, 2618, 2641, 2091, 2095
674, 675, 676, 754,	2642, 2650, 2658,	<code>\footrulewidth</code>
770, 788, 814, 826,	2669, 2688, 2689,	2914, 3017, 3078, 3136
857, 858, 859, 865,	2697, 2703, 2714,	<code>\foreignlanguage</code> 432, 435
872, 881, 884, 938,	2723, 2725, 2745,	<code>\format</code> 32
939, 955, 969, 973,	2758, 2760, 2768,	<code>\FrameCommand</code> 1709
1000, 1400, 1419,	2770, 2776, 2781,	<code>\FrameRestore</code> 1711
1425, 1431, 1432,	2788, 2792, 2806,	<code>\frenchspacing</code> 3491
1440, 1456, 1461,	2809, 2810, 2811,	<code>\fulltextwidth</code>
1468, 1475, 1476,	2849, 2856, 2882, 961, 965, 981
1481, 1482, 1490,	2886, 2898, 2903,	
1496, 1497, 1498,	2907, 2908, 2917,	
1503, 1523, 1546,	2919, 2920, 2925,	
1556, 1563, 1569,	2926, 2931, 2940,	G
1585, 1621, 1625,	2950, 2961, 2963,	<code>\g@addto@macro</code> . 157,
1634, 1640, 1648,	2972, 2974, 2983,	432, 435, 438, 446,
1654, 1668, 1669,	2984, 2985, 2987,	1439, 1471, 1474,
1678, 1684, 1685,	2996, 2998, 3007,	1489, 1495, 1502,
1689, 1703, 1714,	3008, 3009, 3012,	1522, 1540, 1542,
1720, 1740, 1748,	3015, 3028, 3029,	1545, 1549, 1551,
1749, 1755, 1776,	3030, 3053, 3072,	1554, 1560, 1561,
1779, 1783, 1789,	3083, 3086, 3092,	1566, 1568, 1677,
1792, 1795, 1798,	3102, 3112, 3118,	1683, 1719, 1737,
1801, 1804, 1807,	3119, 3123, 3124,	1744, 2027, 2031,
1811, 1815, 1819,	3130, 3133, 3134,	2033, 2044, 2047,
1864, 1880, 1881,	3147, 3148, 3149,	2585, 2598, 2649,
2022, 2034, 2040,	3167, 3178, 3180,	2656, 2665, 2696,
2043, 2054, 2055,	3248, 3253, 3275,	2702, 2710, 2747, 2748
2064, 2066, 2078,	3307, 3345, 3364,	<code>\gdef</code> 156, 1413,
2085, 2086, 2087,	3395, 3396, 3421,	1414, 1415, 1416,
2088, 2092, 2100,	3422, 3428, 3439,	1418, 1426, 1436,
2103, 2104, 2111,	3447, 3453, 3456,	1438, 1459, 1462,
2112, 2113, 2118,	3466, 3467, 3468, 3490	1464, 1467, 1479,
2130, 2135, 2140,	<code>\firstpagestyle</code> 3074	1487, 1493, 1526,
2144, 2145, 2146,	<code>\floatname</code> 941	1529, 1626, 1658,
2147, 2148, 2149,	<code>\flushbottom</code> 800, 802,	1675, 1681, 1717,
2150, 2151, 2153,	804, 806, 808, 811, 813	1733, 1735, 1736,
2157, 2162, 2163,	<code>\footnote</code> 2784	1742, 2254, 2583,
2168, 2171, 2172,	<code>\footnotemark</code> 590, 1540,	2587, 2592, 2622,
2191, 2202, 2215,	1549, 2747, 2748, 2782	2623, 2644, 2645,
2218, 2219, 2248,	<code>\footnoterule</code> 779	2647, 2651, 2653,
2257, 2269, 2297,	<code>\footnotesep</code> . . . 565, 578	2660, 2691, 2692,
2301, 2302, 2307,	<code>\footnotesize</code> 571, 2895,	2694, 2698, 2700,
2333, 2359, 2384,	2909, 2930, 2938,	2705, 2730, 2731, 2736
2388, 2393, 2397,	2948, 2959, 2963,	<code>\geometry</code> . . . 680, 683,
2403, 2409, 2414,	2971, 2977, 2987,	690, 697, 704, 711,
		718, 725, 732, 741, 748

<code>\getrefnumber</code>	<code>\if@ACM@acmthm</code> . 67, 3321	<code>\if@ACM@pbalance</code> 108, 3375
1618, 1642, 1752, 2781	<code>\if@ACM@affiliation@obey</code>	<code>\if@ACM@printacmref</code>
<code>\global</code> 510,	1504,	1635, 2189
513, 549, 569, 870,	2455, 2472, 2474,	<code>\if@ACM@printccs</code>
880, 883, 953, 980,	2476, 2477, 2479, 2482	1629, 2158
1406, 1420, 1452,	<code>\if@ACM@anonymous</code>	<code>\if@ACM@printfolios</code>
1454, 1455, 1500,	120, 1458,	1649, 2917, 2919,
2187, 2188, 2192,	1470, 1477, 1501,	2925, 2926, 2963,
2194, 2208, 2464,	1521, 1541, 1550,	2987, 3083, 3118, 3123
2466, 2471, 2475,	1559, 2030, 2036,	<code>\if@ACM@review</code>
2480, 2483, 2561,	2052, 2081, 2905, 3448	75, 2834, 2851, 2858
2562, 2563, 2580,	<code>\if@ACM@authordraft</code>	<code>\if@ACM@screen</code> 51, 612, 3441
2604, 2608, 2618,	136, 658, 2096	<code>\if@ACM@sigchiamode</code>
2670, 2673, 2715,	<code>\if@ACM@authorversion</code>	165, 556,
2753, 2756, 2844,	84, 2102, 2122	666, 863, 963, 970,
2848, 3376, 3400,	<code>\if@ACM@badge</code>	2064, 2066, 2618, 3010
3402, 3404, 3416, 3420	1594, 2291, 2419, 2435	<code>\if@ACM@timestamp</code>
<code>\grantnum</code> 25, 3438	<code>\if@ACM@balance</code>	128, 2887, 3013, 3125
<code>\grantsponsor</code> . . 25, 3437	104, 3397, 3425	<code>\if@ACM@urlbreakonhyphens</code>
	<code>\if@ACM@citypresent</code>	59, 609
H	2556, 2569	<code>\if@acmowned</code> 1761
<code>\hbox</code> . 580, 2063, 2068, 2456	<code>\if@ACM@countrypresent</code>	<code>\if@Description@present</code>
<code>\headrulewidth</code> 2913, 3077	2558, 2572	866,
<code>\hfill</code> 2446, 2847	<code>\if@ACM@engage</code> . 166,	879, 882, 952, 2755
<code>\href</code> 1528, 1531,	375, 388, 1871,	<code>\if@files</code> 545, 645
2009, 2010, 2294,	2107, 2153, 2970, 2994	<code>\if@insideauthorgroup</code>
2299, 2400, 2412,	<code>\if@ACM@instpresent</code>	1447, 1453
2424, 2439, 3459, 3463	2554, 2566	<code>\if@nobreak</code> 455
<code>\hrule</code> 773, 780, 2446	<code>\if@ACM@journal</code>	<code>\if@noskipsec</code> . . 448, 512
<code>\hsize</code> 572, 1711,	163, 229, 370,	<code>\if@printcopyright</code>
2062, 2207, 2385,	382, 393, 401, 409,	1757, 2114
2387, 2389, 2416,	908, 1422, 1664,	<code>\if@printpermission</code>
2418, 2444, 2486,	2462, 2741, 2764, 2772	1759, 2103
2606, 2616, 2672, 2717	<code>\if@ACM@journal@bibstrip</code>	<code>\if@twocolumn</code> . 3426, 3468
<code>\hskip</code> 475,	164,	<code>\if@undescribed@images</code>
489, 519, 532, 536,	2082, 2106, 2126,	868, 871
2296, 2402, 2411,	2138, 2798, 2922, 3079	<code>\IfBeginWith</code> 1525
2427, 2436, 2457, 3369	<code>\if@ACM@maketitle@typeset</code>	<code>\ifcase</code> . 201, 235, 593,
<code>\hspace</code> . . . 1709, 1893,	442, 1049, 1623	678, 757, 795, 915,
1904, 1913, 1938,	<code>\if@ACM@manuscript</code>	984, 1119, 1582,
1950, 1971, 2621, 2675	162,	1692, 1827, 1883,
<code>\ht</code> 2258, 2266	268, 1661, 2105, 2119	2225, 2272, 2310,
<code>\Huge</code> . 2344, 2346, 2348,	<code>\if@ACM@natbib</code>	2336, 2361, 2487,
2350, 2352, 2354, 2356	112, 276, 367, 623	2515, 2630, 2683,
<code>\hypersetup</code>	<code>\if@ACM@natbib@override</code>	2859, 2923, 3041,
613, 619, 621, 2176	112	3080, 3215, 3259,
<code>\hyphenpenalty</code> 3474	<code>\if@ACM@newfonts</code> 827, 838	3291, 3350, 3377, 3398
	<code>\if@ACM@nonacm</code> 92, 667,	<code>\ifcscname</code> 349
I	1617, 1641, 1751,	<code>\ifdim</code> . . 452, 472, 504,
<code>\if</code> 330	1867, 2089, 2137,	529, 2260, 2268, 2846
<code>\if@ACM@acmcp</code> 168, 273,	2741, 2793, 2929,	<code>\IfEq</code> 2006, 2012,
1712, 2079, 2094,	2937, 2947, 2958,	2013, 2014, 2015,
2164, 2198, 2386,	2966, 2990, 3084,	2016, 2017, 2018, 2019
2605, 3016, 3135, 3251	3088, 3098, 3108, 3128	<code>\IfFileExists</code> 829, 832, 835

<code>\IfInteger</code>	1656	3176, 3180, 3439,	<code>\labelwidth</code>	
<code>\ifluatex</code>	849	3456, 3458, 3462, 3487		1026, 1031, 1034,
<code>\ifNAT@numbers</code>	640	<code>\ifxetex</code>	844	1036, 1038, 1040, 1043
<code>\ifnum</code> 170, 176, 182, 195,		<code>\ignorespaces</code>		<code>\LARGE</code> 2338,
464, 465, 479, 483,		. . . 525, 565, 578,		2340, 2342, 2358,
492, 496, 1618,		870, 1508, 1509,		2369, 2371, 2373,
1642, 1746, 1747,		1511, 1524, 2460,		2375, 2377, 2381,
1748, 1752, 1772,		2461, 2463, 2465,		2522, 2525, 2540, 3071
1777, 1780, 1784,		2466, 2467, 2468,	<code>\Large</code>	2210, 2513, 2531,
1790, 1793, 1796,		2472, 2729, 2769,		3225, 3226, 3228,
1799, 1802, 1805,		2777, 2783, 2791, 3370		3229, 3231, 3245, 3246
1808, 1812, 1816,		<code>\immediate</code>	547, 646	<code>\large</code> 2097, 2518, 2523,
2054, 2090, 2627,		<code>\includecomment</code>		2526, 2541, 2543,
2680, 2722, 2724,		. . . 3442, 3446, 3452		3219, 3220, 3222, 3223
2781, 3055, 3057, 3126		<code>\includegraphics</code> . . .		<code>\lastbox</code> . . 514, 2765, 2773
<code>\ifPDFTeX</code>	815	2009, 2295, 2300,		<code>\leaders</code> 2446
<code>\IfSubStr</code>	1450, 1519	2401, 2413, 2425, 2440		<code>\leavevmode</code> 448, 2446, 2674
<code>\ifvoid</code>	2454	<code>\indent</code>	3349	<code>\leftmargin</code> 1025, 1030,
<code>\ifvoid</code>	784	<code>\input</code>	816	1033, 1035, 1037, 1039
<code>\ifx</code>	155,	<code>\InputIfFileExists</code> . .	25	<code>\leftmargini</code> 1009, 1010,
234, 285, 287, 289,		<code>\institution</code>		1011, 1012, 1025, 1026
291, 293, 295, 297,		. . 11, 1509, 2460, 2731		<code>\leftmarginii</code>
299, 301, 303, 305,		<code>\interfootnotelinepenalty</code>	 1015, 1016,
307, 309, 311, 313,	 559		1017, 1018, 1030, 1031
315, 317, 319, 321,		<code>\interlinepenalty</code> . .		<code>\leftmarginiii</code>
323, 325, 327, 332,	 476, 533, 559		1018, 1019, 1033, 1034
334, 336, 338, 340,		<code>\item</code>	3369, 3471	<code>\leftmarginiv</code>
342, 378, 418, 642,		<code>\itshape</code>		1019, 1020, 1035, 1036
1417, 1428, 1430,		2108, 2110, 3212,		<code>\leftmarginv</code>
1435, 1457, 1460,		3213, 3234, 3235,		1020, 1021, 1037, 1038
1478, 1480, 1485,		3255, 3267, 3289, 3358		<code>\leftmarginvi</code>
1486, 1492, 1565,				. . . 1021, 1039, 1040
1617, 1673, 1674,				<code>\leftskip</code> . 2445, 2718, 3208
1680, 1687, 1716,				<code>\let</code> . 306, 308, 320, 322,
1732, 1741, 1751,				324, 350, 466, 582,
2041, 2075, 2080,				583, 624, 625, 626,
2131, 2140, 2143,				627, 628, 629, 632,
2144, 2145, 2156,				636, 794, 860, 874,
2159, 2165, 2169,				875, 877, 878, 885,
2213, 2216, 2219,				886, 887, 888, 889,
2253, 2293, 2298,				890, 891, 892, 893,
2390, 2394, 2399,				894, 895, 896, 897,
2407, 2410, 2423,				898, 899, 900, 901,
2431, 2438, 2448,				902, 903, 904, 943,
2470, 2549, 2582,				944, 948, 949, 958,
2590, 2591, 2646,				959, 964, 965, 966,
2652, 2659, 2693,				1029, 1044, 1048,
2699, 2704, 2742,				1512, 1513, 1514,
2750, 2762, 2787,				1515, 1516, 1616,
2792, 2804, 2811,				1722, 1725, 2042,
2896, 2907, 2916,				2057, 2058, 2059,
2972, 2974, 2996,				2060, 2072, 2073,
2998, 3028, 3029,				2074, 2077, 2084,
3147, 3148, 3153,				2173, 2187, 2188,

2531, 2532, 2544,	1274, 1278, 1282,	3221, 3224, 3227,
2840, 3270, 3287,	1286, 1290, 1294,	3230, 3236, 3240,
3299, 3302, 3367, 3491	1298, 1302, 1306,	3244, 3247, 3261,
\normalparindent ... <u>771</u>	1310, 1314, 1318,	3262, 3263, 3264,
\normalsize	1322, 1326, 1330,	3265, 3266, 3271,
2360, 2514, 2528,	1335, 1340, 1344,	3272, 3273, 3274,
2529, 2532, 2841, 3491	1348, 1352, 1356,	3293, 3294, 3295,
\num@authorgroups ..	1360, 1364, 1368,	3296, 3297, 3298,
..... <u>1443</u> ,	1372, 1376, 1380,	3303, 3304, 3305,
1454, 2054, 2630,	1384, 1388, 1392,	3306, 3352, 3353,
2634, 2636, 2683, 2724	1582, 1583, 1584,	3354, 3355, 3356,
\num@authorors	1695, 1697, 1699,	3357, 3360, 3361,
<u>1445</u> , 1452, 1466,	1701, 1828, 1830,	3362, 3363, 3379,
1473, 1527, 1530, 2722	1833, 1835, 1836,	3380, 3381, 3383,
\number 464	1838, 1840, 1842,	3385, 3387, 3389,
\numberline 484, 497	1845, 1848, 1851,	3391, 3392, 3394,
\numexpr . 2889, 2891, 2893	1853, 1856, 1859,	3401, 3403, 3405,
\xandlist 2174	1862, 1884, 1895,	3407, 3409, 3411,
	1906, 1914, 1920,	3413, 3415, 3417, 3419
	1926, 1940, 1952,	
O	1959, 1973, 1980,	\orcid <u>10</u> , <u>1524</u>
\onehalfspacing 270	1986, 1993, 1998,	\outer@nobreak 977
\openout 547	2004, 2228, 2230,	
\or 204, 206,	2232, 2234, 2236,	P
208, 210, 212, 214,	2238, 2240, 2242,	\pe 550, 755,
216, 218, 221, 224,	2244, 2246, 2275,	762, 772, 773, 779,
238, 240, 242, 244,	2277, 2279, 2281,	780, 3017, 3136,
246, 248, 250, 252,	2283, 2285, 2287,	3182, 3186, 3190,
254, 256, 595, 596,	2289, 2303, 2305,	3191, 3194, 3195,
597, 598, 599, 600,	2313, 2315, 2317,	3198, 3199, 3203,
602, 603, 605, 606,	2319, 2321, 2323,	3204, 3367, 3469, 3472
682, 689, 696, 703,	2325, 2327, 2329,	\PackageError 56, 64, 72,
710, 717, 724, 731,	2331, 2339, 2341,	81, 89, 101, 105,
740, 747, 759, 760,	2343, 2345, 2347,	109, 117, 125, 133, 143
761, 763, 764, 765,	2349, 2351, 2353,	\PackageInfo 53,
766, 767, 768, 769,	2355, 2357, 2364,	55, 61, 63, 69,
797, 798, 799, 801,	2366, 2368, 2370,	71, 77, 80, 86, 88,
803, 805, 807, 809,	2372, 2374, 2376,	94, 100, 114, 116,
810, 812, 917, 918,	2378, 2380, 2382,	122, 124, 130, 132,
919, 920, 921, 923,	2490, 2492, 2494,	138, 142, 1158,
926, 931, 936, 937,	2496, 2498, 2500,	1198, 1204, 1210, 1216
986, 987, 988, 989,	2502, 2504, 2506,	\PageIndex 15
990, 991, 996, 997,	2508, 2517, 2520,	\pageref 2901
998, 999, 1124,	2521, 2524, 2527,	\pagestyle 3032
1128, 1132, 1136,	2530, 2533, 2536,	\par 432, 435, 449,
1140, 1145, 1148,	2539, 2542, 2632,	505, 541, 782, 975,
1152, 1159, 1163,	2633, 2635, 2637,	1537, 1688, 2077,
1167, 1172, 1176,	2685, 2862, 2864,	2084, 2103, 2108,
1180, 1184, 1189,	2866, 2868, 2870,	2110, 2161, 2167,
1193, 1199, 1205,	2872, 2874, 2876,	2210, 2214, 2217,
1211, 1217, 1221,	2878, 2880, 2932,	2227, 2229, 2231,
1225, 1230, 1234,	2941, 2951, 3043,	2233, 2274, 2276,
1238, 1242, 1246,	3048, 3087, 3097,	2278, 2290, 2306,
1250, 1254, 1258,	3107, 3217, 3218,	2408, 2415, 2432,
1262, 1266, 1270,		2443, 2446, 2449,

<code>\section@raggedright</code>	2344, 2346, 2348,	<code>\textbf</code> .. 1734, 1746, 2823
..... 3206,	2352, 2356, 2358,	<code>\textbullet</code> 588, 1733,
3210, 3211, 3219,	2513, 2518, 2522,	2943, 2946, 2953, 2957
3220, 3222, 3223,	2543, 2909, 3071,	<code>\textcolor</code> 3071
3225, 3226, 3228,	3210, 3211, 3212,	<code>\textheight</code>
3229, 3231, 3232,	3219, 3220, 3222,	2208, 2260, 2262,
3233, 3238, 3239,	3223, 3228, 3229,	2268, 2846, 3020, 3139
3242, 3243, 3245, 3246	3238, 3239, 3242, 3243	<code>\textit</code> 1747,
<code>\Sectionformat</code>	<code>\shortauthors</code> 19, 1478,	2799, 2803, 2804, 2805
3154, 3158, 3160, 3171	1479, 1486, 1487,	<code>\textrightarrow</code>
<code>\SelectFootnoteRule</code>	1489, 1492, 1493, 589, 1729, 1743
..... 775, 777	1495, 2186, 2188, 2908	<code>\textwidth</code> 962, 981, 982,
<code>\selectlanguage</code> 1535, 2771	<code>\shortcite</code> 636, 639	2062, 2385, 2416,
<code>\set@ACM@acmcpbox</code> ..	<code>\shorttitle</code> 2928, 2936,	2444, 2486, 2625, 2672
..... 2199, 2204	2946, 2957, 2964, 2988	<code>\thanks</code> 13, 2028, 2820
<code>\setbox</code> 514, 569,	<code>\showeprint</code> 3454	<code>\thankses</code>
980, 2208, 2262,	<code>\sidebar</code> 940	2031, 2033, 2075, 2820
2398, 2417, 2445,	sidebar (env.) 34	<code>\the</code> .. 1466, 1473, 1527,
2456, 2608, 2618,	<code>\skip</code> 785	1530, 1579, 1581,
2673, 2753, 2765, 2773	<code>\small</code> 558, 945,	2843, 2847, 2899, 3062
<code>\setcctype</code> 16, 1822	952, 960, 1688,	<code>\theACM@time@hours</code> .
<code>\setcitestyle</code>	2227, 2229, 2231, 2893, 2900
... 26, 283, 357, 363	2233, 2519, 2544,	<code>\theACM@time@minutes</code> 2900
<code>\setcopyright</code> .. 16, 1820	2765, 2773, 2789, 3083	<code>\theenumi</code> 992
<code>\setcounter</code> 2067, 2154,	<code>\smallskipamount</code> ... 1024	<code>\theenumii</code> 993
2256, 2891, 2893,	<code>\space</code> 493, 1451,	<code>\theenumiii</code> 994
3214, 3237, 3241, 3252	1520, 1647, 2182,	<code>\theenumiv</code> 995
<code>\setengagemetaddata</code> .	2482, 3028, 3147,	<code>\thefootnote</code> 2061
..... 19, 2046	3439, 3478, 3481, 3489	<code>\theindex</code> 3468
<code>\setkeys</code> . 38, 174, 180,	<code>\specialcomment</code> 3430	<code>\theoremstyle</code>
1405, 1659, 1707,	<code>\standardpagestyle</code> . 2910	3319, 3322, 3338, 3346
1820, 2593, 2594,	<code>\startPage</code> 15, 1611	<code>\thepage</code>
2599, 2600, 2661,	<code>\state</code> . 11, 1514, 2460, 2733	2901, 2917, 2919,
2662, 2666, 2667,	<code>\stepcounter</code> 1543, 1545,	2925, 2926, 2963,
2706, 2707, 2711, 2712	1552, 1555, 1562, 1731	2987, 3083, 3118, 3123
<code>\setlength</code> 755, 756, 762,	<code>\StrDel</code> 2469	<code>\thispagestyle</code> 2263, 2270
771, 1003, 1004,	<code>\streetaddress</code>	<code>\thmname</code> 3286, 3318
1009, 1015, 1018,	. 11, 1512, 2460, 2727	<code>\thmnote</code> 3286, 3318
1019, 1020, 1021,	<code>\string</code>	<code>\thmnumber</code> 3286, 3318
1597, 1600, 2209, 2842	420, 421, 424, 426,	<code>\thr@</code> 324
<code>\setmonofont</code> ... 847, 852	646, 1451, 1520,	<code>\time</code> 2888, 2891, 2893
<code>\settopmatter</code>	1613, 1647, 2785,	<code>\title</code> 10, 2785
... 18, 98, 1647,	2786, 3478, 3481, 3489	<code>\titlenote</code> .. 14, 1539, 2786
1659, 1660, 1662,	<code>\strut</code> 2422, 2437, 3022, 3141	<code>\topsep</code> .. 1028, 1032, 3367
1665, 1667, 1670, 2797	<code>\strutbox</code> 565, 578	<code>\translatedabstract</code> 440
<code>\setTrue</code> 540	<code>\subsection</code> 3185	translatedabstract
<code>\SetWatermarkColor</code> .	<code>\subsubsection</code> 3189	(env.) 21
..... 661, 670	<code>\subtitle</code> 10, 1441	<code>\translatedkeywords</code>
<code>\SetWatermarkFontSize</code>	<code>\subtitlenote</code> .. 14, 1548 21, 437
..... 660, 669		<code>\translatedsubtitle</code>
<code>\SetWatermarkText</code> 662, 671	 21, 434
<code>\sfdefault</code> 864	T	<code>\translatedtitle</code> . 21, 431
<code>\sffamily</code>	<code>\teaserfigure</code> 2026	<code>\trivlist</code> 3368
2338, 2340, 2342,	teaserfigure (env.) ... 18	<code>\tw@</code> 322
	<code>\terms</code> 15, 1613	

<code>\two@digits</code> . . . 2899, 2900	<code>\usebox</code> 2854, 2884	Y
<code>\twocolumn</code> . 2280, 2282, 2284, 2286, 2288, 2304	<code>\usepackage</code> 9, 10, 11, 12, 13, 14	<code>\year</code> 1579, 2899
U	V	Z
<code>\unskip</code> 517, 587, 783, 1511, 1517, 1524, 2457, 2460, 2461, 2463, 2465, 2466, 2467, 2468, 2482, 2551, 2727, 2728, 2729, 2731, 2732, 2733, 2734, 2735, 2736, 2738, 2783, 2791, 2808, 2821	<code>\value</code> 1748 <code>\vbox</code> 569, 980, 2398, 2417, 2445, 2608, 2673, 2753 <code>\vfill</code> 2212, 2214, 2217, 2219 <code>\vskip</code> 506, 541, 785, 793, 975 <code>\vspace</code> 3476 <code>\vsplit</code> 2262 <code>\vtop</code> 2208, 2618	<code>\ze</code> 312, 316, 452, 472, 504, 514, 529, 542, 565, 578, 756, 793, 910, 914, 925, 1009, 1015, 1027, 2077, 2084, 2097, 2101, 2192, 2194, 2209, 2400, 2412, 2424, 2439, 2718, 2765, 2773, 2913, 2914, 3019, 3024, 3035, 3037, 3039, 3065, 3067, 3077, 3078, 3138, 3143, 3181, 3185, 3189, 3197, 3202, 3209, 3268, 3300, 3469, 3472
<code>\unvbox</code> . 570, 787, 792, 2264, 2608, 2674, 2753	W <code>\wd</code> 982, 2457 <code>\write</code> 646	<code>\z@skip</code> 541, 975, 1032, 3208
<code>\upshape</code> 1041	X <code>\xdef</code> 333, 335, 337, 339, 341, 343	
<code>\url</code> . 1717, 1719, 1865, 3439		
<code>\UrlBreakPenalty</code> 2654, 2657		
<code>\urlstyle</code> . . . 592, 601, 604		