

```

#include <stdio.h>
#include <string.h>
int overlapping_counting(char *query, char *data) {
    int ql = strlen(query);
    int dl = strlen(data);
    int count = 0;
    int i = 0; /* position in data */
Loop:
    if( ql > (dl - i)) return count;
    if(strncmp(query, &data[i], ql) == 0) {
        /* found query string at data[i] */
        count ++;
        i = i + 1; /* move to data[i+1] */
    } else {
        i = i + 1;
    }
    goto Loop;
}

int non_overlapping_counting(char *query, char *data) {
    int ql = strlen(query);
    int dl = strlen(data);
    int count = 0;
    int i = 0; /* position in data */
Loop:
    if( ql > (dl - i)) return count;
    if(strncmp(query, &data[i], ql) == 0) {
        /* found query string at data[i] */
        count ++;
        i = i + ql; /* move to data[i+ql] */
    } else {
        i = i + 1;
    }
    goto Loop;
}

int main() {
    char * q = "abca";
    char * d = "abcabcabca";
    printf("overlapping_couting(%s, %s) = %d\n",
           q, d, overlapping_counting(q, d) );
    printf("non_overlapping_couting(%s, %s) = %d\n",
           q, d, non_overlapping_counting(q, d) );
    return 0;
}

```