

Program A, Pre-transformation

```
header packet {
  int p1;
  int p2;
}
control ingress(...) {
  if (p.p1 == v1) { p.p2 = p.p2 + 1; }
  if (p.p1 == v2) { p.p2 = p.p2 + 2; }
  if (p.p1 == v3) { p.p2 = p.p2 + 3; }
}
```

Program A, Post-transformation

```
header packet { ... }
control ingress(...) {
  table T {
    key = { p.p1 : exact; };
    actions = { a1, a2, a3 };

    const entries = {
      v1 : action_1;
      v2 : action_2;
      v3 : action_3;
    }

    apply { T.apply(); }
  }
}
```

action_1:

p.p2 = p2 + 1;

action_2:

p.p2 = p2 + 2;

action_3:

p.p2 = p2 + 3;

```
apply { ...
  if (flipflop == 1) {
    if (lo_exceeded_flag == 1) {
      get_flip_drop_flag_lo();
    } else { drop_flag_lo = 0; }
    if (...) { ... } else { ... }
    if (...) { ... } else { ... }
  } else { // flipflop == 0
    if (lo_exceeded_flag == 1) {
      get_flip_drop_flag_lo();
    } else { drop_flag_lo = 0; }
    if (...) { ... } else { ... }
    if (...) { ... } else { ... }
  }
}
```

```
action get_drop_flag_lo() { ... }
action set_drop_flag_lo() { drop_flag_lo = 0; }
table T1 {
  key = { flipflop : exact;
          lo_exceeded_flag : exact; }
  actions = { get_flip_drop_flag_lo;
              set_drop_flag_lo; }
  const entries = { (1,1) : get_flip_drop_flag_lo();
                    (1,0) : set_drop_flag_lo(); }
}
table T2{...}
table T3{...}
apply {
  T1.apply(); T2.apply(); T3.apply();
}
```

Program B, Pre-transformation

Program B, Post-transformation