

<pre> header packet { int p1; int p2;} control ingress(...) { if (p.p1 == v1) { p.p2 = p.p2 + 1; } if (p.p1 == v2) { p.p2 = p.p2 + 2; } if (p.p1 == v3) { p.p2 = p.p2 + 3; }}</pre>	<p>Table T</p> <pre> key = { p.p1: exact; } actions = { a1, a2, a3 }; const entries = { v1: a1; v2: a2; v3: a3; }</pre>	<p>action a1</p> <pre>p.p2 = p2 + 1;</pre> <p>action a2</p> <pre>p.p2 = p2 + 2;</pre> <p>action a3</p> <pre>p.p2 = p2 + 3;</pre>
---	---	--

Program ME-2, Post-transformation

<pre> if (flipflop == 1) { if (lo_flag == 1) {get_df_lo();} else { drop_flag_lo = 0;} if (...) {...} else {...} if (...) {...} else {...} } else { // flipflop == 0 if (lo_flag == 1) {get_df_lo();} else {drop_flag_lo = 0;} if (...) {...} else {...} if (...) {...} else {...}}}</pre>	<p>action get_df_lo</p> <pre>.....</pre>	<p>action set_df_lo</p> <pre>drop_flag_lo = 0</pre>
	<p>Table T1</p> <pre> key = { flipflop : exact; lo_flag : exact; } actions = { get_df_lo; set_df_lo; } const entries = { (1,1) : get_df_lo(); (1,0) : set_df_lo();}</pre> <p>Table T2</p> <pre>.....</pre> <p>Table T3</p> <pre>.....</pre>	

Program ME-3, Post-transformation