

Program A, Pre-transformation

```
header packet {
    int p1;
    int p2;
}
control ingress(...) {
    if (p.p1 == v1) { p.p2 = p.p2 + 1; }
    if (p.p1 == v2) { p.p2 = p.p2 + 2; }
    if (p.p1 == v3) { p.p2 = p.p2 + 3; }
}
```

```
apply { ...
    if (flipflop == 1) {
        if (lo_exceeded_flag == 1) {
            get_flip_drop_flag_lo();
        } else { drop_flag_lo = 0; }
        if (...) {...} else {...}
        if (...) {...} else {...}
    } else { // flipflop == 0
        if (lo_exceeded_flag == 1) {
            get_flop_drop_flag_lo();
        } else { drop_flag_lo = 0; }
        if (...) {...} else {...}
        if (...) {...} else {...}
    }
}
```

Program B, Pre-transformation

Program A, Post-transformation

```
action a1      action a2
p.p2 = p2 + 1;  p.p2 = p2 + 2;
```

```
action a3
p.p2 = p2 + 3;
```

```
table T
key = { p.p1: exact; }
actions = { a1, a2, a3 };
const entries = {v1: a1; v2: a2;
                  v3: a3;}
```

```
action get_drop_flag_lo
```

```
action set_drop_flag_lo
drop_flag_lo = 0
```

```
Table T2
```

```
Table T3
```

```
Table T1
```

```
key = { flipflop : exact;
        lo_exceeded_flag : exact; }
actions = { get_flip_drop_flag_lo;
            set_drop_flag_lo; }
const entries = {
    (1,1) : get_flip_drop_flag_lo();
    (1,0) : set_drop_flag_lo();}
```

Program B, Post-transformation