

Input: Computation graph $G = (V, E)$ where
 $V = \text{Stateful} \cup \text{Stateless}$, where **Stateful** is the set
of stateful nodes and **Stateless** is the set of
stateless nodes.

Output: Synthesized code for each primary output
(PO) and each input to a stateful ALU

```

1  /* Step 1: Normalize the computation graph. */
2  Normalize( $G$ );
3  assert every stateful node in  $G$  has out-degree 1
4  /* Step 2: Predecessor packing and folding optimizations. */
5  graphModified  $\leftarrow$  FALSE;
6  // Iterate until fixpoint
7  while graphModified do
8    // Folding; returns TRUE iff  $G$  changed
9    for ( $u, v \in E$ ) do
10     | if  $v \in \text{stateful} \wedge u \in \text{stateless}$  then
11     | | graphModified  $\leftarrow$  tryFold( $G, u, v$ )
12     | end
13   end
14   // Predecessor packing; returns TRUE iff  $G$  changed
15   for ( $u, v \in E$ ) do
16     | if one of  $u, v$  is stateful then
17     | | graphModified  $\leftarrow$  tryMerge( $G, u, v$ )
18     | end
19   end

```

```

20 end
21 /* Step 3: Synthesis of stateful updates */
22 for  $v \in \text{stateful}$  do
23   |  $s \leftarrow$  querySketchStateful(stateVar( $v$ ),  $v$ )
24   | assert  $s$ ;
25 end
26 /* Step 4: Min-depth solutions for stateless code */
27  $O \leftarrow POs \cup \{\text{inputs}(v) | v \in \text{Stateful}\}$ ;
28 for  $o \in O$  do
29   | // Find the Backwards Cone of Influence (BCI) of  $o$ 
30   | spec  $\leftarrow$  computeBCI( $o$ ); // spec of  $o$ 
31   |  $i \leftarrow 1$ ; // depth of solution tree
32   | while  $i \leq \text{numPipelinedStages}$  do
33     | |  $s :=$  querySketchStateless( $o, \text{spec}, i$ )
34     | | if success then
35     | | | break
36     | | end
37     | |  $i \leftarrow i + 1$ ; // increment depth
38   | end
39 end

```