

Input: Computation graph $G = (V, E)$ where
 $V = \text{Stateful} \cup \text{Stateless}$, where **Stateful** is the set
of stateful nodes and **Stateless** is the set of
stateless nodes.

Output: Synthesized code for each primary output
(PO) and each input to a stateful ALU

```

1  /* Step 1: Normalize the computation graph. */
2  Normalize( $G$ );
3  assert every stateful node in  $G$  has out-degree 1
4  /* Step 2: Predecessor packing and folding optimizations. */
5  graphModified  $\leftarrow$  FALSE;
6  // Iterate until fixpoint
7  while graphModified do
8      // Folding; tryFold returns TRUE iff  $G$  changed
9      for ( $u, v \in E$ ) do
10         if  $v \in \text{Stateful} \wedge u \in \text{Stateless}$  then
11             | graphModified  $\leftarrow$  tryFold( $G, u, v$ )
12         end
13     end
14     // Predecessor packing; tryMerge returns TRUE iff  $G$  changed
15     for ( $u, v \in E$ ) do
16         if  $u \in \text{Stateful} \vee v \in \text{Stateful}$  then
17             | graphModified  $\leftarrow$  tryMerge( $G, u, v$ );
18         end
19     end

```

```

20 end
21 /* Step 3: Synthesis of stateful updates */
22 for  $v \in \text{stateful}$  do
23     |  $s \leftarrow$  querySketchStateful(stateVar( $v$ ),  $v$ )
24     | assert  $s$ ;
25 end
26 /* Step 4: Min-depth solutions for stateless code */
27  $O \leftarrow POs \cup \{\text{inputs}(v) | v \in \text{Stateful}\}$ ;
28 for  $o \in O$  do
29     // Find the Backwards Cone of Influence (BCI) of  $o$ 
30     spec  $\leftarrow$  computeBCI( $o$ ); // spec of  $o$ 
31      $i \leftarrow 1$ ; // depth of solution tree
32     while  $i \leq \text{numPipelinedStages}$  do
33         |  $s :=$  querySketchStateless( $o$ , spec,  $i$ )
34         | if success then
35             | break
36         | end
37         |  $i \leftarrow i + 1$ ; // increment depth
38     end
39 end

```