

## Per Inference Score

For a frame  $f$  of a model  $m$  in a usage scenario  $S$ ,

Per Inference Score ( $m, f$ )

=

Real-time Score ( $m, f$ )

X

Energy Score ( $m, f$ )

X

Accuracy Score ( $m, f$ )

Range: [0,1]

Range: [0,1]

Range: [0,1]

Range: [0,1]

**Meaning:** A comprehensive score for each inference run that considers real-time, energy, and accuracy requirements

## Per Model Score

For frames  $f(0), f(1), \dots f(N-1)$  for a model  $m$  in a usage scenario  $S$ , where  $N = \text{NumFrames}(m, S)$

Range: [0,1]

Per Model Score ( $m, S$ )

=

Average(

Per Inference Score( $m, f(i)$ )

)

across frames  $f(0), f(1), \dots f(K-1)$

Range: [0,1]

**Note:** If all the frames are dropped, the score is defined to be zero.

## Per Usage Scenario Score

For models  $m(0), m(1), \dots m(K-1)$  in a usage scenario  $S$ , where  $K = \text{NumModels}(S)$ ,

Range: [0,1]

Per Usage Scenario Score ( $S$ )

=

Average(

Per Model Score( $m(i), S$ )

X

QoE Score( $m(i), S$ )

)

across models  $m(0), m(1), \dots m(K-1)$

Range: [0,1]

Range: [0,1]

**Note:** The frame drop rates only can be defined in the usage scenario granularity; QoE score is based on frame drop rates, so the QoE Score is used here

## Benchmark Score

For usage scenarios  $S(0), S(1), \dots S(|B|-1)$  where  $|B| = \text{number of usage scenarios in XR Bench}$ ,  $B$

Range: [0,1]

Benchmark Score

=

Average(

Per Usage Scenario Score ( $S$ )

)

across usage scenarios  $S(0), S(1), \dots S(|B|-1)$

Range: [0,1]