

A.

Initial DSL

```
connect | transform | matrix |
circle | line | 0 | 1 | 2 ..
```


Corpus of programs in the initial DSL



```
(connect (connect
(transform (repeat
(transform line (matrix
1 0 -0.5 (/ 0.5 (tan (/
pi 8)))))) ...
```



```
(connect (connect
(transform (transform
circle (matrix 2 0 0
0))(transform ...)
```




```
(connect (connect
(transform (repeat
(transform line (matrix
1 0 -0.5 (/ 0.5 (tan (/
pi 6)))))) ...
```



...

B.

STITCH uses **corpus-driven top-down synthesis** to find new abstractions that can compress the corpus of program trees



learned_fn_0 =
 $(\lambda x. \lambda y. (\text{transform} (\text{repeat} (\text{transform line} (\text{matrix } 1 \ 0 \ -0.5 \ (/ \ 0.5 \ (\tan \ (/ \ \pi \ x)))))) \times (\text{matrix } 1 \ (/ \ (* \ 2 \ \pi) \ x) \ 0 \ 0)) (\text{matrix } y \ 0 \ 0 \ 0)))$




Draws polygons parameterized by number of sides and side length

C.


Learned library with new abstractions

```
connect | transform | matrix |
circle | line | 0 | 1 | 2
learned_fn_0 | learned_fn_1 |
learned_fn_2...
```


Compressed corpus of programs rewritten with the library



```
(connect (connect
(learned_fn_0 8 1) ..)
```



```
(connect (connect
(transform (transform
circle (matrix 2 0 0
0))(transform ...)
```



```
(connect (connect
(learned_fn_0 6 1) ..)
```