

Algorithms of testing SI

No Author Given

No Institute Given

```

1: procedure CONSTRUCTENCODING(history)
2:   g, readfrom, wwpairs ← CreateKnownGraph(history)
3:   con ← GenConstraints(g, readfrom, wwpairs)
4:   con, g ← Prune(con, g) // §3.3, executed one or more times
5:   return con, g
6:
7: procedure CREATEKNOWNGRAPH(history)
8:   g ← empty Graph // the known graph
9:   wwpairs ← Map { (Key, Tx) → Tx } // consecutive writes
10:  readfrom ← Map { (Key, Tx) → Set(Tx) } // maps a write to its readers
11:  for transaction tx in history:
12:    g.Nodes += tx
13:    for read operation rop in tx:
14:      g.Edges += (rop.read_from_tx, tx) // read-dependencies
15:      readfrom[rop.key, rop.read_from_tx] += tx
16:
17:  // detect RMW (read-modify-write) transactions
18:  for all Keys key that are both read and written by tx:
19:    rop ← the operation in tx that reads key
20:    if wwpairs[key, rop.read_from_tx] ≠ null:
21:      REJECT // multiple consecutive writes, not serializable
22:      wwpairs[key, rop.read_from_tx] ← tx
23:
24:  add session order edges to g // §4.2
25:  return g, readfrom, wwpairs
26:
27: procedure GENCONSTRAINTS(g, readfrom, wwpairs)
28:  // each key maps to set of chains; each chain is an ordered list
29:  chains ← empty Map { Key → Set(List) }
30:  for transaction tx in g:
31:    for write wrop in tx:
32:      chains[wrop.key] += [ tx ] // one-element list
33:
34:  CombineWrites(chains, wwpairs) // §3.1
35:  InferRWEedges(chains, readfrom, g) // infer anti-dependency
36:
37:  con ← empty Set
38:  for (key, chainset) in chains:
39:    for every pair {chaini, chainj} in chainset:
40:      con += Coalesce(chaini, chainj, key, readfrom) // §3.2
41:
42:  return con
43:
44: procedure COMBINERWRITES(chains, wwpairs)
45:  for (key, tx1, tx2) in wwpairs:
46:    // By construction of wwpairs, tx1 is the write immediately
47:    // preceding tx2 on key. Thus, we can sequence all writes
48:    // prior to tx1 before all writes after tx2, as follows:
49:    chain1 ← the list in chains[key] whose last elem is tx1
50:    chain2 ← the list in chains[key] whose first elem is tx2
51:    chains[key] \= {chain1, chain2}
52:    chains[key] += concat(chain1, chain2)
53:
54: procedure INFERRWEEDGES(chains, readfrom, g)
55:  for (key, chainset) in chains:
56:    for chain in chainset:
57:      for i in [0, length(chain) - 2]:
58:        for rtx in readfrom[key, chain[i]]:
59:          if (rtx ≠ chain[i+1]): g.Edges += (rtx, chain[i+1])
60:
61: procedure COALESCE(chain1, chain2, key, readfrom)
62:  edge_set1 ← GenChainToChainEdges(chain1, chain2, key, readfrom)
63:  edge_set2 ← GenChainToChainEdges(chain2, chain1, key, readfrom)
64:  return (edge_set1, edge_set2)
65:
66: procedure GENCHAINTOCHAINEDGES(chaini, chainj, key, readfrom)
67:  if readfrom[key, chaini.tail] = 0:
68:    edge_set ← {(chaini.tail, chainj.head)}
69:    return edge_set
70:
71:  edge_set ← empty Set
72:  for rtx in readfrom[key, chaini.tail]:
73:    edge_set += (rtx, chainj.head)
74:
75:  return edge_set
76:
77: procedure PRUNE(con, g)
78:  // tr is the transitive closure (reachability of every two nodes) of g
79:  tr ← TransitiveClosure(g) // standard algorithm; see [70, Ch.25]
80:  for c = (edge_set1, edge_set2) in con:
81:    if ∃(txi, txj) ∈ edge_set1 s.t. txj ~ txi in tr:
82:      g.Edges ← g.Edges ∪ edge_set2
83:      con -= c
84:    else if ∃(txi, txj) ∈ edge_set2 s.t. txj ~ txi in tr:
85:      g.Edges ← g.Edges ∪ edge_set1
86:      con -= c
87:
88:  return con, g

```

Fig. 1: Alg of Cobra

Algorithm 1 Algs of OOPSLA(testing SER)

```

1: CheckSER (history  $h$ , prefix  $T'$ )
2:   if  $h.T == T'$  then return true
3:   for  $\forall t \in h.T, s.t. \forall t' \in T', \langle t, t' \rangle \notin wr \cup so$  do
4:     if  $T' \not\vdash T' \uplus \{t\}$  then continue
5:     if  $T' \uplus \{t\} \notin seen \wedge \text{CheckSER}(h, T' \uplus \{t\})$  then return true
6:      $seen \leftarrow seen \cup \{T' \uplus \{t\}\}$ 
7:   end
8:    $\triangleright T \uplus \{t\} : 1. \{t'|t' \in T/T' \wedge t' \xrightarrow{wr/so} t\} = \phi$ 
9:    $\triangleright 2.t \text{ writes } y \Rightarrow \{t'|t' \in T/T' \wedge (\exists t'' \in T', t'' \xrightarrow{wr_y} t')\} = \phi$ 
10:

```

Algorithm 2 Algs of OOPSLA(testing SI)

```

1: CheckSI (history  $h$ , prefix  $T'$ )
2:   if  $h.T == T'$  then return true
3:   for  $\forall t \in h.T, s.t. \forall t' \in T', \langle t, t' \rangle \notin wr \cup so$  do
4:     if  $T' \not\vdash T' \uplus \{t\}$  then continue
5:     if  $T' \uplus \{t\} \notin seen \wedge \text{CheckSER}(h, T' \uplus \{t\})$  then return true
6:      $seen \leftarrow seen \cup \{T' \uplus \{t\}\}$ 
7:   end
8:    $\triangleright T \uplus \{t\} : 1. \{t'|t' \in T/T' \wedge t' \xrightarrow{wr/so} t\} = \phi$ 
9:    $\triangleright 2.t \text{ writes } y \Rightarrow \{t'|t' \in T/T' \wedge (\exists z, s.t. t, t' \text{ reads } z$ 
    $, ver(z)_t > ver(z)_{t'}) \wedge (\exists t'' \in T', t'' \xrightarrow{wr_y} t')\} = \phi$ 
10:

```

Algorithm 3 Our algorithm (testing SI)

```

1: CheckSI (history  $h$ )
2:    $graph, readfrom \leftarrow \text{CONSTRUCTENCODING}(h)$ 
3:    $conf \leftarrow \text{GENCONSTRAINTS}(graph, readfrom, wupair)$ 
4: end

5: ConstructEncoding (history  $h$ )
6:    $g \leftarrow$  empty Graph
7:    $readfrom \leftarrow \text{Map} \{ \langle key, Tx \rangle \rightarrow \text{Set} \langle Tx \rangle \}$ 
8:   for  $tx$  in  $h$  do
9:      $g.Node \ += tx$ 
10:    for read operation  $rop$  in  $tx$  do
11:       $g.Node \ += (rop.read\_from\_tx, tx)$ 
12:       $readfrom[\langle rop.key, rop.read\_from\_tx \rangle] \ += tx$ 
13:   add session order edges to  $g$ 
14:   return  $g, readfrom$ 
15: end

16: GenConstraints  $graph, readfrom$ 
17:    $chains \leftarrow$  empty Map  $\{key \rightarrow \text{Set} \langle List \rangle\}$ 
18:   for  $tx$  in  $graph$  do
19:     for write  $wrop$  in  $tx$  do
20:        $chains[wrop.key] \ += [tx]$ 
21:        $rwpairs \leftarrow \text{INFERRWEDGES}(chains, readfrom, graph)$ 
22:        $graph \leftarrow$  empty Graph
23:       for each edge  $e_{rw}$  in  $rwpairs$  do
24:         for edge  $e \notin rwpairs$  wedge  $e \in graph$  do
25:           if  $\exists$  a path  $p$  from  $e$  to  $e_{rw}$  wedge  $(\forall e' \in p, e' \notin rwpairs)$  then  $graph$ 
26:              $\ += [\langle e.head, e_{rw}.tail \rangle]$ 
27:        $conf \leftarrow$  empty Set
28:       for  $\langle key, chainset \rangle$  in  $chains$  do
29:         for every pair  $\langle chain_i, chain_j \rangle$  in  $chainset$  do
30:            $conf \ += \text{COALESCE}(chain_i, chain_j, key, readfrom)$ 
31:       return  $conf$ 
32: end

33: InferRWEedges  $chains, readfrom, g$ 
34:    $rwpairs \leftarrow$  empty Set
35:   for  $\langle key, chainset \rangle$  in  $chains$  do
36:     for  $chain$  in  $chainset$  do
37:       for  $i$  in  $[0, \text{length}(chain)-2]$  do
38:         for  $rtx$  in  $readfrom[\langle key, chain[i] \rangle]$  do
39:           if  $rtx \neq chain[i+1]$  then
40:              $g.edges \ += (rtx, chain[i+1])$ 
41:              $rwpairs \ += (rtx, chain[i+1])$ 
42:   end

43: Coalesce  $chain_1, chain_2, key, readfrom$ 
44:    $edge\_set_1 \leftarrow \text{GENCHAINTOCHAINEDGES}(chain_1, chain_2, key, readfrom)$ 
45:    $edge\_set_2 \leftarrow \text{GENCHAINTOCHAINEDGES}(chain_2, chain_1, key, readfrom)$ 
46: end

47: GenChainToChainEdges  $chain_i, chain_j, key, readfrom$ 
48:   if  $readfrom[\langle key, chain_i.tail \rangle] = \emptyset$  then
49:      $edge\_set \leftarrow \{(chain_i.tail, chain_j.head)\}$ 
50:     return  $edge\_set$ 
51:    $edge\_set \leftarrow$  empty Set
52:   for  $rtx$  in  $readfrom[\langle key, chain_i.tail \rangle]$  do
53:      $edge\_set \ += (rtx, chain_j.head)$ 
54:   return  $edge\_set$ 

```