

1 **User:**
 2 Can you implement a tail-recursive function in
 3 OCaml, which reverses a list of integers?
 4
 5 **ChatGPT:**
 6 let reverse_list lst =
 7 let rec reverse_helper acc = function
 8 | [] -> acc
 9 | hd::tl -> reverse_helper (hd::acc) tl
 10 in reverse_helper [] lst

11
 12 **User:**
 13 Can you show the call stack for input [1;2;3]?
 14

15 **ChatGPT:**
 16 reverse_list [1; 2; 3]
 17 | reverse_helper [] [1; 2; 3]
 18 | | reverse helper [1] [2; 3]
 19 | | | reverse_helper [2; 1] [3]
 20 | | | | reverse_ helper [3; 2; 1] []
 21 | | | | => [3; 2; 1]
 22 | | | => [3; 2; 1]
 23 | | => [3; 2; 1]
 24 | => [3; 2; 1]
 25 => [3; 2; 1]

26
 27 As you can see, the initial call to
 28 "reverse_list" with input [1; 2; 3]
 29 triggers the first call to "reverse_helper"
 30 with an empty accumulator [] and the full
 31 list [1; 2; 3]. The subsequent calls to
 32 "reverse_helper follow the same pattern
 33 as before, building up the reversed list in
 34 the accumulator and recursing with the tail
 35 of the input list until the base case
 36 is reached and the final result is returned.