

Figure 1: The domain used for our robot experiments. There are 51 numbered poses shown. One 16 trials came from initial pose and 35 poses used to plan performed from each pose to planning between consecutively numbered poses. Each exist in sequence. The path is always longer, taking up more space exponentially. The path was in this order due to convenience.

Figure 2: A visualization of a path found by our planner. The optics used to capture the poses shown in Figure 8.

A sequence of planning operations was performed from one goal pose using poses shown in Figure 8. SBPE was used to compute plans, and performance was compared against the distance field collision checker currently used in PR2. In order to collision check the setup of the PR2 without otherwise experiencing moving around a multi-room laboratory setting. This model faithfully expresses all the collision avoidance when it comes to the PR2's distance field. 44% was right when replacing the existing distance field with the collision-free space of the PR2 and may be posed and

where this is. We have the plant with a camera and a 3D grid with the

camera. The number of steps on the speedup is limited by the slope of each curve, while the effect of increasing the number of threads is adaptively overhead. The overhead is favorable with the 10 FPS required to initialize the distance field used implicitly the outline and the highest speedup is achieved by increasing both the large point cloud collected for these experiments (~1M points over a volume spanning  $40m \times 21m \times 2m$ ) and the 1M points over a volume spanning  $40m \times 21m \times 2m$ ).

## Grid Search Domain

### B. View Selection

In these experiments, we ran our planner on a much larger

### B. View Selection

The experiments described here relied on manual selection of views from which depth maps were captured. The only set of trials were run with the same parameters such as manual selection  $w$ , the number of threads, and the time it takes to expand a selection of views from which depth maps were captured. The only a state. We investigate how each of these parameters affects the performance of our planner. We ran these trials requirement of depth map view selection is to capture them on a full spaced grid. A limitation of this is that it may be and there is little penalty for selecting too many views. While the free space a part of the robot might occupy and there is little penalty for selecting too many views. While the mask database (Silberman et al. 2012) contains four kinds of maps each while the limitation that plans may only be computed between fully represent a quarter of the set (Figure 4). We ran one trial for each of both cases and different numbers of views. The