

Table. Architecture parameters (mean \pm standard deviation) of 17 forearm muscles from 12 healthy individuals (9 males and 3 females, age: 25.3 ± 2.2 years, height: 1.74 ± 0.05 m, body mass: 66.9 ± 7.2 kg, body mass index: 22.0 ± 2.2 kgm^{-2} , radius length: 239 ± 16 mm, ulna length: 256 ± 17 mm, forearm circumference: 237 ± 15 mm. Radius length is calculated as the straight-line distance from the styloid process of radius to the lateral humeral epicondyle. Ulna length is measured as the straight-line distance from the styloid process of ulnar to the medial humeral epicondyle. Forearm circumference is the maximum circumference of the forearm). (Abbreviations: fiber length (FL), muscle length (ML), pennation angle (PA), physiological cross-sectional area (PCSA).)

Muscle	Muscle volume (mm^3)	Muscle length (mm)	Fiber length (mm)	FL/ML ratio (-)	PA (deg)	PCSA (mm^2)
Anconeus	6269 ± 2453	40 ± 10	16 ± 3	0.41 ± 0.09	9 ± 3	396 ± 152
Abductor pollicis longus	12266 ± 2837	108 ± 11	39 ± 8	0.36 ± 0.07	9 ± 2	328 ± 103
Extensor carpi radialis brevis	12149 ± 2825	86 ± 17	23 ± 5	0.27 ± 0.04	8 ± 5	520 ± 95
Extensor carpi radialis longus	27492 ± 6041	160 ± 28	50 ± 11	0.32 ± 0.06	9 ± 4	556 ± 127
Extensor carpi ulnaris	11816 ± 3119	143 ± 12	31 ± 12	0.21 ± 0.07	10 ± 2	421 ± 150
Extensor digitorum communis	19911 ± 4032	140 ± 12	35 ± 10	0.24 ± 0.06	9 ± 3	605 ± 164
Extensor digiti minimi	3648 ± 1393	95 ± 28	23 ± 9	0.25 ± 0.06	7 ± 2	165 ± 63

Extensor pollicis longus	6454±2810	89±17	28±7	0.32±0.07	9±4	225±69
Flexor carpi radialis	21214±6708	136±42	48±9	0.37±0.09	8±2	442±113
Flexor carpi ulnaris	24755±5636	173±14	41±9	0.24±0.04	9±2	617±172
Flexor digitorum profundus	68210±11033	174±13	74±11	0.43±0.06	7±2	941±234
Flexor digitorum superficialis	52122±12113	188±19	72±14	0.38±0.06	7±3	732±173
Flexor pollicis longus	17045±3155	149±19	44±9	0.30±0.05	9±3	400±99
Palmaris longus	7789±3505	81±20	41±12	0.50±0.05	7±3	191±65
Pronator quadratus	5846±1770	36±11	22±6	0.63±0.08	11±3	267±62
Pronator teres	25214±10911	84±18	35±10	0.42±0.06	11±2	701±217
Supinator	17129±4388	66±15	23±2	0.32±0.04	26±5	664±137
