



1. For every node,  $v_i$ , in the original graph,  $G$ , we generate the corresponding 1-hop node-level subgraph,  $g_i$

**Original Graph,  $G$**



**1-hop node-level graph embedding  $y_1$ : /c/en/smartphone**




2. We then train and generate the corresponding node-level graph embedding,  $y_i$ , with various families of GE algorithms.

**1-hop node-level graph embedding  $y_2$ : /c/en/mobile\_phone/n**



**1-hop node-level graph embedding  $y_3$ : /c/en/cellular\_telephone/n**




**Reconstructed Adjacency Matrix,  $W_{recon}$**

	$v_1$	$v_2$	$v_3$
$v_1$	0.3	0.8	0.4
$v_2$	0.4	0.2	0.3
$v_3$	0.2	0.7	0.3

3. We reconstruct the adjacency matrix,  $W_{recon}$ , by computing the edge weight between the pair of nodes (e.g., **dot product** of two vectors) and normalizing them.


4. We apply a set threshold,  $t=0.5$ , to preserve only edges with a probability  $\geq t$  for the reconstructed graph,  $G_{recon}$

**Assessment of Topological Structure**



5. We compute the Euclidean distance between the graph embeddings,  $y_i$ , to assess the learned semantic information between nodes,  $v_i$ .

**Assessment of Semantic Information**



--- Missed edge from the original graph,  $G$

--- Added edge from the original graph,  $G$