

1. INPUT / PREPROCESSING


Abstract Algorithm

- programming language for QC
(e.g. Qiskit, Q#, Pennylane, ...)

```
qc = QuantumCircuit(10)
for i in range(4):
    qc += initialize()
    qc += QFT(10)
    ...
```

Gate-level Description

- sequence of abstract and platform independent gates

**Pre-compiled Circuits**


- pre-compiled and temporary stored circuit files

```
// addeder.qasm
include "stdgates.inc"
qubit[1] cin;
qubit[4] a;
```


2. COMPUTATIONAL CAPABILITIES

(A) Nearest Neighbour Connectivity

- **Synthesis** to one - and two-qubit gates
- **Mapping** with nearest neighbor connectivity
- **Scheduling** according to **gate-restriction** for parallelization of CZ gates

**(B) Long-range Interactions**


- **Synthesis** to one - and two-qubit gates
- **Mapping** with **long-range connectivity**
- **Scheduling** according to **gate-restriction** for parallelization of CZ gates

**(C) Multi-qubit Gates**


- **Synthesis** to one - and two-qubit and **multi-qubit gates**
- **Mapping** with mid- to long-range connectivity
- **Scheduling** according to **gate-restriction** for parallelization of CZ gates

**(D) Shuttling / DPQA**

- **Synthesis** to one - and multi-qubit gates
- **Mapping** with possible all-to-all connectivity
- **Scheduling** with **DPQA shuttling restrictions** for AOD number and movements

**(E) Fault-tolerant QC**

- Fault-tolerant state preparation
- Inter-photon connections
- Mid-circuit measurements



3. FIGURES OF MERIT

(A) Gate/depth Count

- number of additionally required gate operations (e.g. SWAP)

(B) Operations Count

- number of AOD movements and trap switch from SLM to AOD

(C) Fidelity & Runtime

- total circuit execution time and estimated success probability