

# Private Variable-Length Coding with Sequential Encoder

Amirreza Zamani<sup>†</sup>, Tobias J. Oechtering<sup>†</sup>, Deniz Gündüz<sup>‡</sup>, Mikael Skoglund<sup>†</sup>

<sup>†</sup>Division of Information Science and Engineering, KTH Royal Institute of Technology

<sup>‡</sup>Dept. of Electrical and Electronic Engineering, Imperial College London

Email: amizam@kth.se, oech@kth.se, d.gunduz@imperial.ac.uk, skoglund@kth.se

**Abstract**—A multi-user private data compression problem is studied. A server has access to a database of  $N$  files,  $(Y_1, \dots, Y_N)$ , each of size  $F$  bits and is connected to an encoder. The encoder is connected through an unsecured link to a user. We assume that each file  $Y_i$  is arbitrarily correlated with a private attribute  $X$ , which is assumed to be accessible by the encoder. Moreover, an adversary is assumed to have access to the link. The users and the encoder have access to a shared secret key  $W$ . We assume that at each time the user asks for a file  $Y_{d_i}$ , where  $(d_1, \dots, d_K)$  corresponds to the demand vector. The goal is to design the delivered message  $\mathcal{C} = (\mathcal{C}_1, \dots, \mathcal{C}_K)$  after the user send his demands to the encoder such that the average length of  $\mathcal{C}$  is minimized, while satisfying: i. The message  $\mathcal{C}$  does not reveal any information about  $X$ , i.e.,  $X$  and  $\mathcal{C}$  are independent, which corresponds to the perfect privacy constraint; ii. The user is able to decode its demands,  $Y_{d_i}$ , by using  $\mathcal{C}$ , and the shared key  $W$ . Here, the encoder sequentially encode each demand  $Y_{d_i}$  at time  $i$ , using the shared key and previous encoded messages. We propose a variable-length coding scheme that uses privacy-aware compression techniques. We study proposed upper and lower bounds on the average length of  $\mathcal{C}$  in an example. Finally, we study an application considering cache-aided networks.

## I. INTRODUCTION

We consider the scenario illustrated in Fig. 1, in which a server has access to a database consisting of  $N$  files  $Y_1, \dots, Y_N$ , where each file, of size  $F$  bits, is sampled from the joint distribution  $P_{X Y_1 \dots Y_N}$ , where  $X$  denotes the private latent variable, whose realization is known to the server. The user requests  $K \leq N$  files from the server sequentially, where  $d_i \in [N] \triangleq \{1, \dots, N\}$  represents the user request at time  $i$ ,  $d_i \neq d_j$  for  $i \neq j$ . We assume that the server delivers the user's request over an unsecured link, but we assume that the two have access to a shared secret key denoted by  $W$ , of size  $T$ . In this work, the user send his demands to the encoder, where  $d_i \in [N] \triangleq \{1, \dots, N\}$  denotes the demand of the user at time  $i$ . We assume that the user asks for  $K$  files where  $K \leq N$  and  $d_i \neq d_j$  for  $i \neq j$ . At time slot  $i$ , the encoder receives  $d_i$  and designs a message  $\mathcal{C}_i$  using  $W$  and the previous messages it has delivered  $(\mathcal{C}_1, \mathcal{C}_2, \dots, \mathcal{C}_{i-1})$  to satisfy  $d_i$ . We note that the encoder is not aware of the future demands.

We assume that the delivery channel is public, and an adversary can use the delivered messages  $\mathcal{C} = (\mathcal{C}_1, \mathcal{C}_2, \dots, \mathcal{C}_K)$  to extract information about  $X$ . The goal of the private delivery problem is to find a response  $\mathcal{C}$  with minimum average length that satisfies user's demands while guaranteeing a certain privacy requirement. Here, we consider the worst case demand combinations  $d = (d_1, \dots, d_K)$




Fig. 1. A server sequentially delivers requests of a user from its database over an unsecured public channel.

to construct  $\mathcal{C}$ , and the expectation is taken over the randomness in the database. In this work, we impose a perfect privacy constraint, i.e., we require  $\mathcal{C}$  to be independent of  $X$ . Let  $\hat{Y}_{d_i}$  denote the decoded message of the user at time slot  $i$  using  $W$  and  $(\mathcal{C}_1, \mathcal{C}_2, \dots, \mathcal{C}_i)$ . The user should be able to recover  $Y_{d_k}$  reliably, i.e.,  $\mathbb{P}\{\hat{Y}_{d_k} \neq Y_{d_k}\} = 0, \forall k \in [K]$ .

We have a variable-length compression problem with a perfect privacy constraint. To solve this problem we combine techniques used in privacy mechanisms [1] and data compression [2].

Privacy mechanisms and compression problems have received increasing attention in recent years [1]–[24]. A notion of perfect secrecy was introduced in [3] by Shannon, where the public and private data are statistically independent. Equivocation as a measure of information leakage for information theoretic security has been used in [4]–[7]. A rate-distortion approach to information theoretic secrecy is studied in [8]. Lossless data compression with secrecy constraints are studied in [9], [10]. The concept of privacy funnel is introduced in [11], where the privacy-utility trade-off has been studied considering the log-loss as a privacy measure as well as a distortion measure for utility. In [13], the problem of privacy-utility trade-off considering mutual information both as measures of utility and privacy is studied. It is shown that under the perfect privacy assumption, the optimal privacy mechanism can be obtained as the solution of a linear program. The result in [13] is generalized to some small bounded leakage in [14], and to a non-invertible leakage matrix in [15]. In [2], an approach to partial secrecy called *secrecy by design* is introduced, and applied to two problems: privacy mechanism design and lossless compression. For the privacy design problem, bounds on privacy-utility trade-off are derived by using the

Functional Representation Lemma (FRL). These results are derived under the perfect secrecy assumption. In [1], the privacy problems considered in [2] are generalized by relaxing the perfect secrecy requirement. In [20], the privacy-utility trade-off with two different per-letter privacy constraints is studied. Moreover, in [2], both fixed-length and variable-length compression problems have been studied, and upper and lower bounds on the average length of the encoded message have been derived. These results are derived under the assumption that the private data is independent of the encoded message. A similar compression problem in cache-aided networks is studied in [21] in the presence of an adversary. In this paper, in contrast to [21], we consider a sequential encoder, and we use variable-length lossless compression techniques as in [2] to find an alternative solution to data delivery in the presence of an adversary. Our key contribution is a multi-part code construction based on an extension of FRL combined with a one-time-pad scheme.

## II. SYSTEM MODEL AND PROBLEM FORMULATION

Let  $Y_i$  denote the  $i$ -th file in the database, which is of size  $F$  bits, i.e.,  $\mathcal{Y}_i \in \{1, \dots, 2^F\}$  and  $|\mathcal{Y}_i| = 2^F$ . Let the discrete random variable (RV)  $X$  defined on the finite alphabet  $\mathcal{X}$  describe the private latent variable and be arbitrarily correlated with the files in the database  $Y = (Y_1, \dots, Y_N)$  where  $|\mathcal{Y}| = |\mathcal{Y}_1| \times \dots \times |\mathcal{Y}_N| = (2^F)^N$  and  $\mathcal{Y} = \mathcal{Y}_1 \times \dots \times \mathcal{Y}_N$ . We denote the joint distribution of the private data and the database by  $P_{XY_1 \dots Y_N}$  and marginal distributions of  $X$  and  $Y_i$  by vectors  $P_X$  and  $P_{Y_i}$  defined on  $\mathbb{R}^{|\mathcal{X}|}$  and  $\mathbb{R}^{2^F}$ . The relation between  $X$  and  $Y$  is given by the matrix  $P_{X|Y_1 \dots Y_N}$  defined on  $\mathbb{R}^{|\mathcal{X}| \times (2^F)^N}$ . The shared secret key is denoted by the discrete RV  $W$  defined on  $\{1, \dots, T\}$ , and is assumed to be known by the encoder and the users, but not the adversary. Furthermore, we assume that  $W$  is uniformly distributed and is independent of  $X$  and  $Y$ . Let the vector  $(Y_{d_1}, \dots, Y_{d_K})$  denote the demands of the user, where  $d_i$  is sent at time  $i$  and  $(d_1, \dots, d_K) \in [N]^K$ . A variable-length prefix-free code with a shared secret key of size  $T$  consists of mappings:

$$\begin{aligned} \text{(encoder)} \mathcal{C}_1 &: [T] \times [N] \rightarrow \{0,1\}^* \\ \text{(encoder)} \mathcal{C}_i &: \{0,1\}^* \times [T] \times [N]^i \rightarrow \{0,1\}^*, \quad i \geq 2, \\ \text{(decoder)} \mathcal{D}_i &: \{0,1\}^* \times [T] \times [N]^i \rightarrow 2^F, \quad \forall i \in [K]. \end{aligned}$$

The output of the encoder in the  $i$ -th time slot  $\mathcal{C}(Y_{d_i}, d_1, \dots, d_i, \mathcal{C}_1, \dots, \mathcal{C}_{i-1})$  is the codeword the server sends over the link to satisfy the demands of the user  $(Y_{d_1}, \dots, Y_{d_i})$ . At the user side, the user employs the decoding function  $\mathcal{D}_i$  in the  $i$ -th time slot to recover its demand  $Y_{d_i}$ , i.e.,  $\hat{Y}_{d_i} = \mathcal{D}_i(W, d_1, \dots, d_i, \mathcal{C}_1, \dots, \mathcal{C}_{i-1})$ . Since the code is prefix free, no codeword in the image of  $\mathcal{C}$  is a prefix of another codeword. The variable-length code  $(\mathcal{C}_1, \dots, \mathcal{C}_K, \mathcal{D}_1, \dots, \mathcal{D}_K)$  is lossless if for all  $k \in [K]$  we have

$$\mathbb{P}(\mathcal{D}_i(W, d_1, \dots, d_i, \mathcal{C}_1, \dots, \mathcal{C}_{i-1}) = Y_{d_i}) = 1. \quad (1)$$

In the following, we define perfectly private codes. The code  $(\mathcal{C}_1, \dots, \mathcal{C}_K, \mathcal{D}_1, \dots, \mathcal{D}_K) = (\mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K)$  is *perfectly private* if

$$I(\mathcal{C}; X) = 0. \quad (2)$$

Let  $\xi$  be the support of  $\mathcal{C}$ , where  $\xi \subseteq \{0,1\}^*$ . For any  $c \in \xi$ , let  $\mathbb{L}(c)$  be the length of the codeword. The lossless code  $(\mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K)$  is  $(\alpha, T, d_1, \dots, d_K)$ -*variable-length* if

$$\mathbb{E}(\mathbb{L}(\mathcal{C})) \leq \alpha, \quad \forall w \in [T] \text{ and } \forall d_1, \dots, d_K, \quad (3)$$

and  $(\mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K)$  satisfies (1). Finally, let us define the set  $\mathcal{H}(\alpha, T, d_1, \dots, d_K)$  as follows:

$\mathcal{H}(\alpha, T, d_1, \dots, d_K) \triangleq \{(\mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K) : (\mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K) \text{ is perfectly-private and } (\alpha, T, d_1, \dots, d_K)\text{-variable-length}\}$ . The private compression design problem with sequential encoder can be stated as follows

$$\mathbb{L}(P_{XY_1 \dots Y_N}, T) = \inf_{(\mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K) \in \mathcal{H}(\alpha, T, d_1, \dots, d_K)} \alpha. \quad (4)$$

**Remark 1.** Letting  $N = K = 1$ , (4) leads to the privacy-compression rate trade-off studied in [2], where upper and lower bounds have been derived.

**Remark 2.** In this paper, to design a code, we consider the worst case demand combinations. This follows since (3) must hold for all possible combinations of the demands.

## III. MAIN RESULTS

In this section, we derive an upper bound on  $\mathbb{L}(P_{XY_1 \dots Y_N}, T)$  defined in (4). For this, we employ the multi-part code construction, which is similar to the two-part code used in [2]. We first encode the private data  $X$  using a one-time-pad [16, Lemma 1], then sequentially encode the user's demands using an extension of the Functional Representation Lemma. To do so, let us, first recall FRL.

**Lemma 1.** (FRL [2, Lemma 1]): For any pair of RVs  $(X, Y)$  distributed according to  $P_{XY}$  supported on alphabets  $\mathcal{X}$  and  $\mathcal{Y}$ , respectively, where  $|\mathcal{X}|$  is finite and  $|\mathcal{Y}|$  is finite or countably infinite, there exists a RV  $U$  supported on  $\mathcal{U}$  such that  $X$  and  $U$  are independent, i.e.,  $I(U; X) = 0$ ,  $Y$  is a deterministic function of  $U$  and  $X$ , i.e.,  $H(Y|U, X) = 0$ , and  $|\mathcal{U}| \leq |\mathcal{X}|(|\mathcal{Y}| - 1) + 1$ . Furthermore, if  $X$  is a deterministic function of  $Y$ , we have  $|\mathcal{U}| \leq |\mathcal{Y}| - |\mathcal{X}| + 1$ .

The proof of Lemma 1 is constructive and is useful to obtain the next lemma. Next, we provide an extension of FRL that helps us find upper bound on  $\mathbb{L}(P_{XY_1 \dots Y_N}, T)$ .

**Lemma 2.** For a fixed integer  $k \geq 1$ , let RVs  $(X, Y, U_1, \dots, U_k)$  be distributed according to  $P_{XYU_1 \dots U_k}$  where  $I(X; U_1, \dots, U_k) = 0$ . Then, there exists a RV  $U_{k+1}$  such that  $X$  and  $(U_1, \dots, U_{k+1})$  are independent, i.e.,

$$I(U_1, \dots, U_{k+1}; X) = 0, \quad (5)$$

$Y$  is a deterministic function of  $(U_1, \dots, U_{k+1})$  and  $X$ , i.e.,

$$H(Y|U_1, \dots, U_{k+1}, X) = 0, \quad (6)$$

and

$$|\mathcal{U}_{k+1}| \leq |\mathcal{X}| |\mathcal{U}_1| \cdot |\mathcal{U}_k| (|\mathcal{Y}| - 1) + 1. \quad (7)$$

*Proof:* Let  $U_1^i \triangleq (U_1, \dots, U_i)$  and let  $U_{k+1}$  be produced based on FRL using  $X \leftarrow (X, U_1, \dots, U_k)$  and  $Y \leftarrow Y$ . We have

$$I(X; U_1^{k+1}) = I(X; U_1^k) + I(X; U_{k+1}|U_1^k) = 0,$$

where the last line follows since the first term is zero by the assumption and the second term is zero due to independence of  $U_{k+1}$  and  $(X, U_1, \dots, U_k)$ . ■

Next, we present our achievable scheme which leads to an upper bound on (4). Let  $m_1 = \min_{U_1: I(U_1; X)=0, H(Y_{d_1}|X, U_1)=0} H(U_1)$  and  $U_1^*$  be an optimizer that achieves  $m_1$ . Furthermore, let  $m_2 = \min_{U_2: I(U_2, U_1^*; X)=0, H(Y_{d_2}|X, U_1^*, U_2)=0} H(U_2)$  and  $U_2^*$  be an optimizer that achieves  $m_2$ . Similarly, let  $m_i = \min_{U_i: I(U_i^*, \dots, U_{i-1}^*, U_i; X)=0, H(Y_{d_i}|X, U_1^*, \dots, U_{i-1}^*, U_i)=0} H(U_i)$  and  $U_i^*$  be an optimizer that achieves  $m_i$ .

**Theorem 1.** Let RVs  $(X, Y) = (X, Y_1, \dots, Y_N)$  be distributed according to  $P_{XY_1 \dots Y_N}$  supported on alphabets  $\mathcal{X}$  and  $\mathcal{Y}$ , and let the shared secret key size be  $|\mathcal{X}|$ , i.e.,  $T = |\mathcal{X}|$ . Then, we have

$$\mathbb{L}(P_{XY}, |\mathcal{X}|) \leq \sum_{i=1}^K \lceil m_i \rceil + \lceil \log(|\mathcal{X}|) \rceil \quad (8)$$

$$\leq \sum_{i=1}^K \lceil \log(|\mathcal{U}_i|) \rceil + \lceil \log(|\mathcal{X}|) \rceil. \quad (9)$$

where

$$|\mathcal{U}_i| \leq |\mathcal{X}| |\mathcal{U}_1| \cdot |\mathcal{U}_{i-1}| (|\mathcal{Y}_{d_i}| - 1) + 1, \quad (10)$$

$$|\mathcal{U}_1| \leq |\mathcal{X}| (|\mathcal{Y}_{d_1}| - 1) + 1, \quad (11)$$

and  $|\mathcal{Y}_{d_i}| = 2^F, \forall i \in [K]$ .

*Sketch of proof:* The complete proof is provided in Appendix A. We use a multi-part code construction to achieve both upper bounds. As shown in Fig. 2, the encoder first encodes the private data  $X$  using one-time-pad coding [16, Lemma 1] and sends it over the shared link, which uses  $\lceil \log(|\mathcal{X}|) \rceil$  bits. The rest follows since by assumption the encoder has access to the realization of  $X$  and in the one-time-pad coding, the RV added to  $X$  is the shared key, which is of size  $|\mathcal{X}|$ , and as a result the output has uniform distribution. At each time, the encoder receives  $Y_{d_i}$ . Then, the encoder produces  $U_1^K$  as follows. First, the encoder receives  $Y_{d_1}$  and produces  $U_1$  based on FRL using  $Y \leftarrow Y_{d_1}$  and  $X \leftarrow X$ . The encoder uses any lossless codes to encode  $U_1$  and sends it over the shared link. Note that  $I(U_1; X) = 0$ ,  $H(Y_{d_1}|U_1, X) = 0$ , and  $|\mathcal{U}_1| \leq |\mathcal{X}| (|\mathcal{Y}_{d_1}| - 1) + 1$ . Next, the encoder receives  $Y_{d_2}$  and produces  $U_2$  using Lemma 2 with  $k = 1$  and encode it to send over the shared link. Latter follows since the encoder has access to  $U_1$ . We have  $I(X; U_1, U_2) = 0$ ,  $H(Y_{d_2}|U_1, U_2, X) = 0$ , and  $|\mathcal{U}_2| \leq |\mathcal{X}| |\mathcal{U}_1| (|\mathcal{Y}_{d_2}| - 1) + 1$ . After receiving the  $i$ -th demand, i.e.,  $Y_{d_i}$ , the encoder produces  $U_i$  using Lemma 2 with  $k = i - 1$  and  $U_1^{i-1}$ . We have  $I(X; U_1^i) = 0$ ,  $H(Y_{d_i}|U_1^i, X) = 0$ , and  $|\mathcal{U}_i| \leq |\mathcal{X}| |\mathcal{U}_1| \cdot |\mathcal{U}_{i-1}| (|\mathcal{Y}_{d_i}| - 1) + 1$ . This procedure continuous until encoding the last demanded file  $Y_{d_K}$ . Note that the leakage from the delivered messages sent over the shared link to the adversary is zero since by construction we have  $I(X; U_1^K) = 0$ . Furthermore, if we choose the randomness used in the one-time-pad coding independent of  $(X, U_1^K)$  we have  $I(X; U_1^K, \tilde{X}) = 0$ , where  $\tilde{X}$  is the output of the one-time-pad coding.

As shown in Fig. 3, at user side, the user, first decodes  $X$  using one-time-pad decoder. Then, it decodes  $Y_{d_i}$  using




Fig. 2. Sequentially encoding design: illustration of the achievability scheme of Theorem 1. Multi-part code construction is used to produce the delivered message,  $\mathcal{C}$ . The encoder sends  $\mathcal{C}$  over the link, which is independent of  $X$ .

$(C_1, \dots, C_i)$  and  $X$ . Using this scheme the compression rate in (9) is achieved. Finally, following the similar approach (8) is obtained. □




Fig. 3. Illustration of the sequentially decoding process of the user for the achievability scheme of Theorem 1.

Next, we obtain a converse bound (lower bound) on (4).

**Theorem 2.** Let the shared key  $W$  be independent of  $(X, Y)$ . For any RVs  $(X, Y_1, \dots, Y_N)$  distributed according to  $P_{XY_1 \dots Y_N}$ , where  $|\mathcal{X}|$  is finite and  $|\mathcal{Y}|$  is finite or countably infinite and any shared key size  $T \geq 1$  we have

$$\mathbb{L}(P_{XY}, T) \geq \max_{x \in \mathcal{X}} H(Y_{d_1}, \dots, Y_{d_K} | X = x). \quad (12)$$

*Proof:* Let  $U = (U_1, \dots, U_K)$  be the response of the encoder to satisfy the demands  $(d_1, \dots, d_K)$ . Hence,  $U$  satisfies

$$I(U; X) = 0, \quad (13)$$

$$H(Y_{d_1}, \dots, Y_{d_K} | W, U) = 0. \quad (14)$$

Noting that (14) implies  $H(Y_{d_1}, \dots, Y_{d_K} | W, U, X) = 0$ , thus, by using [2, Lemma 6] we obtain the result. ■

Next we study the lower and upper bounds derived in Theorem 1 and Theorem 2 in a numerical example and we obtain an asymptotic constant-factor approximation of the  $\mathbb{L}(P_{XY}, T)$  when  $F$  is large enough.

**Example 1.** Let  $X \sim \text{Bern}(p) \in \{0, 1\}$  and  $Z_i^j \sim \text{Bern}(\frac{1}{2})$  be i.i.d RVs for  $i \in [F]$  and  $j \in [N]$ . We also assume that  $\{Z_i^j\}$  is independent of  $X$ . Furthermore, let  $Y_i^j = Z_i^j \wedge X$ , where  $Y_i^j$  corresponds to the  $i$ -th bit of the  $j$ -th file in the database and  $\wedge$  stands for the logical “and” operator. Let




Fig. 4. In this work a server wants to send a response over a shared link to satisfy users' demands, but since the database is correlated with the private data existing schemes are not applicable. In the delivery phase, the server sends the response to an encoder using blocks of size  $CF$  bits and the encoder hide the information about  $X$  using one-time-pad coding and send the rest of message using an extension of Functional Representation Lemma (FRL).

$(Y_{d_1}, \dots, Y_{d_K})$  be the demanded files by the user. We have  $H(Y_{d_1}, \dots, Y_{d_K} | X = 0) = 0$  since  $Y_i^j = 0$ . Moreover, we have

$$\begin{aligned} H(Y_{d_1}, \dots, Y_{d_K} | X = 1) &= H(Z_{d_1}, \dots, Z_{d_K} | X = 1) \\ &= H(Z_{d_1}, \dots, Z_{d_K}) = KF. \end{aligned} \quad (15)$$

Hence, using Theorem 2 we have  $\mathbb{L}(P_{XY}, T) \geq KF$ . Using Theorem 1 and (15) the ratio between upper and lower bounds can be obtained asymptotically as follows

$$\begin{aligned} \lim_{F \rightarrow \infty} \frac{\sum_{i=1}^K [\log(|\mathcal{U}_i|)] + [\log(|\mathcal{X}|)]}{\max_{x \in \mathcal{X}} H(Y_{d_1}, \dots, Y_{d_K} | X = x)} &= \\ \lim_{F \rightarrow \infty} \frac{\log(2^{F+1}-1) + \log(2(2^{F+1}-1)(2^F-1)+1) + \dots + 1}{KF} &= \\ \lim_{F \rightarrow \infty} \frac{\log(2^{\frac{K(K+1)}{2}F})}{KF} &= \frac{K+1}{2}. \end{aligned} \quad (16)$$

Using (16), asymptotically we have

$$1 \leq \lim_{F \rightarrow \infty} \frac{\mathbb{L}(P_{XY}, 2)}{\max_{x \in \mathcal{X}} H(Y_{d_1}, \dots, Y_{d_K} | X = x)} \leq \frac{K+1}{2}. \quad (17)$$

In other words, we have

$$K \leq \lim_{F \rightarrow \infty} \frac{\mathbb{L}(P_{XY}, 2)}{F} \leq \frac{K(K+1)}{2}. \quad (18)$$

For instance, if the user asks for two files, i.e.,  $K = 2$ , we have  $2 \leq \lim_{F \rightarrow \infty} \frac{\mathbb{L}(P_{XY}, 2)}{F} \leq 3$ .

**A. Application: Cache-aided networks with sequential encoder**

We consider the scenario illustrated in Fig. 4, in which a server has access to a database consisting of  $N$  files  $Y_1, \dots, Y_N$ , where each file, of size  $F$  bits, is sampled from the joint distribution  $P_{XY_1 \dots Y_N}$ , where  $X$  denotes the private latent variable. We assume that the server does not know the

realization of the private variable  $X$ . The server is connected to an encoder equipped with a local buffer of size  $CF$  bits and has access to a public cache of size  $LF$  bits as well. The encoder is connected to  $K$  users over a shared link, where user  $i$  has access to a local cache memory of size  $MF$  bits. Furthermore, we assume that the encoder and the users have access to a shared secret key denoted by  $W$ , of size  $T$ . The system works in two phases: the placement and delivery phases, respectively, [25]. In the placement phase, the server and encoder fill the local caches using the database. Let  $Z_k$  denote the content of the local cache memory of user  $k$ ,  $k \in [K]$  after the placement phase. In the delivery phase, first the users send their demands to the encoder and the server, where  $d_k \in [N]$  denotes the demand of user  $k$ . The server sends a response, denoted by  $\mathcal{C}' = (\mathcal{C}'_1, \mathcal{C}'_2, \dots)$ , to the encoder using blocks each of size  $CF$  bits to satisfy all the demands. The encoder designs a message  $\mathcal{C}_i$  using the  $i$ -th block of the server's response, i.e.,  $\mathcal{C}'_i$ , and the shared key and send it over the shared link to the users. The encoder can store  $\mathcal{C}_i$  in the public cache which is assumed to be not accessible by the users. The public cache enables the encoder to use previous stored messages to design the next message, i.e., the encoder can use  $(\mathcal{C}_1, \dots, \mathcal{C}_{i-1})$  to design message  $\mathcal{C}_i$ . We assume that an adversary has access to the shared link and the public cache as well, and uses the delivered message  $\mathcal{C} = (\mathcal{C}_1, \mathcal{C}_2, \dots)$  and the content of public cache denoted by  $P$  to extract information about  $X$ . However, the adversary does not have access to the users' local cache contents or the secret key. Since the files in the database are all correlated with the private latent variable  $X$ , the coded caching and delivery techniques introduced in [25] do not satisfy the privacy requirement. The goal of the cache-aided private delivery problem is to find a response  $\mathcal{C}$  with minimum possible average length that satisfies a certain privacy constraint and the zero-error decodability constraint of users. Furthermore, the contents of the public cache  $P$  must satisfy the privacy constraint. Here, we consider the worst case demand combinations  $d = (d_1, \dots, d_K)$  to construct  $\mathcal{C}$ , and the expectation is taken over the randomness in the database. Similarly to [25], we have  $K$  caching functions to be used during the placement phase:

$$\theta_k : [Y] \rightarrow [2^{LFM}], \quad \forall k \in [K], \quad (19)$$

such that

$$Z_k = \theta_k(Y_1, \dots, Y_N), \quad \forall k \in [K]. \quad (20)$$

The output of the server  $\mathcal{C}'(Y, d_1, \dots, d_K)$  is the codeword the server sends to the encoder by using blocks of  $CF$  bits to satisfy the demands of users  $(Y_{d_1}, \dots, Y_{d_K})$ . Let  $\mathcal{C}'_i$  be the  $i$ -th block of the codeword  $\mathcal{C}'$ . Due to the limited size of the local buffer  $C$ , the encoder uses a sequentially coding scheme as follows. First, the encoder receives  $\mathcal{C}'_1$  and encode it using the shared key. Let the output be  $\mathcal{C}_1$ . The encoder sends  $\mathcal{C}_1$  over the shared link and also stores it to the public cache. Then, the encoder receives the second block  $\mathcal{C}'_2$  and encodes it using  $W$  and  $\mathcal{C}_1$ . The output is denoted by  $\mathcal{C}_2$  and is sent through the shared link and is stored to the public cache. Here, we assume that  $L$  is a large quantity. Furthermore, the encoder encodes  $i$ -th block  $\mathcal{C}'_i$  using  $W$

and  $(\mathcal{C}_1, \dots, \mathcal{C}_{i-1})$ . The encoding scheme continues until the last block of the codeword  $\mathcal{C}'$ . Let  $\mathcal{C} = (\mathcal{C}_1, \mathcal{C}_2, \dots)$  denote the delivered message consisting of the messages sent over the shared link  $\mathcal{C}_i$ . At the user side, user  $k$  employs the decoding function  $\mathcal{D}_k$  to recover its demand  $Y_{d_k}$ , i.e.,  $\hat{Y}_{d_k} = \mathcal{D}_k(Z_k, W, \mathcal{C}, d_1, \dots, d_K)$ . The variable-length code  $(\mathcal{C}', \mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K)$  is lossless if for all  $k \in [K]$  we have

$$\mathbb{P}(\mathcal{D}_k(\mathcal{C}, W, Z_k, d_1, \dots, d_K) = Y_{d_k}) = 1. \quad (21)$$

In the following, we define perfectly private codes. The code  $(\mathcal{C}', \mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K)$  is *perfectly private* if

$$I(\mathcal{C}; X) = 0. \quad (22)$$

Let  $\xi$  be the support of  $\mathcal{C}$ , where  $\xi \subseteq \{0, 1\}^*$ . For any  $c \in \xi$ , let  $\mathbb{L}(c)$  be the length of the codeword. The lossless code  $(\mathcal{C}', \mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K)$  is  $(\alpha, T, d_1, \dots, d_K)$ -*variable-length* if

$$\mathbb{L}(\mathbb{L}(\mathcal{C})) \leq \alpha, \quad \forall w \in [T] \text{ and } \forall d_1, \dots, d_K, \quad (23)$$

and  $(\mathcal{C}', \mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K)$  satisfies (21). Finally, let us define the set  $\mathcal{H}(\alpha, T, d_1, \dots, d_K)$  as follows:

$\mathcal{H}(\alpha, T, d_1, \dots, d_K) \triangleq \{(\mathcal{C}', \mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K) : (\mathcal{C}', \mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K) \text{ is perfectly-private and } (\alpha, T, d_1, \dots, d_K)\text{-variable-length}\}$ . The cache-aided private compression design problem can be stated as follows

$$\mathbb{L}(P_{X Y_1, \dots, Y_N}, T, C) = \inf_{(\mathcal{C}', \mathcal{C}, \mathcal{D}_1, \dots, \mathcal{D}_K) \in \mathcal{H}(\alpha, T, d_1, \dots, d_K)} \alpha. \quad (24)$$

In the next theorem, let  $\mathcal{C}' \triangleq (C_{\gamma_1}, \dots, C_{\gamma_Q})$  be the code designed by the achievable scheme in [25, Theorem 1], where  $Q \triangleq \binom{K}{p+1}$ ,  $M \in \{\frac{N}{K}, \frac{2N}{K}, \dots, N\}$ , and  $p \triangleq \frac{KM}{N}$  is an integer.

**Theorem 3.** *Let the local buffer size be  $\frac{F}{\binom{K}{p}}$  bits, i.e.,  $C = \frac{1}{\binom{K}{p}}$ ,  $L$  be large enough, and let  $M \in \{\frac{N}{K}, \frac{2N}{K}, \dots, N\}$ . Then, we have*

$$\mathbb{L}(P_{XY}, |\mathcal{X}|, \frac{1}{\binom{K}{p}}) \leq \sum_{i=1}^Q [\log(|\mathcal{U}_i|)] + [\log(|\mathcal{X}|)]. \quad (25)$$

where

$$|\mathcal{U}_i| \leq |\mathcal{X}| |\mathcal{U}_1| \cdot |\mathcal{U}_{i-1}| (|C_{\gamma_i}| - 1) + 1, \quad (26)$$

$$|\mathcal{U}_1| \leq |\mathcal{X}| (|C_{\gamma_1}| - 1) + 1, \quad (27)$$

and  $|C_{\gamma_i}| = 2^{CF} = 2^{\frac{F}{\binom{K}{p}}}$ ,  $\forall i \in [Q]$ .

*Proof:* The proof follows similar arguments as Theorem 1. In the placement phase, we use the same scheme as in [25]. In the delivery phase, we use the following strategy. We use multi-part code construction to achieve the upper bound. The encoder first encodes the private data  $X$  using one-time-pad coding [16, Lemma 1] and sends it over the shared link, which uses  $\lceil \log(|\mathcal{X}|) \rceil$  bits. Next, the server produces the response  $\mathcal{C}'$  as in [25, Theorem 1] and sends it to the encoder using blocks of  $CF$  bits. At each time, the encoder receives  $C_{\gamma_i}$  since the size of buffer equals to the size of  $C_{\gamma_i}$ . Then, the encoder produces  $U_1^Q$  as follows. First, the encoder receives  $C_{\gamma_1}$  and produces

$U_1$  based on FRL using  $Y \leftarrow C_{\gamma_1}$  and  $X \leftarrow X$ , where  $C_{\gamma_1}$  is the first codeword of the response  $\mathcal{C}'$ . The encoder uses any lossless codes to encode  $U_1$  and sends it over the shared link. Furthermore, the encoder stores it to the public cache. Note that  $I(U_1; X) = 0$ ,  $H(C_{\gamma_1}|U_1, X) = 0$ , and  $|\mathcal{U}_1| \leq |\mathcal{X}|(|\mathcal{Y}| - 1) + 1$ . Next, the encoder receives  $C_{\gamma_2}$  and produces  $U_2$  using Lemma 2 with  $k = 1$  and encode it to send over the shared link. Latter follows since the encoder has access to  $U_1$  which is stored in the public cache. We have  $I(X; U_1, U_2) = 0$ ,  $H(C_{\gamma_2}|U_1, U_2, X) = 0$ , and  $|\mathcal{U}_2| \leq |\mathcal{X}| |\mathcal{U}_1| (|\mathcal{Y}| - 1) + 1$ . After receiving the  $i$ -th codeword of the response  $\mathcal{C}'$ , i.e.,  $C_{\gamma_i}$ , the encoder produces  $U_i$  using Lemma 2 with  $k = i - 1$  and  $U_1^{i-1}$  which are stored in the public cache. We have  $I(X; U_1^i) = 0$ ,  $H(C_{\gamma_i}|U_1^i, X) = 0$ , and  $|\mathcal{U}_i| \leq |\mathcal{X}| |\mathcal{U}_1| \cdot |\mathcal{U}_{i-1}| (|\mathcal{Y}| - 1) + 1$ . This procedure continues until encoding the last codeword of the response  $C_{\gamma_Q}$ . Note that the leakage from the delivered messages sent over the shared link and public cache to the adversary is zero since by construction we have  $I(X; U_1^Q) = 0$ . Furthermore, if we choose the randomness used in the one-time-pad coding independent of  $(X, U_1^Q)$  we have  $I(X; U_1^Q, \tilde{X}) = 0$ , where  $\tilde{X}$  is the output of the one-time-pad coding. At user side, each user, e.g., user  $i$ , first decodes  $X$  using one-time-pad decoder. Then, it sequentially decodes  $\mathcal{C}'$  using  $\mathcal{C}$  and  $X$ . Finally, it decodes  $Y_{d_i}$  using  $Z_i$  and the response  $\mathcal{C}'$ . Finally, using this scheme the compression rate in (25) is achieved.  $\blacksquare$

## APPENDIX A

*Proof of Theorem 1:*

Let  $W$  be the shared secret key with key size  $T = |\mathcal{X}|$ , which is uniformly distributed over  $\{1, \dots, T\} = \{1, \dots, |\mathcal{X}|\}$  and independent of  $(X, Y_1, \dots, Y_N)$ . As shown in Fig. 2, first, the private data  $X$  is encoded using the shared secret key [16, Lemma 1]. Thus, we have

$$\tilde{X} = X + W \text{ mod } |\mathcal{X}|.$$

Next, we show that  $\tilde{X}$  has uniform distribution over  $\{1, \dots, |\mathcal{X}|\}$  and  $I(X; \tilde{X}) = 0$ . We have

$$H(\tilde{X}|X) = H(X+W|X) = H(W|X) = H(W) = \log(|\mathcal{X}|). \quad (28)$$

Furthermore,  $H(\tilde{X}|X) \leq H(\tilde{X})$ , and combining it with (28), we obtain  $H(\tilde{X}|X) = H(\tilde{X}) = \log(|\mathcal{X}|)$ . For encoding  $\tilde{X}$  the encoder uses  $\lceil \log(|\mathcal{X}|) \rceil$  bits and sends it over the shared link. We denote the encoded message  $\tilde{X}$  by  $\tilde{\mathcal{C}}_1$ . First, the encoder receives  $Y_{d_1}$  and produces  $U_1$  based on FRL using  $Y \leftarrow Y_{d_1}$  and  $X \leftarrow X$ . Thus, we have  $I(U_1; X) = 0$ ,  $H(Y_{d_1}|U_1, X) = 0$ ,  $|\mathcal{U}_1| \leq |\mathcal{X}|(|\mathcal{Y}| - 1) + 1$ . The encoder uses any lossless codes to encode  $U_1$  and sends it over the shared link. Let  $\mathcal{C}_1$  denote the encoded message  $U_1$ . Furthermore, the encoder stores  $\mathcal{C}_1$  to the public cache. Next, the encoder receives  $Y_{d_2}$  and produces  $U_2$  based on Lemma 2 with  $k = 1$  and  $U_1$  that is stored in the public cache, encode it to  $\mathcal{C}_2$  and sends it over the shared link. Thus, we obtain  $I(U_1, U_2; X) = 0$ ,  $H(Y_{d_2}|U_2, U_1, X) = 0$ , and  $|\mathcal{U}_2| \leq |\mathcal{X}| |\mathcal{U}_1| (|\mathcal{Y}_{d_2}| - 1) + 1$ . Furthermore, the encoder stores  $\mathcal{C}_2$  in the public cache. After receiving  $Y_{d_i}$ , the

encoder produces  $U_i$  using Lemma 2 with  $k = i - 1$  and  $U_1^{i-1}$  which are stored in the public cache. We have

$$I(U_1, \dots, U_i; X) = 0, \quad (29)$$

$$H(Y_{d_i} | U_1, \dots, U_i, X) = 0, \quad (30)$$

$$|\mathcal{U}_i| \leq |\mathcal{X}| |\mathcal{U}_1| \cdot |\mathcal{U}_{i-1}| (|\mathcal{Y}_{d_i}| - 1) + 1. \quad (31)$$

This procedure continues until encoding  $Y_{d_K}$  to  $\mathcal{C}_K$ . By using the construction used in Lemma 2, we have

$$\begin{aligned} H(\tilde{X}, U_1^K) &= H(\tilde{X}) + \sum_i H(U_i) \\ &\leq \sum_{i=1}^K [\log(|\mathcal{X}| |\mathcal{U}_1| \cdot |\mathcal{U}_{i-1}| (|\mathcal{Y}_{d_i}| - 1) + 1)] + \lceil \log(|\mathcal{X}|) \rceil, \end{aligned}$$

where we used the fact that  $U_1, \dots, U_K, \tilde{X}$  are jointly independent. Furthermore, we choose  $W$  to be independent of  $(X, Y_1, \dots, Y_N, U_1, \dots, U_K)$  which results in  $I(\tilde{X}; U_1^K) = 0$ .

Next, we present the decoding strategy at the user side. Since  $W$  is shared, the user decodes  $X$  by using  $\tilde{\mathcal{C}}_1$  and  $W$ , i.e., by using one-time-pad decoder. By adding  $|\mathcal{X}| - W$  to  $\tilde{X}$  we obtain  $X$ . Then, as shown in Fig. 3, user 1 decodes  $Y_{d_1}$  using  $\mathcal{C}_1$  and  $X$ . This follows by  $H(Y_{d_1} | U_1, X)$ . The user sequentially decodes  $Y_{d_i}$  based on (30).

What remains to be shown is the leakage constraint. We choose  $W$  independent of  $(X, Y_1, \dots, Y_N, U_1, \dots, U_K)$ .

$$\begin{aligned} I(\mathcal{C}; X) &= I(\tilde{\mathcal{C}}_1, \mathcal{C}_1^K; X) = I(\tilde{X}, U_1^K; X) \\ &= I(U_1^K; X) + I(\tilde{X}; X | U_1^K) = I(\tilde{X}; X | U_1^K) \\ &\stackrel{(a)}{=} H(\tilde{X} | U_1^K) - H(\tilde{X} | X, U_1^K) \\ &= H(\tilde{X} | U_1^K) - H(X + W | X, U_1^K) \\ &\stackrel{(b)}{=} H(\tilde{X} | U_1^K) - H(W) \\ &\stackrel{(c)}{=} H(\tilde{X}) - H(W) = \log(|\mathcal{X}|) - \log(|\mathcal{X}|) = 0 \end{aligned}$$

where (a) follows from (29); (b) follows since  $W$  is independent of  $(X, U_1^K)$ ; and (c) from the independence of  $U_1^K$  and  $\tilde{X}$ . The latter follows since we have

$$\begin{aligned} 0 \leq I(\tilde{X}; X | U_1^K) &= H(\tilde{X} | U_1^K) - H(W) \\ &\stackrel{(i)}{=} H(\tilde{X} | U_1^K) - H(\tilde{X}) \leq 0. \end{aligned}$$

Thus,  $\tilde{X}$  and  $U_1^K$  are independent. Step (i) follows by the fact that  $W$  and  $\tilde{X}$  are uniformly distributed over  $\{1, \dots, |\mathcal{X}|\}$ , i.e.,  $H(W) = H(\tilde{X})$ .

## REFERENCES

- [1] A. Zamani, T. J. Oechtering, and M. Skoglund, "Bounds for privacy-utility trade-off with non-zero leakage," in *2022 IEEE International Symposium on Information Theory (ISIT)*, 2022, pp. 620–625.
- [2] Y. Y. Shkel, R. S. Blum, and H. V. Poor, "Secrecy by design with applications to privacy and compression," *IEEE Transactions on Information Theory*, vol. 67, no. 2, pp. 824–843, 2021.
- [3] C. E. Shannon, "Communication theory of secrecy systems," *The Bell System Technical Journal*, vol. 28, no. 4, pp. 656–715, 1949.
- [4] D. Gündüz, E. Erkip, and H. V. Poor, "Lossless compression with security constraints," in *2008 IEEE International Symposium on Information Theory*, 2008, pp. 111–115.
- [5] —, "Source coding under secrecy constraints," *Securing Wireless Communications at the Physical Layer*, pp. 173–199, 2010.
- [6] R. F. Schaefer, H. Boche, A. Khisti, and H. V. Poor, *Information theoretic security and privacy of information systems*. Cambridge University Press, 2017.
- [7] L. Sankar, S. R. Rajagopalan, and H. V. Poor, "Utility-privacy tradeoffs in databases: An information-theoretic approach," *IEEE Transactions on Information Forensics and Security*, vol. 8, no. 6, pp. 838–852, 2013.
- [8] H. Yamamoto, "A rate-distortion problem for a communication system with a secondary decoder to be hindered," *IEEE Transactions on Information Theory*, vol. 34, no. 4, pp. 835–842, 1988.
- [9] D. Gündüz, E. Erkip, and H. V. Poor, "Secure lossless compression with side information," in *2008 IEEE Information Theory Workshop*, 2008, pp. 169–173.
- [10] D. Gunduz, E. Erkip, and H. V. Poor, "Lossless compression with security constraints," in *2008 IEEE International Symposium on Information Theory*, 2008, pp. 111–115.
- [11] A. Makhdoumi, S. Salamatian, N. Fawaz, and M. Médard, "From the information bottleneck to the privacy funnel," in *2014 IEEE Information Theory Workshop*, 2014, pp. 501–505.
- [12] C. Schieler and P. Cuff, "Rate-distortion theory for secrecy systems," *IEEE Transactions on Information Theory*, vol. 60, no. 12, pp. 7584–7605, 2014.
- [13] B. Rassouli and D. Gündüz, "On perfect privacy," *IEEE Journal on Selected Areas in Information Theory*, vol. 2, no. 1, pp. 177–191, 2021.
- [14] A. Zamani, T. J. Oechtering, and M. Skoglund, "A design framework for strongly  $\chi^2$ -private data disclosure," *IEEE Transactions on Information Forensics and Security*, vol. 16, pp. 2312–2325, 2021.
- [15] A. Zamani, T. J. Oechtering, and M. Skoglund, "Data disclosure with non-zero leakage and non-invertible leakage matrix," *IEEE Transactions on Information Forensics and Security*, vol. 17, pp. 165–179, 2022.
- [16] Y. Y. Shkel and H. V. Poor, "A compression perspective on secrecy measures," *IEEE Journal on Selected Areas in Information Theory*, vol. 2, no. 1, pp. 163–176, 2021.
- [17] F. P. Calmon, A. Makhdoumi, M. Medard, M. Varia, M. Christiansen, and K. R. Duffy, "Principal inertia components and applications," *IEEE Transactions on Information Theory*, vol. 63, no. 8, pp. 5011–5038, Aug 2017.
- [18] S. Asoodeh, M. Diaz, F. Alajaji, and T. Linder, "Estimation efficiency under privacy constraints," *IEEE Transactions on Information Theory*, vol. 65, no. 3, pp. 1512–1534, 2019.
- [19] I. Issa, S. Kamath, and A. B. Wagner, "Maximal leakage minimization for the Shannon cipher system," in *2016 IEEE International Symposium on Information Theory*, 2016, pp. 520–524.
- [20] A. Zamani, T. J. Oechtering, and M. Skoglund, "Bounds for privacy-utility trade-off with per-letter privacy constraints and non-zero leakage," in *2022 IEEE Information Theory Workshop (ITW)*, 2022, pp. 13–18.
- [21] A. Zamani, T. J. Oechtering, D. Gündüz, and M. Skoglund, "Cache-aided private variable-length coding with zero and non-zero leakage," *arXiv preprint arXiv:2306.13184*, 2023.
- [22] S. Asoodeh, M. Diaz, F. Alajaji, and T. Linder, "Information extraction under privacy constraints," *Information*, vol. 7, no. 1, p. 15, 2016.
- [23] A. Zamani, T. J. Oechtering, and M. Skoglund, "On the privacy-utility trade-off with and without direct access to the private data," *arXiv preprint arXiv:2212.12475*, 2022.
- [24] B. Rassouli, F. E. Rosas, and D. Gündüz, "Data disclosure under perfect sample privacy," *IEEE Transactions on Information Forensics and Security*, pp. 1–1, 2019.
- [25] M. A. Maddah-Ali and U. Niesen, "Fundamental limits of caching," *IEEE Transactions on Information Theory*, vol. 60, no. 5, pp. 2856–2867, 2014.