

```

C1 = ["Landmark", "Sculpture"]
C2 = ["Building", "Estate"]
res = client.label_detection(Image)
annotations = res.label_annotations
labels = [obj.name for obj in
           annotations]
if any([l in C1 for l in labels]):
    return "C1"
elif any([l in C2 for l in labels]):
    return "C2"

```

(a) Application source code

Target classes:
 ["Landmark", "Sculpture"]
 ["Building", "Estate"]

Decision type:
 Multi-Choice

Matching order:
 App-order

(b) Decision-process summary

<i>DNN output</i> y (score, label)	<i>Target class</i> $c^{(j)}$	<i>Matched?</i> $M^{(j)}$
1 st check: <[0.8, "Building"]>	C1	False (mismatch)
2 nd check: <[0.6, "Estate"]>	C1	False (mismatch)
3 rd check: <[0.2, "Landmark"]>	C1	False (score below θ)
4 th check: <[0.1, "Sculpture"]>	C1	False (score below θ)
5 th check: <[0.8, "Building"]>	C2	True ← EOD
6 th check: <[0.6, "Building"]>	C2	True
7 th check: <[0.2, "Landmark"]>	C2	False
8 th check: <[0.1, "Sculpture"]>	C2	False

(c) Generic description of the decision process

on DNN output $y = [0.1, 0.2, 0.8, 0.6]$ & score threshold $\theta = 0.3$