

Invocation of ML API

```

Landmark = ["Landmark", "Sculpture"]
Building = ["Building", "Estate",
            "Mansion"]
Person = ["Person", "Lady"]
res = client.label_detection(Img)
annotations = res.label_annotations
labels = [obj.name for obj in annotations]
if any([l in Landmark for l in labels]):
    return "Landmark"
elif any([l in Building for l in labels]):
    return "Building"
elif any([l in Person for l in labels]):
    return "Person"
else: ## obj.name not in any list
    return "It is others."

```

Branch condition that uses API output

```

text = types.Document(content=Text)
res = client.analyze_sentiment(text)
sentiment = res.document_sentiment
sentiment_score = sentiment.score
if sentiment_score < 0.3:
    print("It's a negative sentence!")
elif sentiment_score > 0.6:
    print("It's a positive sentence!")
else: ## between 0.3 and 0.6
    print("It's a neutral sentence!")

```

Structure indicating decision types

```

Plant = ["Houseplant", "Bonsai",
         "Plant", "Flowerpot"]
res =
    client.label_detection(Img)
for obj in
    response.label_annotations:
    if obj.name in Plant:
        return "Plant found!"
return "No plant found."

```

```

Protein = ["Hamburger", "Meat",
           "Patty"]
Grain = ["Noodle", "Pasta", "Bread"]
Fruit = ["Apple", "Orange", "Pear"]
res = client.label_detection(Img)
returned_set = set()
for obj in res.label_annotations:
    if obj.name in Protein:
        returned_set.add("protein")
    elif obj.name in Grain:
        returned_set.add("grain")
    elif obj.name in Fruit:
        returned_set.add("fruit")
return returned_set

```

(a) Aander-ETL
(Label output, Multi-Choice, App-Order)

(b) FoodDelivery
(Float-point value output, Multi-Choice)

(c) Plant-watcher
(Label output, True-False)

(d) The-Coding-Kid
(Label output, Multi-Select)