

## Invocation of ML API

## Branch condition that uses API output

## Structure indicating decision types

```
Landmark = ["Landmark", "Sculpture"]
Building = ["Building", "Estate", "Mansion"]
Person = ["Person", "Lady"]
response = client.label_detection(Image)
detected_labels = [obj.name for obj in
                    response.label_annotations]
if any([l in Landmark for l in detected_labels]):
    return "Landmark"
elif any([l in Building for l in detected_labels]):
    return "Building"
elif any([l in Person for l in detected_labels]):
    return "Person"
else: ## obj.name not in any list
    return "It is others."
```

(a) Aander-ETL (Label output, Multi-Choice, App-Order)

```
Plant = ["Houseplant", "Bonsai",
         "Plant", "Flowerpot"]
response =
    client.label_detection(Image)
for obj in
    response.label_annotations:
    if obj.name in Plant:
        return "Plant found!"
    return "No plant found."
```

(c) Plant-watcher (Label output, True-False)

```
text = types.Document(content=Text)
response = client.analyze_sentiment(text)
score = response.document_sentiment.score
if sentiment_score < 0.3:
    print("It's a negative sentence!")
elif sentiment_score > 0.6:
    print("It's a positive sentence!")
else: ## between 0.3 and 0.6
    print("It's a neutral sentence!")
```

(b) FoodDelivery (Float-point value output)

```
Protein = ["Hamburger", "Meat", "Patty"]
Grain = ["Noodle", "Pasta", "Bread"]
Fruit = ["Apple", "Orange", "Pear"]
response = client.label_detection(Image)
returned_set = set()
for obj in response.label_annotations:
    if obj.name in Protein:
        returned_set.add("protein")
    elif obj.name in Grain:
        returned_set.add("grain")
    elif obj.name in Fruit:
        returned_set.add("fruit")
return returned_set
```

(d) The-Coding-Kid (Label output, Multi-Select)