

Config.	Example 1: LLM catches a dependency violation <pre> <name>io.file.buffer.size</name> <value>4096</value> <description>The size of buffer for use in sequence files during read and write operations.</description> <name>io.bytes.per.checksum</name> <value>4097</value> <description>The number of bytes per checksum. Must not be larger than io.file.buffer.size.</description> ... </pre>	Example 2: LLM catches an invalid port value <pre> <name>dfs.journalnode.httpaddress </name> <value>0.0.0.0:80800</value> <description> The address and port the JournalNode HTTP server listens on. </description> ... </pre>	Example 3: LLM misses an invalid option <pre> <name>hadoop.ssl.hostname.verifier </name> <value>STRICT_I8</value> <description> The hostname verifier to provide for HttpsURLConnections. Valid values are DEFAULT,STRICT, STRICT_I6, DEFAULT_AND_LOCALHOST and ALLOW_ALL </description> ... </pre>	Example 4: LLM reports a false alarm <pre> <name>io.mapfile.bloom.error.rate</name> <value>0.01</value> <description> The rate of false positives in BloomFilter-s used in BloomMapFile. As this value decreases, the size of BloomFilter-s increases exponentially. This value is the probability of encountering false positives (default is 0.5%). </description> ... </pre>
	Q: Any mistakes in the above configuration file?	Q: Any mistakes in the above configuration file?	Q: Any mistakes in the above configuration file?	Q: Any mistakes in the above configuration file?
A:	The value of io.bytes.per.checksum should be less than or equal to io.file.buffer.size.	The port number is too big. The port number should be less than 65535.	The value of the property hadoop.security.-crypto.cipher.suite is wrong.	The value of the property io.mapfile.bloom.-error.rate is 0.01, which is too low.