

AgentCoder: Test Executor

```
from codegeex.benchmark.execution import check_correctness

def process_humaneval_test(sample, problems, example_test=False, language=language, test_case=True):
    task_id = sample["task_id"]
    task_id = problems.index(sample)
    prompt = sample["prompt"]
    code = sample["completion"]
    # Pre-process for different languages
    if language == "python" or language == "py":
        test_case = sample["test_list"]
        tests = ""
        for test in test_case:
            tests += "\n" + test
        test_string = code + "\n" + tests
    return test_string

def preprocess_data(task):
    if f"```py" in task["completion"]:
        task["completion"] = task["completion"][task["completion"].find(f"```py") + len(f"```py"):]
        task["completion"] = task["completion"][:task["completion"].find("```")]
    elif "```" in task["completion"]:
        task["completion"] = task["completion"][task["completion"].find("```") + 3:]
        task["completion"] = task["completion"][:task["completion"].find("```")]
    return task

def test_report(dataset, lg):
    correct = 0
    for i in tqdm(range(len(dataset))):
        dataset[i]["full_code"] = process_humaneval_test(dataset[i], dataset,
example_test=False, language=lg, test_case=False)
        result = check_correctness(dataset[i]["task_id"], dataset[i], lg, 5, ".tmp")
        if result["passed"] == True:
            correct += 1
        dataset[i]["report_passed"] = result["passed"]
        dataset[i]["report_result"] = result["result"]
    print("=====Start Report Testing=====")
    correct_percent = correct / len(dataset) * 100
    print(f"test_report, {correct_percent:0.2f}")
    return dataset

def test_agent(dataset, lg):
    correct = 0
    for i in tqdm(range(len(dataset))):
        dataset[i]["full_code"] = process_humaneval_test(dataset[i], dataset,
example_test=False, language=lg, test_case=False)
        result = check_correctness(dataset[i]["task_id"], dataset[i], lg, 5, ".tmp")
        if result["passed"] == True:
            correct += 1
        dataset[i]["result"] = result["result"]
        dataset[i]["passed"] = result["passed"]
    print("=====Start Agent Testing=====")
    print("test_agent", correct)
    return dataset

model_list = ["gpt-3.5-turbo", "palm-2-codechat-bison", "claude-instant-1", "gpt-4-1106-preview", "gpt-4"]
language = ["py"]
for model_name in model_list:
    print(f"===== {model_name} =====")
    epoch = 5
    path = AgentCoderProgrammerSaveResultPath
    with open(path, "r") as f:
        dataset = json.load(f)
    for current_epoch in range(epoch):
        with open(f"./dataset/{model_name}_{current_epoch}.json", "w") as f:
            json.dump(dataset, f)
        test_report(dataset, lg)
        test_agent(dataset, lg)
        dataset = call_completion(dataset, model_name, lg)
```