

Prompt Template of DynamicPlan(**T**, **Q**, **chain**)

(a) Part I - Atomic Operation Demo

```
{OPERATION_INSTRUCTION}
{SERIALIZED_TABLE}
Question: {QUESTION}
Operation: {OPERATION_AND_ARGUMENTS}
Explanation: {INTRODUCTION_TO_THE_OPERATION}
```

.....

(b) Part II: Operation Chain Demo

```
{OPERATION_CHAIN_INSTRUCTION}
{SERIALIZED_TABLE}
Question: {QUESTION}
Operation Chain: {COMPLETE_OPERATION_CHAIN}
```

.....

(c) Part III: Input Sample

```
{SERIALIZED_LATEST_TABLE (T) }
Question: {QUESTION (Q) }
Candidates: {POSSIBLE_NEXT_OPERATIONS}
Operation Chain: {INCOMPLETE_OPERATION_CHAIN (chain) }
{REST_OPERATIONS_OF_OPERATION_CHAIN}
```

// Introduce how atomic operations work

Operation: f_select_column(County, Population)

Explanation: The question asks ... We only need column Country and Population to answer the question so we use f_select_column to select them.

// Complete operation chain with an ending tag [E]

Question: What was the last year where this team was a part of the USL a-league?

Operation Chain: f_add_column(Year) → f_select_row(row 1, row 2) → f_select_column(Year, League) → f_sort_column(Year) → [E]

// Incomplete operation chain with an arrow "→" at the end triggering the LLM to complete the chain with candidate operations

Question: Which country had the most cyclists with in the top 10?

Candidates: f_select_row, f_select_column, ...

Operation Chain: f_add_column(Country) →

// Extract the first generated operation f_select_row as our next operation since it is based on the most up-to-date intermediate table

f_select_row (row 1, row 2 ... row 10 ... → ... → [E]