Input Prompt

[Original Table]

Rank	Cyclist
1	Alejandro (ESP)
2	Davide (ITA)
3	Paolo (ITA)
4	Haimar (ESP)

[Question]
Which country had the most cyclists finish with in the top 3?

(a) Generic Reasoning



There are 2 cyclists from Spain. They are Alejandro and *Haimar*. The answer is *Spain*. ✗

***Multiple Reasoning Steps** in Generic Reasoning fails to solve the complex table.*
Question asks cyclists in top 3 but Haimar is not in top 3.

Rank	Cyclist
4	Haimar (ESP)

(b) Program-aided Reasoning



SQL: `SELECT Country FROM table WHERE Rank<=3 GROUP BY Country ORDER BY COUNT(*) DESC LIMIT 1` ✗

***Generated Programs** in Program-aided Reasoning fails to solve the complex table.*
SQL can't execute the query since "Country" is in the same cell with "Name".

Cyclist
Alejandro (ESP)

(c) Chain-of-Table (ours)

***Iteratively** repeat **Step 1, 2, 3** with the intermediate table & the operation history*

Step 1: Sample next operation based on Table, Question, Operation History



f_add_col()

Step 2: Generate arguments for the sampled operation



Added Col Header = "Country"

Added Col Cells = "ESP,ITA,..."

Input Prompt (next iteration)

[Intermediate Table]

Rank	Cyc.	Country
1	Alej.	ESP

[Operation History] f_add_col()

[Question] *Which country … in the top 3?*

Step 3: **Transform table to store the tabular reasoning process**

Complete Operation History
Represent Tabular Reasoning Chain

Iter 1: f_add_col(Country)
Iter 2: f_select_row(1,2,3)
Iter 3: f_group_by(Country)
Iter 4: f_sort_by(Count)

Final Query Prompt

[Q] Which country had the most cyclists finish with in the top 3?

Country	Count
ITA	2
ESP	1



Italy ✓