

You

Question: Given an integer array `citations`, where `citations[i]` represents the number of times the *i*-th paper of a researcher has been cited, and `citations` are already sorted in ascending order. Calculate and return the researcher's h-index.

Please design an `AOD` class using Python language, which has an instance attribute `citations`, a private function `private_Paper_cited`, and a public function `public_ascend_order`. In the private function `private_Paper_cited`, return the researcher's h-index. Finally, in the public function `public_ascend_order`, call the private function `private_Paper_cited` and return the result.



ChatGPT

Certainly! Below is an example implementation of the described class in Python:

```
python Copy code

class AOD:
    def __init__(self, citations):
        self.citations = citations

    def public_ascend_order(self):
        # Call the private function and return the result
        return self.private_Paper_cited()

    def private_Paper_cited(self):
        n = len(self.citations)
        h_index = 0

        # Binary search to find the h-index
        left, right = 0, n - 1
        while left <= right:
            mid = left + (right - left) // 2
            if self.citations[mid] >= n - mid:
                h_index = n - mid
                right = mid - 1
            else:
                left = mid + 1

        return h_index

# Example usage:
citations = [0, 1, 3, 5, 6]
aod_instance = AOD(citations)
result = aod_instance.public_ascend_order()
print("Researcher's h-index:", result)
```

private_Paper_cited