

HumanEval

Prompt:

```
def truncate_number(number: float) ->float:
```

```
    """
```

Given a positive floating point number, it can be decomposed into an integer part (largest integer smaller than given number) and decimals (leftover part always smaller than 1).

Return the decimal part of the number.

```
>>>truncate_number(3.5)
```

```
0.5
```

```
    """
```

Function Programming

MBPP

Prompt:

You are an expert Python programmer, and here is your task:

...

Write a function to check if the given tuple list has all k elements. Your code should pass these tests:

```
["assert check_k_elements([(4, 4), (4, 4, 4), (4, 4), (4, 4, 4, 4), (4, )], 4) == True", "assert check_k_elements([(7, 7, 7), (7, 7)], 7) == True", "assert check_k_elements([(9, 9), (9, 9, 9, 9)], 7) == False"]
```

[BEGIN]

Function Programming

OOP

Prompt:

Firstly, design a **CN** class using Python language, which has instance attributes **sx**, **sy**, **tx**, and **ty**, a private function **private_Convert_numbers**, and a public function **public_Convert_numbers**. Then, implement the following problem in the private function **private_Convert_numbers**. Finally, call the private function **private_Convert_numbers** in the public function **public_Convert_numbers** to return the result.

Problem: Given four integers **sx**, **sy**, **tx**, and **ty**. If it is possible to reach the endpoint **(tx, ty)** from the starting point **(sx, sy)** through a series of transformations, return **True**, otherwise return **False**. From point **(x, y)**, it can be transformed to either **(x, x+y)** or **(x+y, y)**.

Object-Oriented Programming