



User

First, design a **ROE** class using the Python language. The class should have an instance attribute called **nums**, a private function called **private_relative_order**, and a public function called **public_relative_order**. In the private function **private_relative_order**, move all the zeros in the array **nums** to the end while maintaining the relative order of the non-zero elements. Finally, in the public function **public_relative_order**, call the private function **private_relative_order** and return the result.



Qwen-14b

class ROE:

```
def __init__(self, nums):
```

```
    self.nums = nums
```

```
def _private_relative_order(self):
```

```
    zeros = []
```

```
    non_zeros = []
```

```
    for num in self.nums:
```

```
        if num == 0:
```

```
            zeros.append(num)
```

```
        else:
```

```
            non_zeros.append(num)
```

```
    self.nums = non_zeros + zeros
```

```
def public_relative_order(self):
```

```
    self._private_relative_order()
```

```
    return self.nums
```

pass@k, k=80 ✓

pass@o, o=80 ✓



WizardCoder-15b

class ROE:

```
def __init__(self, nums):
```

```
    self.nums = nums
```

```
def private_relative_order(self):
```

```
    count = 0
```

```
    for i in range(len(self.nums)):
```

```
        if self.nums[i] != 0:
```

```
            self.nums[i], self.nums[count] = self.nums[count],
```

```
                self.nums[i]
```

```
            count += 1
```

```
def public_relative_order(self):
```

```
    self.private_relative_order()
```

```
    return self.nums
```

pass@k, k=80 ✓

pass@o, o=80 ✗