

---

**Algorithm 1:** HiFT Training Algorithm

---

**Require:** model  $M$  with  $n$  layers, number of layers per group  $m$ , batch size  $B$ , step budget  $T$ , optimizer  $P$ , parameter queue  $Q$ , update strategy  $S$ , learning rate schedule  $\eta_t$

**Initialize:** Initialize queue  $Q$  by layer identifier

UpdateStrategy( $Q, S$ )

**for**  $t = 1, \dots, T$  **do**

    Freeze all parameters of  $M$

    Sample batch  $\mathcal{B} \subset \mathcal{D}$  with random seed  $s$

$E \leftarrow \text{QueueGetAndRemove}(Q, m)$

    ▷ Select key features of layers to be updated

    QueueAddTail( $Q, E$ )

    ▷ Removed elements added to tail of queue

$\theta_s \leftarrow \text{SelectParameters}(M, E)$

    Set requires\_grad = True of parameters  $\theta_s$

    UpdateOptimizerParameter( $P, \theta_s$ )

    ForwardPropagation( $M, \mathcal{B}$ )

    MoveOptimizerState2GPU( $P, \theta_s$ )

    ▷ Preserve optimizer state of  $\theta_s$  within the GPU

    Backpropagation( $P, \theta_s, M$ ) and Clear gradients

    MoveOptimizerState2CPU( $P, \theta_s$ )

    ▷ Keep optimizer state within the CPU

**if** IsAllLayerUpdate( $t, n, m$ ) **then**

        Update learning rate  $\eta_t$

**end**

**else**

        Keep the learning rate  $\eta_t$  constant

**end**

**end**

---