

Writing Style = -2.28

```
... /Account;->name:Ljava/lang/String; # # ap
ut-object v0, v4, v6 # # iget-object v0, p2,
Landroid/accounts/Account;->type:Ljava/lang/String
; # # aput-object v0, v4, v7 # # move-o
bjeet v0, p1 # # move-object v6, v5 # #
move-object v7, v5 # # invoke-virtual/range {
v0 .. v7}, Landroid/database/sqlite/SQLiteDatabase
;->query(Ljava/lang/String;[Ljava/lang/String;Ljav
a/lang/String;[Ljava/lang/String;Ljava/lang/String
;Ljava/lang/String;Ljava/lang/String;Landroid/dat
abase/Cursor; # # move-result-object v8 # #
.line 2470 # # .local v8, cursor:Landroid/databa
se/Cursor; # # :goto_0 # # :try_start_0 # #
invoke-interface {v8}, Landroid/database/Cursor;->
moveToNext()Z # # move-result v0 # # if
-eqz v0, :cond_0 # # .line 2471 # # const/
4 v0, 0x0 # # invoke-interface {v8, v0}, Land
roid/database/Cursor;->getString(I)Ljava/lang/Stri
ng; # # move-result-object v9 # # .line
2472 # # .local v9, tmpkey:Ljava/lang/String; # #
const/4 v0, 0x1 # # invoke-interface {v8, v0}
```

Writing Style = -1.76

```
... yForm.application.$error"> # #
<span ng-message="required">{{ 'APP.ENTRIES.FORM.L
ABEL.VALIDATION.APPLICATION.REQUIRED' | translate
}}</span> # # <spa
n ng-message="maxlength">{{ 'APP.ENTRIES.FORM.LABE
L.VALIDATION.APPLICATION.MAXLENGTH' | translate }}</
span> # # <span ng
-message="pattern">{{ 'APP.ENTRIES.FORM.LABEL.VALI
DATION.APPLICATION.PATTERN' | translate }}</span> # #
</div> # # </div> # #
<div class="form-group has-feedback" # # ng-class="{h
as-error": entryForm.scope.$invalid && !entryForm.
scope.$pristine,
'has-success': entryForm.scope.$valid && entryForm
.scope.$dirty}"> # # <label for
="scope" class="control-label col-md-3"> # #
```

Writing Style = -1.30

```
... ns', options); # # // if options is a string
use default options and use string for logger na
me # # let name # # if (typeof options === 'string
') { # # name = options # # options = {} # #
} # # if (!instance) { # # return instance
} # # Object.assign(_options, options) # #
# /** # # * handle morgan # # */ # # if (_optio
ns.morgan && _options.morgan.app) { # # let ap
p = _options.morgan.app # # let format = _optio
ns.morgan.format # # app.use(morgan(format,
_options.morgan)) # # } # # /** # # * handle
line # # */ # # if (_options.line !== false) { # #
if (typeof _options.line !== 'object') { # #
_options.line = {} # # } # # _options.line
.path = _options.line.path || __dirname # #
log4js.extend(log4js, _options.line) # # } # #
log4js.getLogger('jsdebugger').level = _options.le
vel # # // define default categories based on a
ppenders # # let categories = { # # default: {
# # appenders: [], # # level: 'ALL' # # } # #
} # # for (let appender in _options.appender
```

Writing Style = -0.80

```
... ed to initialize the pseudorandom number gener
ator. Should be # # used for testing only.
If the seed is None then the pseudorandom number
generator is seeded randomly and subsequent calls
to this function # # return unrelated resul
ts. # # Returns: # # an integer in the r
ange 0 .. 2**n - 1 # # "" # # raise NotImplem
entedError("must be implemented by subclass") # #
# # class Urandom(Rng): # # ""A pseudorandom number
generator using os.urandom. # # The results of
this pseudorandom number generator should be indis
tinguishable # # from random data. # # "" # #
def RandomBits(self, n: int, *, seed: Optional[int
] = None) -> int: # # ""See base class. # #
del seed # # Cannot seed os.urandom # # ba = os.
urandom((n + 7) // 8) # # seq = int.from_bytes(b
a, "little") # # if n % 8 != 0: # # seq >>=
-n % 8 # # return seq # # class Shake128(Rn
g): # # ""Uses SHAKE128 to generate pseudorandom
bits. # # SHAKE128 is a cryptographically stron
g pseudorandom number generator. # # It is defined
```

Facts & Trivia = -2.19

```
... tripMenuItem = new System.Windows.Forms.ToolSt
ripMenuItem(); # # this.editToolStripMenuI
tem = new System.Windows.Forms.ToolStripMenuIte
m(); # # this.addSplineToolStripMenuIte
m = new System.Windows.Forms.ToolStripMenuItem();
# # this.addSplinePointToolStripMenuItem
m = new System.Windows.Forms.ToolStripMenuItem();
# # this.toolStripSeparator2 = new Syst
em.Windows.Forms.ToolStripSeparator(); # #
this.deleteSplineToolStripMenuItem = new System.Wi
ndows.Forms.ToolStripMenuItem(); # # th
is.deleteSplinePointToolStripMenuItem = new System
.Windows.Forms.ToolStripMenuItem(); # #
this.toolStripSeparator3 = new System.Windows.Fo
rm.S.ToolStripSeparator(); # # this.camera
PropertiesToolStripMenuItem = new System.Windows.F
orms.ToolStripMenuItem(); # # this.dupl
icateSplineToolStripMenuItem = new System.Windows.
Forms.ToolStripMenuItem(); # # this.too
lStripSeparator4 = new System.Windows.Forms.ToolSt
ripSeparator(); # # this.toolStripSepar
```

Facts & Trivia = -1.52

```
... # # import java.util.Collections; # # import jav
ax.inject.Inject; # # import lombok.Getter; # # impor
t lombok.Setter; # # import net.runelite.api.Client;
# # import net.runelite.api.GameState; # # import net.
runelite.api.ItemComposition; # # import net.runelit
e.api.MenuAction; # # import net.runelite.api.MenuEnt
ry; # # import net.runelite.api.events.ConfigChange
d; # # import net.runelite.api.events.FocusChanged;
# # import net.runelite.api.events.MenuEntryAdded;
# # import net.runelite.api.events.MenuOpened; # # impo
rt net.runelite.api.events.MenuOptionClicked; # # impo
rt net.runelite.api.events.PostItemComposition; # #
import net.runelite.api.events.WidgetMenuOptionCli
cked; # # import net.runelite.api.widgets.WidgetInfo
; # # import net.runelite.api.widgets.WidgetItem;
# # import net.runelite.client.config.ConfigManager;
# # import net.runelite.client.game.ItemManager; # # impo
rt net.runelite.client.input.KeyManager; # # import ne
t.runelite.client.menus.MenuManager; # # import ne
t.runelite.client.menus.WidgetMenuOption; # # import ne
t.runelite.client.plugins.Plugin; # # import net.r
```

Facts & Trivia = -0.98

```
... empty) # # val resp = requestEntity(GET, ent
ityPath, paramMap) # # new RestResult(resp.statu
s, getTransactionId(resp), getRespData(resp)) # #
} # # /** # # * Parses result of WskActivatio
n.list to extract sequence of activation ids. # #
* # # * @param rr run result, should be from Whis
kActivation.list otherwise behavior is undefined # #
* @return sequence of activations # # */ # # def
isActiveAction(rr: RestResult; Seq[String] = { # #
r.rg.getBodyListJsonObject.map(r => RestResult.getFiel
d(r, "activationId").toString()) # # } # # /** # #
* Gets activation logs by id. # # * # # * @para
m activationId the activation id # # * @param exp
ectedExitCode (optional) the expected exit code fo
r the command # # * if the code is anything but D
ONTCARE_EXIT, assert the code is as expected # #
*/ # # def activationLogs(activationId: String, exp
ectedExitCode: Int = OK, intValue)(implicit w: Ws
kProps): RestResult = { # # val path = Path("$
basePath/namespaces/${wp.namespace})/$noun/$activat
ionId/logs") # # val resp = requestEntity(GET,
```

Facts & Trivia = -0.47

```
... nager - ServiceClient** dialog box, expand the
**Projects** node, and then click **Solution**.#
9. In the projects list, point to **Common**, and
then select the check box next to the project name
.# 10. In the left pane, expand the **Assemblies**
* node, and then click **Framework**. Scroll down
the assemblies list, point to the **System.Servic
eModel** assembly, select the check box next to th
e assembly name, and then click **OK**. #
The reference was added to gain access to the serv
ice and data contracts and to the WCF client libra
ries. #
# 11. In **Solution Explorer**, expa
nd the **ServiceClient** project and double-click
**Program.cs**. # 12. To the **using** section at
the top of the file, add the following **using** d
irectives. # # ````cs # # using HotelBoo
king; # # using System.ServiceModel; # # ````
# 13. At the beginning of the **Main** method, add
the following lines of code before the commented c
ode. # # ````cs # # ChannelFactory<IHote
lBookingService> serviceFactory = # # n
```

Educational Value = -2.06

```
... :Icon" x="671" y="131" w="-1" h="-1" measured
W="48" measuredH="48" zOrder="11" locked="false" i
sInGroup="-1"/> # # <control controlID="135" con
trolTypeID="com.balsamiq.mockups:Paragraph" x="39
6" y="452" w="416" h="27" measuredW="200" measured
H="80" zOrder="12" locked="false" isInGroup="-1">
# # <controlProperties> # # <text>Note%
3A%20You%20cannot%20add%20rating%20to%20a%20skill.
%20%20They%20are%20updated%20once%20you%20receive%
20feedback%20on%20your%20task</text> # # </co
ntrolProperties> # # </control> # # <control
controlID="136" controlTypeID="com.balsamiq.mockup
s:BrowserWindow" x="249" y="0" w="746" h="524" me
asuredW="450" measuredH="400" zOrder="13" locked="
true" isInGroup="-1"> # # <controlProperties>
# # <text>A%20Web%20Page%20http%3A//teamflo
wy.com/users/project/task/%3Fid%3D3%26subtask%3Dcre
ate</text> # # </controlProperties> # # </
control> # # <control controlID="137" controlTyp
eID="com.balsamiq.mockups:TabBar" x="249" y="73"
w="746" h="423" measuredW="287" measuredH="100" z0
```

Educational Value = -1.16

```
... ALPHAMASK VERTEXCOLOR"); # # ShaderVariation
* alphaTexturePS = graphics._>GetShader(PS, "Basic
", "ALPHAMAP VERTEXCOLOR"); # # unsigned alp
haFormat = Graphics::GetAlphaFormat(); # # fo
r (unsigned i = batchSize; i < batchSize; ++i) # #
{ # # const UIBatch& batch = batches[i]; # #
if (batch.vertexStart_ == batch.vertexEnd_) # #
continue; # # ShaderVariation* ps; # #
ShaderVariation* vs; # # if (!batch.text
ure_) # # { # # ps = noTexturePS; # #
} # # vs = noTextureVS; # # } # #
else # # { # # // If texture cont
ains only an alpha channel, use alpha shader (for
fonts) # # vs = diffTextureVS; # # } # #
if (batch.texture_>GetFormat() == alphaFormat) # #
ps = alphaTexturePS; # # else if (batch
.blendMode_ != BLEND_ALPHA && batch.blendMode_ !=
BLEND_ADDALPHA && batch.blendMode_ != BLEND_PREMUL
ALPHA) # # ps = diffMaskTexturePS; # #
else # # ps = diffTex
turePS; # # } # # graphics._>SetTex
```

Educational Value = -0.41

```
... # # namespace Azure.ResourceManager.HybridC
ontainerService # # { # # public partial class Pr
ovisionedContainerData : IUtf8JsonSerializable # #
{ # # void IUtf8JsonSerializable.Write(Utf8
JsonWriter writer) # # { # # writ
er.WriteStartObject(); # # if (Optional
.IsDefined(Identity)) # # { # #
writer.WriteString("identity"); # #
JsonSerializer.Serialize(writer, Identity); # #
} # # if (Optional.IsDefined(Properties
)) # # { # # writer.Writ
eProperty("properties"); # # wr
iter.WriteObjectValue(Properties); # #
} # # if (Optional.IsDefined(ExtendedLo
cation)) # # { # # write
r.WritePropertyName("extendedLocation"); # #
writer.WriteObjectValue(ExtendedLocation); # #
} # # if (Optional.IsCollectionDefined(
Tags)) # # { # # writer.
WritePropertyName("tags"); # # writ
er.WriteStartObject(); # # foreach
```

Educational Value = 0.34

```
... sforma os `swapcase` maiúsculas em uma string
em minúsculas e as letras minúsculas em maiúsculas
`ruby "HELLO WORLD".swapcase => Hello World` #
# ## Capitalizar: # # * O método `capitalize`
transforma a primeira letra em uma string em mai
úsculas e o restante na string em minúsculo. `ruby
"HELLO".capitalize => Hello "HELLO, HOW ARE YOU?".
capitalize => Hello, how are you?` # # Observe
que a primeira letra só é maiúscula se estiver no
início da string. `ruby "HELLO".capitalize => -
hello "THELLO".capitalize => !hello` # # ## Mar
chá ré: # # * O método `reverse` inverte a or
dem dos caracteres em uma string. `ruby "Hello Wor
ld!".reverse => "!dlrow olleh"` # # ## Dividido
: # # * O `split` pega uma string, `divide`
a em uma matriz e retorna a matriz. # #
`ruby "Hello, how are you?".split => ["He
llo", "how", "are", "you?"]` # # ##
# # * O método padrão divide a string com base no
espaço em branco, a menos que um separador diferen
te seja fornecido (veja o segundo exemplo). `ruby
```

Required Expertise = -1.48

```
... x; # # border-top-right-radius: 1000px; # # }
# # /* # # line 123, /Users/annaershova/.rvm/gems/ruby-2
.2.1/gems/foundation-rails-5.3.0.1/vendor/assets/s
tylesheets/foundation/components/_sub-nav.scss # #
# # .sub-nav { # # display: block; # # width: auto;
# # overflow: hidden; # # margin: -0.25rem 0 1.12
5rem; # # padding-top: 0.25rem; # # margin-right:
0; # # margin-left: -0.75rem; # # } # # /* # # line 69, /U
sers/annaershova/.rvm/gems/ruby-2.2.1/gems/foundat
ion-rails-5.3.0.1/vendor/assets/stylesheets/founda
tion/components/_sub-nav.scss # # .sub-nav dt { # #
text-transform: uppercase; # # } # # /* # # line 75, /User
s/annaershova/.rvm/gems/ruby-2.2.1/gems/foundatio
n-rails-5.3.0.1/vendor/assets/stylesheets/foundatio
n/components/_sub-nav.scss # # .sub-nav dt, # # .su
b-nav dd, # # .sub-nav li { # # float: left; # # di
splay: inline; # # margin-left: 1rem; # # margin-b
ottom: 0.625rem; # # font-family: "gotham-rounded"
, "Helvetica", Helvetica, Arial, sans-serif; # #
font-weight: normal; # # font-size: 0.875rem; # #
color: #999999; # # } # # /* # # line 85, /Users/annaersho
```

Required Expertise = -0.24

```
... # # <td class="description last">
# # <td class="type"> # # # # <span class="param-type">int
eger</span> # # # # <td cla
ss="attributes"> # # # # &lt;optional><br> # # # # </td> # #
# # # # <td class="d
efault"> # # # # </td> # #
# # # # <td class="description last"><p>
```

Required Expertise = 0.45

```
... ILE_CONTENT; # # import static com.google.gerrit
.acceptance.PushOneCommit.FILE_NAME; # # import stat
ic com.google.gerrit.acceptance.PushOneCommit.SUBJ
ECT; # # import static com.google.gerrit.extensions.
client.ListChangesOption.ALL_REVISIONS; # # import s
tatic com.google.gerrit.extensions.client.ListChan
gesOption.CHANGE_ACTIONS; # # import static com.goog
le.gerrit.extensions.client.ListChangesOption.CHEC
K; # # import static com.google.gerrit.extensions.c
lient.ListChangesOption.COMMIT_FOOTERS; # # import s
tatic com.google.gerrit.extensions.client.ListChan
gesOption.CURRENT_ACTIONS; # # import static com.goo
gle.gerrit.extensions.client.ListChangesOption.CUR
RENT_COMMIT; # # import static com.google.gerrit.ex
tensions.client.ListChangesOption.CURRENT_REVISION
; # # import static com.google.gerrit.extensions.cli
ent.ListChangesOption.DETAILED_ACCOUNTS; # # import
static com.google.gerrit.extensions.client.ListCha
ngesOption.DETAILED_LABELS; # # import static com.g
oogle.gerrit.extensions.client.ListChangesOption.L
ABELS; # # import static com.google.gerrit.extension
```

Required Expertise = 1.07

```
... *****
*/ # # /* # # * @brief Forward declaration of
the DSPI edMA master handle typedefs. # # */ # # typede
f struct _dspi_master_edma_handle dspi_master_edma_ha
ndle_t; # # /* # # * @brief Forward declaration o
f the DSPI edMA slave handle typedefs. # # */ # # type
def struct _dspi_slave_edma_handle dspi_slave_edma
_handle_t; # # /* # # * @brief Completion callba
ck function pointer type. # # * # # * @param base D
SPI peripheral base address. # # * @param handle A
pointer to the handle for the DSPI master. # # * # #
* @param status Success or error code describing wheth
er the transfer completed. # # * @param userData An
arbitrary pointer-sized value passed from the applica
tion. # # */ # # typedef void (*dspi_master_ed
ma_transfer_callback_t)(SPI_Type *base, # #
dspi_master_edma_handle_t *handle, # #
status_t status, # #
void *userData); # # /* # # * @brief Completion cal
lback function pointer type. # # * # # * @param bas
e DSPI peripheral base address. # # * # # * @param handl
```