

Source Code	Natural Language Description	Core Apply Analysis Rules
<pre> 1 module counter   (clk, rst, en,   count);  2   input clk, rst,   en; 3   output reg [1:0]   count; 4   always @(posedge   clk) 5       if (rst) 6           count &lt;=   2'd0; 7       else if (en) 8           count &lt;=   count + 2'd1; 9 endmodule </pre>	<p>Line 1: module &lt;counter&gt; has &lt;four&gt; ports, their names are &lt;clk, rst, en and count&gt;.</p> <p>Line 2: In the &lt;four&gt; ports, &lt;clk, rst, en&gt; are inputs. &lt;clk&gt; has &lt;1&gt;-bit width, &lt;rst&gt; has &lt;1&gt;-bit width, &lt;en&gt; has &lt;1&gt;-bit width.</p> <p>Line 3: &lt;Output&gt; signal &lt;count&gt; has &lt;2&gt;-bit width in range &lt;1:0&gt;. It is a &lt;reg&gt; variable.</p> <p>Line 4: This module has &lt;one&gt; trigger block.</p> <p>Line 4: The sensitive list in &lt;first&gt; trigger block is &lt;on the positive edge&gt; of &lt;clk&gt;.</p> <p>Line 5-8: In this &lt;always&gt; block, &lt;if&gt; &lt;rst&gt; is 1, then initialize &lt;count&gt; to &lt;2'd0&gt;, else if &lt;en&gt; is true, then &lt;add&gt; &lt;2'd1&gt; to the count.</p>	<pre> module_declaration : module_keyword   module_identifier     module_parameter_port_list?     list_of_port_declarations? ';'     module_item* 'endmodule' ;  list_of_port_declarations : '('   port_declaration     ( ',' port_declaration )* ')'     '(' port ( ',' port )+ ')'     '(' port_implicit ')'     '(' port_explicit ')'     '(' ')' ;  module_item : attribute_instance*   module_declaration       attri_inst*       module_instant       attri_inst* initial_construct       attri_inst* always_construct;  module_declaration :   net_declaration     reg_declaration     integer_declaration </pre>