

Example 1, Sample Bronze Problem: 187 bronze find the cow!

```
# Iterate though grass string from...
for i in range(len(grass)-1, -1, -1):
    if grass[i:i+2] == ")")":
        count_front_legs += 1
    elif grass[i:i+2] == "(("":
        count_bessite += count_front_legs
    ...
```

Incorrect zero-shot solution

```
for i in range(1, len(grass)):
    if grass[i] == '('
    and grass[i-1] == '(':
        back_legs_count += 1
    elif grass[i] == ')'
    and grass[i-1] == ')':
        possible_locations +=
        back_legs_count
    ...
```

Correct Solution with Problem Memory

Perhaps the simplest definition is that there must be the same total number of ('s and)'s, and for any prefix of the string, there must be at least as many ('s as)'s. For example, the following strings are all balanced:

```
()
(())
()()()
```

Memory: 188 bronze typ

Example 2: Sample Silver Problem: 210 silver milk routing

```
def milk_routing(n, m, x, pipes):
    graph = {i: [] for i in range(1, n+1)}
    for i, j, l, c in pipes:
        graph[i].append((j, l, c))
        graph[j].append((i, l, c))
    visited = {i: 0 for i in range(1, n+1)}
    while q:
        ...
```

Incorrect zero-shot solution

```
def dijkstra(graph, source, n, capacity):
    time_taken = [float('inf')] * (n+1)
    time_taken[source] = 0
    min_heap = [0, source]
    while min_heap:
        ...
```

Correct Solution with Problem Memory

```
def dijkstra(n, edges, source, destination...
    dist = [float('inf')] * (n+1)
    visited = [(0, source)]
    heapq.heapify(visited)
    dist[source] = 0
    while visited:
        ...
```

Memory: 969 gold milk pumping

Example 3: Sample Gold Problem: 400 gold roadblock

```
def main():
    graph, N, M = read_input()
    shortest_distance, shortest_path = dijkstra(..
    max_increase = 0
    for u, v in shortest_path:
        original_length = graph[q][v]
        graph[u][v] *= 2
    ...
```

Incorrect zero-shot solution

```
def main(fields, pathways):
    graph = {i: {} for i in range(1, fields+1)}
    for a, b, length in pathways:
        graph[a][b] = length
        graph[b][a] = length
    shortest_path, min_dist = dijkstra(graph...)
    max_increase = 0
    for i in range(1, len(shortest_path))
    ...
```

Correct Solution with Semantic Memory

Let SG be a tree. For every query of the form (u, v) we want to find the lowest common ancestor of the nodes u and v , i.e. we want to find a node w that lies on the path from u to the root node, that lies on the path from v to the root node, and if there are multiple nodes we pick the one that is farthest away from the root node.

Memory: LCA Algorithms