

Please reply with a Python 3 solution to the below problem. Make sure to wrap your code in 'python' and ' ' Markdown delimiters, and include exactly one block of code with the entire solution. Feel free to either return just the one code block with your solution or the one code block with explanatory text before and/or after -- however, you will only be evaluated on the correctness of your code.

[BEGIN PROBLEM] Farmer John has lost his prize cow Bessie, and he needs to find her!

Fortunately, there is only one long path running across the farm, and Farmer John knows that Bessie has to be at some location on this path. If we think of the path as a number line, then Farmer John is currently at position x and Bessie is currently at position y (unknown to Farmer John). If Farmer John only knew where Bessie was located, he could walk directly to her, traveling a distance of $|x - y|$. Unfortunately, it is dark outside and Farmer John can't see anything. The only way he can find Bessie is to walk back and forth until he eventually reaches her position.

```
def lost_cow(x: int, y: int) -> int:
    direction = 1
    start_position = x
    total_distance_traveled = 0

    while True:
        destination = start_position + direction
        total_distance_traveled += abs(start_position - destination)

        if min(start_position, destination) <= y <= max(start_position, destination):
            break

        direction *= -2
        start_position = destination

    return total_distance_traveled
```

This code is not correct. There are several bugs in your code, but I think it's important to verify your understanding of the problem. Let's converse and make sure you understand the problem correctly. Let's go through the sample case together, where the farmer starts at 3, and the cow is at 6. After 1 round, where should the farmer be?

If Farmer John starts at position 3, in his first move, he will shift to position $3+1=4$. Then he changes his direction and moves twice the distance he moved in his previous step, so he moves 2 steps towards the left from his current position to end up in position $4-2=2$. Note that while his current position is 2, he has traveled a total of 3 units - 1 unit to the right and 2 unit to the left.

Okay. So just to verify you understand, where should he be in round 3?

In round 3, Farmer John changes his direction again and now moves twice the distance he moved in the previous step i.e., 4 units to the right from his current position of 1. So, he will end up at position $1 + 4 = 5$. This round covers a total distance of 4 units. So after 3 rounds, he should be at position 5.

This is not correct. He should actually be at position $3 + 4 = 7$. What are you missing in your understanding of the problem?

My mistake. I misunderstood the way direction changes and distance increments were accounted for.

In each round, when Farmer John reverses direction, he doesn't move in relation to his current position. Instead, he moves relative to his starting position, 'x'. In each round, the distance he moves doubles in magnitude and alternates in direction.

Yes this is correct! Each movement is relative to his starting position. Knowing this, can you implement code that exhibits the intuition we described above?

```
def lost_cow(x: int, y: int) -> int:
    current = x
    direction = 1
    total_distance_traveled = 0

    while True:
        # Move to the next position relative to starting position
        next_position = x + direction

        # Accumulate total distance traveled
        total_distance_traveled += abs(next_position - current)

        # If Bessie is found between old and new positions, reduce
        # excess travel distance and break loop
        if min(current, next_position) <= y <= max(current, next_position):
            total_distance_traveled -= abs(next_position - y)
            break

        # Prepare for next iteration
        direction *= -2
```