

Description

The new algorithm idea is to calculate the utility of each test input by incorporating the concept of uncertainty reduction through mutual information, where the focus is on maximizing the information gain from the unobserved test input in relation to the learned surrogate model and the cost and budget constraints. It involves adjusting the utility value based on the reduction in uncertainty, the cost of observation, the remaining budget, and the distance of the test input from the known solutions, to provide an efficient and adaptive approach to prioritizing the evaluation of test inputs.

Code

```
import torch
import torch.distributions as tdist

def utility(train_x, train_y, best_x, best_y, test_x, mean_test_y, std_test_y, cost_test_y, budget_used, budget_total):

    # Calculate the expected improvement (EI) for each test input
    with torch.no_grad():
        z = (mean_test_y - best_y) / torch.sqrt(torch.pow(std_test_y, 2) + torch.pow(train_y.std(), 2))
        ei = (mean_test_y - best_y) * tdist.Normal(0, 1).cdf(z) + torch.sqrt(torch.pow(std_test_y, 2) + torch.pow(train_y.std(), 2)) * tdist.Normal(0, 1).log_prob(z).exp()

    # Calculate the reduction in uncertainty through mutual information
    with torch.no_grad():
        mi = torch.max(torch.tensor(0), (torch.log(torch.pow(std_test_y, 2) + torch.pow(train_y.std(), 2)) - torch.log(torch.pow(train_y.std(), 2))) / 2)

    # Adjust the utility value based on the reduction in uncertainty, cost of evaluation, and remaining budget
    utility_value = (ei * (1 - mi)) - torch.exp(-cost_test_y) * (budget_total - budget_used)

    # Calculate the distance of the test input from the known solutions
    distance_to_known = torch.cdist(test_x, train_x)

    # Adjust the utility value based on the diversity and coverage of the unobserved test input space
    diversity_coverage_factor = torch.mean(torch.min(distance_to_known, dim=1).values)
    utility_value += diversity_coverage_factor
    return utility_value
```