


# Training

Swallows and  
Non-Swallows



**Classifier**

1 swallows  
0 non-swallows

# Inference

LTHRM

$$\begin{bmatrix} 43 & 46 & \dots & 47 \\ 44 & 50 & \dots & 53 \\ \vdots & \vdots & \ddots & \vdots \\ 45 & 51 & \dots & 56 \end{bmatrix}$$


$(36 \times t)$

Rolling  
window

$$\begin{bmatrix} \begin{bmatrix} 43 & 46 & \dots & 47 \\ 44 & 50 & \dots & 53 \\ \vdots & \vdots & \ddots & \vdots \\ 45 & 51 & \dots & 56 \end{bmatrix} \\ \vdots \\ \begin{bmatrix} 43 & 46 & \dots & 47 \\ 44 & 50 & \dots & 53 \\ \vdots & \vdots & \ddots & \vdots \\ 45 & 51 & \dots & 56 \end{bmatrix} \end{bmatrix}$$

$(36 \times 500)$

Convert to inputs  
for the Conv Net




**Classifier**

output class  
 $\mathbf{o} = [0 \ 0 \ 0 \ 1 \ 1 \dots]$   
confidence  
 $\mathbf{c} = [0.98 \ 0.95 \ 0.61 \ 0.76 \dots]$

Swallow confidence  $\mathbf{S} = \mathbf{o} \odot \mathbf{c}$   
 $\mathbf{s} = [0 \ 0 \ 0 \ 0.76 \ 0.99 \dots]$

Binary swallow confidence,  $> 0.2$   
 $\mathbf{s}_b = [0 \ 0 \ 0 \ 1 \ 1 \dots]$

$\mathbf{S}$  &  $\mathbf{s}_b$  during a swallow sequence



Find groups of  
1s in  $\mathbf{s}_b$

For each group, use  
index with largest  
value in  $\mathbf{S}$

Predicted swallow  
starts

$[4 \ 580 \ 1391 \ 2049 \dots]$