

CoVerD

Planning:

1. Sampling: for $k \in \{t, \dots, \text{MAX_K} = 200\}$, estimate average analysis time and success rate by submitting to GPUPoly $n_{\text{samples}} I_S(x)$ with random S ; if success rate = 0 for n_{fail} k -s, reduce the number of samples n_{samples}
2. Dynamic programming: define a function f_R mapping a set size k to its optimal refinement size k_{ref} , for every $k \in \{t + 1, \dots, \text{MAX_K}\}$
3. For every candidate covering verification design, defined by (q, m) :
 1. Estimate the block size distribution $\text{dist}(q, m)$
 2. Predict the overall analysis time $T_{\text{dist}(q, m)}$
4. Let (q^*, m^*) be the candidate with the minimal $T_{\text{dist}(q^*, m^*)}$
5. Define $L = \text{random_ordered_set}(v, \left\lfloor \frac{q^{*m^*+1} - 1}{q^* - 1} \right\rfloor)$

↓ $f_R, (q^*, m^*), L$

Analysis:

```
while (CoveringGenerator( $q^*, m^*, t, L$ ) has more blocks):  
    blocks = blocks.push(next_block())  
    while blocks is not empty:  
        // continue as Calzone  
        // upon refinement to  $S$ , use  $C_S(|S|, f_R(|S|), t)$   
return robust
```

Refinements'
covering
database

robust /
non-robust